.things that Matter

System Analysis & UML Diagrams

Document Information	
---	---
Company Name	**.things that Matter**
Document Type	**System Analysis & Diagrams**
Version	**1.0**
Date	**January 21, 2026**
Author	**Matome Mboweni, CTO**

Table of Contents

1. C4 Model Diagrams 2. Use Case Diagrams 3. Class Diagrams 4. Sequence Diagrams 5. Activity Diagrams 6. State Machine Diagrams 7. Data Flow Diagrams 8. Entity Relationship Diagram 9. Deployment Diagram 10. Component Diagrams

---

1. C4 Model Diagrams

1.1 System Context Diagram (Level 1)

Shows the system's boundaries and interactions with external actors.

```
mermaid
C4Context
    title System Context Diagram - .things that Matter

    Person(merchant, "Merchant", "E-commerce business owner who wants to distrib
    Person(consumer, "Consumer", "Online shopper who discovers and purchases pro
    Person(developer, "Developer", "Third-party integrator building Matter-enabl
    Person(aiAgent, "AI Agent", "Autonomous commerce bot that processes product


    System(matterPlatform, ".things that Matter Platform", "Commerce infrastruct

    System_Ext(socialMedia, "Social Media Platforms", "Discord, Telegram, Twitte
    System_Ext(clipApi, "CLIP API (Replicate)", "AI model for semantic vectoriza
    System_Ext(cloudflareR2, "Cloudflare R2", "Object storage CDN")
    System_Ext(merchantStore, "Merchant Storefront", "Original e-commerce platfo
    System_Ext(chromeStore, "Chrome Web Store", "Browser extension distribution"

    Rel(merchant, matterPlatform, "Uploads product catalogs", "HTTPS/JSON")
    Rel(consumer, matterPlatform, "Discovers products via extension", "Browser E
    Rel(developer, matterPlatform, "Integrates via SDK/API", "REST API")
    Rel(aiAgent, matterPlatform, "Reads .thing files efficiently", "Binary Proto

    Rel(matterPlatform, clipApi, "Generates semantic vectors", "HTTPS")
    Rel(matterPlatform, cloudflareR2, "Stores artifacts", "S3 API")
    Rel(matterPlatform, socialMedia, "Distributes polyglot images", "Image Uploa
    Rel(consumer, merchantStore, "Completes purchase", "Redirect")
    Rel(matterPlatform, chromeStore, "Publishes extension", "Store API")
```

Text Representation:



1.2 Container Diagram (Level 2)

Shows the high-level technical building blocks.

```
mermaid
C4Container
    title Container Diagram - .things that Matter Platform


    Person(merchant, "Merchant", "Uploads products")
    Person(consumer, "Consumer", "Discovers products")

    System_Boundary(platform, ".things that Matter Platform") {
        Container(compiler, "Commerce Compiler", "Rust", "Transforms product dat
        Container(shadowIndex, "Shadow Index API", "Node.js/Vercel", "Hash-to-ar
        Container(extension, "Browser Extension (Lens)", "JavaScript/WASM", "Det
        Container(dashboard, "Merchant Dashboard", "Next.js", "Self-service prod
        ContainerDb(supabase, "Database", "PostgreSQL/Supabase", "Stores hash ma
        ContainerDb(redis, "Cache", "Redis Cloud", "Hot lookup caching")
    }

    System_Ext(clipApi, "CLIP API", "Semantic vectorization")
    System_Ext(r2, "Cloudflare R2", "Artifact storage")

    Rel(merchant, dashboard, "Manages products", "HTTPS")
    Rel(dashboard, shadowIndex, "Triggers compilation", "REST API")
    Rel(shadowIndex, compiler, "Invokes", "Function call")
    Rel(compiler, clipApi, "Vectorizes images", "HTTPS")
    Rel(compiler, r2, "Stores artifacts", "S3 API")
    Rel(shadowIndex, supabase, "Reads/Writes", "PostgreSQL")
    Rel(shadowIndex, redis, "Caches lookups", "Redis Protocol")
    Rel(consumer, extension, "Browses web", "Browser")
    Rel(extension, shadowIndex, "Resolves hashes", "HTTPS")
    Rel(extension, r2, "Fetches .thing files", "HTTPS")
```

Text Representation:


.things that Matter Platform
Merchant Dashboard (Next.js)
API
Shadow Index API (Node.js/Vercel)
API
Browser Extension (Lens)
Commerce Compiler (Rust)
Supabase (PostgreSQL)
Redis Cloud (Cache)
Cloudflare R2 (CDN)
CLIP API (Replicate)

2. Use Case Diagrams

2.1 Merchant Use Cases


```
mermaid
graph TB
    subgraph "Merchant Use Cases"
        M((Merchant))

        UC1[Upload Product Catalog]
        UC2[View Compiled Products]
        UC3[Download Polyglot Images]
        UC4[Get matter:// Links]
        UC5[Update Product Prices]
        UC6[View Analytics]
        UC7[Manage API Keys]
        UC8[Batch Compile Products]

        M --> UC1
        M --> UC2
        M --> UC3
        M --> UC4
        M --> UC5
        M --> UC6
        M --> UC7
        M --> UC8

        UC1 -.->|includes| UC8
        UC5 -.->|triggers| UC1
    end
```

Text Representation:



2.2 Consumer Use Cases


```
mermaid
graph TB
    subgraph "Consumer Use Cases"
        C((Consumer))

        UC1[Install Browser Extension]
        UC2[Discover Matter Products]
        UC3[View Product Details]
        UC4[Verify Product Authenticity]
        UC5[Click to Purchase]
        UC6[Share Product with Friends]
        UC7[Configure Extension Settings]
        UC8[View Purchase History]

        C --> UC1
        C --> UC2
        C --> UC3
        C --> UC4
        C --> UC5
        C --> UC6
        C --> UC7
        C --> UC8

        UC2 -.->|includes| UC4
        UC3 -.->|extends| UC5
    end
```

Text Representation:



2.3 Developer Use Cases

```
mermaid
graph TB
    subgraph "Developer Use Cases"
        D((Developer))

        UC1[Access Compilation API]
        UC2[Read .thing Files]
        UC3[Verify Signatures]
        UC4[Perform Semantic Search]
        UC5[Batch Process Products]
        UC6[Integrate SDK]
        UC7[View API Documentation]
        UC8[Monitor API Usage]

        D --> UC1
        D --> UC2
        D --> UC3
        D --> UC4
        D --> UC5
        D --> UC6
        D --> UC7
        D --> UC8

        UC1 -.->|includes| UC3
        UC2 -.->|includes| UC3
    end
```

2.4 AI Agent Use Cases

```
mermaid
graph TB
    subgraph "AI Agent Use Cases"
        A((AI Agent))

        UC1[Parse .thing Files O1]
        UC2[Read Product Fields Directly]
        UC3[Perform Semantic Similarity Search]
        UC4[Verify Product Authenticity]
        UC5[Batch Fetch Catalogs]
        UC6[Estimate Token Usage]
        UC7[Cache Product Data]

        A --> UC1
        A --> UC2
        A --> UC3
        A --> UC4
        A --> UC5
        A --> UC6
        A --> UC7

        UC1 -.->|enables| UC2
        UC5 -.->|includes| UC4
    end
```

---

3. Class Diagrams

3.1 Domain Model - Core Entities

```
mermaid
classDiagram
    class Product {
        +string id
        +byte[] hash
        +uint8 version
        +string title
        +string description
        +uint64 price
        +string currency
        +string sku
        +string imageUrl
        +byte[] thumbnail
        +float[] clipVector
        +string[] categories
        +string[] tags
        +string checkoutUrl
        +string merchantId
        +InventoryStatus inventoryHint
        +uint64 createdAt
        +uint64 expiresAt
        +string sourceUrl
        +byte[] signature
        +byte[] signerPubkey
        +validate() bool
        +toFlatBuffer() byte[]
        +fromFlatBuffer(byte[]) Product
    }

    class ThingFile {
        +uint32 magic
        +uint8 version
        +Product product
        +Gist gist
        +serialize() byte[]
        +deserialize(byte[]) ThingFile
        +verify() bool
    }

    class Gist {
        +string title
        +uint64 price
```

```
    +string currency
    +string imageUrl
    +toJSON() string
}

class InventoryStatus {
    <>
    UNKNOWN
    IN_STOCK
    LOW_STOCK
    OUTOFSTOCK
}


class PolyglotImage {
    +byte[] imageData
    +XMPMetadata xmpBeacon
    +byte[] eofPayload
    +string mimeType
    +embed(ThingFile) PolyglotImage
    +extract() ThingFile
}


class XMPMetadata {
    +string hash
    +string gist
    +uint8 version
    +toXML() string
    +fromXML(string) XMPMetadata
}

class MatterURI {
    +string hash
    +map~string,string~ params
    +toString() string
    +parse(string) MatterURI
}

ThingFile "1" *-- "1" Product
ThingFile "1" *-- "1" Gist
Product "1" --> "1" InventoryStatus
PolyglotImage "1" *-- "1" XMPMetadata
PolyglotImage "1" o-- "1" ThingFile
MatterURI "1" --> "1" ThingFile
```

Text Representation:


DOMAIN MODEL
ThingFile
+magic: uint32
+version: uint8
+product: Product
+gist: Gist
+serialize(): byte[]
+deserialize(): ThingFile
+verify(): bool
PolyglotImage
+imageData: byte[]
+xmpBeacon: XMPMetadata
+eofPayload: byte[]
+mimeType: string
+embed(): PolyglotImage
+extract(): ThingFile
Product
+id: string
+hash: byte[]
+title: string
+description: string
+price: uint64
+currency: string
+clipVector: float[512]
+checkoutUrl: string
+signature: byte[]
+signerPubkey: byte[]
+validate(): bool
+toFlatBuffer(): byte[]
XMPMetadata
+hash: string
+gist: string
+version: uint8
+toXML(): string
+fromXML(): XMPMetadata
MatterURI
+hash: string
+params: map
+toString(): string
+parse(): MatterURI
<>
InventoryStatus
Gist



3.2 Commerce Compiler Architecture

```
mermaid
classDiagram
    class CommerceCompiler {
        -PrivateKey signingKey
        -CLIPClient clipClient
        -Compressor compressor
        -Serializer serializer
        +compile(ProductInput) CompileResult
        +sign(byte[]) Signature
        +verify(byte[], Signature) bool
        +vectorize(Image) float[]
        +embed(ThingFile, Image) PolyglotImage
    }

    class ProductInput {
        +string id
        +string title
        +string description
        +uint64 price
        +string currency
        +string imageUrl
        +string checkoutUrl
        +validate() ValidationResult
    }

    class CompileResult {
        +string hash
        +string thingUrl
        +string imageUrl
        +string matterUri
        +Gist gist
    }

    class CLIPClient {
        -string apiKey
        -string endpoint
        +vectorize(Image) float[]
        +vectorizeText(string) float[]
    }

    class Compressor {
        +compress(byte[]) byte[]
```

```
        +decompress(byte[]) byte[]
    }

    class Serializer {
        +serialize(Product) byte[]
        +deserialize(byte[]) Product
    }

    class CryptoModule {
        +generateKeyPair() KeyPair
        +sign(byte[], PrivateKey) Signature
        +verify(byte[], Signature, PublicKey) bool
        +hash(byte[]) byte[]
    }

    class SteganographyEngine {
        +injectXMP(Image, XMPMetadata) Image
        +appendEOF(Image, byte[]) Image
        +extractXMP(Image) XMPMetadata
        +extractEOF(Image) byte[]
    }

    CommerceCompiler --> CLIPClient
    CommerceCompiler --> Compressor
    CommerceCompiler --> Serializer
    CommerceCompiler --> CryptoModule
    CommerceCompiler --> SteganographyEngine
    CommerceCompiler ..> ProductInput : uses
    CommerceCompiler ..> CompileResult : produces
```

3.3 Browser Extension Architecture

```
mermaid
classDiagram
    class LensExtension {
        +init()
        +destroy()
    }

    class ContentScript {
        -MutationObserver observer
        +startObserving()
        +stopObserving()
        +detectBeacons(Element[])
        +injectOverlay(Product)
    }

    class BackgroundWorker {
        -Cache cache
        +fetchThingFile(string) ThingFile
        +resolveHash(string) ArtifactUrls
        +verifySignature(ThingFile) bool
    }

    class OverlayUI {
        -ShadowRoot shadowRoot
        +render(Product)
        +show()
        +hide()
        +onBuyClick()
    }

    class WASMVerifier {
        +verify(byte[], byte[], byte[]) bool
        +hash(byte[]) byte[]
    }

    class IndexedDBCache {
        +get(string) ThingFile
        +set(string, ThingFile)
        +clear()
        +getExpired() string[]
    }

    class XMPDetector {
        +detect(Image) XMPMetadata
```

```
        +hasBeacon(Image) bool
    }

    class URIHandler {
        +register()
        +handle(string)
        +parse(string) MatterURI
    }

    LensExtension --> ContentScript
    LensExtension --> BackgroundWorker
    LensExtension --> OverlayUI
    ContentScript --> XMPDetector
    ContentScript --> URIHandler
    BackgroundWorker --> WASMVerifier
    BackgroundWorker --> IndexedDBCache
    OverlayUI --> BackgroundWorker
```

---

4. Sequence Diagrams

4.1 Product Compilation Flow

```
mermaid
sequenceDiagram
    participant M as Merchant
    participant D as Dashboard
    participant API as Shadow Index API
    participant C as Commerce Compiler
    participant CLIP as CLIP API
    participant R2 as Cloudflare R2
    participant DB as Supabase

    M->>D: Upload product JSON
    D->>API: POST /v1/compile
    API->>C: compile(productInput)

    C->>C: Validate input schema
    C->>CLIP: POST /vectorize (image)
    CLIP-->>C: 512-dim vector

    C->>C: Compress description (Zstd)
    C->>C: Serialize to FlatBuffers
    C->>C: Calculate SHA-256 hash
    C->>C: Sign with Ed25519


    C->>C: Generate polyglot image
    Note over C: Inject XMP beacon
    Note over C: Append EOF binary


    C->>R2: Upload .thing file
    R2-->>C: thing_url
    C->>R2: Upload polyglot image
    R2-->>C: image_url

    C-->>API: CompileResult
    API->>DB: INSERT hash mapping
    DB-->>API: OK

    API-->>D: { hash, thingurl, imageurl, matter_uri }
    D-->>M: Display compiled product
```

Text Representation:


Merchant
Dashboard
Shadow Index API
Compiler
CLIP API
R2 CDN
Datab
Upload Product
POST /compile
compile()
Validate Input
POST /vectorize
512-dim
Compress, Serialize, Hash, Sign
Generate Polyglot
Upload .thing
Upload image



4.2 Product Discovery Flow (Consumer)

```
mermaid
sequenceDiagram
    participant C as Consumer
    participant B as Browser
    participant CS as Content Script
    participant BW as Background Worker
    participant API as Shadow Index API
    participant R2 as Cloudflare R2
    participant Cache as IndexedDB
    participant Store as Merchant Store

    C->>B: Browse social media
    B->>CS: DOM mutation (new images)
    CS->>CS: Scan for XMP beacons


    alt XMP Beacon Found
        CS->>CS: Extract hash from beacon
        CS->>BW: resolveProduct(hash)


        BW->>Cache: get(hash)
        alt Cache Hit
            Cache-->>BW: Cached ThingFile
        else Cache Miss
            BW->>API: GET /resolve/{hash}
            API-->>BW: { thing_url, gist }
            BW->>R2: GET thing_url
            R2-->>BW: .thing file bytes
            BW->>BW: Verify Ed25519 signature (WASM)
            BW->>Cache: set(hash, thingFile)
        end

        BW-->>CS: Product data
        CS->>CS: Inject Shadow DOM overlay
        CS-->>C: Display product card

        C->>CS: Click "Buy Now"
        CS->>B: Navigate to checkout_url
        B->>Store: Load checkout page
    end
```

Text Representation:


Consumer
Browser
Content Script
Background Worker
Shadow Index API
R2 CDN
Index Cache
Browse Page
DOM Mutation
Scan for XMP Beacons
Extract Hash
resolve Product
Check Cache
[Cache Miss]
GET /resolve
GET .thing
Verify Signature (WASM)
Cache



4.3 AI Agent Efficient Read Flow

```
mermaid
sequenceDiagram
    participant Agent as AI Agent
    participant SDK as Matter SDK
    participant R2 as Cloudflare R2
    participant Local as Local Memory

    Agent->>SDK: fetchProduct(hash)
    SDK->>R2: GET /{hash}.thing
    R2-->>SDK: .thing bytes (memory-mapped)

    SDK->>SDK: Verify signature
    SDK-->>Agent: ThingFile (zero-copy)

    Agent->>SDK: readPrice()
    Note over SDK: Direct byte offset access
    Note over SDK: No parsing required
    SDK-->>Agent: price (O(1) read)

    Agent->>SDK: readClipVector()
    Note over SDK: Direct memory access
    SDK-->>Agent: float[512]

    Agent->>Local: Compare with query vector
    Local-->>Agent: Similarity score

    Note over Agent: Total: ~5ms vs ~500ms for HTML scraping
```

4.4 Batch Compilation Flow

```
mermaid
sequenceDiagram
    participant M as Merchant
    participant API as Shadow Index API
    participant Q as Job Queue
    participant W as Worker
    participant C as Compiler
    participant CLIP as CLIP API
    participant R2 as R2 CDN

    M->>API: POST /v1/batch (1000 products)
    API->>API: Validate batch input
    API->>Q: Enqueue compilation jobs
    API-->>M: { batch_id, status: "processing" }

    loop For each product
        Q->>W: Dequeue job
        W->>C: compile(product)
        C->>CLIP: vectorize(image)
        CLIP-->>C: vector
        C->>C: Process & sign
        C->>R2: Upload artifacts
        W->>Q: Mark complete
    end

    M->>API: GET /v1/batch/{batch_id}
    API-->>M: { status: "complete", results: [...] }
```

---

5. Activity Diagrams

5.1 Product Compilation Pipeline

```
mermaid
flowchart TD
    Start([Start]) --> Validate{Validate Input}
    Validate -->|Invalid| Error1[Return Validation Error]
    Error1 --> End1([End])

    Validate -->|Valid| FetchImage[Fetch Product Image]
    FetchImage -->|Failed| Error2[Return Image Fetch Error]
    Error2 --> End2([End])

    FetchImage -->|Success| Vectorize[Send to CLIP API]
    Vectorize -->|Failed| Error3[Return Vectorization Error]
    Error3 --> End3([End])


    Vectorize -->|Success| Compress[Compress Description with Zstd]
    Compress --> Serialize[Serialize to FlatBuffers]
    Serialize --> Hash[Calculate SHA-256 Hash]
    Hash --> Sign[Sign with Ed25519]


    Sign --> CreateGist[Create Gist Object]
    CreateGist --> InjectXMP[Inject XMP Metadata into Image]
    InjectXMP --> AppendEOF[Append .thing Binary to Image EOF]

    AppendEOF --> UploadThing[Upload .thing to R2]
    UploadThing --> UploadImage[Upload Polyglot Image to R2]
    UploadImage --> IndexHash[Index Hash in Database]

    IndexHash --> GenerateURI[Generate matter:// URI]
    GenerateURI --> Return[Return CompileResult]
    Return --> End4([End])
```

Text Representation:


Start
Validate Input
[Invalid]
[Valid]
Return Error
Fetch Product Image
[Failed]
[Success]
Return Error
Send to CLIP API
Compress with Zstd
Serialize FlatBuffer
Calculate SHA-256



5.2 Product Discovery Activity

```
mermaid
flowchart TD
    Start([User browses page]) --> Observe[MutationObserver detects images]
    Observe --> ScanLoop{More images?}

    ScanLoop -->|Yes| CheckXMP{Has XMP beacon?}
    CheckXMP -->|No| ScanLoop
    CheckXMP -->|Yes| ExtractHash[Extract hash from XMP]

    ExtractHash --> CheckCache{In cache?}
    CheckCache -->|Yes| UseCache[Use cached ThingFile]
    CheckCache -->|No| FetchAPI[Query Shadow Index API]

    FetchAPI --> FetchThing[Fetch .thing from CDN]
    FetchThing --> VerifySig{Signature valid?}

    VerifySig -->|No| ShowWarning[Show warning badge]
    ShowWarning --> ScanLoop

    VerifySig -->|Yes| CacheIt[Cache in IndexedDB]
    CacheIt --> UseCache

    UseCache --> RenderOverlay[Render Shadow DOM overlay]
    RenderOverlay --> ScanLoop

    ScanLoop -->|No| WaitMutation[Wait for DOM changes]
    WaitMutation --> Observe
```

---

6. State Machine Diagrams

6.1 ThingFile Lifecycle States

```
mermaid
stateDiagram-v2
    [*] --> Draft: Product JSON received

    Draft --> Validating: validate()
    Validating --> Invalid: Validation failed
    Validating --> Valid: Validation passed

    Invalid --> [*]: Discard

    Valid --> Processing: compile()
    Processing --> Vectorizing: Fetch CLIP embedding
    Vectorizing --> Compressing: Apply Zstd
    Compressing --> Serializing: Build FlatBuffer
    Serializing --> Signing: Apply Ed25519

    Signing --> Signed: Signature complete

    Signed --> Embedding: Create polyglot image
    Embedding --> Uploading: Push to CDN

    Uploading --> Published: Available on CDN


    Published --> Cached: Fetched by client
    Cached --> Verified: Signature validated
    Cached --> Rejected: Signature invalid


    Verified --> Displayed: Shown to user
    Displayed --> Published: Cache expires

    Rejected --> [*]: Discard

    Published --> Expired: TTL exceeded
    Expired --> [*]: Remove from index
```

Text Representation:


(Start)
Product JSON received
Draft
validate()
Validating
[Failed]
[Passed]
Invalid
Valid
compile()
(End)
Processing
Vectorize
Compress
Serialize
Signing
Signed



6.2 Browser Extension States

```
mermaid
stateDiagram-v2
    [*] --> Idle: Extension loaded

    Idle --> Scanning: Page loaded / DOM changed
    Scanning --> Idle: No beacons found

    Scanning --> BeaconDetected: XMP beacon found
    BeaconDetected --> CheckingCache: Extract hash

    CheckingCache --> CacheHit: Found in IndexedDB
    CheckingCache --> CacheMiss: Not in cache

    CacheMiss --> Fetching: Request from API
    Fetching --> Verifying: .thing received
    Fetching --> Error: Fetch failed

    Verifying --> Verified: Signature valid
    Verifying --> Rejected: Signature invalid

    Verified --> Caching: Store in IndexedDB
    Caching --> CacheHit

    CacheHit --> Rendering: Build overlay
    Rendering --> Displayed: Show to user

    Displayed --> Idle: User scrolls away
    Displayed --> Purchasing: User clicks Buy


    Purchasing --> Redirecting: Open checkout URL
    Redirecting --> Idle: Navigation complete

    Error --> Idle: Retry later
    Rejected --> Idle: Show warning
```


---


7. Data Flow Diagrams

7.1 Level 0 - Context Diagram





7.2 Level 1 - System Processes


DATA FLOW DIAGRAM - LEVEL 1
Product JSON
Merchant
1.0 COMPILE PRODUCT
D1: R2 Storage
URLs
URLs
Hash + Metadata
2.0 INDEX PRODUCT
D2: Database (Supabase)
Indexed Hash
Consumer
Hash
.thing
3.0 RESOLVE PRODUCT
.thing bytes
4.0 VERIFY SIGNATURE
Verified Product



7.3 Level 2 - Compilation Process Detail


DATA FLOW DIAGRAM - LEVEL 2
(Compilation Process)
Product JSON
1.1 VALIDATE INPUT
Valid Product
External Image Server
Image
1.2 FETCH IMAGE
Image Bytes
CLIP API (Replicate)
Vector
1.3 VECTORIZE IMAGE
512-dim Vector
1.4 COMPRESS DESCRIPTION
Compressed Bytes
1.5 SERIALIZE FLATBUFFERS
Binary Buffer



---

8. Entity Relationship Diagram

8.1 Database Schema ERD

```
mermaid
erDiagram
    MERCHANT ||--o{ PRODUCT : owns
    MERCHANT ||--o{ API_KEY : has
    PRODUCT ||--|| THINGFILE : compilesto
    THINGFILE ||--|| POLYGLOTIMAGE : embeds_in
    THINGFILE ||--o{ RESOLUTIONLOG : tracked_by
    PRODUCT ||--o{ PRODUCT_TAG : has
    TAG ||--o{ PRODUCTTAG : appliesto

    MERCHANT {
        uuid id PK
        string name
        string email
        string apikeyhash
        timestamp created_at
        timestamp updated_at
        boolean active
    }

    API_KEY {
        uuid id PK
        uuid merchant_id FK
        string key_hash
        string name
        timestamp created_at
        timestamp expires_at
        boolean active
    }

    PRODUCT {
        uuid id PK
        uuid merchant_id FK
        string external_id
        string title
        text description
        bigint price_cents
        string currency
        string sku
        string image_url
        string checkout_url
        string inventory_status
        timestamp created_at
```

```
    timestamp updated_at
}

THING_FILE {
    string hash PK
    uuid product_id FK
    string thing_url
    string image_url
    string matter_uri
    bytea clip_vector
    bytea signature
    bytea signer_pubkey
    timestamp created_at
    timestamp expires_at
    integer version
}


POLYGLOT_IMAGE {
    string hash PK
    string thing_hash FK
    string cdn_url
    string mime_type
    integer file_size
    boolean xmp_intact
    boolean eof_intact
    timestamp created_at
}


RESOLUTION_LOG {
    uuid id PK
    string thing_hash FK
    string client_ip
    string user_agent
    string referer
    timestamp resolved_at
}

TAG {
    uuid id PK
    string name
    string category
}
```

```
    PRODUCT_TAG {
        uuid product_id FK
        uuid tag_id FK
    }
```

Text Representation:


ENTITY RELATIONSHIP DIAGRAM
MERCHANT
PK id: uuid
name: string
email: string
apikeyhash
createdat
updatedat
active: boolean
API_KEY
PK id: uuid
FK merchant_id: uuid
key_hash: string
name: string
createdat
expiresat
active: boolean
owns
PRODUCT
PK id: uuid
FK merchantid: uuid
externalid
title: string
description: text
pricecents
currency
sku
imageurl
checkouturl
inventory_status
created_at
updated_at
THING_FILE
PK hash: string
FK productid: uuid
thingurl
image_url
matter_uri
clipvector
signature
signer_pubkey
createdat
expiresat
version
embeds_in
has
POLYGLOT_IMAGE
PK hash: string
PRODUCT_TAG



---

9. Deployment Diagram

9.1 Production Infrastructure

```
mermaid
graph TB
    subgraph "Client Layer"
        Browser[Web Browser]
        Extension[Lens Extension]
        Agent[AI Agent]
    end

    subgraph "CDN Layer"
        CF[Cloudflare CDN]
    end

    subgraph "Application Layer - Vercel"
        Dashboard[Merchant Dashboard
Next.js]
        API[Shadow Index API
Edge Functions]
    end

    subgraph "Compute Layer"
        Compiler[Commerce Compiler
Serverless Function]
    end

    subgraph "Data Layer"
        subgraph "Supabase"
            PG[(PostgreSQL)]
            Auth[Auth Service]
        end
        Redis[(Redis Cloud)]
        R2[(Cloudflare R2)]
    end

    subgraph "External Services"
        CLIP[Replicate CLIP API]
        ChromeStore[Chrome Web Store]
    end

    Browser --> CF
    Extension --> CF
    Agent --> CF

    CF --> Dashboard
    CF --> API
```

```
    CF --> R2


    Dashboard --> API
    API --> Compiler
    API --> PG
    API --> Redis


    Compiler --> CLIP
    Compiler --> R2

    Dashboard --> Auth

    Extension -.-> ChromeStore
```

Text Representation:


DEPLOYMENT DIAGRAM
CLIENT LAYER
Web Browser
Lens Extension
AI Agent (Bot)
CDN LAYER
Cloudflare CDN (Edge Network)
APPLICATION LAYER (Vercel)
Merchant Dashboard (Next.js)
Shadow Index API (Edge Functions)


COMPUTE LAYER
Commerce Compiler
(Serverless Function)
DATA LAYER
Supabase
(PostgreSQL)
• Hash mappings
• Metadata
• Analytics
Redis Cloud
(Cache)
• Hot lookups
• Rate limits
Cloudflare R2
(Storage)
• .thing files
• Polyglot imgs
EXTERNAL SERVICES
Replicate API
(CLIP Model)
Chrome Web Store
(Extension)

10. Component Diagrams

10.1 Commerce Compiler Components

```
mermaid
graph TB
    subgraph "Commerce Compiler (matter-core)"
        subgraph "Ingestion Layer"
            Validator[Input Validator
Zod/Pydantic]
            ImageFetcher[Image Fetcher
HTTP Client]
        end

        subgraph "Processing Layer"
            CLIPClient[CLIP Client
Replicate API]
            Compressor[Compressor
Zstd]
            Serializer[Serializer
FlatBuffers]
            Hasher[Hasher
SHA-256]
            Signer[Signer
Ed25519]
        end

        subgraph "Emission Layer"
            StegEngine[Steganography Engine]
            XMPInjector[XMP Injector]
            EOFAppender[EOF Appender]
            URIGenerator[URI Generator
matter://]
        end

        subgraph "Output Layer"
            Uploader[CDN Uploader
R2 Client]
            Indexer[Index Writer
DB Client]
        end
    end

    Validator --> ImageFetcher
    ImageFetcher --> CLIPClient
    CLIPClient --> Compressor
    Compressor --> Serializer
```

```
    Serializer --> Hasher
    Hasher --> Signer
    Signer --> StegEngine
    StegEngine --> XMPInjector
    XMPInjector --> EOFAppender
    EOFAppender --> URIGenerator
    URIGenerator --> Uploader
    Uploader --> Indexer
```

10.2 Browser Extension Components

```
mermaid
graph TB
    subgraph "Browser Extension (Lens)"
        subgraph "Content Script"
            DOMObserver[DOM Observer
MutationObserver]
            XMPDetector[XMP Detector
Image Scanner]
            URIHandler[URI Handler
matter:// Protocol]
            OverlayManager[Overlay Manager
Shadow DOM]
        end

        subgraph "Background Worker"
            APIClient[API Client
Fetch]
            WASMVerifier[WASM Verifier
libmatter.wasm]
            CacheManager[Cache Manager
IndexedDB]
            StateManager[State Manager]
        end

        subgraph "UI Components"
            ProductCard[Product Card]
            SettingsPage[Settings Page]
            WarningBadge[Warning Badge]
        end
    end

    DOMObserver --> XMPDetector
    XMPDetector --> StateManager
    URIHandler --> StateManager
    StateManager --> CacheManager
    StateManager --> APIClient
    APIClient --> WASMVerifier
    WASMVerifier --> CacheManager
    CacheManager --> OverlayManager
    OverlayManager --> ProductCard
    OverlayManager --> WarningBadge
```

10.3 Shadow Index API Components

```
mermaid
graph TB
    subgraph "Shadow Index API"
        subgraph "API Routes"
            CompileRoute[POST /compile]
            BatchRoute[POST /batch]
            ResolveRoute[GET /resolve/:hash]
            GistRoute[GET /gist/:hash]
            HealthRoute[GET /health]
        end

        subgraph "Middleware"
            AuthMiddleware[Authentication
API Key Validation]
            RateLimiter[Rate Limiter
Token Bucket]
            Validator[Request Validator
Zod Schema]
            ErrorHandler[Error Handler]
        end

        subgraph "Services"
            CompilerService[Compiler Service]
            ResolverService[Resolver Service]
            CacheService[Cache Service
Redis]
            StorageService[Storage Service
R2]
        end

        subgraph "Data Access"
            DBClient[Database Client
Supabase]
            RedisClient[Redis Client]
            R2Client[R2 Client]
        end
    end

    CompileRoute --> AuthMiddleware
    BatchRoute --> AuthMiddleware
    ResolveRoute --> RateLimiter
    GistRoute --> RateLimiter
```

```
    AuthMiddleware --> Validator
    RateLimiter --> Validator
    Validator --> ErrorHandler

    ErrorHandler --> CompilerService
    ErrorHandler --> ResolverService

    CompilerService --> StorageService
    CompilerService --> DBClient
    ResolverService --> CacheService
    CacheService --> RedisClient
    StorageService --> R2Client
```

---

11. Appendix: Diagram Legend

Symbol Reference

Symbol	Meaning
▢	System/Container
○	Actor/User
◇	Decision Point
═══	Data Flow
———	Control Flow

◆	Composition
◇	Aggregation
—▶	Dependency
– –▶	Optional/Async

Color Coding (for rendered Mermaid)

Color	Meaning
---	---
Blue	Core System Components
Green	External Services
Orange	Data Stores
Purple	User Interfaces
Red	Security Components

---

12. Document Control

Version	Date	Author	Changes

1.0	Jan 21, 2026	M. Mboweni	Initial comprehensive diagrams

Document Version: 1.0 **Last Updated:** January 21, 2026 **Related Documents:** 01-PROJECT-CHARTER, 02-TECHNICAL-ARCHITECTURE, 03-PRD