Clojure Cheat Sheet (Clojure 1.3 - 1.5, sheet v9)

Documentation

clojure.repl/ doc find-doc apropos source pst javadoc (foo.bar/ is namespace for later syms)

Primitives

Numbers

Literals Long: 7, hex 0xff, oct 017, base 2 2r1011, base 36 36rCRAZY BigInt: 7N Ratio: -22/7 Double: 2.78

-1.2e-5 BigDecimal: 4.2M

Arithmetic + - * / quot rem mod inc dec max min

= == not= < > <= >= compare Compare

Bitwise bit-{and, or, xor, not, flip, set, shift-right,

shift-left, and-not, clear, test}

byte short int long float double bigdec bigint Cast

num rationalize biginteger

Test nil? identical? zero? pos? neg? even? odd?

Random rand rand-int BigDecimal with-precision

Unchecked *unchecked-math* unchecked-{add, dec, divide,

inc, multiply, negate, remainder, subtract}-int

Strings

Create str format See also IO/to string

Use count get subs compare (clojure.string/) join escape split split-lines replace replace-first reverse (1.5) re-quote-replacement (String) .indexOf

.lastIndexOf

Regex #"pattern" re-find re-seq re-matches re-pattern

re-matcher re-groups (clojure.string/) replace replace-first (1.5) re-quote-replacement

Letters ${\sf (clojure.string/)\ capitalize\ lower-case\ upper-case}$ Trim (clojure.string/) trim trim-newline triml trimr

char char? string? (clojure.string/) blank? Test

Other

Characters char char-name-string char-escape-string

keyword keyword? find-keyword Keywords

Symbols symbol symbol? gensym

Collections

Collections

Generic ops count empty not-empty into conj (clojure.walk/)

walk prewalk prewalk-demo prewalk-replace postwalk postwalk-demo postwalk-replace

Content tests distinct? empty? every? not-every? some

not-any?

Capabilities sequential? associative? sorted? counted?

reversible?

Type tests coll? list? vector? set? map? seq?

Lists

Create '() list list*

Examine first nth peek .indexOf .lastIndexOf

'Change' cons conj rest pop

Vectors

[] vector vec vector-of Create

Examine (my-vec idx) \rightarrow (nth my-vec idx) get peek

.indexOf .lastIndexOf

'Change' assoc pop subvec replace conj rseq

Ops (1.4) mapv filterv reduce-kv

Sets

Create #{} set hash-set sorted-set sorted-set-by Examine (my-set item) ightarrow (get my-set item) contains?

'Change' conj disj

Rel algebra (clojure.set/) join select project union difference

intersection

Get map (clojure.set/) index rename-keys rename map-invert

Test (clojure.set/) subset? superset?

Maps

Create {} hash-map array-map zipmap sorted-map

sorted-map-by bean frequencies group-by

Examine (:key my-map) \rightarrow (get my-map :key) get-in

contains? find keys vals

assoc assoc-in dissoc merge merge-with 'Change'

select-keys update-in

key val Entry

Sorted maps rseq subseq rsubseq

Transients (clojure.org/transients)

Create transient persistent!

Change conj! pop! assoc! dissoc! disj! Note: always use return

value for later changes, never original!

Misc

= == identical? not= not compare clojure.data/diff Compare

true? false? nil? instance? Test

Sequences

Creating a Lazy Seq

From collection seq vals keys rseq subseq rsubseq

From producer fn lazy-seq repeatedly iterate From constant repeat range

From other file-seq line-seq resultset-seq

re-seq tree-seq xml-seq iterator-seq

enumeration-seq

From seq keep keep-indexed

Seq in, Seq out

Get shorter distinct filter remove take-nth for Get longer

cons conj concat lazy-cat mapcat cycle

interleave interpose

Tail-items rest nthrest fnext nnext drop drop-while

take-last for

Head-items

take take-while butlast drop-last for 'Change' conj concat distinct flatten group-by

> partition partition-all partition-by split-at split-with filter remove replace shuffle

Rearrange reverse sort sort-by compare

Process items map pmap map-indexed mapcat for replace seque

Using a Seq

Extract item first second last rest next ffirst nfirst

fnext nnext nth nthnext rand-nth when-first

max-kev min-kev

Construct coll zipmap into reduce reductions set vec

into-array to-array-2d

Pass to fn apply Search some filter

Force evaluation doseq dorun doall Check for forced realized?

Zippers (clojure.zip/)

Create zipper seq-zip vector-zip xml-zip Get loc up down left right leftmost rightmost

Get seg lefts rights path children

'Change' make-node replace edit insert-child insert-left

insert-right append-child remove

Move next prev

Misc root node branch? end?

10

to writer

Open

Binary

spit slurp (to writer/from reader, Socket, string with to/from

file name, URI, etc.)

to *out* pr prn print printf println newline (clojure.pprint/) print-table

> (clojure.pprint/) pprint cl-format also: (binding [*out* writer] ...)

format with-out-str pr-str prn-str print-str to string

println-str

from *in* read-line (clojure.tools.reader.edn/) read from reader line-seq (clojure.tools.reader.edn/) read also:

(binding [*in* reader] ...) java.io.Reader from string ${\tt with-in-str~(clojure.tools.reader.edn/)~read-string}$

with-open (clojure.java.io/) text: reader writer binary: input-stream output-stream

(.write ostream byte-arr) (.read istream byte-arr) java.io.OutputStream

java.io.InputStream GitHub: gloss byte-spec Misc flush (.close s) file-seq *in* *out* *err*

(clojure.java.io/) file copy delete-file resource as-file as-url as-relative-path GitHub: fs

(1.4) *data-readers* default-data-readers (1.5)

default-data-reader-fn

Functions

Data readers

fn defn defn- definline identity constantly memfn Create comp complement partial juxt memoize fnil every-pred

some-fn

Call apply -> ->> (1.5) as-> cond-> cond->> some->

some->> fn? ifn?

Abstractions

Protocols (clojure.org/protocols) Define (defprotocol Slicey (slice [at]))

(extend-type String Slicey (slice [at] ...)) Extend Extend null (extend-type nil Slicey (slice [_] nil))

Reifv (reify Slicey (slice [at] ...))

Records (clojure.org/datatypes)

(defrecord Pair [h t]) Define (:h (Pair. 1 2)) ightarrow 1 Access Create Pair. ->Pair map->Pair

Types (clojure.org/datatypes)

Define (deftype Pair [h t]) (.h (Pair. 1 2)) \rightarrow 1 Access Pair. ->Pair Create

(deftype Pair [h t]

With methods Object

(toString [this] (str "<" h "," t ">")))

Multimethods (clojure.org/multimethods)

Define (defmulti my-mm dispatch-fn)

(defmethod my-mm :dispatch-value [args] ...) Method define

Dispatch get-method methods

Remove remove-method remove-all-methods

Prefer prefer-method prefers

Relation derive isa? parents ancestors descendants

make-hierarchy

Macros

Loop

Create defmacro definline

Debug macroexpand-1 macroexpand (clojure.walk/)

macroexpand-all

and or when when-not when-let when-first if-not Branch

if-let cond condp case for doseq dotimes while

Arrange .. doto -> ->> (1.5) as-> cond-> cond->> some->

some->>

Scope binding locking time with-{in-str, local-vars, open, out-str, precision, redefs, redefs-fn}

lazy-cat lazy-seq delay Lazv Doc. assert comment doc

Reader Macros

Quote 'form \rightarrow (quote form)

١ Character literal

Single line comment ;

Metadata (see Metadata section)

Deref @form \rightarrow (deref form) 0

Syntax-quote Unquote

~@ Unquote-splicing Regex Pattern p

#"p" #/ Var quote $\#' \times \to (\text{var } \times)$ $\#(...) \rightarrow (\mathsf{fn} \; [\mathsf{args}] \; (...))$ #()

Ignore next form

Metadata (clojure.org/special_forms)

General ^{:key1 val1 :key2 val2 ...}

Abbrevs ^Type ightarrow ^{:tag Type}, ^:key ightarrow ^{:key true}

^:dynamic ^:private ^:doc ^:const Common

(defn ^:private ^String my-fn ...) Examples (def

^:dynamic *dyn-var* val)

On Vars meta with-meta vary-meta alter-meta! reset-meta!

doc find-doc test

Special Forms (clojure.org/special_forms)

def if do let quote var fn loop recur throw try

monitor-enter monitor-exit

Binding Forms / (examples) let fn defn defmacro loop for

doseq if-let when-let Destructuring

Vars and global environment (clojure.org/vars)

def defn defn- definline defmacro defmethod Def variants

defmulti defonce defrecord

Interned vars declare intern binding find-var var Var objects with-local-vars var-get var-set alter-var-root

var?

Var validators set-validator! get-validator Namespace

Current *ns*

(tutorial) ns in-ns create-ns $\mathsf{Create}/\mathsf{Switch}$ Add alias def import intern refer Find

all-ns find-ns

ns-{name, aliases, map, interns, publics, Examine

refers, imports}

From symbol resolve ns-resolve namespace ns-unalias ns-unmap remove-ns Remove

Loading

Load libs (tutorial) require use import refer

List loaded loaded-libs

Load misc load load-file load-reader load-string

Concurrency

Atoms atom swap! reset! compare-and-set!

Futures future future-{call, done?, cancel, cancelled?}

future?

Threads bound-fn bound-fn* {get, push, pop}-thread-bindings

thread-bound?

Misc locking pcalls pvalues pmap seque promise deliver

Refs and Transactions (clojure.org/refs)

Create ref

Examine $\texttt{deref @ (@form} \rightarrow (\mathsf{deref form}))$

Transaction sync dosync io!

In transaction ensure ref-set alter commute Validators set-validator! get-validator

ref-history-count ref-{min, max}-history History

Agents and Asynchronous Actions (clojure.org/agents)

Create agent

Examine agent-error

Change state send send-off restart-agent (1.5)

send-via set-agent-send-executor! set-agent-send-off-executor!

Block waiting await await-for

set-validator! get-validator Ref validators Watchers add-watch remove-watch

Thread handling shutdown-agents

Error error-handler set-error-handler! error-mode

set-error-mode!

Misc *agent* release-pending-sends

Java Interoperation (clojure.org/java_interop)

General .. doto Classname/ Classname. new bean comparator enumeration-seq import iterator-seq

memfn set!

Cast boolean byte short char int long float double

bigdec bigint num cast biginteger

Exceptions throw try catch finally pst (1.4) ex-info

ex-data

Arravs

make-array {object, boolean, byte, short, char, Create

int, long, float, double}-array aclone to-array

to-array-2d into-array

Use aget aset aset-{boolean, byte, short, char, int,

long, float, double} alength amap areduce Cast

booleans bytes shorts chars ints longs floats doubles

Proxy

Create proxy get-proxy-class {construct, init}-proxy Misc

proxy-mappings proxy-super update-proxy

Other

Code

/ Shell

XML clojure.xml/parse xml-seq

REPL *1 *2 *3 *e *print-dup* *print-length*

print-level *print-meta* *print-readably*

compile-files *compile-path* *file* *warn-on-reflection* compile gen-class

gen-interface loaded-libs test

Misc eval force hash name *clojure-version* clojure-version *command-line-args*

(clojure.java.browse/) browse-url (clojure.java.shell/) sh Browser

with-sh-dir with-sh-env