Clojure Cheat Sheet (Clojure 1.3 - 1.6, sheet v18)

Documentation

clojure.repl/ doc find-doc apropos source pst javadoc (foo.bar/

is namespace for later syms)

Primitives

Numbers Literals

Long: 7, hex Oxff, oct 017, base 2 2r1011, base

36 36rCRAZY BigInt: 7N Ratio: -22/7 Double: 2.78

-1.2e-5 BigDecimal: 4.2M

+ - * / quot rem mod inc dec max min +' -' *' inc' Arithmetic

dec,

Compare = == not= < > <= >= compare

Bitwise bit-and bit-or bit-xor bit-not bit-flip bit-set bit-shift-right bit-shift-left bit-and-not bit-clear bit-test (1.6) unsigned-bit-shift-right

(see BigInteger for integers larger than Long) byte short int long float double bigdec bigint num

rationalize biginteger

zero? pos? neg? even? odd? number? rational? Test

integer? ratio? decimal? float?

Random rand rand-int BigDecimal with-precision

Unchecked *unchecked-math* unchecked-add unchecked-dec

unchecked-inc unchecked-multiply unchecked-negate

unchecked-subtract

Strings

Cast

Create $\operatorname{\mathtt{str}}$ format See also $\operatorname{IO}/\operatorname{\mathtt{to}}$ string

Use count get subs compare (clojure.string/) join escape split split-lines replace replace-first reverse (1.5) re-quote-replacement (String) .indexOf .lastIndexOf

#"pattern" re-find re-seq re-matches re-pattern Regex ${\tt re-matcher\ re-groups\ (clojure.string/)\ replace}$

replace-first (1.5) re-quote-replacement Letters (clojure.string/) capitalize lower-case upper-case Trim (clojure.string/) trim trim-newline triml trimr Test char char? string? (clojure.string/) blank? (String)

.startsWith .endsWith .contains

Other

Characters char char-name-string char-escape-string

keyword keyword? find-keyword Keywords Symbols symbol symbol? gensym

Collections

Collections

count empty not-empty into conj (clojure.walk/) Generic ops

walk prewalk prewalk-demo prewalk-replace postwalk postwalk-demo postwalk-replace

Content tests distinct? empty? every? not-every? some not-any? Capabilities sequential? associative? sorted? counted?

reversible?

coll? list? vector? set? map? seq? (1.6) record? Type tests

Lists

Create '() list list*

first nth peek .indexOf .lastIndexOf Examine

'Change cons conj rest pop

Vectors

Create [] vector vec vector-of

Examine (my-vec idx) \rightarrow (nth my-vec idx) get peek .indexOf

'Change' assoc pop subvec replace coni rsed Ops (1.4) mapv filterv reduce-kv

Sets

Create #{} set hash-set sorted-set sorted-set-by Examine (my-set item) \rightarrow (get my-set item) contains?

'Change' conj disj

Set ops (clojure.set/) union difference intersection select See

also Relations

Test (clojure.set/) subset? superset?

Maps

Create {} hash-map array-map zipmap sorted-map

sorted-map-by bean frequencies group-by (clo-

jure.set/) index

Examine (:key my-map) \rightarrow (get my-map :key) get-in

contains? find keys vals

assoc assoc-in dissoc merge merge-with 'Change'

select-keys update-in (clojure.set/) rename-keys

map-invert GitHub: Medley

Entry key val

Sorted maps rseq subseq rsubseq Relations (set of maps, each with same keys, aka rels)

(clojure.set/) join select project union difference Rel algebra

intersection index rename

Transients (clojure.org/transients)

Create transient persistent!

Change conj! pop! assoc! dissoc! disj! Note: always use return

value for later changes, never original!

Misc

= == identical? not= not compare clojure.data/diff

Test true? false? instance? nil? (1.6) some?

Sequences

Compare

Creating a Lazy Seq

From collection seq vals keys rseq subseq rsubseq From producer fn lazy-seq repeatedly iterate

From constant repeat range

From other file-seq line-seq resultset-seq re-seq tree-seq xml-seq iterator-seq enumeration-seq

keep keep-indexed From seg

Seq in, Seq out

distinct filter remove take-nth for Get shorter cons conj concat lazy-cat mapcat cycle Get longer

interleave interpose

rest nthrest next fnext nnext drop drop-while Tail-items

take-last for

Head-items take take-while butlast drop-last for

conj concat distinct flatten group-by partition 'Change' partition-all partition-by split-at split-with

filter remove replace shuffle Rearrange reverse sort sort-by compare

map pmap map-indexed mapcat for replace seque Process items

Using a Sea

Extract item first second last rest next ffirst nfirst

fnext nnext nth nthnext rand-nth when-first

max-key min-key

Construct coll zipmap into reduce reductions set vec

into-array to-array-2d

Pass to fn apply some filter Search Force evaluation doseq dorun doall

Check for forced realized?

Zippers (clojure.zip/)

Create zipper seq-zip vector-zip xml-zip Get loc up down left right leftmost rightmost

lefts rights path children Get sea

make-node replace edit insert-child insert-left 'Change

insert-right append-child remove

Move next prev

Misc root node branch? end?

IO

to *out*

to/from spit slurp (to writer/from reader, Socket, string with file name, URI, etc.)

pr prn print printf println newline (clo-

jure.pprint/) print-table to writer

(clojure.pprint/) pprint cl-format also: (binding

[*out* writer] ...) format with-out-str pr-str prn-str print-str to string

println-str

from *in* read-line (clojure.tools.reader.edn/) read

line-seq (clojure.tools.reader.edn/) read also: from reader (binding [*in* reader] ...) java.io.Reader

with-in-str (clojure.tools.reader.edn/) read-string from string Open

with-open (clojure.java.io/) text: reader writer binary: input-stream output-stream (.write ostream byte-arr) (.read

istream byte-arr) java.io.OutputStream java.io.InputStream GitHub: gloss byte-spec flush (.close s) file-seq *in* *out* *err*

(clojure.java.io/) file copy delete-file resource as-file as-url as-relative-path GitHub: fs (1.4) *data-readers* default-data-readers (1.5)

default-data-reader-fn

Functions

Data readers

Binary

Misc

fn defn defn- definline identity constantly memfn Create comp complement partial juxt memoize fnil every-pred

some-fn

Call apply -> ->> trampoline (1.5) as-> cond->>

some-> some->>

fn? ifn?

Abstractions (Clojure type selection flowchart) Namespace Protocols (clojure.org/protocols) Current Create/Switch (tutorial) ns in-ns create-ns Define (defprotocol Slicey (slice [at])) Add alias def import intern refer Extend (extend-type String Slicey (slice [at] ...)) (extend-type nil Slicey (slice [_] nil)) Find all-ns find-ns Extend null Examine ns-name ns-aliases ns-map ns-interns ns-publics Reifv (reify Slicey (slice [at] ...)) ns-refers ns-imports Test satisfies? extends? From symbol resolve ns-resolve namespace the-ns Other extend extend-protocol extenders Remove ns-unalias ns-unmap remove-ns Records (clojure.org/datatypes) Loading Define (defrecord Pair [h t]) (:h (Pair. 1 2)) \rightarrow 1 Load libs Access (tutorial) require use import refer Pair. ->Pair map->Pair List loaded Create loaded-libs record? Test Load misc load load-file load-reader load-string Types (clojure.org/datatypes) Concurrency Define (deftype Pair [h t]) Atoms atom swap! reset! compare-and-set! Access (.h (Pair. 1 2)) \rightarrow 1 **Futures** future future-call future-done? future-cancel Create Pair. ->Pair future-cancelled? future? (deftype Pair [h t] Threads $\verb|bound-fn bound-fn*| get-thread-bindings|$ With methods Object push-thread-bindings pop-thread-bindings (toString [this] (str "<" h "," t ">"))) thread-bound? Misc locking pcalls pvalues pmap seque promise deliver Multimethods (clojure.org/multimethods) (defmulti my-mm dispatch-fn) Refs and Transactions (clojure.org/refs) Method define (defmethod my-mm :dispatch-value [args] ...) Create ref Dispatch get-method methods Examine $deref @ (@form \rightarrow (deref form))$ Remove remove-method remove-all-methods Transaction sync dosync io! Prefer prefer-method prefers In transaction ensure ref-set alter commute Relation derive isa? parents ancestors descendants Validators set-validator! get-validator make-hierarchy History ref-history-count ref-min-history ref-max-history Macros Agents and Asynchronous Actions (clojure.org/agents) Create defmacro definline Create agent Debug macroexpand-1 macroexpand (clojure.walk/) Examine agent-error macroexpand-all send send-off restart-agent (1.5) Change state Branch and or when when-not when-let when-first if-not send-via set-agent-send-executor! if-let cond condp case (1.6) when-some if-some set-agent-send-off-executor! Loop for doseq dotimes while Block waiting await await-for .. doto -> ->> (1.5) as-> cond-> cond->> some-> Arrange Ref validators set-validator! get-validator some->> Watchers add-watch remove-watch Scope binding locking time with-in-str with-local-vars Thread handling shutdown-agents with-open with-out-str with-precision with-redefs Frror error-handler set-error-handler! error-mode with-redefs-fn set-error-mode! Lazy lazy-cat lazy-seq delay Misc *agent* release-pending-sends assert comment doc Java Interoperation (clojure.org/java_interop) Reader Macros (clojure.org/reader) .. doto Classname/ Classname. new bean comparator quote: 'form \rightarrow (quote form) enumeration-seq import iterator-seq memfn set! class class? bases supers type ١ Character literal Single line comment Cast boolean byte short char int long float double ; Metadata (see Metadata section) bigdec bigint num cast biginteger throw try catch finally pst (1.4) ex-info ex-data ${\tt Deref:\ @form\ }\rightarrow\ (\ {\tt deref\ form})$ Exceptions Svntax-quote Arrays Unquote make-array object-array boolean-array byte-array ~@ Unquote-splicing short-array char-array int-array long-array Regex Pattern p (see Strings/Regex section) #"p" float-array double-array aclone to-array to-array-2d ${\tt Var-quote} \ {\tt \#'x} \ \to \ (\ {\tt var} \ {\tt x})$ #() Anonymous function literal: $\#(\ldots) \to (fn [args] (\ldots))$ into-array Use aget aset aset-boolean aset-byte aset-short aset-char Ignore next form aset-int aset-long aset-float aset-double alength amap Metadata (clojure.org/reader, special_forms) Cast booleans bytes shorts chars ints longs floats doubles General ^{:key1 val1 :key2 val2 ...} Proxy (Clojure type selection flowchart) ^Type \rightarrow ^{:tag Type}, ^:key \rightarrow ^{:key true} ^:dynamic ^:private ^:doc ^:const Abbrevs proxy get-proxy-class construct-proxy init-proxy Create Common Misc proxy-mappings proxy-super update-proxy (defn ^:private ^String my-fn ...) (def ^:dynamic Examples *dyn-var* val) Other On Vars meta with-meta vary-meta alter-meta! reset-meta! doc XMI cloiure.xml/parse xml-seq find-doc test REPL *1 *2 *3 *e *print-dup* *print-length* *print-level* *print-meta* *print-readably*

Code

Misc

Browser

compile-files *compile-path* *file*

eval force hash name *clojure-version*

clojure-version *command-line-args*

loaded-libs test

with-sh-dir with-sh-env

warn-on-reflection compile gen-class gen-interface

(clojure.java.browse/) browse-url (clojure.java.shell/) sh

Special Forms (clojure.org/special_forms)

def if do let letfn quote var fn loop recur throw try monitor-enter monitor-exit Binding Forms / (examples) let fn defn defmacro loop for doseq Destructuring if-let when-let (1.6) if-some when-some

Vars and global environment (clojure.org/vars)

Def variants

def defn defn- definline defmacro defmethod
defmulti defonce defrecord

Interned vars

Var objects

with-local-vars var-get var-set alter-var-root
var? bound? thread-bound?

Var validators

set-validator! get-validator