Clojure Cheat Sheet (Clojure 1.3 - 1.6, sheet v22)

clojure.repl/ doc find-doc apropos source pst javadoc (foo.bar/ is

namespace for later syms)

Primitives

Numbers

Long: 7, hex 0xff, oct 017, base 2 2r1011, base 36 Literals

36rCRAZY BigInt: 7N Ratio: -22/7 Double: 2.78 -1.2e-5

BigDecimal: 4.2M

Arithmetic + - * / quot rem mod inc dec max min +' -' *' inc'

dec'

== < > <= >= compare Compare

bit-and bit-or bit-xor bit-not bit-flip bit-set Bitwise

bit-shift-right bit-shift-left bit-and-not bit-clear bit-test (1.6) unsigned-bit-shift-right (see

BigInteger for integers larger than Long) Cast byte short int long float double bigdec bigint num

rationalize biginteger

zero? pos? neg? even? odd? number? rational? integer? Test

ratio? decimal? float?

Random rand rand-int BigDecimal with-precision

Unchecked

unchecked-math unchecked-add unchecked-dec unchecked-inc unchecked-multiply unchecked-negate

unchecked-subtract

Strings

str format "a string" "escapes $\b f \n \ \ 377$ Create

hex \ucafe" See also IO/to string

Use count get subs compare (clojure.string/) join escape split split-lines replace replace-first reverse (1.5) ${\tt re-quote-replacement~(String)~.indexOf~.lastIndexOf}$

Regex #"pattern" re-find re-seq re-matches re-pattern re-matcher

re-groups (clojure.string/) replace replace-first (1.5)

re-quote-replacement

 ${\sf (clojure.string/)\ capitalize\ lower-case\ upper-case}$ Letters (clojure.string/) trim trim-newline triml trimr char char? string? (clojure.string/) blank? (String) Trim Test

.startsWith .endsWith .contains

Other

char char-name-string char-escape-string literals: \a Characters

\newline (more at link)

keyword keyword? find-keyword literals: :kw :my.ns/kw Keywords

::in-cur-ns

Symbols symbol symbol? gensym literals: my-sym my.ns/foo

Misc literals: true false nil

Collections

Collections

count empty not-empty into conj (clojure.walk/) walk Generic ops

prewalk prewalk-demo prewalk-replace postwalk

postwalk-demo postwalk-replace

Content tests distinct? empty? every? not-every? some not-any? sequential? associative? sorted? counted? reversible? Capabilities Type tests coll? list? vector? set? map? seq? (1.6) record?

Lists

Create '() list list*

 $\verb|first nth peek .indexOf .lastIndexOf| \\$ Examine

'Change cons conj rest pop

Vectors

Create [] vector vec vector-of (1.4) mapv filterv

Examine (my-vec idx) \rightarrow (nth my-vec idx) get peek .indexOf

.lastIndexOf

'Change' assoc pop subvec replace conj rseq

Ops (1.4) reduce-kv

Sets

Create #{} set hash-set sorted-set sorted-set-by (flat-

land.ordered.set/) ordered-set

Examine $(my\text{-set item}) \rightarrow (\text{get my-set item}) \text{ contains}?$ conj disj 'Change

(clojure.set/) union difference intersection select See Set ops

also Relations

(clojure.set/) subset? superset? Test

Sorted sets rseq subseq rsubseq

Maps

Create {} hash-map array-map zipmap sorted-map sorted-map-by bean frequencies group-by (clojure.set/) index (flat-

 $land.ordered.map/) \ \, ordered-map \ \, (clojure.data.priority-map/)$ priority-map (flatland.useful.map/) ordering-map

Examine (my-map k) \rightarrow (get my-map k) also (:key my-map) \rightarrow (get my-map :key) get-in contains? find keys vals

'Change assoc assoc-in dissoc merge merge-with select-keys update-in (clojure.set/) rename-keys map-invert GitHub:

Medley

Ops (1.4) reduce-kv

Entry key val

Sorted maps rseq subseq rsubseq Relations (set of maps, each with same keys, aka rels)

transient persistent!

(clojure.set/) join select project union difference Rel algebra

intersection index rename

Transients (clojure.org/transients)

Change conj! pop! assoc! dissoc! disj! Note: always use return value

for later changes, never original!

Misc

Create

Compare = identical? not= not compare clojure.data/diff

Test true? false? instance? nil? (1.6) some?

Sequences

Creating a Lazy Seq

From collection seq vals keys rseq subseq rsubseq From producer fn lazy-seq repeatedly iterate

From constant repeat range

file-seq line-seq resultset-seq re-seq tree-seq From other

xml-seq iterator-seq enumeration-seq

keep keep-indexed From seq

Seq in, Seq out

Get shorter distinct filter remove take-nth for

Get longer cons conj concat lazy-cat mapcat cycle interleave

interpose

Tail-items rest nthrest next fnext nnext drop drop-while

take-last for

Head-items take take-while butlast drop-last for

'Change' conj concat distinct flatten group-by partition

partition-all partition-by split-at split-with filter

remove replace shuffle reverse sort sort-by compare

Rearrange Process items map pmap map-indexed mapcat for replace seque

Using a Seq

Extract item first second last rest next ffirst nfirst fnext

nnext nth nthnext rand-nth when-first max-key

min-key

Construct coll zipmap into reduce reductions set vec into-array

to-array-2d (1.4) mapv filterv

Pass to fn apply Search some filter Force evaluation doseq dorun doall Check for forced realized?

Zippers (clojure.zip/)

Create zipper seq-zip vector-zip xml-zip Get loc up down left right leftmost rightmost

Get sea lefts rights path children

'Change make-node replace edit insert-child insert-left

insert-right append-child remove

Move next prev

Misc root node branch? end?

10

to writer

from reader

to/from spit slurp (to writer/from reader, Socket, string with file

name, URI. etc.)

to *out* pr prn print printf println newline (clojure.pprint/) print-table

(clojure.pprint/) pprint cl-format also: (binding [*out* writer] ...)

format with-out-str pr-str prn-str print-str to string

println-str

from *in* read-line (clojure.tools.reader.edn/) read

line-seq (clojure.tools.reader.edn/) read also: (binding

[*in* reader] ...) java.io.Reader with-in-str (clojure.tools.reader.edn/) read-string from string Open

with-open (clojure.java.io/) text: reader writer binary: input-stream output-stream

(.write ostream byte-arr) (.read istream byte-arr) Binary java.io.OutputStream java.io.InputStream GitHub: gloss

byte-spec

flush (.close s) file-seq *in* *out* *err* (clojure.java.io/) file copy delete-file resource as-file

as-url as-relative-path GitHub: fs

Data readers (1.4) *data-readers* default-data-readers (1.5)

default-data-reader-fn

Functions

Call

Misc

Create fn defn- definline identity constantly memfn comp

complement partial juxt memoize fnil every-pred some-fn apply -> ->> trampoline (1.5) as-> cond-> cond->> some->

some->>

Test fn? ifn?

Abstractions (Clojure type selection flowchart)

Protocols (clojure.org/protocols)

(defprotocol Slicey (slice [at])) Define Extend (extend-type String Slicey (slice [at] ...)) (extend-type nil Slicey (slice [_] nil)) Extend null (reify Slicey (slice [at] ...)) Reify

satisfies? extends? Test extend extend-protocol extenders Other

Records (clojure.org/datatypes)

Define (defrecord Pair [h t]) (:h (Pair. 1 2)) \rightarrow 1 Access Pair. ->Pair map->Pair Create

record? Test

Types (clojure.org/datatypes)

Define (deftype Pair [h t]) (.h (Pair. 1 2)) \rightarrow 1 Access Pair. ->Pair Create (deftype Pair [h t]

With methods Object

(toString [this] (str "<" h "," t ">")))

Multimethods (clojure.org/multimethods)

(defmulti my-mm dispatch-fn) Define

Method define (defmethod my-mm :dispatch-value [args] ...)

Dispatch get-method methods

Remove remove-method remove-all-methods

Prefer prefer-method prefers

Relation derive isa? parents ancestors descendants

make-hierarchy

Macros

Create defmacro definline

Debug macroexpand-1 macroexpand (clojure.walk/) macroexpand-all Branch and or when when-not when-let when-first if-not if-let

cond condp case (1.6) when-some if-some

Loop for doseq dotimes while

Arrange . doto -> ->> (1.5) as-> cond-> some-> some->> Scope

binding locking time with-in-str with-local-vars

with-open with-out-str with-precision with-redefs

with-redefs-fn

lazy-cat lazy-seq delay Lazy assert comment doc Doc.

Reader Macros (clojure.org/reader)

quote: 'form o (quote form)

Character literal Single line comment ;

Metadata (see Metadata section)

Deref: $@form \rightarrow (deref form)$

Syntax-quote

Unquote

~@ Unquote-splicing

Regex Pattern p (see Strings/Regex section) #"p"

${\tt Var-quote} \ {\tt \#'x} \ \to \ (\ {\tt var} \ {\tt x})$

#() Anonymous function literal: $\#(\ldots) \to (fn [args] (\ldots))$

Ignore next form

Metadata (clojure.org/reader, special_forms)

General ^{:key1 val1 :key2 val2 ...}

^Type \rightarrow ^{:tag Type}, ^:key \rightarrow ^{:key true} ^:dynamic ^:private ^:doc ^:const Abbrevs

Common

(defn ^:private ^String my-fn ...) Examples (def ^:dynamic

dyn-var val)

On Vars meta with-meta vary-meta alter-meta! reset-meta! doc

find-doc test

Special Forms (clojure.org/special_forms)

def if do let letfn quote var fn loop recur set! throw try

monitor-enter monitor-exit

(examples) let fn defn defmacro loop for doseq Binding Forms / if-let when-let (1.6) if-some when-some Destructuring

Vars and global environment (clojure.org/vars)

Def variants def defn defn- definline defmacro defmethod defmulti

defonce defrecord

Interned vars declare intern binding find-var var

Var objects with-local-vars var-get var-set alter-var-root var?

bound? thread-bound?

Var validators set-validator! get-validator

Namespace

Current *ng*

Create/Switch (tutorial) ns in-ns create-ns Add alias def import intern refer

Find all-ns find-ns

Examine ns-name ns-aliases ns-map ns-interns ns-publics

ns-refers ns-imports

From symbol resolve ns-resolve namespace the-ns Remove ns-unalias ns-unmap remove-ns

Loading

Load libs (tutorial) require use import refer

List loaded loaded-libs

Load misc load load-file load-reader load-string

Concurrency

Atoms atom swap! reset! compare-and-set!

future future-call future-done? future-cancel **Futures**

future-cancelled? future?

Threads bound-fn bound-fn* get-thread-bindings

push-thread-bindings pop-thread-bindings thread-bound?

locking pcalls pvalues pmap seque promise deliver

Refs and Transactions (clojure.org/refs)

Create ref

Examine $\mathtt{deref} \ \mathtt{@} \ (\mathtt{@form} \ \to (\mathsf{deref} \ \mathsf{form}))$

Transaction sync dosync io!

In transaction ensure ref-set alter commute Validators set-validator! get-validator

History ref-history-count ref-min-history ref-max-history

Agents and Asynchronous Actions (clojure.org/agents)

Create agent Examine agent-error

Change state send send-off restart-agent (1.5)

send-via set-agent-send-executor!

set-agent-send-off-executor!

Block waiting await await-for

Ref validators set-validator! get-validator Watchers add-watch remove-watch

Thread handling shutdown-agents

Error error-handler set-error-handler! error-mode

set-error-mode!

Misc *agent* release-pending-sends

Java Interoperation (clojure.org/java_interop)

.. doto Classname/ Classname. new bean comparator General

enumeration-seq import iterator-seq memfn set! class

class? bases supers type

Cast boolean byte short char int long float double bigdec

bigint num cast biginteger

Exceptions throw try catch finally pst (1.4) ex-info ex-data

Arrays

make-array object-array boolean-array byte-array Create short-array char-array int-array long-array float-array double-array aclone to-array to-array-2d into-array aget aset aset-boolean aset-byte aset-short aset-char Use aset-int aset-long aset-float aset-double alength amap

Cast booleans bytes shorts chars ints longs floats doubles

Proxy (Clojure type selection flowchart)

Create proxy get-proxy-class construct-proxy init-proxy Misc proxy-mappings proxy-super update-proxy

Other

Misc

XML clojure.xml/parse xml-seq

REPL *1 *2 *3 *e *print-dup* *print-length* *print-level*

print-meta *print-readably* *compile-files* *compile-path* *file*

Code *warn-on-reflection* compile gen-class gen-interface loaded-libs test

eval force hash name *clojure-version* clojure-version

command-line-args (clojure.java.browse/) browse-url (clojure.java.shell/) sh Browser

/ Shell with-sh-dir with-sh-env