

Clojure Cheat Sheet (Clojure 1.3 - 1.6, sheet v15)

Documentation

clojure.repl/ doc find-doc apropos source pst javadoc (foo.bar/ is namespace for later syms)

Primitives

Numbers

Literals Long: 7, hex 0xff, oct 017, base 2 2r1011, base 36 36rCRAZY BigInt: 7N Ratio: -22/7 Double: 2.78 -1.2e-5 BigDecimal: 4.2M

Arithmetic + - * / quot rem mod inc dec max min

Compare = == not= < > <= >= compare

Bitwise bit-and bit-or bit-xor bit-not bit-flip bit-set bit-shift-right bit-shift-left bit-and-not bit-clear bit-test (1.6) unsigned-bit-shift-right

Cast byte short int long float double bigdec bigint num rationalize biginteger

Test zero? pos? neg? even? odd? number? rational? integer? ratio? decimal? float?

Random rand rand-int

BigDecimal with-precision

Unchecked *unchecked-math* unchecked-add unchecked-dec unchecked-inc unchecked-multiply unchecked-negate unchecked-subtract

Strings

Create str format See also IO/to string

Use count get subs compare (clojure.string/) join escape split split-lines replace replace-first reverse (1.5) re-quote-replacement (String) .indexOf .lastIndexOf #"pattern" re-find re-seq re-matches re-pattern re-matcher re-groups (clojure.string/) replace replace-first (1.5) re-quote-replacement (clojure.string/) capitalize lower-case upper-case (clojure.string/) trim trim-newline triml trimr

Test char char? string? (clojure.string/) blank?

Other

Characters char char-name-string char-escape-string

Keywords keyword keyword? find-keyword

Symbols symbol symbol? gensym

Collections

Collections

Generic ops count empty not-empty into conj (clojure.walk/) walk prewalk prewalk-demo prewalk-replace postwalk postwalk-demo postwalk-replace

Content tests distinct? empty? every? not-every? some not-any?

Capabilities sequential? associative? sorted? counted? reversible?

Type tests coll? list? vector? set? map? seq? (1.6) record?

Lists

Create '() list list*

Examine first nth peek .indexOf .lastIndexOf

'Change' cons conj rest pop

Vectors

Create [] vector vec vector-of

Examine (my-vec idx) → (nth my-vec idx) get peek .indexOf .lastIndexOf

'Change' assoc pop subvec replace conj rseq

Ops (1.4) mapv filterv reduce-kv

Sets

Create #{ } set hash-set sorted-set sorted-set-by (my-set item) → (get my-set item) contains?

Examine conj disj

'Change' (clojure.set/) join select project union difference intersection

Get map (clojure.set/) index rename-keys rename map-invert

Test (clojure.set/) subset? superset?

Maps

Create {} hash-map array-map zipmap sorted-map sorted-map-by bean frequencies group-by (:key my-map) → (get my-map :key) get-in contains? find keys vals

'Change' assoc assoc-in dissoc merge merge-with select-keys update-in

Entry key val

Sorted maps rseq subseq rsubseq

Transients (clojure.org/transients)

Create transient persistent!

Change conj! pop! assoc! dissoc! disj! Note: always use return value for later changes, never original!

Misc

Compare = == identical? not= not compare clojure.data/diff

Test true? false? instance? nil? (1.6) some?

Sequences

Creating a Lazy Seq

From collection seq vals keys rseq subseq rsubseq

From producer fn lazy-seq repeatedly iterate

From constant repeat range

From other file-seq line-seq resultset-seq re-seq tree-seq xml-seq iterator-seq enumeration-seq

From seq keep keep-indexed

Seq in, Seq out

Get shorter distinct filter remove take-nth for

Get longer cons conj concat lazy-cat mapcat cycle interleave interpose

Tail-items rest nthrest next fnext nnext drop drop-while take-last for

Head-items take take-while butlast drop-last for

'Change' conj concat distinct flatten group-by partition partition-all partition-by split-at split-with filter remove replace shuffle

Rearrange reverse sort sort-by compare

Process items map pmap map-indexed mapcat for replace seque

Using a Seq

Extract item first second last rest next ffirst nfirst fnext nnext nth nthnext rand-nth when-first max-key min-key

Construct coll zipmap into reduce reductions set vec into-array to-array-2d

Pass to fn apply

Search some filter

Force evaluation doseq dorun doall

Check for forced realized?

Zipper (clojure.zip/)

Create zipper seq-zip vector-zip xml-zip

Get loc up down left right leftmost rightmost

Get seq lefts rights path children

'Change' make-node replace edit insert-child insert-left insert-right append-child remove

Move next prev

Misc root node branch? end?

IO

to/from spit slurp (to writer/from reader, Socket, string with file name, URI, etc.)

to *out* pr prn print printf println newline (clojure.pprint/) print-table

to writer (clojure.pprint/) pprint cl-format also: (binding [*out* writer] ...)

to string format with-out-str pr-str prn-str print-str println-str

from *in* read-line (clojure.tools.reader.edn/) read

from reader line-seq (clojure.tools.reader.edn/) read also: (binding [*in* reader] ...) java.io.Reader

from string with-in-str (clojure.tools.reader.edn/) read-string

Open with-open (clojure.java.io/) text: reader writer binary: input-stream output-stream

Binary (.write ostream byte-arr) (.read istream byte-arr) java.io.OutputStream java.io.InputStream GitHub: gloss byte-spec

Misc flush (.close s) file-seq *in* *out* *err* (clojure.java.io/) file copy delete-file resource as-file as-url as-relative-path GitHub: fs

Data readers (1.4) *data-readers* default-data-readers (1.5) *default-data-reader-fn*

Functions

Create fn defn defn- definline identity constantly memfn comp complement partial juxt memoize fnil every-pred some-fn

Call apply -> ->> trampoline (1.5) as-> cond-> cond->> some-> some->>

Test fn? ifn?

Abstractions (Clojure type selection flowchart)

Protocols (clojure.org/protocols)

```
Define      ( defprotocol Slicey (slice [at]))
Extend      ( extend-type String Slicey (slice [at] ...))
Extend null  ( extend-type nil Slicey (slice [_] nil))
Reify       ( reify Slicey (slice [at] ...))
Test        satisfies?
```

Records (clojure.org/datatypes)

```
Define      ( defrecord Pair [h t])
Access      (:h (Pair. 1 2)) → 1
Create      Pair. ->Pair map->Pair
Test        record?
```

Types (clojure.org/datatypes)

```
Define      ( deftype Pair [h t])
Access      (.h (Pair. 1 2)) → 1
Create      Pair. ->Pair
            ( deftype Pair [h t]
              With methods      Object
                              (toString [this] (str "<" h "," t ">")))
With methods
```

Multimethods (clojure.org/multimethods)

```
Define      ( defmulti my-mm dispatch-fn)
Method define ( defmethod my-mm :dispatch-value [args] ...)
Dispatch     get-method methods
Remove       remove-method remove-all-methods
Prefer       prefer-method prefers
Relation     derive isa? parents ancestors descendants
            make-hierarchy
```

Macros

```
Create      defmacro definline
Debug       macroexpand-1 macroexpand (clojure.walk/)
            macroexpand-all
Branch      and or when when-not when-let when-first if-not
            if-let cond condp case (1.6) when-some if-some
Loop        for doseq dotimes while
Arrange     .. doto -> ->> (1.5) as-> cond-> cond->> some->
            some->>
Scope       binding locking time with-in-str with-local-vars
            with-open with-out-str with-precision with-redefs
            with-redefs-fn
Lazy        lazy-cat lazy-seq delay
Doc.        assert comment doc
```

Reader Macros

```
'      Quote 'form → (quote form)
\      Character literal
;      Single line comment
~      Metadata (see Metadata section)
@      Deref @form → (deref form)
`      Syntax-quote
~      Unquote
~@     Unquote-splicing
#"p"   Regex Pattern p
#'     Var quote #'x → (var x)
#()    #(…) → (fn [args] (...))
#_     Ignore next form
```

Metadata (clojure.org/special_forms)

```
General    ^{:key1 val1 :key2 val2 ...}
Abbrevs    ^Type → ^{:tag Type}, ^:key → ^{:key true}
Common     ^:dynamic ^:private ^:doc ^:const
Examples   (defn ^:private ^String my-fn ...) (def
            ^:dynamic *dyn-var* val)
On Vars    meta with-meta vary-meta alter-meta! reset-meta!
            doc find-doc test
```

Special Forms (clojure.org/special_forms)

```
def if do let letfn quote var fn loop recur throw try
monitor-enter monitor-exit
Binding Forms / (examples) let fn defn defmacro loop for
Destructuring   doseq if-let when-let (1.6) if-some when-some
```

Vars and global environment (clojure.org/vars)

```
Def variants  def defn defn- definline defmacro defmethod
            defmulti defonce defrecord
Interned vars declare intern binding find-var var
Var objects   with-local-vars var-get var-set alter-var-root
            var? bound? thread-bound?
Var validators set-validator! get-validator
```

Namespace

```
Current      *ns*
Create/Switch (tutorial) ns in-ns create-ns
Add          alias def import intern refer
Find         all-ns find-ns
Examine      ns-name ns-aliases ns-map ns-interns ns-publics
            ns-refers ns-imports
            resolve ns-resolve namespace the-ns
From symbol  ns-unalias ns-unmap remove-ns
Remove
```

Loading

```
Load libs    (tutorial) require use import refer
List loaded   loaded-libs
Load misc     load load-file load-reader load-string
```

Concurrency

```
Atoms        atom swap! reset! compare-and-set!
Futures      future future-call future-done? future-cancel
            future-cancelled? future?
Threads      bound-fn bound-fn* get-thread-bindings
            push-thread-bindings pop-thread-bindings
            thread-bound?
Misc         locking pcalls pvalues pmap seque promise deliver
```

Refs and Transactions (clojure.org/refs)

```
Create       ref
Examine      deref @ (@form → (deref form))
Transaction  sync dosync io!
In transaction ensure ref-set alter commute
Validators   set-validator! get-validator
History      ref-history-count ref-min-history
            ref-max-history
```

Agents and Asynchronous Actions (clojure.org/agents)

```
Create       agent
Examine      agent-error
Change state  send send-off restart-agent (1.5)
            send-via set-agent-send-executor!
            set-agent-send-off-executor!
Block waiting await await-for
Ref validators set-validator! get-validator
Watchers      add-watch remove-watch
Thread handling shutdown-agents
Error          error-handler set-error-handler! error-mode
            set-error-mode!
Misc          *agent* release-pending-sends
```

Java Interoperation (clojure.org/java_interop)

```
General      .. doto Classname/ Classname. new bean comparator
            enumeration-seq import iterator-seq memfn set!
            class
Cast         boolean byte short char int long float double
            bigdec bigint num cast biginteger
Exceptions   throw try catch finally pst (1.4) ex-info ex-data
```

Arrays

```
Create       make-array object-array boolean-array byte-array
            short-array char-array int-array long-array
            float-array double-array aclone to-array to-array-2d
            into-array
Use          aget aset aset-boolean aset-byte aset-short aset-char
            aset-int aset-long aset-float aset-double alength amap
            areduce
Cast         booleans bytes shorts chars ints longs floats doubles
```

Proxy (Clojure type selection flowchart)

```
Create       proxy get-proxy-class construct-proxy init-proxy
Misc         proxy-mappings proxy-super update-proxy
```

Other

```
XML          clojure.xml/parse xml-seq
REPL         *1 *2 *3 *e *print-dup* *print-length* *print-level*
            *print-meta* *print-readably*
Code         *compile-files* *compile-path* *file*
            *warn-on-reflection* compile gen-class gen-interface
            loaded-libs test
Misc         eval force hash name *clojure-version*
            clojure-version *command-line-args*
Browser      (clojure.java.browse/) browse-url (clojure.java.shell/) sh
/ Shell      with-sh-dir with-sh-env
```