Clojure Cheat Sheet (Clojure 1.3 - 1.6, sheet v15)

Documentation

clojure.repl/ doc find-doc apropos source pst javadoc (foo.bar/ is

namespace for later syms)

Primitives

Numbers

Literals Long: 7, hex 0xff, oct 017, base 2 2r1011, base 36

36rCRAZY BigInt: 7N Ratio: -22/7 Double: 2.78 -1.2e-5

BigDecimal: 4.2M

Arithmetic + - * / quot rem mod inc dec max min

Compare = == not= < > <= >= compare

Bitwise bit-and bit-or bit-xor bit-not bit-flip bit-set bit-shift-right bit-shift-left bit-and-not bit-clear

bit-test (1.6) unsigned-bit-shift-right

Cast byte short int long float double bigdec bigint num

rationalize biginteger

Test zero? pos? neg? even? odd? number? rational? integer?

ratio? decimal? float?

Random rand rand-int. **BigDecimal** with-precision

Unchecked *unchecked-math* unchecked-add unchecked-dec

unchecked-inc unchecked-multiply unchecked-negate

unchecked-subtract

Strings

str format See also IO/to string Create

Use count get subs compare (clojure.string/) join escape split split-lines replace replace-first reverse (1.5)

re-quote-replacement (String) .indexOf .lastIndexOf Regex #"pattern" re-find re-seq re-matches re-pattern

re-matcher re-groups (clojure.string/) replace replace-first

(1.5) re-quote-replacement

Letters (clojure.string/) capitalize lower-case upper-case Trim (clojure.string/) trim trim-newline triml trimr

Test char char? string? (clojure.string/) blank?

Other

Characters char char-name-string char-escape-string

Kevwords keyword keyword? find-keyword

Symbols symbol symbol? gensym

Collections

Collections

count empty not-empty into conj (clojure.walk/) walk Generic ops

prewalk prewalk-demo prewalk-replace postwalk

postwalk-demo postwalk-replace

Content tests distinct? empty? every? not-every? some not-any?

Capabilities sequential? associative? sorted? counted?

reversible?

Type tests coll? list? vector? set? map? seq? (1.6) record?

Lists

Create '() list list*

first nth peek .indexOf .lastIndexOf Examine

'Change' cons conj rest pop

Vectors

Create [] vector vec vector-of

(my-vec idx) \rightarrow (nth my-vec idx) get peek .indexOf Examine

.lastIndexOf

'Change' assoc pop subvec replace conj rseq Ops (1.4) mapv filterv reduce-kv

Sets

Create #{} set hash-set sorted-set sorted-set-by Examine (my-set item) ightarrow (get my-set item) contains?

'Change' coni disi Rel algebra

(clojure.set/) join select project union difference

intersection

Get map (clojure.set/) index rename-keys rename map-invert

(clojure.set/) subset? superset? Test

Maps

Create {} hash-map array-map zipmap sorted-map

sorted-map-by bean frequencies group-by

(:key my-map) \rightarrow (get my-map :key) get-in contains? Examine

find keys vals

'Change' assoc assoc-in dissoc merge merge-with select-keys

update-in

Entry key val

Sorted maps rseq subseq rsubseq

Transients (clojure.org/transients)

Create transient persistent!

conj! pop! assoc! dissoc! disj! Note: always use return value Change

for later changes, never original!

Misc

= == identical? not= not compare clojure.data/diff Compare

Test true? false? instance? nil? (1.6) some?

Sequences

Creating a Lazy Seq

From collection seq vals keys rseq subseq rsubseq From producer fn lazy-seq repeatedly iterate

From constant repeat range

From other file-seq line-seq resultset-seq re-seq tree-seq

xml-seq iterator-seq enumeration-seq

From seq keep keep-indexed

Seq in, Seq out

Get shorter distinct filter remove take-nth for

Get longer cons coni concat lazv-cat mapcat cycle interleave

interpose

Tail-items rest nthrest next fnext nnext drop drop-while

take-last for

Head-items take take-while butlast drop-last for

'Change' conj concat distinct flatten group-by partition partition-all partition-by split-at split-with

> filter remove replace shuffle reverse sort sort-by compare

Process items map pmap map-indexed mapcat for replace seque

Using a Seq

Rearrange

Extract item first second last rest next ffirst nfirst fnext

nnext nth nthnext rand-nth when-first max-key

min-kev

Construct coll zipmap into reduce reductions set vec into-array

to-array-2d

Pass to fn apply Search some filter Force evaluation doseq dorun doall

Check for forced realized?

Zippers (clojure.zip/)

Create zipper seq-zip vector-zip xml-zip Get loc up down left right leftmost rightmost

Get sea lefts rights path children

make-node replace edit insert-child insert-left 'Change

> insert-right append-child remove next prev

Move

Misc root node branch? end?

10

to *out*

to writer

to/from spit slurp (to writer/from reader, Socket, string with file

name, URI, etc.)

pr prn print printf println newline (clojure.pprint/) print-table

(clojure.pprint/) pprint cl-format also: (binding [*out*

writer] ...) to string format with-out-str pr-str prn-str print-str

println-str

from *in* read-line (clojure.tools.reader.edn/) read

from reader line-seq (clojure.tools.reader.edn/) read also: (binding

[*in* reader] ...) java.io.Reader from string

with-in-str (clojure.tools.reader.edn/) read-string Open with-open (clojure.java.io/) text: reader writer binary:

input-stream output-stream

(.write ostream byte-arr) (.read istream byte-arr)

Binary

java.io.OutputStream java.io.InputStream GitHub:

gloss byte-spec

Misc flush (.close s) file-seq *in* *out* *err* (clojure.java.io/) file copy delete-file resource as-file

as-url as-relative-path GitHub: fs

(1.4) *data-readers* default-data-readers (1.5) Data readers

default-data-reader-fn

Functions

Create fn defn defn- definline identity constantly memfn comp complement partial juxt memoize fnil every-pred some-fn

Call apply -> ->> trampoline (1.5) as-> cond-> cond->> some->

some->>

Test fn? ifn?

Abstractions (Clojure type selection flowchart)

Protocols (clojure.org/protocols)

(defprotocol Slicey (slice [at])) Define Extend (extend-type String Slicey (slice [at] ...)) (extend-type nil Slicey (slice [_] nil)) Extend null Reifv (reify Slicey (slice [at] ...))

satisfies? Test

Records (clojure.org/datatypes)

(defrecord Pair [h t]) Define Access (:h (Pair. 1 2)) \rightarrow 1 Create Pair. ->Pair map->Pair

Test record?

Types (clojure.org/datatypes)

Define (deftype Pair [h t]) (.h (Pair. 1 2)) \rightarrow 1 Access Create Pair. ->Pair (deftype Pair [h t] With methods

Object

(toString [this] (str "<" h "," t ">")))

Multimethods (clojure.org/multimethods)

(defmulti my-mm dispatch-fn) Define

Method define (defmethod my-mm :dispatch-value [args] ...)

Dispatch get-method methods

Remove remove-method remove-all-methods

Prefer prefer-method prefers

Relation derive isa? parents ancestors descendants

make-hierarchy

Macros

Create defmacro definline

Debug macroexpand-1 macroexpand (clojure.walk/) macroexpand-all and or when when-not when-let when-first if-not if-let Branch

cond condp case (1.6) when-some if-some

for doseq dotimes while Loop

.. doto -> ->> (1.5) as-> cond-> cond->> some->> Arrange binding locking time with-in-str with-local-vars Scope

with-open with-out-str with-precision with-redefs

with-redefs-fn

Lazy lazy-cat lazy-seq delay

assert comment doc Doc.

Reader Macros

Quote 'form \rightarrow (quote form)

Character literal ١

Single line comment

Metadata (see Metadata section)

Deref $@form \rightarrow (deref form)$ 0

Syntax-quote

Unquote

~@ Unquote-splicing

#"p" Regex Pattern p

Var quote $\#' \times \to (\text{var } \times)$

 $\#(...) \rightarrow (\mathsf{fn} [\mathsf{args}] (...))$ #()

Ignore next form

Metadata (clojure.org/special forms)

^{:key1 val1 :key2 val2 ...} General

Abbrevs ^Type \rightarrow ^{:tag Type}, ^:key \rightarrow ^{:key true}

Common ^:dynamic ^:private ^:doc ^:const

Examples (defn ^:private ^String my-fn ...) (def ^:dynamic

dyn-var val)

On Vars meta with-meta vary-meta alter-meta! reset-meta! doc

find-doc test

Special Forms (clojure.org/special_forms)

def if do let letfn quote var fn loop recur throw try

monitor-enter monitor-exit

Binding Forms / (examples) let fn defn defmacro loop for doseq

Destructuring if-let when-let (1.6) if-some when-some

Vars and global environment (clojure.org/vars)

Def variants def defn defn- definline defmacro defmethod

defmulti defonce defrecord

Interned vars declare intern binding find-var var

with-local-vars var-get var-set alter-var-root var? Var objects

bound? thread-bound?

Var validators set-validator! get-validator

Namespace

Current *ns*

Create/Switch (tutorial) ns in-ns create-ns Add alias def import intern refer

Find all-ns find-ns

Examine ns-name ns-aliases ns-map ns-interns ns-publics

ns-refers ns-imports

From symbol resolve ns-resolve namespace the-ns Remove ns-unalias ns-unmap remove-ns

Loading

Load libs (tutorial) require use import refer

List loaded loaded-libs

Load misc load load-file load-reader load-string

Concurrency

Atoms atom swap! reset! compare-and-set!

Futures future future-call future-done? future-cancel

future-cancelled? future?

Threads bound-fn bound-fn* get-thread-bindings

push-thread-bindings pop-thread-bindings thread-bound?

Misc locking pcalls pvalues pmap seque promise deliver

Refs and Transactions (clojure.org/refs)

Create ref

Examine $deref @ (@form \rightarrow (deref form))$ Transaction sync dosync io! In transaction ensure ref-set alter commute

set-validator! get-validator Validators

History ref-history-count ref-min-history ref-max-history

Agents and Asynchronous Actions (clojure.org/agents)

Create agent

Examine agent-error

Change state send send-off restart-agent (1.5)

send-via set-agent-send-executor! set-agent-send-off-executor!

Block waiting await await-for

Ref validators set-validator! get-validator Watchers add-watch remove-watch

Thread handling shutdown-agents

Frror error-handler set-error-handler! error-mode

set-error-mode!

Misc *agent* release-pending-sends

Java Interoperation (clojure.org/java_interop)

General .. doto Classname/ Classname. new bean comparator enumeration-seq import iterator-seq memfn set! class Cast boolean byte short char int long float double bigdec

bigint num cast biginteger

throw try catch finally pst (1.4) ex-info ex-data Exceptions

Arrays

Create make-array object-array boolean-array byte-array

short-array char-array int-array long-array float-array double-array aclone to-array to-array-2d into-array aget aset aset-boolean aset-byte aset-short aset-char Use aset-int aset-long aset-float aset-double alength amap

areduce

Cast booleans bytes shorts chars ints longs floats doubles

Proxy (Clojure type selection flowchart)

Create proxy get-proxy-class construct-proxy init-proxy

Misc proxy-mappings proxy-super update-proxy

Other

Code

XML clojure.xml/parse xml-seq

RFPI *1 *2 *3 *e *print-dup* *print-length* *print-level*

print-meta *print-readably*

compile-files *compile-path* *file* *warn-on-reflection* compile gen-class gen-interface

loaded-libs test

Misc eval force hash name *clojure-version* clojure-version

command-line-args

Browser (clojure.java.browse/) browse-url (clojure.java.shell/) sh

/ Shell with-sh-dir with-sh-env