Clojure Cheat Sheet (Clojure 1.3 - 1.6, sheet v16)

Documentation

clojure.repl/	doc find-doc apropos source pst javadoc (foo.bar/ is namespace for later syms)

Primitives

Numbers

Literals	Long: 7, hex 0xff, oct 017, base 2 2r1011, base 36 36rCRAZY BigInt: 7N Ratio: -22/7 Double: 2.78 -1.2e-5 BigDecimal: 4.2M
Arithmetic	+ - * / quot rem mod inc dec max min +' -' *' inc' dec'
Compare	= == not= < > <= >= compare
Bitwise	bit-and bit-or bit-xor bit-not bit-flip bit-set bit-shift-right bit-shift-left bit-and-not bit-clear bit-test (1.6) unsigned-bit-shift-right
Cast	byte short int long float double bigdec bigint num rationalize biginteger
Test	zero? pos? neg? even? odd? number? rational? integer? ratio? decimal? float?
Random	rand rand-int
BigDecimal	with-precision
Unchecked	*unchecked-math* unchecked-add unchecked-dec unchecked-inc unchecked-multiply unchecked-negate unchecked-subtract

Strings

Create	str format See also IO/to string
Use	count get subs compare (clojure.string/) join escape split split-lines replace replace-first reverse (1.5) re-quote-replacement (String) .indexOf .lastIndexOf
Regex	#"pattern" re-find re-seq re-matches re-pattern re-matcher re-groups (clojure.string/) replace replace-first (1.5) re-quote-replacement
Letters	(clojure.string/) capitalize lower-case upper-case
Trim	(clojure.string/) trim trim-newline triml trimr
Test	char char? string? (clojure.string/) blank?

Other

Characters	char char-name-string char-escape-string
Keywords	keyword keyword? find-keyword
Symbols	symbol symbol? gensym

Collections

Collections

Generic ops	count empty not-empty into conj (clojure.walk/) walk prewalk prewalk-demo prewalk-replace postwalk postwalk-demo postwalk-replace
Content tests	distinct? empty? every? not-every? some not-any?
Capabilities	sequential? associative? sorted? counted? reversible?
Type tests	coll? list? vector? set? map? seq? (1.6) record?

Lists

Create	'() list list*
Examine	first nth peek .indexOf .lastIndexOf
'Change'	cons conj rest pop

Vectors

Create	[] vector vec vector-of
Examine	(my-vec idx) → (nth my-vec idx) get peek .indexOf .lastIndexOf
'Change'	assoc pop subvec replace conj rseq
Ops	(1.4) mapv filterv reduce-kv

Sets

Create	#{} set hash-set sorted-set sorted-set-by
Examine	(my-set item) → (get my-set item) contains?
'Change'	conj disj
Set ops	(clojure.set/) union difference intersection select See also Relations
Test	(clojure.set/) subset? superset?

Maps

Create	{} hash-map array-map zipmap sorted-map sorted-map-by bean frequencies group-by (clojure.set/) index
Examine	(:key my-map) → (get my-map :key) get-in contains? find keys vals
'Change'	assoc assoc-in dissoc merge merge-with select-keys update-in (clojure.set/) rename-keys map-invert GitHub: Medley
Entry	key val
Sorted maps	rseq subseq rsubseq

Relations (set of maps, each with same keys, aka rels)

Rel algebra	(clojure.set/) join select project union difference intersection index rename

Transients (clojure.org/transients)

Create	transient persistent!
Change	conj! pop! assoc! dissoc! disj! Note: always use return value for later changes, never original!

Misc

Compare	= == identical? not= not compare clojure.data/diff
Test	true? false? instance? nil? (1.6) some?

Sequences

Creating a Lazy Seq

From collection	seq vals keys rseq subseq rsubseq
From producer fn	lazy-seq repeatedly iterate
From constant	repeat range
From other	file-seq line-seq resultset-seq re-seq tree-seq xml-seq iterator-seq enumeration-seq
From seq	keep keep-indexed

Seq in, Seq out

Get shorter	distinct filter remove take-nth for
Get longer	cons conj concat lazy-cat mapcat cycle interleave interpose
Tail-items	rest nthrest next fnext nnext drop drop-while take-last for
Head-items	take take-while butlast drop-last for
'Change'	conj concat distinct flatten group-by partition partition-all partition-by split-at split-with filter remove replace shuffle
Rearrange	reverse sort sort-by compare
Process items	map pmap map-indexed mapcat for replace seque

Using a Seq

Extract item	first second last rest next ffirst nfirst fnext nnext nth nthnext rand-nth when-first max-key min-key
Construct coll	zipmap into reduce reductions set vec into-array to-array-2d
Pass to fn	apply
Search	some filter
Force evaluation	doseq dorun doall
Check for forced	realized?

Zippers (clojure.zip/)

Create	zipper seq-zip vector-zip xml-zip
Get loc	up down left right leftmost rightmost
Get seq	lefts rights path children
'Change'	make-node replace edit insert-child insert-left insert-right append-child remove
Move	next prev
Misc	root node branch? end?

IO

to/from ...	spit slurp (to writer/from reader, Socket, string with file name, URI, etc.)
to *out*	pr prn print printf println newline (clojure.pprint/) print-table
to writer	(clojure.pprint/) pprint cl-format also: (binding [*out* writer] ...)
to string	format with-out-str pr-str prn-str print-str println-str
from *in*	read-line (clojure.tools.reader.edn/) read
from reader	line-seq (clojure.tools.reader.edn/) read also: (binding [*in* reader] ...) java.io.Reader
from string	with-in-str (clojure.tools.reader.edn/) read-string
Open	with-open (clojure.java.io/) text: reader writer binary: input-stream output-stream
Binary	(.write ostream byte-arr) (.read istream byte-arr) java.io.OutputStream java.io.InputStream GitHub: gloss byte-spec
Misc	flush (.close s) file-seq *in* *out* *err* (clojure.java.io/) file copy delete-file resource as-file as-url as-relative-path GitHub: fs
Data readers	(1.4) *data-readers* default-data-readers (1.5) *default-data-reader-fn*

Functions

Create	fn defn defn- definline identity constantly memfn comp complement partial juxt memoize fnil every-pred some-fn
Call	apply -> ->> trampoline (1.5) as-> cond-> cond->> some-> some->>
Test	fn? ifn?

Abstractions (Clojure type selection flowchart)

Protocols (clojure.org/protocols)

Define	`( defprotocol Slicey (slice [at]))`
Extend	`( extend-type String Slicey (slice [at] ...))`
Extend null	`( extend-type nil Slicey (slice [_] nil))`
Reify	`( reify Slicey (slice [at] ...))`
Test	`satisfies?`

Records (clojure.org/datatypes)

Define	`( defrecord Pair [h t])`
Access	`(:h (Pair. 1 2))` → `1`
Create	`Pair. ->Pair map->Pair`
Test	`record?`

Types (clojure.org/datatypes)

Define	`( deftype Pair [h t])`
Access	`(.h (Pair. 1 2))` → `1`
Create	`Pair. ->Pair` `( deftype Pair [h t]`
With methods	`Object` `(toString [this] (str "<" h "," t ">")))`

Multimethods (clojure.org/multimethods)

Define	`( defmulti my-mm dispatch-fn)`
Method define	`( defmethod my-mm :dispatch-value [args] ...)`
Dispatch	`get-method methods`
Remove	`remove-method remove-all-methods`
Prefer	`prefer-method prefers`
Relation	`derive isa? parents ancestors descendants make-hierarchy`

Macros

Create	`defmacro definline`
Debug	`macroexpand-1 macroexpand` (clojure.walk/) `macroexpand-all`
Branch	`and or when when-not when-let when-first if-not if-let cond condp case (1.6) when-some if-some`
Loop	`for doseq dotimes while`
Arrange	`.. doto -> ->> (1.5) as-> cond-> cond->> some-> some->>`
Scope	`binding locking time with-in-str with-local-vars with-open with-out-str with-precision with-redefs with-redefs-fn`
Lazy	`lazy-cat lazy-seq delay`
Doc.	`assert comment doc`

Reader Macros

`'`	Quote 'form → (quote form)
`\`	Character literal
`;`	Single line comment
`^`	Metadata (see Metadata section)
`@`	Deref @form → (deref form)
`` ` ``	Syntax-quote
`~`	Unquote
`~@`	Unquote-splicing
`#"`*p*`"`	Regex Pattern *p*
`#'`	Var quote #'x → (var x)
`#()`	#(...) → (fn [args] (...))
`#_`	Ignore next form

Metadata (clojure.org/special_forms)

General	`^{:key1 val1 :key2 val2 ...}`
Abbrevs	`^Type` → `^{:tag Type}`, `^:key` → `^{:key true}`
Common	`^:dynamic ^:private ^:doc ^:const`
Examples	`(defn ^:private ^String my-fn ...)` `(def ^:dynamic *dyn-var* val)`
On Vars	`meta with-meta vary-meta alter-meta! reset-meta! doc find-doc test`

Special Forms (clojure.org/special_forms)

`def if do let letfn quote var fn loop recur throw try monitor-enter monitor-exit`

Binding Forms / Destructuring	`(examples) let fn defn defmacro loop for doseq if-let when-let (1.6) if-some when-some`

Vars and global environment (clojure.org/vars)

Def variants	`def defn defn- definline defmacro defmethod defmulti defonce defrecord`
Interned vars	`declare intern binding find-var var`
Var objects	`with-local-vars var-get var-set alter-var-root var? bound? thread-bound?`
Var validators	`set-validator! get-validator`

Namespace

Current	`*ns*`
Create/Switch	`(tutorial) ns in-ns create-ns`
Add	`alias def import intern refer`
Find	`all-ns find-ns`
Examine	`ns-name ns-aliases ns-map ns-interns ns-publics ns-refers ns-imports`
From symbol	`resolve ns-resolve namespace the-ns`
Remove	`ns-unalias ns-unmap remove-ns`

Loading

Load libs	`(tutorial) require use import refer`
List loaded	`loaded-libs`
Load misc	`load load-file load-reader load-string`

Concurrency

Atoms	`atom swap! reset! compare-and-set!`
Futures	`future future-call future-done? future-cancel future-cancelled? future?`
Threads	`bound-fn bound-fn* get-thread-bindings push-thread-bindings pop-thread-bindings thread-bound?`
Misc	`locking pcalls pvalues pmap seque promise deliver`

Refs and Transactions (clojure.org/refs)

Create	`ref`
Examine	`deref @` (@form → (deref form))
Transaction	`sync dosync io!`
In transaction	`ensure ref-set alter commute`
Validators	`set-validator! get-validator`
History	`ref-history-count ref-min-history ref-max-history`

Agents and Asynchronous Actions (clojure.org/agents)

Create	`agent`
Examine	`agent-error`
Change state	`send send-off restart-agent (1.5) send-via set-agent-send-executor! set-agent-send-off-executor!`
Block waiting	`await await-for`
Ref validators	`set-validator! get-validator`
Watchers	`add-watch remove-watch`
Thread handling	`shutdown-agents`
Error	`error-handler set-error-handler! error-mode set-error-mode!`
Misc	`*agent* release-pending-sends`

Java Interoperation (clojure.org/java_interop)

General	`.. doto Classname/ Classname. new bean comparator enumeration-seq import iterator-seq memfn set! class`
Cast	`boolean byte short char int long float double bigdec bigint num cast biginteger`
Exceptions	`throw try catch finally pst (1.4) ex-info ex-data`

Arrays

Create	`make-array object-array boolean-array byte-array short-array char-array int-array long-array float-array double-array aclone to-array to-array-2d into-array`
Use	`aget aset aset-boolean aset-byte aset-short aset-char aset-int aset-long aset-float aset-double alength amap areduce`
Cast	`booleans bytes shorts chars ints longs floats doubles`

Proxy (Clojure type selection flowchart)

Create	`proxy get-proxy-class construct-proxy init-proxy`
Misc	`proxy-mappings proxy-super update-proxy`

Other

XML	`clojure.xml/parse xml-seq`
REPL	`*1 *2 *3 *e *print-dup* *print-length* *print-level* *print-meta* *print-readably*`
Code	`*compile-files* *compile-path* *file* *warn-on-reflection* compile gen-class gen-interface loaded-libs test`
Misc	`eval force hash name *clojure-version* clojure-version *command-line-args*`
Browser / Shell	(clojure.java.browse/) `browse-url` (clojure.java.shell/) `sh with-sh-dir with-sh-env`