Clojure Cheat Sheet (Clojure 1.3 - 1.6, sheet v27)

doc find-doc apropos dir source pst javadoc (foo.bar/ is clojure.repl/

namespace for later syms)

Primitives

Numbers

Literals Long: 7, hex 0xff, oct 017, base 2 2r1011, base 36

36rCRAZY BigInt: 7N Ratio: -22/7 Double: 2.78 -1.2e-5

BigDecimal: 4.2M

Arithmetic + - * / quot rem mod inc dec max min +' -' *' inc' dec'

== < > <= >= compare Compare

bit-and bit-or bit-xor bit-not bit-flip bit-set Bitwise bit-shift-right bit-shift-left bit-and-not bit-clear bit-test (1.6) unsigned-bit-shift-right (see BigInteger

for integers larger than Long)

Cast byte short int long float double bigdec bigint num

rationalize biginteger

zero? pos? neg? even? odd? number? rational? integer? ratio? decimal? float? Test

rand rand-int Random

BigDecimal with-precision Unchecked *unchecked-math* unchecked-add unchecked-dec

unchecked-inc unchecked-multiply unchecked-negate

unchecked-subtract

Strings

str format "a string" "escapes $\b \int n\t \$ octal \377 hex Create

\ucafe" See also IO/to string

Use count get subs compare (clojure.string/) join escape split split-lines replace replace-first reverse (1.5) re-quote-replacement (String) .indexOf .lastIndexOf

Regex #"pattern" re-find re-seq re-matches re-pattern re-matcher

re-groups (clojure.string/) replace replace-first (1.5)

re-quote-replacement

(clojure.string/) capitalize lower-case upper-case (clojure.string/) trim trim-newline triml trimr Letters Trim

char char? string? (clojure.string/) blank? (String) .startsWith Test

.endsWith .contains

Other

Characters char char-name-string char-escape-string literals: \a

\newline (more at link)

keyword keyword? find-keyword literals: :kw :mv.ns/kw Keywords

::in-cur-ns

Symbols symbol symbol? gensym literals: my-sym my.ns/foo

literals: true false nil Misc

Collections

Collections

count empty not-empty into conj (clojure.walk/) walk Generic ops

prewalk prewalk-demo prewalk-replace postwalk

postwalk-demo postwalk-replace

distinct? empty? every? not-every? some not-any? Content tests Capabilities sequential? associative? sorted? counted? reversible? Type tests coll? list? vector? set? map? seq? (1.6) record?

Lists (conj, pop, & peek at beginning)

Create () list list*

Examine ${\tt first\ nth\ peek\ .indexOf\ .lastIndexOf}$

'Change cons conj rest pop

Vectors (conj, pop, & peek at end)

Create [] vector vec vector-of (1.4) mapv filterv

Examine $(my\text{-vec idx}) \rightarrow (nth my\text{-vec idx}) \text{ get peek .indexOf}$

.lastIndexOf

'Change' assoc pop subvec replace conj rseq

Ops (1.4) reduce-kv

Sets

Create unsorted #{} set hash-set (clojure.data.int-map/) int-set

dense-int-set

Create sorted sorted-set sorted-set-by (clojure.data.avl/) sorted-set sorted-set-by (flatland.ordered.set/) ordered-set

Examine $(my\text{-set item}) \rightarrow (\text{get my-set item}) \text{ contains}?$

'Change conj disj

(clojure.set/) union difference intersection select See Set ops

also Relations

(clojure.set/) subset? superset?

Sorted sets rseq subseq rsubseq

Maps

Create unsorted {} hash-map array-map zipmap bean frequencies group-by

(clojure.set/) index (clojure.data.int-map/) int-map Create sorted $\verb|sorted-map-by| (clojure.data.avl/) | \verb|sorted-map-by| (clojure.data.avl/) | \\$

sorted-map-by (flatland.ordered.map/) ordered-map (clojure.data.priority-map/) priority-map (flat-

land.useful.map/) ordering-map

 $(\texttt{my-map k}) \, \rightarrow \, (\texttt{get my-map k}) \; \texttt{also (:key my-map)} \, \rightarrow \, ($ Examine get my-map :key) get-in contains? find keys vals

'Change' assoc assoc-in dissoc merge merge-with select-keys update-in (clojure.set/) rename-keys map-invert GitHub:

Medlev

(1.4) reduce-kv Ops

Entry key val

Sorted maps rseq subseq rsubseq Queues (conj at end, peek & pop from beginning)

Create clojure.lang.PersistentQueue/EMPTY (no literal syntax or

constructor fn)

Examine peek 'Change conj pop

Relations (set of maps, each with same keys, aka rels)

(clojure.set/) join select project union difference Rel algebra

intersection index rename

Transients (clojure.org/transients)

Create transient persistent! Change conj! pop! assoc! dissoc! disj! Note: always use return value for

later changes, never original!

Misc Test

= identical? not= not compare clojure.data/diff Compare

true? false? instance? nil? (1.6) some?

Sequences

Creating a Lazy Seq

From collection seq vals keys rseq subseq rsubseq sequence

lazy-seq repeatedly iterate From producer fn

From constant repeat range

From other file-seq line-seq resultset-seq re-seq tree-seq

 ${\tt xml-seq} \ {\tt iterator-seq} \ {\tt enumeration-seq}$

From seq keep keep-indexed

Seq in, Seq out

Get shorter distinct filter remove take-nth for

Get longer cons conj concat lazy-cat mapcat cycle interleave

interpose

Tail-items rest nthrest next fnext nnext drop drop-while take-last

for Head-items

take take-while butlast drop-last for conj concat distinct flatten group-by partition partition-all partition-by split-at split-with filter

remove replace shuffle

Rearrange reverse sort sort-by compare Process items map pmap map-indexed mapcat for replace seque

Using a Seq

Construct coll

'Change'

Extract item first second last rest next ffirst nfirst fnext nnext

nth nthnext rand-nth when-first max-key min-key zipmap into reduce reductions set vec into-array

to-array-2d (1.4) mapv filterv

Pass to fn apply some filter Search Force evaluation doseq dorun doall

Zippers (clojure.zip/)

Check for forced

Create zipper seq-zip vector-zip xml-zip Get loc up down left right leftmost rightmost

realized?

lefts rights path children Get sea

make-node replace edit insert-child insert-left insert-right 'Change

append-child remove

next prev root node branch? end? Misc

10

to/from spit slurp (to writer/from reader, Socket, string with file name,

URI. etc.)

to *out* pr prn print printf println newline (clojure.pprint/) print-table to writer

(clojure.pprint/) pprint cl-format also: (binding [*out* writer] ...)

to string format with-out-str pr-str prn-str print-str println-str

read-line (clojure.tools.reader.edn/) read

from *in* ${\tt line-seq~(clojure.tools.reader.edn/)~read~also:~(binding~[*in*]$ from reader

reader] ...) java.io.Reader with-in-str (clojure.tools.reader.edn/) read-string

Open with-open (clojure.java.io/) text: reader writer binary:

input-stream output-stream

(.write ostream byte-arr) (.read istream byte-arr) java.io.OutputStream java.io.InputStream GitHub: gloss

byte-spec

flush (.close s) file-seq *in* *out* *err* (clo-

jure.java.io/) file copy delete-file resource as-file as-url as-relative-path GitHub: fs

Data readers (1.4) *data-readers* default-data-readers (1.5)

default-data-reader-fn

Functions

Call

from string

Binary

Misc

Create fn defn defn- definline identity constantly memfn comp

> complement partial juxt memoize fnil every-pred some-fn apply -> ->> trampoline (1.5) as-> cond-> cond->> some->

some->>

fn? ifn?

Abstractions (Clojure type selection flowchart) Protocols (clojure.org/protocols) Define (defprotocol Slicey (slice [at])) Extend (extend-type String Slicey (slice [at] ...)) Extend null (extend-type nil Slicey (slice [_] nil)) Reifv (reify Slicey (slice [at] ...)) satisfies? extends? Test Other extend extend-protocol extenders Records (clojure.org/datatypes) Define (defrecord Pair [h t]) (:h (Pair. 1 2)) \rightarrow 1 Access Create Pair. ->Pair map->Pair Test record? Types (clojure.org/datatypes) Define (deftype Pair [h t]) (.h (Pair. 1 2)) \rightarrow 1 Access Pair. ->Pair Create (deftype Pair [h t] With methods Object (toString [this] (str "<" h "," t ">")))

Multimethods (clojure.org/multimethods)

(defmulti my-mm dispatch-fn)

Method define (defmethod my-mm :dispatch-value [args] ...)

get-method methods Dispatch

Remove remove-method remove-all-methods

Prefer prefer-method prefers Relation derive underive isa? parents ancestors descendants

make-hierarchy

Macros

Create defmacro definline

macroexpand-1 macroexpand (clojure.walk/) macroexpand-allDebug Branch

and or when when-not when-let when-first if-not if-let cond

condp case (1.6) when-some if-some

Loop for doseq dotimes while

.. doto -> ->> (1.5) as-> cond-> cond->> some-> some->> Arrange binding locking time with-in-str with-local-vars with-open Scope

with-out-str with-precision with-redefs with-redefs-fn

lazy-cat lazy-seq delay Lazy assert comment doc Doc.

Reader Macros (clojure.org/reader)

quote: 'form ightarrow (quote form)

Character literal Single line comment

; Metadata (see Metadata section)

0 Deref: @form → (deref form)

Svntax-quote

Unquote

~@ Unquote-splicing

#"p" Regex Pattern p (see Strings/Regex section)

 $Var-quote \#'x \to (var x)$

#() Anonymous function literal: $\#(\dots) \to (fn [args] (\dots))$

Ignore next form

Metadata (clojure.org/reader, special_forms)

General ^{:kev1 val1 :kev2 val2 ...}

^Type \(\tau^{\tau} \) \(\ta Abbrevs

Common

(defn ^:private ^String my-fn ...) Examples

dyn-var val)

On Vars meta with-meta vary-meta alter-meta! reset-meta! doc

find-doc test

Special Forms (clojure.org/special_forms)

def if do let letfn quote var fn loop recur set! throw try

monitor-enter monitor-exit

Binding Forms / (examples) let fn defn defmacro loop for doseq if-let

Destructuring when-let (1.6) if-some when-some

Vars and global environment (clojure.org/vars)

Def variants def defn defn- definline defmacro defmethod defmulti

defonce defrecord Interned vars

declare intern binding find-var var Var objects with-local-vars var-get var-set alter-var-root var?

bound? thread-bound?

Var validators set-validator! get-validator

Namespace

Current

Create/Switch (tutorial) ns in-ns create-ns ЬЬА alias def import intern refer

Find all-ns find-ns

Examine

ns-name ns-aliases ns-map ns-interns ns-publics

ns-refers ns-imports

From symbol resolve ns-resolve namespace the-ns Remove ns-unalias ns-unmap remove-ns

Loading

Load libs (tutorial) require use import refer

List loaded loaded-libs

load load-file load-reader load-string Load misc

Concurrency

Atoms atom swap! reset! compare-and-set!

future future-call future-done? future-cancel Futures

future-cancelled? future?

Threads bound-fn bound-fn* get-thread-bindings push-thread-bindings

pop-thread-bindings thread-bound?

Misc locking pcalls pvalues pmap seque promise deliver

Refs and Transactions (clojure.org/refs)

ref

 $\texttt{deref @ (@form} \rightarrow (\texttt{deref form}))$ Examine

Transaction sync dosync io!

In transaction ensure ref-set alter commute Validators

set-validator! get-validator
ref-history-count ref-min-history ref-max-history History

Agents and Asynchronous Actions (clojure.org/agents)

Create agent Examine agent-error

Change state send send-off restart-agent (1.5) send-via

set-agent-send-executor! set-agent-send-off-executor!

Block waiting await await-for

Ref validators set-validator! get-validator Watchers add-watch remove-watch

Thread handling shutdown-agents

error-handler set-error-handler! error-mode Error

set-error-mode!

agent release-pending-sends

Java Interoperation (clojure.org/java_interop)

.. doto Classname/ Classname. new bean comparator General

enumeration-seq import iterator-seq memfn set! class class? bases supers type gen-class gen-interface

definterface

boolean byte short char int long float double bigdec

bigint num cast biginteger

throw try catch finally pst (1.4) ex-info ex-data Exceptions

Arrays

make-array object-array boolean-array byte-array short-array Create

char-array int-array long-array float-array double-array

aclone to-array to-array-2d into-array

Use aget aset aset-boolean aset-byte aset-short aset-char aset-int aset-long aset-float aset-double alength amap areduce

booleans bytes shorts chars ints longs floats doubles

Proxy (Clojure type selection flowchart)

Create proxy get-proxy-class construct-proxy init-proxy

Misc proxy-mappings proxy-super update-proxy

Other

Misc

XML clojure.xml/parse xml-seq

REPL *1 *2 *3 *e *print-dup* *print-length* *print-level*

print-meta *print-readably*

Code *compile-files* *compile-path* *file* *warn-on-reflection* compile loaded-libs test

> eval force hash name *clojure-version* clojure-version *command-line-args*

(clojure.java.browse/) browse-url (clojure.java.shell/) sh Browser

with-sh-dir with-sh-env