# Clojure Cheat Sheet (Clojure 1.3 - 1.5, sheet v9)

#### Documentation

clojure.repl/ doc find-doc apropos source pst javadoc (foo.bar/ is namespace for later syms)

**Primitives** 

Numbers

Literals Long: 7, hex 0xff, oct 017, base 2 2r1011, base 36 36rCRAZY BigInt: 7N Ratio: -22/7 Double: 2.78

-1.2e-5 BigDecimal: 4.2M

Arithmetic + - \* / quot rem mod inc dec max min

= == not= < > <= >= compare Compare

Bitwise bit-{and, or, xor, not, flip, set, shift-right,

shift-left, and-not, clear, test}

byte short int long float double bigdec bigint Cast

num rationalize biginteger

Test nil? identical? zero? pos? neg? even? odd?

Random rand rand-int **BigDecimal** with-precision

\*unchecked-math\* unchecked-{add, dec, divide, Unchecked

inc, multiply, negate, remainder, subtract}-int

Strings

Create str format See also IO/to string

Use  $\verb|count get subs compare (clojure.string/) join|\\$ escape split split-lines replace replace-first reverse (String) .indexOf .lastIndexOf (1.5)

re-quote-replacement

Regex #"pattern" re-find re-seq re-matches re-pattern

re-matcher re-groups (clojure.string/) replace replace-first (1.5) re-quote-replacement

Letters  ${\sf (clojure.string/)\ capitalize\ lower-case\ upper-case}$ Trim (clojure.string/) trim trim-newline triml trimr

Test char char? string? (clojure.string/) blank?

Other

Characters char char-name-string char-escape-string

keyword keyword? find-keyword Keywords

Symbols symbol symbol? gensym

### Collections

Collections

Generic ops count empty not-empty into conj (clojure.walk/)

walk prewalk prewalk-demo prewalk-replace postwalk postwalk-demo postwalk-replace

Content tests distinct? empty? every? not-every? some

not-any?

Capabilities sequential? associative? sorted? counted?

reversible?

Type tests coll? list? vector? set? map? seq?

Lists

Create '() list list\*

Examine first nth peek .indexOf .lastIndexOf

'Change' cons conj rest pop

Vectors

[] vector vec vector-of Create

Examine (my-vec idx)  $\rightarrow$  ( nth my-vec idx) get peek

.indexOf .lastIndexOf

'Change' assoc pop subvec replace conj rseq

Ops (1.4) mapv filterv reduce-kv

Sets

Create #{} set hash-set sorted-set sorted-set-by

Examine (my-set item) ightarrow ( get my-set item) contains?

'Change' conj disj

Rel algebra (clojure.set/) join select project union difference

intersection

Get map (clojure.set/) index rename-keys rename map-invert

Test (clojure.set/) subset? superset?

Maps

Examine

Create {} hash-map array-map zipmap sorted-map

sorted-map-by bean frequencies group-by (:key my-map)  $\rightarrow$  ( get my-map :key) get-in

contains? find keys vals

assoc assoc-in dissoc merge merge-with 'Change'

select-keys update-in

key val Entry

Sorted maps rseq subseq rsubseq Transients (clojure.org/transients)

Create transient persistent!

Change conj! pop! assoc! dissoc! disj! Note: always use return

value for later changes, never original!

Misc

= == identical? not= not compare clojure.data/diff Compare

true? false? nil? instance? Test

Sequences

Creating a Lazy Seq

From collection seq vals keys rseq subseq rsubseq

From producer fn lazy-seq repeatedly iterate

From constant repeat range

From other file-seq line-seq resultset-seq re-seq tree-seq xml-seq iterator-seq

enumeration-seq

From seq keep keep-indexed

Seq in, Seq out

Get shorter distinct filter remove take-nth for

Get longer cons conj concat lazy-cat mapcat cycle

interleave interpose

Tail-items rest nthrest fnext nnext drop drop-while

take-last for

Head-items

take take-while butlast drop-last for conj concat distinct flatten group-by 'Change'

partition partition-all partition-by split-at

split-with filter remove replace shuffle

Rearrange reverse sort sort-by compare

Process items map pmap map-indexed mapcat for replace seque

Using a Seq

Extract item first second last rest next ffirst nfirst

fnext nnext nth nthnext rand-nth when-first

max-key min-key

Construct coll zipmap into reduce reductions set vec

into-array to-array-2d

Pass to fn apply Search some filter

Force evaluation doseq dorun doall Check for forced realized?

Zippers (clojure.zip/)

Create zipper seq-zip vector-zip xml-zip

Get loc up down left right leftmost rightmost Get seg lefts rights path children

'Change' make-node replace edit insert-child insert-left

insert-right append-child remove

Move next prev

Misc root node branch? end?

10

to string

Open

Binary

spit slurp (to writer/from reader, Socket, string with to/from

file name, URI, etc.)

to \*out\* pr prn print printf println newline (clojure.pprint/) print-table

to writer (clojure.pprint/) pprint cl-format also: (binding [\*out\* writer] ...)

format with-out-str pr-str prn-str print-str

println-str from \*in\* read-line (clojure.tools.reader.edn/) read

from reader line-seq (clojure.tools.reader.edn/) read also:

(binding [\*in\* reader] ...) java.io.Reader with-in-str (clojure.tools.reader.edn/) read-string from string

with-open (clojure.java.io/) text: reader writer

binary: input-stream output-stream

(.write ostream byte-arr) (.read istream byte-arr) java.io.OutputStream

java.io.InputStream GitHub: gloss byte-spec Misc flush (.close s) file-seq \*in\* \*out\* \*err\*

(clojure.java.io/) file copy delete-file resource as-file as-url as-relative-path GitHub: fs Data readers (1.4) \*data-readers\* default-data-readers (1.5)

\*default-data-reader-fn\*

**Functions** 

Create fn defn defn- definline identity constantly memfn comp complement partial juxt memoize fnil every-pred

some-fn

Call apply -> ->> (1.5) as-> cond-> cond->> some->

some->>

Test fn? ifn?

## **Abstractions**

### Protocols (clojure.org/protocols)

Define ( defprotocol Slicey (slice [at])) ( extend-type String Slicey (slice [at] ...)) Extend Extend null (extend-type nil Slicey (slice [\_] nil)) Reifv ( reify Slicey (slice [at] ...))

### Records (clojure.org/datatypes)

( defrecord Pair [h t]) Define (:h (Pair. 1 2)) ightarrow 1 Access Create Pair. ->Pair map->Pair

### Types (clojure.org/datatypes)

Define ( deftype Pair [h t]) (.h (Pair. 1 2))  $\rightarrow$  1 Access Pair. ->Pair Create

( deftype Pair [h t]

make-hierarchy

With methods Object

(toString [this] (str "<" h "," t ">")))

# Multimethods (clojure.org/multimethods)

Define ( defmulti my-mm dispatch-fn) ( defmethod my-mm :dispatch-value [args] ...) Method define Dispatch get-method methods Remove remove-method remove-all-methods Prefer prefer-method prefers Relation derive isa? parents ancestors descendants

#### Macros

Create defmacro definline Debug macroexpand-1 macroexpand (clojure.walk/) macroexpand-all and or when when-not when-let when-first if-not Branch if-let cond condp case Loop for doseq dotimes while Arrange .. doto -> ->> (1.5) as-> cond-> cond->> some-> some->> Scope binding locking time with-{in-str, local-vars, open, out-str, precision, redefs, redefs-fn} lazy-cat lazy-seq delay Lazv Doc. assert comment doc

### Reader Macros

Quote 'form  $\rightarrow$  (quote form) ١ Character literal Single line comment ; Metadata (see Metadata section) Deref @form → (deref form) 0 Syntax-quote Unquote Unquote-splicing ~@ Regex Pattern p #"p" #/ Var quote  $\#' \times \to (\text{var } \times)$  $\#(...) \rightarrow (fn [args] (...))$ #() Ignore next form

# Metadata (clojure.org/special\_forms)

General ^{:key1 val1 :key2 val2 ...} Abbrevs ^Type ightarrow ^{:tag Type}, ^:key ightarrow ^{:key true} ^:dynamic ^:private ^:doc ^:const Common (defn ^:private ^String my-fn ...) Examples (def ^:dynamic \*dyn-var\* val) On Vars meta with-meta vary-meta alter-meta! reset-meta! doc find-doc test

# Special Forms (clojure.org/special\_forms)

def if do let quote var fn loop recur throw try monitor-enter monitor-exit Binding Forms / (examples) let fn defn defmacro loop for doseq if-let when-let Destructuring

# Vars and global environment (clojure.org/vars)

def defn defn- definline defmacro defmethod Def variants defmulti defonce defrecord Interned vars declare intern binding find-var var Var objects with-local-vars var-get var-set alter-var-root var? Var validators set-validator! get-validator

### Namespace

Current \*ns\* (tutorial) ns in-ns create-ns Create/Switch

Add alias def import intern refer

all-ns find-ns Find

ns-{name, aliases, map, interns, publics, Examine

refers, imports}

From symbol resolve ns-resolve namespace ns-unalias ns-unmap remove-ns Remove

## Loading

Load libs (tutorial) require use import refer

List loaded loaded-libs

Load misc load load-file load-reader load-string

### Concurrency

Atoms atom swap! reset! compare-and-set!

**Futures** future future-{call, done?, cancel, cancelled?}

future?

Threads bound-fn bound-fn\* {get, push, pop}-thread-bindings

thread-bound?

Misc locking pcalls pvalues pmap seque promise deliver

### Refs and Transactions (clojure.org/refs)

Create ref

Examine  $\texttt{deref @ (@form} \rightarrow (\mathsf{deref form}))$ 

Transaction sync dosync io!

In transaction ensure ref-set alter commute Validators set-validator! get-validator

ref-history-count ref-{min, max}-history History

### Agents and Asynchronous Actions (clojure.org/agents)

Create agent Examine agent-error Change state send send-off restart-agent (1.5) send-via set-agent-send-executor! set-agent-send-off-executor! Block waiting await await-for set-validator! get-validator Ref validators Watchers add-watch remove-watch Thread handling shutdown-agents error-handler set-error-handler! error-mode Error set-error-mode! Misc \*agent\* release-pending-sends

# Java Interoperation (clojure.org/java\_interop)

General .. doto Classname/ Classname. new bean

comparator enumeration-seq import iterator-seq

memfn set!

Cast boolean byte short char int long float double

bigdec bigint num cast biginteger

Exceptions throw try catch finally pst (1.4) ex-info

ex-data

# Arravs

Create make-array {object, boolean, byte, short, char, int, long, float, double}-array aclone to-array

to-array-2d into-array

aget aset aset-{boolean, byte, short, char, int, Use

long, float, double} alength amap areduce booleans bytes shorts chars ints longs floats Cast

doubles

# Proxy

Create proxy get-proxy-class {construct, init}-proxy Misc proxy-mappings proxy-super update-proxy

# Other

**XML** clojure.xml/parse xml-seq REPL \*1 \*2 \*3 \*e \*print-dup\* \*print-length\* \*print-level\* \*print-meta\* \*print-readably\* Code \*compile-files\* \*compile-path\* \*file\* \*warn-on-reflection\* compile gen-class gen-interface loaded-libs test Misc eval force hash name \*clojure-version\* clojure-version \*command-line-args\*

 $({\sf clojure.java.browse/}) \ \ {\tt browse-url} \ \ ({\sf clojure.java.shell/}) \ \ {\tt sh}$ Browser / Shell with-sh-dir with-sh-env