Clojure Cheat Sheet (Clojure 1.3, sheet v1.4)

Documentation clojure.repl/ doc

pl/ doc find-doc apropos source pst javadoc
 (foo.bar/ is namespace for later syms)

Primitives

Numbers
Literals Long:

Literals Long: 7 BigInt: 7N Ratio: -22/7 Double:

2.78 BigDecimal: 4.2M

Arithmetic + - * / quot rem mod inc dec max min

Compare = == not= < > <= >= compare
Bitwise bit-{and, or, xor, not, flip, set,

shift-right, shift-left, and-not, clear,

test}

Cast byte short int long float double bigdec

bigint num rationalize biginteger
nil? identical? zero? pos? neg? even? odd?

Random rand rand-int

BigInt with-precision

Unchecked unchecked-{add, dec, divide, inc, multiply,

negate, remainder, subtract}-int

Strings

Test

Create str format See also IO/to string

Use count get subs compare (clojure.string/) join

 $\hbox{\tt escape split split-lines replace replace-first}$

reverse (String) .indexOf .lastIndexOf

Regex #"pattern" re-find re-seq re-matches

re-pattern re-matcher re-groups (clojure.string/)

replace replace-first

Letters (clojure.string/) capitalize lower-case upper-case Trim (clojure.string/) trim trim-newline triml trimr

Test char char? string? (clojure.string/) blank?

Other

Characters char char-name-string char-escape-string

Keywords keyword? find-keyword

Symbols symbol? gensym

Collections

Collections

Generic ops count empty not-empty into conj

Content tests distinct? empty? every? not-every? some

not-any?

Capabilities sequential? associative? sorted? counted?

reversible?

Type tests coll? list? vector? set? map? seq?

Lists

Create '() list list*

Examine first nth peek .indexOf .lastIndexOf

'Change' cons conj rest pop

Vectors

Create [] vector vec vector-of

Examine (my-vec idx) \rightarrow (nth my-vec idx) get peek

.indexOf .lastIndexOf

'Change' assoc pop subvec replace conj rseq

Sets Create

#{} set hash-set sorted-set sorted-set-by

Examine $(my\text{-set item}) \rightarrow (get my\text{-set item})$

contains?

'Change' conj disj

Rel algebra (clojure.set/) join select project union

difference intersection

Get map (clojure.set/) index rename-keys rename

map-invert

Test (clojure.set/) subset? superset?

Maps

'Change'

Create {} hash-map array-map zipmap sorted-map

sorted-map-by bean frequencies group-by

Examine (:key my-map) \rightarrow (get my-map :key)

get-in contains? find keys vals assoc assoc-in dissoc merge merge-with

select-keys update-in

Entry key val
Sorted maps rseq subseq rsubseq

Transients (clojure.org/transients)

Create transient persistent!

Change conj! pop! assoc! dissoc! disj! Note: always use

return value for later changes, never original!

Misc

Compare = == identical? not= not compare

clojure.data/diff

Test true? false? nil? instance?

Sequences Creating a Lazy Seq From collection seq vals keys rseq subseq rsubseq From producer fn lazy-seq repeatedly iterate From constant repeat range From other file-seq line-seq resultset-seq re-seq tree-seq xml-seq iterator-seq enumeration-seq From seq keep keep-indexed Seq in, Seq out Get shorter distinct filter remove for cons conj concat lazy-cat mapcat cycle Get longer interleave interpose Tail-items rest nthrest fnext nnext drop drop-while take-last for Head-items take take-nth take-while butlast drop-last for 'Change' conj concat distinct flatten group-by partition partition-all partition-by split-at split-with filter remove replace shuffle reverse sort sort-by compare Rearrange Process items map pmap map-indexed mapcat for replace seque Using a Seq Extract item first second last rest next ffirst nfirst fnext nnext nth nthnext rand-nth when-first max-key min-key Construct coll zipmap into reduce reductions set vec into-array to-array-2d Pass to fn apply

Force evaluation

Check for forced

Search

10

Create	zipper seq-zip vector-zip xml-zip
Get loc	up down left right leftmost rightmost
Get seq	lefts rights path children
'Change'	make-node replace edit insert-child insert-left insert-right append-child remove
Move	next prev

some filter

realized?

doseq dorun doall

Misc root node branch? end?

to/from	<pre>spit slurp (to writer/from reader, Socket, string</pre>
	with file name, URI, etc.)
to *out*	<pre>pr prn print printf println newline (clo- jure.pprint/) print-table</pre>
to writer	<pre>(clojure.pprint/) pprint cl-format also:</pre>
	(binding [*out* writer])
to string	format with-out-str pr-str prn-str
	print-str println-str
from *in*	read-line read
from reader	<pre>line-seq read also: (binding [*in* reader]) java.io.Reader</pre>
from string	read-string with-in-str
Open	with-open (clojure.java.io/) text: reader writer

binary: input-stream output-stream Binary (.write ostream byte-arr) (.read istream byte-arr) java.io.OutputStream java.io.InputStream GitHub: gloss byte-spec

Misc flush (.close s) file-seq *in* *out* *err*

(clojure.java.io/) file copy GitHub: fs

Functions

Create	fn defn defn- definline identity constantly
	memfn comp complement partial juxt memoize
	fnil every-pred some-fn
Call	-> ->> apply
Test	fn? ifn?

```
Abstractions
Protocols (clojure.org/protocols)
              ( defprotocol Slicey (slice [at]))
              ( extend-type String Slicey (slice [at]
 Extend
              ...))
 Extend null
             ( extend-type nil Slicey (slice [_] nil))
              ( reify Slicey (slice [at] ...))
 Reify
Records (clojure.org/datatypes)
 Define
          ( defrecord Pair [h t])
 Access
         (:h (Pair. 1 2)) \rightarrow 1
 Create
         Pair. ->Pair map->Pair
Types (clojure.org/datatypes)
 Define
                ( deftype Pair [h t])
 Access
                (.h (Pair. 1 2)) \rightarrow 1
 Create
                Pair. ->Pair
                ( deftype Pair [h t]
 With methods
                  Object
                   (toString [this] (str "<" h "," t ">")))
Multimethods (clojure.org/multimethods)
 Define
                 ( defmulti my-mm dispatch-fn)
 Method define
                 ( defmethod my-mm :dispatch-value [args]
                 ...)
 Dispatch
                get-method methods
 Remove
                remove-method remove-all-methods
 Prefer
                prefer-method prefers
```

Macros	
Create	defmacro definline macroexpand-1 macroexpand
Branch	and or when when-not when-let when-first
	if-not if-let cond condp case
Loop	for doseq dotimes while
Arrange	doto ->
Scope	binding locking time with-{in-str,
	local-vars, open, out-str, precision, redefs,
	redefs-fn}
Lazy	lazy-cat lazy-seq delay
Doc.	assert comment doc

derive isa? parents ancestors

descendants make-hierarchy

Relation

Reader	Macros
,	Quote 'form \rightarrow (quote form)
\	Character literal
;	Single line comment
^	Metadata (see Metadata section)
0	$Deref \ @form \to (deref \ form)$
•	Syntax-quote
~	Unquote
~@	Unquote-splicing
#"p"	Regex Pattern p
#'	Var quote $\#'x \to (var x)$
#()	$\#() \rightarrow (fn \; [args] \; ())$
#_	Ignore next form

Metadata	(clojure.org/special_torms)
General	^{:key1 val1 :key2 val2}
Abbrevs	^Type $ ightarrow$ ^{:tag Type}, ^:key $ ightarrow$ ^{:key true}
Common	^:dynamic ^:private ^:static ^:const
Examples	<pre>(defn ^:private ^:static ^String my-fn) (def ^:dynamic *dyn-var* val)</pre>
On Vars	meta with-meta vary-meta alter-meta! reset-meta! doc find-doc test

```
Special Forms (clojure.org/special_forms)
 def if do let quote var fn loop recur throw try
 monitor-enter monitor-exit
 Binding Forms /
                 (examples) let fn defn defmacro loop
 Destructuring
                 for doseq if-let when-let
```

Vars and global environment (clojure.org/vars)

Def variants def defn defn- definline defmacro

defmethod defmulti defonce defrecord declare intern binding find-var var

Interned vars declare intern binding find-var var Var objects with-local-vars var-get var-set

alter-var-root var?

Var validators set-validator! get-validator

Namespace

Examine

Current *ns*

 $\begin{array}{lll} {\sf Create/Switch} & {\sf (tutorial)} \ {\sf ns} \ {\sf in-ns} \ {\sf create-ns} \\ {\sf Add} & {\sf alias} \ {\sf def} \ {\sf import} \ {\sf intern} \ {\sf refer} \end{array}$

Find all-ns find-ns

ns-{name, aliases, map, interns,

publics, refers, imports}

From symbol resolve ns-resolve namespace
Remove ns-unalias ns-unmap remove-ns

Loading

Load libs (tutorial) require use import refer

List loaded loaded-libs

Load misc load load-file load-reader load-string

Concurrency

Atoms atom swap! reset! compare-and-set! Futures future-{call, done?, cancel,

cancelled?} future?

Threads bound-fn bound-fn* {get, push,

pop}-thread-bindings thread-bound?

Misc locking pcalls pvalues pmap seque promise

deliver

Refs and Transactions (clojure.org/refs)

Create ref

Examine $deref @ (@form \rightarrow (deref form))$

Transaction sync dosync io!

In transaction ensure ref-set alter commute Validators set-validator! get-validator

History ref-history-count ref-{min, max}-history

Agents and Asynchronous Actions (clojure.org/agents)

Create agent
Examine agent-error

Change state send send-off restart-agent

Block waiting await await-for

Ref validators set-validator! get-validator

Watchers add-watch remove-watch

Thread handling shutdown-agents
Error error-handler set-error-handler!

Lifoi effor handrer set effor handrer

error-mode set-error-mode!
agent release-pending-sends

Java Interoperation (clojure.org/java_interop)

General .. doto Classname/ Classname. new

bean comparator enumeration-seq import

iterator-seq memfn set!

Cast boolean byte short char int long float

double bigdec bigint num cast biginteger

Exceptions throw try catch finally pst

Arrays

Misc

Create make-array {object, boolean, byte, short,

char, int, long, float, double}-array aclone

to-array to-array-2d into-array

Use aget aset aset-{boolean, byte, short, char,

int, long, float, double alength amap areduce
booleans bytes shorts chars ints longs floats

doubles

Proxy

Cast

Create proxy get-proxy-class {construct, init}-proxy
Misc proxy-mappings proxy-super update-proxy

Misc eval force hash name *clojure-version*
clojure-version *command-line-args*