CSAM Paratus 26.0 - Integrations - amPHI

Template: T7.3.0.10_Integration Documentation

Document attributes

Date (yyyymmdd)	2024-01-22	
Document Owner	Team Manager Development	
Author	Tobias Arvsell	
Status	Approved	
Approved by	Daniel Mester Pirttijärvi	Date: 2024-01-22
Distribution		
Process link	S7.3.0.1_Development - phase 3 S7.3.0.1.1_Development - Sub-process Design and Development	

Revision history

Date	Rev.no.	Change	Author
2021-01-22	0.1	Initial revision	Tobias Arvsell
2021-02-10	1.0	Approved version	Daniel Mester Pirttijärvi
2021-10-29	1.1	Updated document for next version	Magdalena Lönnerstrand
2021-11-17	1.2	Typos and formatting.	Daniel Mester Pirttijärvi
2021-11-23	1.3	Added new fields	Tobias Arvsell
2021-11-23	2.0	Approved for v24	Daniel Mester Pirttijärvi
2022-03-21	2.1	Updated document for v25	Magdalena Lönnerstrand
2022-10-20	2.2	Updated symbol objects specifications	Tobias Arvsell
2022-10-28	2.3	Correction: wards property of destinations is an array, not an object.	Daniel Mester Pirttijärvi
2022-10-31	3.0	Approved for v25	Daniel Mester Pirttijärvi
2023-04-20	3.1	Updated document for v26	Daniel Mester Pirttijärvi
2023-04-20	4.0	Approved for v26	Daniel Mester Pirttijärvi
2024-01-22	4.1	Updated property *assignmentid* of symbols. Updated api version to 2.2.0.	Tobias Arvsell
2024-01-22	5.0	Approved for v26	Daniel Mester Pirttijärvi

Table of Contents

1 Outline 5

2 Technical Architecture 5

3 Interfaces overview 5

4 Interface details 6

4.1 Assignments 6

4.1.1 Technology 6

4.1.2 Input parameter 6

4.1.3 Output parameter 6

4.1.4 Exception handling 6

4.1.5 Interface definition 6

4.2 Symbols 6

4.2.1 Technology 7

4.2.2 Input parameter 7

4.2.3 Output parameter 7

4.2.4 Exception handling 7

4.2.5 Interface definition 8

4.3 Unit 8

4.3.1 Technology 8

4.3.2 Input parameter 8

4.3.3 Output parameter 8

4.3.4 Exception handling 8

4.3.5 Interface definition 8

4.4 Command 8

4.4.1 Technology 8

4.4.2 Input parameter 8

4.4.3 Output parameter 9

4.4.4 Exception handling 9

4.4.5 Interface definition 9

4.5 Notes 9

4.5.1 Technology ... 9
4.5.2 Input parameter ... 9
4.5.3 Output parameter ... 10
4.5.4 Exception handling ... 10
4.5.5 Interface definition ... 10
4.6 Messages ... 10
4.6.1 Technology ... 10
4.6.2 Input parameter ... 11
4.6.3 Output parameter ... 11
4.6.4 Exception handling ... 12
4.6.5 Interface definition ... 12
4.7 Apiversion ... 12
4.7.1 Technology ... 12
4.7.2 Input parameter ... 12
4.7.3 Output parameter ... 12
4.7.4 Exception handling ... 12
4.7.5 Interface definition ... 12
4.8 Destinations ... 12
4.8.1 Technology ... 12
4.8.2 Input parameter ... 12
4.8.3 Output parameter ... 13
4.8.4 Exception handling ... 13
4.8.5 Interface definition ... 13
4.9 Loggedinusers ... 14
4.9.1 Technology ... 14
4.9.2 Input parameter ... 14
4.9.3 Output parameter ... 14
4.9.4 Exception handling ... 14
4.9.5 Interface definition ... 14
5 Appendix ... 14

5.1 Assignments 14
5.1.1 Specification 14
5.1.2 Example message 20
5.2 Symbols 30
5.2.1 Specification 30
5.2.2 Example message 33
5.3 Unit 35
5.3.1 Specification 35
5.3.2 Example message 35
5.4 Command 36
5.4.1 Specification 36
5.4.2 Example message 36
5.5 Notes 36
5.5.1 Specification 36
5.5.2 Example message 37
5.6 Messages 37
5.6.1 Specification 37
5.6.2 Example message 37
5.7 Destinations 37
5.7.1 Specification 37
5.7.2 Example message 37

1 Outline

This document describes the REST API hosted in Paratus Navigation.

2 Technical Architecture

Paratus Navigation exposes a REST API for an external system to use. This means that Paratus Navigation does not initiate any contact with the external system, instead it is the external system that must send and receive updates so that the systems are synchronized. All requests and responses use JSON as a data format. The Content-Type header should be set to *application/json* when sending data in the request body.

The base URL is as default https://<ip>:443/api/rest/

3 Interfaces overview

Status **New/Updated/ no change**	**Interface name**	**Description**
No change	Assignments	Get all assignments, get a specific assignment, or update an assignment.
No change	Symbols	Get, update, add or remove symbols shown in the map
No change	Unit	Get general information about the unit.
No change	Command	Gets or updates information about medical command.
No change	Notes	Gets all notes or add new notes for an assignment.
No change	Messages	Returns all messages or sends a message.
No change	Apiversion	Returns the current version of the REST API.
No change	Destinations	Adds a list of predefined destinations.
No change	Loggedinusers	Log out the specified user

4 Interface details

4.1 ASSIGNMENTS

This route returns all assignments that are currently active in Paratus Navigation. It also includes closed assignments that has been active in the last hour.

If an id is provided as a path parameter it is possible to get or update a specific assignment.

The URL for this route is <baseurl>/assignments.

4.1.1 Technology

Supports the standard HTTP method.

- GET – Returns all active assignments or a specific assignment.
- PUT – Updates information for an assignment.

4.1.2 Input parameter

4.1.2.1 GET

If no path parameter is given this call will return all assignments

If the path parameter *id* is provided. It should refer to a matching id of an existing assignment.

4.1.2.2 PUT

The path parameter *id* must be provided. It should refer to a matching id of an existing assignment.

A request body should also be provided specifying which properties to update, see section 5.1.2.1 for an example.

4.1.3 Output parameter

All HTTP methods returns standard HTTP status codes.

4.1.3.1 GET

The response body is a JSON formatted array with assignment objects, see specification in section 5.1.2.2.

4.1.3.2 PUT

No response body.

4.1.4 Exception handling

Returns standard HTTP response codes.

4.1.5 Interface definition

See section 5.1.

4.2 SYMBOLS

This route can be used to retrieve all symbols shown in the map, update or add symbols, or delete one or all symbols. There are three different types of symbols, vehicle, area or point/icon.

The URL for this route is <baseurl>/symbols.

4.2.1 Technology

Supports the standard HTTP methods.

- GET – Returns all symbols that are visible in the map.
- PUT – Update or add symbols to the map.
- POST – Replace all symbols.
- DELETE – Remove a symbol from the map.

4.2.2 Input parameter

4.2.2.1 GET

No input parameters.

4.2.2.2 PUT

No path parameters

A request body must be provided containing one or more symbol objects to update or add (if the *id* is not provided). In section 5.2.1 the different object types are specified.

4.2.2.3 POST

No path parameters

A request body must be provided with all the symbols to show in the map. The existing will be replaced. The body should be an array of objects where each object is defined as one of the types specified in section 5.2.1.

4.2.2.4 DELETE

The path parameter *id* must be provided. It should refer to a matching id of an existing symbol.

4.2.3 Output parameter

All HTTP methods returns standard HTTP status codes.

4.2.3.1 GET

The response body is a JSON formatted array with symbol objects. Each object is one of the types specified in section 5.2.1.

4.2.3.2 POST

No response body.

4.2.3.3 DELETE

No response body.

4.2.4 Exception handling

Returns standard HTTP status codes.

4.2.5 Interface definition

See section 5.2.

4.3 UNIT

This route returns general information about the unit, e.g. radio number, position and current state.

The URL for this route is <baseurl>/unit.

4.3.1 Technology

Supports the standard HTTP methods.

- GET – Returns information about the unit.

4.3.2 Input parameter

No input parameters

4.3.3 Output parameter

Returns standard HTTP status codes.

The response body contains JSON formatted unit object as specified in section 5.3.1.

4.3.4 Exception handling

Returns standard HTTP status codes.

4.3.5 Interface definition

See section 5.3.

4.4 COMMAND

This route returns or updates information about medical command for a specified assignment.

The URL for this route is <baseurl>/command.

4.4.1 Technology

Supports the standard HTTP methods.

- GET – Returns medical command information for the specified assignment.
- POST – Updates medical command information for the specified assignment.

4.4.2 Input parameter

4.4.2.1 GET

The path parameter *id* must be provided. It should refer to a matching id of an existing assignment.

4.4.2.2 POST

The path parameter *id* must be provided. It should refer to a matching id of an existing assignment.

A request body must be provided with the information to update. The body should contain a JSON object with the properties specified in section 5.4.1.

4.4.3 Output parameter

Returns standard HTTP status codes.

4.4.3.1 GET

The response body contains a JSON formatted object with the medical command information for the specified assignment. The properties in the object are specified in section 5.4.1.

4.4.3.2 POST

No response body.

4.4.4 Exception handling

Returns standard HTTP status codes.

4.4.5 Interface definition

See section 5.4.

4.5 NOTES

This route returns all notes for an assignment using the GET-method. By using the POST-method it is possible to add one or more notes to an assignment.

The URL for this route is <baseurl>/notes.

4.5.1 Technology

Supports the standard HTTP methods.

- GET – Returns medical command information for the specified assignment.
- POST – Updates medical command information for the specified assignment.

4.5.2 Input parameter

4.5.2.1 GET

The path parameter *id* must be provided. It should refer to a matching id of an existing assignment.

4.5.2.2 POST

The path parameter *id* must be provided. It should refer to a matching id of an existing assignment.

A request body must be provided with the information to update. The body should contain an array of JSON objects where each object represents a note. The objects must have the following properties.

Name	Description	**Type**	Example
assignment_id	Unique identifier for the assignment	GUID	dfd4fd99-1fa9-4624-9cfe-05e65ef63fa9
author	Radio number for the unit that has written the note	String	3319110
created	Time when the note was created. Formatted as a JSON timestamp	String	2020-11-14T11:48:50Z

id	Unique identifier for the note	GUID	de9168e5-d422-4bc8-a6e2-71067b12ea63
text	The note content	String	“Three cars involved and one truck.”

4.5.3 Output parameter

Returns standard HTTP status codes.

4.5.3.1 GET

The response body contains an array of JSON formatted objects where each object represents a note. The properties for each object are the following.

Name	Description	**Type**	Example
assignment_id	Unique identifier for the assignment	GUID	dfd4fd99-1fa9-4624-9cfe-05e65ef63fa9
author	Radio number for the unit that has written the note	String	3319110
created	Time when the note was created. Formatted as a JSON timestamp	String	2020-11-14T11:48:50Z
id	Unique identifier for the note	GUID	de9168e5-d422-4bc8-a6e2-71067b12ea63
text	The note content	String	“Three cars involved and one truck.”

4.5.3.2 POST

No response body.

4.5.4 Exception handling

Returns standard HTTP status codes.

4.5.5 Interface definition

See section 5.5.2 for example message,

4.6 MESSAGES

This route and using the GET-method return all messages that has been sent and received in Paratus Navigation. If the POST-method is used it is possible to send a message to another radio receiver.

The URL for this route is <baseurl>/messages.

4.6.1 Technology

Supports the standard HTTP methods.

- GET – Returns all sent and received messages.

- POST – Sends a message through Paratus Navigation to another radio receiver.

4.6.2 Input parameter

4.6.2.1 GET

No input parameters.

4.6.2.2 POST

No path parameters.

A request body must be provided with the message to send. The body should contain a JSON object representing the message which should define the properties in the table below.

Name	Description	Type	Example
author	Radio number for the unit that has written the message	String	3319180
destination	Radio number for the receiving unit	String	3319110
created	Time when the message was create. Formatted as a JSON timestamp	String	2020-11-14T11:48:50Z
text	The message content	String	“Access road from the south blocked.”

4.6.3 Output parameter

Returns standard HTTP status codes.

4.6.3.1 GET

The response body contains an array of JSON formatted objects where each object represents a message. The properties for each object are the following.

Name	Description	Type	Example
id	Unique identifier for the message	GUID	de9168e5-d422-4bc8-a6e2-71067b12ea63
author	Radio number for the unit that has written the message	String	3319180
destination	Radio number for the receiving unit	String	3319110
created	Time when the message was created. Formatted as a JSON timestamp.	String	2020-11-14T11:48:50Z
text	The message content	String	“Access road from the south blocked.”

Table 1 - Message object

4.6.3.2 POST

No response body.

4.6.4 Exception handling

Returns standard HTTP status codes.

4.6.5 Interface definition

See section 5.6.2 for example message.

4.7 APIVERSION

This route returns the current version of this API. The current version is 2.2.0.

The URL for this route is <baseurl>/apiversion.

4.7.1 Technology

Supports the standard HTTP methods.

- GET – Returns the current version of this API.

4.7.2 Input parameter

No input parameters.

4.7.3 Output parameter

Returns standard HTTP status codes.

The response body contains a string with the current version, e.g., 2..0.

4.7.4 Exception handling

Returns standard HTTP status codes.

4.7.5 Interface definition

No further specification needed.

4.8 DESTINATIONS

By using this route, it is possible to add a list of predefined destinations in Paratus Navigation, which be selectable by the user.

The URL for this route is <baseurl>/destinations.

4.8.1 Technology

Supports the standard HTTP methods.

- POST – Adds a list of predefined destinations.

4.8.2 Input parameter

No path parameter.

The request body should contain an array of JSON objects, where each object represents a destination. A destination object is defined by the properties in the table below.

Name	Description	Type	Example
name	Name of destination	String	Södersjukhuset
abbreviation	Abbreviation for the destination name	String	SÖS
position	Position for the destination	JSON object	See Table 3 - Position object
type	Type of destination. Destinations can be sorted in Paratus Navigation based on this type.	String	Akutsjukhus
wards	A list of wards that belongs to this destination. This list must contain at least one entry.	JSON array	See Table 4 - Ward object

Table 2 - Destination object

Name	Description	Type	Example
wgs84_dd_la	Latitude in decimal degrees	Double	58.164322
wgs84_dd_lo	Longitude in decimal degrees	Double	13.564223

Table 3 - Position object

Name	Description	Type	Example
id	Id of the ward.	Integer	1
name	Name of the ward.	String	Akutmottagning
abbreviation	Abbreviation of the ward.	String	AKM
status_code	Status code to send by radio to alarm central.	Integer	38684
position	Position of the ward.	JSON object	See Table 3 - Position object.

Table 4 - Ward object

4.8.3 Output parameter

Returns standard HTTP status codes.

4.8.4 Exception handling

Returns standard HTTP status codes.

4.8.5 Interface definition

See section 5.7.2 for an example message.

4.9 LOGGEDINUSERS

This route informs Paratus Navigation that the specified user is logged out in the external calling system.

The URL for this route is <baseurl>/loggedinusers.

4.9.1 Technology

Supports the standard HTTP methods.

- DELETE – Removes information about the logged in user.

4.9.2 Input parameter

The path parameter *id* must be provided. It should refer to a username for a previously logged in user.

4.9.3 Output parameter

Returns standard HTTP status codes.

4.9.4 Exception handling

Returns standard HTTP status codes.

4.9.5 Interface definition

No further definition needed.

5 Appendix

5.1 ASSIGNMENTS

5.1.1 Specification

In Table 5 below all properties for an assignment object is specified.

Name	Description	Type	Example
rowid	Unique identifier for the assignment.	GUID	dfd4fd99-1fa9-4624-9cfe-05e65ef63fa9
assignment_number	Assignment number which consist of central number, case folder id, case id and mission id separated with :	String	17:4325532:1:1
created	Time when the assignment was created. Formatted as a JSON timestamp.	String	2020-11-14T11:48:50Z
received	Time when the assignment was received in Paratus	String	2020-11-14T11:48:50Z

	Navigation. Formatted as a JSON timestamp.		
accepted	Time when the assignment was accepted in Paratus Navigation. Formatted as a JSON timestamp.	String	2020-11-14T11:48:50Z
is_closed	Indicates if the assignment is closed or not	Boolean	true/false
close_reason	Contains possible reason for closing the assignment (entered by the user)	JSON object	See Table 6 - Close reason object
is_selected	Indicates if the assignment is selected in Paratus Navigation. A value of 0 indicates that the assignment is not seleted, all values >= 1 indicates that the assignment is selected.	Integer	1
is_destination_alarm_sent	Indicates if the destination has been alarmed	Boolean	true/false
selected_destination	Id for selected destination	String	
eta	Estimated time of arrival. Formatted as a JSON timestamp.	String	2020-03-31T14:45:00Z
is_head_unit	Indicates if the unit is currently the commander for this assignment.	Boolean	true/false
is_routed	Indicates if the route is plotted in the map.	Boolean	true/false
distance	The total driven distance on the assignment. Given in meters.	Integer	3402
methane_report	Methane-report, if a methane-report is not	JSON object	See Table 7

	registered in Paratus Navigation the field will contain an empty object ({})		
rek_report	REK report according to SLL plotting document.	JSON object	See example message
position	Position for the assignment.	JSON object	See Table 12
to_position	If the patient should be delivered to specific destination, this will be the position for that destination.	JSON object	See Table 12
properties	An array of all information tags sent from the alarm central. Content of this array may vary in different configurations.	Array of JSON objects.	See example message.
state	Current state of the assignment.	JSON object	See Table 13
state_entries	Contains information about all assignment state transitions and the distance that has been driven in each state.	Array of JSON object	See example message
state_configuration	Current configuration of assignment states for this assignment.	Array of JSON objects	See Table 14

Table 5 - Assignment object

Name	Description	Type	Example
reason	One of the options selected in Paratus Navigation.	String	Patient saknades
comment	May contain any user comment	String	Tomt på platsen

Table 6 - Close reason object

Name	Description	Type	Example

created	Time when the report was created. Formatted as a JSON timestamp.	String	2020-11-14T11:48:50Z
last_updated	Time when the report was last updated. Formatted as a JSON timestamp.	String	2020-11-14T12:14:34Z
access_road	Information about the access road	JSON object	See Table 8
exact_location	Address where the report is registered.	String	Storgatan 3
extra_resources	Information about extra resource	JSON object	See Table 9
hazards	Selected possible threats and risks on site.	Array of strings.	[“Brand”, “Rök”]
inventory_level	Current level of inventory for the incident site.	JSON object	See Table 10
major_incident	Indicates if it is a suspected major incident.	Boolean	true/false
numbers_affected	Total number of affected.	Integer	4
numbers_affected_green	Number of affected that is categorized as green.	Integer	2
numbers_affected_yellow	Number of affected that is categorized as yellow.	Integer	1
numbers_affected_red	Number of affected that is categorized as red.	Integer	1
position	Position where this report where registered.	JSON object	See Table 11
special_injuries	Special injuries	String	
time_first_departure	Time for first transport departure. Formatted as a JSON timestamp.	String	2020-03-31T14:45:00Z
types	Selected type of event.	Array of strings.	[“Trafikolycka”]

Table 7 - Methane report object

Name	Description	Type	Example
is_obstructed	Indicates if the access road is obstructed.	Boolean	true/false
comment	Contains any user entered comment for the obstructed access road	String	“Vägen blockerad. Kör söderifrån.”

Table 8 - Access road object

Name	Description	Type	Example
ambulances	Number of extra ambulances.	Integer	2
chemical_suit	Number of extra chemical suits.	Integer	1
emergency_wagon	Number of extra emergency wagons.	Integer	1
medical_team	Number of extra medical teams.	Integer	0
sanitation_wagon	Number of extra sanitation wagons.	Integer	2
doctor_on_duty	Number of extra doctors on duty.	Integer	1
helicopter	Number of extra helicopters.	Integer	2
commander_unit	Number of extra commander units.	Integer	0
PAM	Number of extra PAM units.	Integer	0
medical_transport	Number of extra medical transports.	Integer	0
transport_ambulance	Number of extra transport ambulances.	Integer	0
units_total	Number of units in total. The sum of above units.	Integer	9

Table 9 - Extra resources object

Name	Description	Type	Example
selected_level_index	The current selected index of inventory. The index refers to the *levels* property.	Integer	1
levels	All levels of inventory. Fixed values for 0, a third, two thirds, three thirds.	Array of strings	[“0”, “1_3”, “2_3”, “3_3”]

Table 10 - Inventory level object

Name	Description	Type	Example
wgs84_dd_la	Latitude in decimal degrees	Double	58.164322
wgs84_dd_lo	Longitude in decimal degrees	Double	13.564223

rt90_x	X value for RT90 coordinate	Double	6581976.875412831
rt90_y	Y value of RT90 coordinate	Double	1628492.661460190
sweref99_e	Easting value of SWEREF 99 TM coordinate	Double	674219.1730
sweref99_n	Northing value of SWEREF 99 TM coordinate.	Double	6581806.7920

Table 11 – Extended position object

Name	Description	Type	Example
wgs84_dd_la	Latitude in decimal degrees	Double	58.164322
wgs84_dd_lo	Longitude in decimal degrees	Double	13.564223

Table 12 - Position object

Name	Description	Type	Example
action_name	Name of the transition to the state	String	Framme
allowed_states	Defines the states which it is allowed to transit to from this state.	Array of JSON objects.	See example message.
state_id	Unique id for the state.	Integer	1
state_name	Name of the state.	String	Framme

Table 13 - State object

Name	Description	Type	Example
name	Name of the state	String	Framme
allowed_transitions	Defines the states which it is allowed to transit to from this state. Each entry refers to a state id.	Array of integers.	[2, 4]
id	Unique id for the state.	Integer	1

transition_name	Name of the transition to state.	String	Framme

Table 14 - State configuration object

5.1.2 Example message

5.1.2.1 PUT

Below is an example for a request body when updating an assignment using the PUT method. This will update the property *is_destination_alarm_sent* for the specified assignment.

```
{
   "is_destination_alarm_sent" : true
}
```

5.1.2.2 GET

Below is an example for a response body when using the GET method to fetch a specific assignment, If the path parameter *id* was not specified the response body would be an array of the objects below.

```
{
   "assignment_number" : "[SiteID:CaseFolderID:CaseID:MissionNo]",
   "created" : "2011-12-12T16:31:24Z",
   "received" : "2014-10-10T16:19:34Z",
   "accepted" : "2014-10-10T16:19:42Z",
   "rowid" : "0faaa8e0-956b-444b-baea-ddf6e806ba6d",
   "is_closed" : "false",
   "close_reason" :  {
       "reason" : "Patient saknades",
       "comment" : ""
   },
   "is_selected" : "1",
   "is_destination_alarm_sent" : "false",
   "selected_destination" : "",
   "eta" : "2015-03-31T14:45:00Z",
   "is_head_unit" : "false",
   "is_routed" : "false",
   "distance" : "0",
   "methane_report" : {
       "created" : "2015-03-31T14:14:00.353Z",
       "last_updated" : "2015-03-31T14:44:34.934Z",
       "access_road" : {
           "is_obstructed" : false,
```

```
            "comment" : ""
        },
        "exact_location" : "Storgatan 3",
        "extra_resources" : {
            "ambulances" : 0,
            "chemical_suit" : 0,
            "emergency_wagon" : 0,
            "medical_team" : 0,
            "sanitation_wagon" : 0,
            "doctor_on_duty" : 0,
            "helicopter" : 0,
            "commander_unit" : 0,
            "PAM" : 0,
            "medical_transport" : 0,
            "transport_ambulance" : 0,
            "units_total" : 0,
        },
        "hazards" : [
            "Halka",
            "Rök/Gas"
        ],
        "inventory_level" : {
            "selected_level_index" : 1,
            "levels" : [ "0", "1_3", "2_3", "3_3" ]
        },
        "major_incident" : false,
        "numbers_affected_green" : 0,
        "numbers_affected_green" : 0,
        "numbers_affected_yellow" : 0,
        "numbers_affected_red" : 0,
        "position " : {
            "rt90_x" : 6581976.875412831,
            "rt90_y" : 1628492.661460190,
            "sweref99_e" : 674219.1730,
            "sweref99_n" : 6581806.7920,
            "wgs84_dd_la" : 59.3389850,
```

```
            "wgs84_dd_lo" : 18.063270
        },
        "special_injuries" : "",
        "time_first_departure" : "2015-03-31T14:45:00Z",
        "types " : [
            "Trafikolycka"
        ]
    },
    "rek_report" : {
        "created" : "2015-03-31T14:14:00.353Z",
        "last_updated" : "2015-03-31T14:44:34.934Z",
        "affected_count" : "",
        "resources_on_site" : "",
        "comments" : "",
        "position " : {
            "rt90_x" : 6581976.875412831,
            "rt90_y" : 1628492.661460190,
            "sweref99_e" : 674219.1730,
            "sweref99_n" : 6581806.7920,
            "wgs84_dd_la" : 59.3389850,
            "wgs84_dd_lo" : 18.063270
        },
        "command_organization" : {
            "medical_commander" : "",
            "hq_commander" : "",
            "hq_commander_medical" : "",
            "section_commander_assembly_point" : "",
            "section_commander_collect_point" : "",
            "section_commander_1_incident_site " : "",
            "section_commander_2_incident_site" : "",
            "section_commander_breakpoint" : "",
        },
        "incident_organization" : {
            "breakpoint" : "",
            "command_site" : "",
            "incident_site" : "",
            "assembly_site" : "",
            "assembly_point_injured" : "",
            "assembly_point_uninjured" : "",
            "collect_point" : "",
            "landing_site" : ""
        }
```

```
    }
    "position" : {
        "wgs84_dd_la" : 60.60837241855120,
        "wgs84_dd_lo" : 15.62368821634720
    },
    "to_position" : {
        "wgs84_dd_la" : -200.0,
        "wgs84_dd_lo" : -200.0
    },
    "properties" : [
        {
            "name" : "created",
            "value" : "2011-12-12 16:31"
        },
        {
            "name" : "sender",
            "value" : "370002"
        },
        {
            "name" : "central",
            "value" : "1"
        },
        {
            "name" : "area",
            "value" : ""
        },
        {
            "name" : "caseindex1",
            "value" : "Trafikolycka"
        },
        {
            "name" : "caseindex2",
            "value" : ""
        },
        {
            "name" : "caseindex3",
            "value" : ""
```

```
        },
        {
            "name" : "city",
            "value" : "Falun"
        },
        {
            "name" : "comment",
            "value" : "Trafikolycka, bil krockat med moped"
        },
        {
            "name" : "firstname",
            "value" : "Test"
        },
        {
            "name" : "ib",
            "value" : "1"
        },
        {
            "name" : "id",
            "value" : "1234567890"
        },
        {
            "name" : "lastname",
            "value" : "Testman"
        },
        {
            "name" : "municipality",
            "value" : "Falun"
        },
        {
            "name" : "personid",
            "value" : "1910101010-1010"
        },
        {
            "name" : "positionwgs84",
            "value" : "La=60.61 Lo=15.62"
```

```
        },
        {
            "name" : "priority",
            "value" : "1"
        },
        {
            "name" : "priorityin",
            "value" : "1"
        },
        {
            "name" : "radiogroup",
            "value" : ""
        },
        {
            "name" : "radiogroupname",
            "value" : ""
        },
        {
            "name" : "routedirections",
            "value" : "Rakt fram"
        },
        {
            "name" : "street",
            "value" : "Krokusvägen 3"
        },
        {
            "name" : "toaddress",
            "value" : ""
        },
        {
            "name" : "tocity",
            "value" : ""
        },
        {
            "name" : "toposition",
            "value" : ""
```

```
        },
        {
            "name" : "sendtime",
            "value" : ""
        },
        {
            "name" : "pickuptime",
            "value" : ""
        },
        {
            "name" : "toarea",
            "value" : ""
        },
        {
            "name" : "tomunicipality",
            "value" : ""
        },
        {
            "name" : "departuretime",
            "value" : ""
        },
        {
            "name" : "topositionrt90",
            "value" : ""
        },
        {
            "name" : "allradiogroups",
            "value" : []
        },
        {
            "name" : "additionalcoordinationinformation",
            "value" : ""
        },
        {
            "name" : "additionalinfo",
            "value" : ""
```

```
        },
        {
            "name" : "objectid",
            "value" : ""
        },
        {
            "name" : "alarmcategory",
            "value" : ""
        },
        {
            "name" : "alarmeventcode",
            "value" : ""
        },
        {
            "name" : "areanumberandphonenumber",
            "value" : ""
        },
        {
            "name" : "assignedresourceincasefolder",
            "value" : [ "" ]
        },
        {
            "name" : "testassignment",
            "value" : "true"
        }
    ],
    "state" : {
        "action_name" : "Framme",
        "allowed_states" : [
            {
               "action_name" : "Hämtat",
               "state_id" : 3,
               "state_name" : "*HÄMTAT*"
            },
            {
               "action_name" : "Hemåt",
```

```
            "state_id" : 5,
            "state_name" : "*HEMÅT*"
        },
        {
            "action_name" : "Klar uppdrag",
            "state_id" : 6,
            "state_name" : "*KLAR UPPDRAG*"
        },
        {
            "action_name" : "Uppd. disp.",
            "state_id" : 7,
            "state_name" : "*UPPD DISP*"
        }
    ],
    "state_id" : 2,
    "state_name" : "*FRAMME*"
},
"state_entries" : [
    {
        "distance" : 23,
        "from_id" : 0,
        "to_id" : 1,
        "time" : "2015-03-31T18:25:43+01:00"
    },
    {
        "distance" : 2348,
        "from_id" : 1,
        "to_id" : 2,
        "time" : "2015-03-31T18:25:43+01:00"
    }
],
"state_configuration" : [
    {
        "allowed_transitions" : [ 2, 6 ],
        "id" : 1,
        "name" : "Kvitterat",
```

```
            "transition_name" : "Kvittera"
        },
        {
            "allowed_transitions" : [ 3, 5, 6, 7 ],
            "id" : 2,
            "name" : "Framme",
            "transition_name" : "Framme"
        },
        {
            "allowed_transitions" : [ 4, 5 ],
            "id" : 3,
            "name" : "Hämtat",
            "transition_name" : "Hämtat"
        },
        {
            "allowed_transitions" : [ 5 ],
            "id" : 4,
            "name" : "Avlämnar",
            "transition_name" : "Avlämnar"
        },
        {
            "allowed_transitions" : [ 6 ],
            "id" : 5,
            "name" : "Hemåt",
            "transition_name" : "Hemåt"
        },
        {
            "allowed_transitions" : [],
            "id" : 6,
            "name" : "Klar",
            "transition_name" : "Klar"
        },
        {
            "allowed_transitions" : [ 5 ],
            "id" : 7,
            "name" : "Uppd. disp.",
```

```
            "transition_name" : "Uppd. disp."
        }
    ]
}
```

5.2 SYMBOLS

5.2.1 Specification

Name	Description	Type	Example
id	Unique identifier for the symbol. If not provided the symbol will be added.	GUID	dfd4fd99-1fa9-4624-9cfe-05e65ef63fa9
mapitemtype	Type of symbol	Integer	0 (Vehicle)
state	Status text shown in the map	String	Framme
heading	Heading for the vehicle, 0 - 360 degrees.	Double	53.2
description	Additional text that will be shown in the map, e.g. name of the vehicle.	String	254-9110
assignmentid	Id of the assignment the symbol is connected to.	String	<Central_id>:<case_id>, e.g. 15:123456
position	Position for the symbol.	JSON object	See Table 19.
unitid	Name of the vehicle	String	9110
is_deleted	Indicates if the symbol is deleted.	Boolean	true/false
additionalInfo	Contains a JSON object with additional information.	JSON object	
sequenceId	Id of an action sequence which can be executed when the symbol is clicked.	Integer	
sequenceIdActionText	The text to display for option above.	String	
icon	Path to the icon. Path relative to Paratus Navigation runtime directory.	String	./image2.png

Table 15 - Symbol object (Vehicle type)

Name	Description	**Type**	Example
id	Unique identifier for the symbol. If not provided the symbol will be added.	GUID	dfd4fd99-1fa9-4624-9cfe-05e65ef63fa9
mapitemtype	Type of symbol	Integer	1 (Area)
description	Additional text that will be shown in the map.	String	Skadeområde
assignmentid	Id of the assignment the symbol is connected to.	String	<Central_id>:<case_id>, e.g. 15:123456
is_deleted	Indicates if the symbol is deleted.	Boolean	true/false
additionalInfo	Contains a JSON object with additional information.	JSON object	
sequenceId	Id of an action sequence which can be executed when the symbol is clicked.	Integer	
sequenceIdActionText	The text to display for option above.	String	
fillColor	A hex color string representing the fill color of this area	String	#FF00FF
fillOpacity	The opacity for the fill color of this area	Integer	Value between 0 and 1
lineColor	A hex color string representing the color of the line surrounding this area	String	#000000
lineColorOpacity	The opacity for the line color surrounding this area	Integer	Value between 0 and 1
lineWidth	The width of the line surrounding this area	Integer	
coordinates	An array containing all coordinates that compose this area	Array of JSON objects	See Table 19 for specification of JSON object.

Table 16 - Symbol object (Area type)

Name	Description	**Type**	Example

id	Unique identifier for the symbol. If not provided the symbol will be added.	GUID	dfd4fd99-1fa9-4624-9cfe-05e65ef63fa9
mapitemtype	Type of symbol	Integer	2 (Icon)
icon	Path to the icon. Path relative to Paratus Navigation runtime directory.	String	./image2.png
description	Additional text that will be shown in the map.	String	Skadeplats
assignmentid	Id of the assignment the symbol is connected to.	String	<Central_id>:<case_id>, e.g. 15:123456
position	Position for the symbol.	JSON object	See Table 19.
is_deleted	Indicates if the symbol is deleted.	Boolean	true/false
additionalInfo	Contains a JSON object with additional information.	JSON object	
sequenceId	Id of an action sequence which can be executed when the symbol is clicked.	Integer	
sequenceIdActionText	The text to display for option above.	String	

Table 17 - Symbol object (Icon type)

Name	Description	**Type**	Example
id	Unique identifier for the symbol. If not provided the symbol will be added.	GUID	dfd4fd99-1fa9-4624-9cfe-05e65ef63fa9
mapitemtype	Type of symbol	Integer	3 (Line)
description	Additional text that will be shown in the map.	String	Avgränsningslinje
assignmentid	Id of the assignment the symbol is connected to.	String	<Central_id>:<case_id>, e.g. 15:123456
is_deleted	Indicates if the symbol is deleted.	Boolean	true/false
additionalInfo	Contains a JSON object with additional information.	JSON object	

sequenceId	Id of an action sequence which can be executed when the symbol is clicked.	Integer	
sequenceIdActionText	The text to display for option above.	String	
lineColor	A hex color string representing the color of the line	String	#000000
lineColorOpacity	The opacity for the line	Integer	Value between 0 and 1
lineWidth	The width of the line	Integer	
coordinates	An array containing all coordinates that compose this line	Array of JSON objects	See Table 19 for specification of JSON object.

Table 18 - Symbol object (Line type)

Name	Description	**Type**	Example
wgs84_dd_la	Latitude in decimal degrees	Double	58.164322
wgs84_dd_lo	Longitude in decimal degrees	Double	13.564223

Table 19 - Position object

5.2.2 Example message

Below is an example of the content in the response body when using the GET method.

Possible values for mapitemtype are 0 (vehicle), 1 (area), 2 (point/icon) or 3 (line)


```
[{
    "id" : "dfd4fd99-1fa9-4624-9cfe-05e65ef63fa9",
    "mapitemtype" : 0,
    "state" : "status text",
    "united" : "9110",
    "heading" : 53.2,
    "description" : "254-9110 ",
    "assignmentId" : "15:303421",
    "position" : {
      "wgs84_dd_la" : 59.36404,
      "wgs84_dd_lo" : 13.47386
    },
    "is_deleted" : false
},
{
    "id" : "dfd4fd99-1fa9-4624-9cfe-05e65ef63fa9",
    "mapitemtype" : 2,
    "icon" : "./image2.png",
    "description" : "desc",
    "assignmentid" : "15:303421",
    "position" : {
```

```
      "wgs84_dd_la" : 59.36404,
      "wgs84_dd_lo" : 13.47386
    },
    "is_deleted" : false
},
{
    "id" : "dfd4fd99-1fa9-4624-9cfe-05e65ef63fa9",
    "mapitemtype" : 1,
    "description" : "Description text",
    "assignmentId" : "15:303421",
    "is_deleted" : false,
    "fillColor" : "#FF0000",
    "fillOpacity" : 1,
    "lineColor" : " #000000",
    "lineColorOpacity" : 1,
    "lineWidth" : 2,
    "coordinates" : [
      {
          "wgs84_dd_la" : 59.36404,
          "wgs84_dd_lo" : 13.47386}
      },
      {
          "wgs84_dd_la" : 59.36404,
          "wgs84_dd_lo" : 13.57386}
      },
      {
          "wgs84_dd_la" : 59.46404,
          "wgs84_dd_lo" : 13.57386}
      },
      {
          "wgs84_dd_la" : 59.46404,
          "wgs84_dd_lo" : 13.47386}
      }
},
{
    "id" : "dfd4fd99-1fa9-4624-9cfe-05e75ef63fa0",
    "mapitemtype" : 3,
    "description" : "Description text",
    "assignmentId" : "15:303421",
    "is_deleted" : false,
    "lineColor" : " #000000",
    "lineColorOpacity" : 1,
    "lineWidth" : 2,
    "coordinates" : [
      {
          "wgs84_dd_la" : 59.36404,
          "wgs84_dd_lo" : 13.47386}
      },
      {
          "wgs84_dd_la" : 59.36404,
          "wgs84_dd_lo" : 13.57386}
      },
      {
```

```
            "wgs84_dd_la" : 59.46404,
            "wgs84_dd_lo" : 13.57386}
        },
        {
            "wgs84_dd_la" : 59.46404,
            "wgs84_dd_lo" : 13.47386}
        }
}]
```


5.3 UNIT

5.3.1 Specification

Specification of object returned in the response body when using the GET method.

Name	Description	**Type**	Example
id	Unique identifier for the unit.	GUID	dfd4fd99-1fa9-4624-9cfe-05e65ef63fa9
issi	ISSI number for the unit.	String	331911
msisdn	MSISDN number for the unit.	String	3319110
position	The current position for the unit.	JSON object	See Table 21 - Position object.
state	The current state of the unit.	JSON object	See *Table 22 - State object*.

Table 20 - Unit object

Name	Description	**Type**	Example
wgs84_dd_la	Latitude in decimal degrees	Double	58.164322
wgs84_dd_lo	Longitude in decimal degrees	Double	13.564223

Table 21 - Position object

Name	Description	**Type**	Example
action_name	Name of the state transition	String	Idle
allowed_states	A list with id of states for which it is allowed to change.	Array of integers	1,2,3
state_id	Id of the state.	Integer	1
state_name	Name of the state.	String	Idle

Table 22 - State object

5.3.2 Example message


```
{
```

```
   "id" : " dfd4fd99-1fa9-4624-9cfe-05e65ef63fa9",
   "issi" : "331911",
   "msisdn" : "3319110",

   "position" : {
      "wgs84_dd_la" : -9.255963134931783e+061,
      "wgs84_dd_lo" : -9.255963134931783e+061
   },
   "state" : {
      "action_name" : "Idle",
      "allowed_states" : [],
      "state_id" : 10,
      "state_name" : "Idle"
   }
}
```


5.4 COMMAND

5.4.1 Specification

Specification of the object received in the response body for the GET method and also used in the request body for the POST method.

Name	Description	Type	Example
unit_id	Unique identifier for the unit which currently is the medical commander	GUID	dfd4fd99-1fa9-4624-9cfe-05e65ef63fa9
radio_number	Radio number for the unit which currently is the medical commander	String	3319110
created	Time when this information was updated. Formatted as a JSON timestamp	String	2020-11-14T11:48:50Z
assignment_id	Unique identifier for the assignment.	GUID	dfd4fd99-1fa9-4624-9cfe-05e65ef63fa9

Table 23 - Command info object

5.4.2 Example message


```
{
    "unit_id" : "dfd4fd99-1fa9-4624-9cfe-05e65ef63fa9",
    "radio_number" : "3319110",
    "created" : "2014-11-14T11:48:50Z",
"assignment_id" : "dfd4fd99-1fa9-4624-9cfe-05e65ef63fa9"
}
```


5.5 NOTES

5.5.1 Specification

Specified in section 4.5.

5.5.2 Example message


```
[{
   "assignment_id" : "8b7d025a-5236-4f74-aeee-05a5ca697140",
   "author" : "3319180",
   "created" : "2014-11-14T11:48:50Z",
   "id" : "de9168e5-d422-4bc8-a6e2-71067b12ea63",
   "text" : "Tre bilar inblandade och en lastbil. Ankomstvägen
hindrad av bilkö."
}]
```


5.6 MESSAGES

5.6.1 Specification

Specified in section 4.6

5.6.2 Example message


```
[{
   "author" : "3319180",
   "destination" : "3319210",
   "created" : "2014-11-14T11:48:50Z",
   "id" : "de9168e5-d422-4bc8-a6e2-71067b12ea63",
   "text" : "Tre bilar inblandade och en lastbil. Ankomstvägen
hindrad av bilkö."
}]
```


5.7 DESTINATIONS

5.7.1 Specification

Specified in section 4.8.

5.7.2 Example message


```
[{
   "name" : "Södersjukhuset",
   "abbreviation" : "SÖS",
   "position" : {
     "wgs84_dd_la" : 18.3233342,
     "wgs84_dd_lo" : 24.767692
   },
   "type" : "AkutSjukhus",
   "wards" : [{
     "id" : "",
     "name" : "Akutmottagning",
     "abbreviation" : "",
     "status_code" : 38684,
     "position" : {
        "wgs84_dd_la" : 18.3233342,
      "wgs84_dd_lo" : 24.767692
```

```
      }
    },
    {
      "id" : "1",
      "name" : "Röntgen",
      "abbreviation" : "",
      "position" : {
         "wgs84_dd_la" : 18.3233342,
         "wgs84_dd_lo" : 24.767692
      }
    }]
}]
```