

NETWORK 23

OpenBD-OTR.Local

Open Source Project

Mats Strömberg


2012

<http://www.network23.net/otr/>

Table of Contents

Introduction.....	3
OpenBD-OTR.Local	3
What's needed to get OpenBD-OTR.Local running?	5
What does it look like?	6
The Main screen.	6
Customers.....	8
Main screen for customers.....	8
Adding a new customer.....	8
Edit a customer.....	8
DB Instances	9
Main screen for Oracle Instances	9
DB Hosts	10
Main screen for DB Hosts	10
Tablespaces	11
Tablespaces main screen.....	11
Upload CSV or XLS	11
Export as CSV.....	12
Export as XLS.....	12
TBS Trend.....	13
Main screen for Tablespace Usage Trends.....	13
Trend defined by 2 snapshots	13
Trend defined on a Monthly basis.....	13
Graphical Output	14
Snapshots	15
No Friday snapshots!.....	15
Enterprise Manager	16
How do we get started?	17
DDL Scripts.....	17
OTR_DB_SPACE_REP_SCHEMA.sql.....	17
OTR_DB_SPACE_REP_DDL.sql	17
OTR_DB_SPACE_REP_TBS+SCHEMA_CLIENT.sql	18
Done with Step 1	18
Web Frontend using Open BlueDragon.....	19
Download OpenBD-OTR.Local	19
Make changes to the file Application.cfc to fit your Company and setup	20
Oracle Settings.....	20
Mail Server Settings.....	20
Company Settings.....	21
Snapshots	21

General Settings	21
SFTP Settings.....	22
Tablespace Warning Settings	22
Test your OpenBD Installation.....	23
Change listener port for Jetty	24
Configuring OpenBD for OTR.....	24
Login to OpenBD Administrator	24
OpenBD Administrator Main Screen	25
Add Datasource OTR_OTRREP	25
Add Datsource OTR_SYSMAN.....	27
Test the new Datasources	28
Get your OTR ready for use	29
Get Instances from EM Repository.....	29
Create your first Customer	29
Create the Tablespace relationships	29
Add all your customers.....	29
Define a Gather TBS/NFS Space Usage Statistics Job	30
Define Job for creating Host/Instance PDF.	31
Test your Setup.....	32
Installing from SVN	34
Introduction.....	34
SVN Clients.....	34
Getting the Code from SVN	34
Where to Put the OTR	34
Reporting Bugs	34
Requesting Features	35
OTR Philosophy.....	35
Trademarks.....	36
Credits.....	36
Disclaimer / Warranties.....	36



Oracle® Tablespace Report

Open Source Project

Introduction

Oracle Tablespace Report is used to gather various statistics e.g. tablespace usage (allocated, used and free) space. The statistics are stored centrally in the OTR Repository located in an OTR Instance.

This project got started out of a work from a Danish friend, Lars-Bo Vanting, at the time we worked together at T-Systems Schweiz AG back in 2005.

Initially it was only based on Tables, Views and PL/SQL. The current version has expanded on the basis and added a web GUI (based on the excellent open source project Open BlueDragon <http://www.openbd.org>).

OpenBD-OTR.Local

OpenBD-OTR.Local is built using a new tool from the Open BlueDragon project called OpenBD.Local.

OpenBD.Local Windows Runtime environment allows you to package up webapps as complete downloadable applications that will have a presence in the main System Tray.

It ships with everything you need, including the Java Runtime. All you need to do is to supply the OpenBD Web App folder.

OpenBD.Local is Windows Jetty Service container where you can deploy any Java application... and of course fits right in the hand of OpenBD and OTR!

OpenBD-OTR.Local has to be setup a little bit different than the OTR. OpenBD-OTR.Local is identical to the original OTR but what we don't want, is having more local workstations doing the scheduled jobs like the Friday snapshot or generating host/instance PDF Reports.

One way to use OpenBD-OTR.Local is to install the OpenBD-OTR.Local on every DBA's Workstation, configure the OTR datasources OTR_OTRREP and OTR_SYSMAN but only have 1 single Workstation acting like a master and have this workstation have the scheduled tasks defined.

One major problem with this type of setup is that usually a workstation gets shutdown during nights or weekends and won't be able to do its scheduled tasks.

A better way would be to install OTR on a central Linux/UNIX Server and configure it as described in the OTR Documentation. This way we can let the central OTR take care of all scheduled tasks.

What's needed to get OpenBD-OTR.Local running?

- Basis for the Oracle® Tablespace Report, from here on simply OTR, tool is the Oracle® Enterprise Manager 10g so this is the first thing to be installed if not already done. Anyone running 10 or more Oracle Instances should never be without the Enterprise Manager!!!

I'm about to do tests on the Oracle® Cloud Control 12c and make sure we're able to use this as well...

- The OTR.Local which can be found at <http://www.network23.net/otr/> or (in the cloud) at <http://project-otr.jelastic.com>

The complete source is available on Google Code <http://code.google.com/p/oracle-tablespace-report/>


- The SQL files needed to setup the Repository on your OTR Repository Database. Also downloaded from <http://www.network23.net/otr/>

NOTE: To avoid license problem with Oracle, the OTR Repository should NOT be installed in the Grid Control, Cloud Control or a RMAN Repository Database! The OTR can very well be run on a Standard Edition DB or even an Oracle XE instance. Future releases of OTR might even be possible to use MySQL as a Repository.

What does it look like?

We're assuming the OTRREP schema and its objects have been created on the OTR Repository database.

The Main screen.



From here we will administrate our Customers, the Database Instances and the relationship of Customer/Database instance(s) and the Tablespaces used.

From here one will generate reports of space usage at a defined point in time. This can be a report containing database instances for all customers or for a single customer. Reports can be stored as Excel files or as PDF files.

On the right side is the monitoring/alert pane where Instances with some sort of problem coming up will be listed. It will display if the Instance is down or if a Tablespace has a problem. With a mouse-over on a red alert the actual tablespace will be shown and how much free space in MB is still available and the "real" % used. With "real" means it's calculating the free space in % based on the "can grow to" value for the tablespace.

With a click on the red TBS alert, you get the possibility to adjust the tablespace with just one click.

Assuming we have a space problem on a BIGFILE tablespace.

Customers DB Instances DB Hosts Tablespaces TBS Trend New Snapshot Del Snapshot GridControl

OTR
Last Snapshot: 22.11.2011

My Company Inc. - Tablespace Adjustments

CFINDEX

Datafile	Can grow to	Used	Increase with 2GB
/u01/oradata/cfidbt_db/CFIDBT/cfindex.dbf	66,000 MB	65,400 MB	Yes

At the moment we have not used any extra storage but **Please** make sure that the storage have enough space available for this file to grow.

With just one click this tablespace will extend the “Can Grow to” with another 2GB.

If it would be a non-BIGFILE tablespace...

Customers DB Instances DB Hosts Tablespaces TBS Trend New Snapshot Del Snapshot GridControl

OTR
Last Snapshot: Nov 11, 2011

My Company Inc. - Tablespace Adjustments

LEGDATASTANDARD

Datafile	Can grow to	Used	Increase with 2GB
/u01/oradata/legmbcp_db/LEGMBCP/LEGDATASTANDARD117.dbf	2,000 MB	1,500 MB	Yes
/u01/oradata/legmbcp_db/LEGMBCP/LEGDATASTANDARD118.dbf	2,000 MB	100 MB	Yes

This is not a BIGFILE Tablespace so the file should not get bigger than 32GB!

There are currently **118** files in this Tablespace. Most likely you should add a new file to it.

/u01/oradata/legmbcp_db/LEGMBCP/LEGDATASTANDARD119.dbf	2,000 MB	100 MB	ADD FILE
--	----------	--------	--------------------------

We have made our best effort to make sure this filename is not already used.
At the moment we're only expanded the storage usage with 100MB but **Please** make sure there is enough space on the storage for this file to grow.

A list of the files within this tablespace, that have autoextend still on, will be displayed. You can select to increase the “Can grow to” on one of these datafiles or add a new 2GB file which will have its initial size set to 100MB and the “Can grow to” to 2GB.

If a valid Mail Server and Mail account is configured a mail will be sent out with a reminder about checking the storage to make sure you don’t run out of space.

Customers

Main screen for customers

Customers using one or more Oracle Services

My Company Inc. - Oracle Customers

Company ID	Company name	Edit	Delete	New
ABS	Company A			
ALP	Company B			
ACO	Company C			
FPB	Company D			
GCA	Company E			
PHZ	Company P			
ZGK	Company Z			
ICB	InCore Bank AG			
MBC	Maerki Baumann & Co. AG			

Copyright © 2010 - 2011 NETWORK 23
Powered By: OpenBD Version: 2,1 - OpenBD Build: 2011-11-22 01:00:56 GMT
Open BlueDragon Administrator

From this screen we will administrate our customers. The company info contains Company ID or Mandator and a Customer name.

Adding a new customer

My Company Inc. - New Oracle Customers

Company ID:

Name of Company:

Simply fill out the form and click on Save.

Customer ID is a 3 letter short name of the customer. This is later used as a connection to the database instance and the tablespaces used by this customer.

Edit a customer

My Company Inc. - Edit Oracle Customers

Company ID:

Name of Company:


Note: Changing the Customer ID will bring a problem with the collected statistics and with the connection to the tablespaces, so try to keep this unchanged...

DB Instances

In this module you will register all your Oracle Instances.

Main screen for Oracle Instances

[Customers](#) [DB Instances](#) [DB Hosts](#) [Tablespaces](#) [TBS Trend](#) [New Snapshot](#) [Del Snapshot](#) [GridControl](#)


Last Snapshot: Nov 25, 2011

DB Instances and the Type there of...
SEE = Shared Enterprise Edition,
DEE = Dedicated Enterprise Edition,
DEV = Development Servers or
INT = Internally Used

Company Inc. - Oracle Instances

Environment	Description	SID	SYSTEM Password	Edit	Delete	New
SEE	ACO KDPrevent PROD	ACOKDPP	*****			
SEE	Amis CCR INT	AMCCRI	*****			
SEE	Amis CCR PROD	AMCCRP	*****			
SEE	Amis DEPOT PROD	AMDEPOTP	*****			
SEE	Amis MBC PROD	AMMBCP	*****			
SEE	Amis ZGK PROD	AMZGKP	*****			
SEE	CFIDB INT	CFIDBI	*****			
SEE	CFIDB PROD	CFIDBP	*****			
DEE	CFIDB PROD Backup	CFIDBT	*****			
SEE	SAP FD DEV	FD1	*****			
SEE	FFP MBC Prod	FFPMBCP	*****			

It contains Info like Oracle SID, what type of instance this is, DEE = Dedicated Enterprise Edition, DSE = Dedicated Standard Edition, SEE = Shared Enterprise Edition, SSE = Shared Standard Edition, DEV = Development Instances or INT = Internal Enterprise or Standard Edition (might be the Enterprise Manager Instance, a RMAN Instance or a SnapManager for Oracle Instance as an example). It also contains a short description for the Instance. This is usually related to an Application and/or Production/Integration/Test Instance.

System password (used to monitor and increase Tablespaces). This password is encrypted in the OTR repository. To check if the password is OK, just click on the . It will turn if OK otherwise .

[Customers](#) [DB Instances](#) [DB Hosts](#) [Tablespaces](#) [TBS Trend](#) [New Snapshot](#) [Del Snapshot](#) [GridControl](#)


Last Snapshot: 18.11.2011

My Company Inc. - New Oracle Instance


Oracle SID:

Environment:

Description:

SYSTEM Password:

[Customers](#) [DB Instances](#) [DB Hosts](#) [Tablespaces](#) [TBS Trend](#) [New Snapshot](#) [Del Snapshot](#) [GridControl](#)


Last Snapshot: 18.11.2011

My Company Inc. - Edit Oracle Instance

Oracle SID: CFIDBP

Environment:


Description: CFIDB PROD

SYSTEM Password:

DB Hosts

Main screen for DB Hosts

[Customers](#) [DB Instances](#) [DB Hosts](#) [Tablespaces](#) [TBS Trend](#) [New Snapshot](#) [Del Snapshot](#) [GridControl](#)


Last Snapshot: 18.11.2011

DB Instances and the physical location...
The report lists the location as of last Friday or the latest snapshot

Company Inc. - Oracle Hosts & Instances

Host	SID
delios	FFPMBCP
delios	GWGMBCP
delios	HYPMBCP
delios	HYPZGKP
hyperion.mbczh.ch	AMCCRI
hyperion.mbczh.ch	AMCCRP
hyperion.mbczh.ch	AMDEPOTP
hyperion.mbczh.ch	AMZGKP
hyperion.mbczh.ch	FD1
hyperion.mbczh.ch	F11
hyperion.mbczh.ch	FP1

This is simply a list of which Instance is running on which physical host as of the latest snapshot, usually the automated Friday snapshot. A pdf file will be generated on a weekly basis to keep track of where an Instance once where in case of DB Instances has to get moved around and you have had some setup or maintain scripts stuffed away on the previous server.

Tablespaces

This is the heart of OTR. Here the connection between Customer, DB Instance and the Tablespaces are made.

Tablespaces main screen

Customers DB Instances DB Hosts **Tablespaces** TBS Trend New Snapshot Del Snapshot GridControl

Here you define the relationships between Customers, Instances and one or more Tablespace(s)

My Company Inc. - Oracle Customer/App/Tablespace

Export Result as CSV - Export Result to Excel - Upload a new CSV or XLS

#	Customer	Application	SID	Tablespace
1	ACO	ACO KDPrevent PROD	ACOKDPP	APPL_DATA
2	ACO	ACO KDPrevent PROD	ACOKDPP	APPL_IDX
3	ACO	ACO KDPrevent PROD	ACOKDPP	TSAL_DEFAULT
4	ACO	ACO KDPrevent PROD	ACOKDPP	TSAR_DEFAULT
5	ACO	ACO KDPrevent PROD	ACOKDPP	TSAR_TRANSACTION
6	ACO	ACO KDPrevent PROD	ACOKDPP	TSDR_DEFAULT
7	ACO	ACO KDPrevent PROD	ACOKDPP	TSDR_DYNAMIC
8	ACO	ACO KDPrevent PROD	ACOKDPP	TSET_DEFAULT
9	ACO	ACO KDPrevent PROD	ACOKDPP	TSKDMATCH_DEFAULT
10	ACO	ACO KDPrevent PROD	ACOKDPP	TSKDMATCH_IDX
11	ACO	ACO KDPrevent PROD	ACOKDPP	TSMD_DEFAULT

OTR
Last Snapshot: 18.11.2011

The source for this information can be a .CSV file or an Excel Document. This file will be uploaded to the OTR repository server. In case of an Excel source the file will be converted into a .csv file and stored on a defined location where it will be used as source for an external table.

Upload CSV or XLS

Upload a new CSV or XLS

Upload Tablespace Info from an Excel or a CSV File.

ACOKDPP APPL_DATA

My Company Inc. - Oracle Tablespace Usage CSV or XLS Upload

CSV/XLS File: Browse...

Upload Reset

The .CSV contains 4 fields/row and will have the following structure:

```
ICB;Amis CCR INT;AMCCRI;TSDATLARGE
ICB;Amis CCR INT;AMCCRI;TSDATNORM
ICB;Amis CCR INT;AMCCRI;TSDATSN
ICB;Amis CCR INT;AMCCRI;TSIDX
```

It contains the Customer ID, The Instance Description, OraSID and Tablespace name

The other possibility and also the easiest way, is to keep this info in an Excel sheet.


	A	B	C	D
1	ACO	ACO KDPprevent PROD	ACOKDPP	APPL_DATA
2	ACO	ACO KDPprevent PROD	ACOKDPP	APPL_IDX
3	ACO	ACO KDPprevent PROD	ACOKDPP	TSAL_DEFAULT
4	ACO	ACO KDPprevent PROD	ACOKDPP	TSAR_DEFAULT
5	ACO	ACO KDPprevent PROD	ACOKDPP	TSAR_TRANSACTION
6	ACO	ACO KDPprevent PROD	ACOKDPP	TSDR_DEFAULT
7	ACO	ACO KDPprevent PROD	ACOKDPP	TSDR_DYNAMIC
8	ACO	ACO KDPprevent PROD	ACOKDPP	TSET_DEFAULT
9	ACO	ACO KDPprevent PROD	ACOKDPP	TSKDMATCH_DEFAULT
10	ACO	ACO KDPprevent PROD	ACOKDPP	TSKDMATCH_IDX
11	ACO	ACO KDPprevent PROD	ACOKDPP	TSMD_DEFAULT
12	ACO	ACO KDPprevent PROD	ACOKDPP	TXAL_DEFAULT
13	ACO	ACO KDPprevent PROD	ACOKDPP	TXAR_DEFAULT
14	ACO	ACO KDPprevent PROD	ACOKDPP	TXAR_TRANSACTION
15	ACO	ACO KDPprevent PROD	ACOKDPP	TXDR_DEFAULT
16	ACO	ACO KDPprevent PROD	ACOKDPP	TXDR_DYNAMIC
17	ACO	ACO KDPprevent PROD	ACOKDPP	TXET_DEFAULT
18	ACO	ACO KDPprevent PROD	ACOKDPP	TXMD_DEFAULT
19	ICB	Amis CCR INT	AMCCRI	TSDATLARGE
20	ICB	Amis CCR INT	AMCCRI	TSDATNORM
21	ICB	Amis CCR INT	AMCCRI	TSDATSN
22	ICB	Amis CCR INT	AMCCRI	TSIDX
23	ICB	Amis CCR PROD	AMCCRP	TSDATLARGE
24	ICB	Amis CCR PROD	AMCCRP	TSDATNORM
25	ICB	Amis CCR PROD	AMCCRP	TSDATSN
26	ICB	Amis CCR PROD	AMCCRP	TSIDX

The content in Excel is the same as for the .csv

Company ID, Instance description, OraSID and Tablespace name.


Export as CSV

This info can also be exported locally as either a .csv file



Export as XLS

Or as an Excel document



TBS Trend

This will display the trend of growth graphically in a Bar chart.

Main screen for Tablespace Usage Trends

Customers DB Instances DB Hosts Tablespaces **TBS Trend** New Snapshot Del Snapshot GridControl

OTR
Last Snapshot: 18.11.2011

My Company Inc. - Instance Tablespace Trend

Here you can see the Trend in growth of the tablespace usage as a Bar chart.

Instance: ACOKDPP Year: 2011 From: 31.12.2010 To: 18.11.2011

Show Trend

Copyright © 2010 - 2011 NETWORK 23
Powered By: OpenBD Version: 2,1 - OpenBD Build: 2011-11-22 01:00:56 GMT
Open BlueDragon Administrator

Trend defined by 2 snapshots

Statistical data can be displayed from a time period between 2 snapshots.

My Company Inc. - Instance Tablespace Trend

Instance: CFIDBP 1 snapshot / Month: ☐ Year: 2011 From: 04.11.2011 To: 18.11.2011

Show Trend

Copyright © 2010 - 2011 NETWORK 23
Powered By: OpenBD Version: 2,1 - OpenBD Build: 2011-11-22 01:00:56 GMT
Open BlueDragon Administrator

Trend defined on a Monthly basis

This will pick the last snapshot from each month within the selected year.

My Company Inc. - Instance Tablespace Trend


Instance: CFIDBP 1 snapshot / Month: ☒ Year: 2011 From: 04.11.2011 To: 18.11.2011

Show Trend


Copyright © 2010 - 2011 NETWORK 23
Powered By: OpenBD Version: 2,1 - OpenBD Build: 2011-11-22 01:00:56 GMT
Open BlueDragon Administrator

Graphical Output


The output will display the output as a bar-chart.



The currently used space in the tablespace...



and the size the tablespace can grow to.



Snapshots

The statistics is stored in the OTR repository as a snapshot. This is done as a weekly Scheduled job defined in the OpenBD Administrator. This job should be scheduled shortly before Friday Midnight.

Snapshots can also be generated manually.

Customers DB Instances DB Hosts Tablespaces TBS Trend **New Snapshot** Del Snapshot GridControl

This will generate a new snapshot with today's date, containing Tablespace and NFS Storage usage.

My Company Inc. - Tablespace Report

Report Date: 18.11.2011

Customer: ALL

Include: ☒ Development DB's ☒ Internal DB's (GridControl & SnapManager for Oracle)

Run Report

LOADING

Current Status

SID	Status
CFIDBT	TBS

Updated every 5 Minutes
For more Info...
MouseOver the Status column.

[All](#) | [Trouble](#)

Copyright © 2010 - 2011 NETWORK 23
Powered By: OpenBD Version: 2,1 - OpenBD Build: 2011-11-22 01:00:56 GMT
Open BlueDragon Administrator

Only one snapshot / day will be stored, so creating a new snapshot again on the same day will simply delete the previous one and create a new snapshot for that day.

No Friday snapshots!

Customers DB Instances DB Hosts Tablespaces TBS Trend **New Snapshot** Del Snapshot GridControl

No manually generated snapshots on a Friday!

My Company Inc. - Oracle Tablespace Report

Report Date: 18.11.2011

Customer: ALL

Include: ☒ Development DB's ☒ Internal DB's (GridControl & SnapManager for Oracle)

Run Report

LOADING

Current Status

SID	Status
CFIDBT	TBS

Updated every 5 Minutes
For more Info...
MouseOver the Status column.

[All](#) | [Trouble](#)

Copyright © 2010 - 2011 NETWORK 23
Powered By: OpenBD Version: 2,0 - OpenBD Build: 2011-11-12 08:09:43 GMT
Open BlueDragon Administrator

Since Fridays are our scheduled snapshot day you are not allowed to create manual snapshots on this day. It's possible to delete manually generated snapshots but not the Friday snapshots.

Customers DB Instances DB Hosts Tablespaces TBS Trend **New Snapshot** **Del Snapshot** GridControl

Delete a specific snapshot. You can not delete Friday snapshots.

My Company Inc. - Delete Tablespace Snapshot

Report Date: 22.11.2011 Friday Snapshots are not listed

Delete Snapshot

Copyright © 2010 - 2011 NETWORK 23
Powered By: OpenBD Version: 2,1 - OpenBD Build: 2011-11-22 01:00:56 GMT
Open BlueDragon Administrator

Enterprise Manager

Since we're DBA's we of course need access to our "real" toolbox. Therefor we have a direct link to the login for Oracle® Enterprise Manager.

[Customers](#) [DB Instances](#) [DB Hosts](#) [Tablespaces](#) [TBS Trend](#) [New Snapshot](#) [Del Snapshot](#) [GridControl](#)

This is a direct Link to the Oracle GridControl

Last Snapshot: 22.11.2011

My Company Inc. - Oracle Tablespace Report

Report Date: 22.11.2011

Customer: ALL

Include: ☒ Development DB's ☒ Internal DB's (GridControl & SnapManager for Oracle)

Run Report

Current Status

SID	Status
CFIDBT	TBS

Updated every 5 Minutes
For more Info...
MouseOver
the Status column.
[All](#) | [Trouble](#)

Copyright © 2010 - 2011 NETWORK 23
Powered By: OpenBD Version: 2,1 - OpenBD Build: 2011-11-22 01:00:56 GMT
[Open BlueDragon Administrator](#)

How do we get started?

First of all we need to setup the repository OTR schema and the objects used for the repository, assuming of course that Enterprise Manager is already installed!

DDL Scripts

These scripts are located under DOC\OTR-Reporting\Setup\DDL but since OTR.Local isn't installed yet you can download these scripts from <http://www.network23.net/otr> and the menu OTR.Local

```
OTR_DB_SPACE_REP_SCHEMA.sql
OTR_DB_SPACE_REP_DDL.sql
OTR_CR_VIEW_TBS_FREE.sql
OTR_CR_VIEW_DB_HOST.sql
OTR_DB_SPACE_REP_DROP_DDL.sql
OTR_DB_SPACE_REP_TBS+SCHEMA_CLIENT.sql
```

OTR_DB_SPACE_REP_SCHEMA.sql

The first script to run is the OTR_DB_SPACE_REP_SCHEMA.sql which will create new tablespace(s) for the OTR Repository, Create the schema owner OTRREP and setup the grants needed.

To avoid any license problems make sure not to use the Enterprise Manager Repository Instance for your OTR Repository!

```
>@OTR_DB_SPACE_REP_SCHEMA.sql
Enter Database Alias for the OTR Repository [OTR]: SMO
Enter Password for user SYS: *****
Enter path for the otr_rep_data01.dbf [/u01/oradata/otr_db/OTR]: /u01/oradata/smo_db/SMO
Enter path for the otr_rep_indx01.dbf [/u01/oradata/otr_db/OTR]: /u01/oradata/smo_db/SMO
OTR Datafiles will be placed under
/u01/oradata/smo_db/SMO/otr_rep_data01.dbf
/u01/oradata/smo_db/SMO/otr_rep_indx01.dbf
If this is correct press Enter otherwise Ctrl+C
```

OTR_DB_SPACE_REP_DDL.sql

Next script to run is the OTR_DB_SPACE_REP_DDL.sql

```
>@OTR_DB_SPACE_REP_DDL.sql
Enter Database Alias for the OTR Repository [OTR]: SMO
Enter Password for user SYS: *****
Enter Password for user OTRREP: *****
NOTICE: Path for the External table must be LOCALLY on the OGC DB Server (no UNC path allowed!)
Path for the External Table [/orascripts/scripts/monitoring/xt/OTR]: /orascripts/scripts/monitoring/xt/OTR
Enter SQLNET.DEFAULT_DOMAIN [MBCZH.CH]: MBCZH.CH
```

This script will create a directory object for our external table, all other tables used to store the repository data.

This script will also call the 2 scripts OTR_CR_VIEW_TBS_FREE.sql and OTR_CR_VIEW_DB_HOST.sql.

OTR_DB_SPACE_REP_TBS+SCHEMA_CLIENT.sql

This step is optional OTR_DB_SPACE_REP_TBS+SCHEMA_CLIENT.sql. Installing an OTRREP Schema in your target DB's is not needed. This schema will only contain a few views used to display tablespace usage on the current instance. OTR will pick this info up without this schema!

```
>@OTR_DB_SPACE_REP_TBS+SCHEMA_CLIENT.sql
Enter Database Alias for the Target DB (TNSNAMES): HYPCCRP

Choose the Permanent (USER) tablespace for the OTRREP user
-----
Below is the list of online tablespaces in this database which can
can be used for storing data and objects.
Tablespace marked with a * is the default permanent tablespace.
selecting the SYSTEM tablespace as tablespace for OTRREP when
there is an USERS tablespace available don't make sense!!!
Select the OTRREP user's Standard tablespace.

TABLESPACE_NAME          CONTENTS  DB DEFAULT USER TABLESPACE
-----
DATA_ASSENTISDEF         PERMANENT
DATA_ASSENTISRT          PERMANENT
FFPMBCDATA               PERMANENT
FFPMBCINDX               PERMANENT
FFPZGKDATA               PERMANENT
FFPZGKINDX               PERMANENT
HYPICBDATA               PERMANENT
HYPICBINDX               PERMANENT
IDX_ASSENTISDEF          PERMANENT
IDX_ASSENTISRT           PERMANENT
INDX                     PERMANENT
SYSAUX                   PERMANENT
SYSTEM                   PERMANENT
USERS                     PERMANENT *
```

Pressing <return> will result in the database's default Permanent tablespace (identified by *) being used.

Enter USER TABLESPACE Name: **USERS**

Choose the OTRREP user's Temporary tablespace.

```
TABLESPACE_NAME          CONTENTS  DB DEFAULT TEMP TABLESPACE
-----
TEMP                     TEMPORARY *
```

Pressing <return> will result in the database's default Temporary tablespace (identified by *) being used.

Enter Temporary TABLESPACE Name: **TEMP**

... Creating OTRREP user

Entering SYSTEM or SYSAUX as Temporary Tablespace will generate an Error and the script stops.

Done with Step 1

This rounds up the first part and we have to download the OTR.Local.

Web Frontend using Open BlueDragon

For the Web frontend of OTR.Local we need the server software from the OpenBD project. OpenBD is the world's first truly open source GPL Java and Google App Engine CFML runtime. CFML is a powerful tag/script based language that takes away all the heavy lifting of producing highly scalable web and email based services and sites.

Download OpenBD-OTR.Local

At <http://www.network23.net/otr/> we need to download the OpenBD-OTR.Local. This contains OpenBD.Local, JRE, OpenBD and the OTR Web GUI all nicely packed up in a standard Windows Installer.



Agree to the GNU 3 License Agreement and select where to install OpenBD-OTR.

Default it will put OTR under C:\Network23\OpenBD-OTR.

The installation will create a Start Menu entry for you as well.

Before you start OpenBD-OTR you need to adjust one file in the Application folder.

In directory C:\Network23\OpenBD-OTR\webapp\otr locate the file Application.cfc

This file has to be adjusted to match your OTR and EM Repository.

Make changes to the file Application.cfc to fit your Company and setup

Most all parameters for the OTR Application is defined in the file otr/Application.cfc

Update the following settings.

Oracle Settings

```
<!--- SQLNET.DEFAULT_DOMAIN for DB-Links --->
<cfset Application.oracle.domain_name = "MBCZH.CH" />
<!--- Datasource Settings --->
<cfset Application.datasource = "OTR_OTRREP" />
<cfset Application.dbusername = "OTRREP" />
<cfset Application.dbpassword = "otrrep4otr" />
```

The **Application.oracle.domain_name** should correspond to the SQLNET.DEFAULT_DOMAIN within your Oracle environment.

If you change the password for the Schema Owner OTRREP it needs to be changed here also.

Mail Server Settings

```
<!--- MailServer Settings --->
<cfset Application.mailserver = "smtp.mycompany.ch" />
<cfset Application.mailport = "25" />
<cfset Application.mailtimeout = "60" />
<!--- Mail address for DBA or DBA Group --->
<cfset Application.dba_group_mail = "DB-Services@mycompany.com" />
```

Application.mailserver is the host of your mail server. If this parameter is left empty **no** mails will be sent when a Tablespace gets extended.

Application.mailport is the SMTP Port used by the mail server. Usually this is port 25.

Application.mailtimeout is the number of seconds to wait before timing out the connection to the SMTP server.

Application.dba_group_mail is the mail address for the DBA or a DBA Group mail account. The mail will also be sent from this account.

If the mail server is configured, OTR will send an E-mail each time a Tablespace is adjusted. The content of the mail will be something like:

Subject: Tablespace **TBSNAME** on **ORASID** just got another 2GB!

Tablespace **TBSNAME** on Instance **ORASID** was just extended with 2GB more.

ORASID is located on host **mydbhost.mycompany.com**

Please make sure there is enough storage space available for this tablespace to grow.

Company Settings

```
<!-- Company Settings --->
<cfset Application.company = "My Company Inc." />
<!-- Excel Document Info --->
<!-- Foreign Characters for Excel
    ß = chr(223)
    å = chr(229)
    ä = chr(228)
    ö = chr(246)
    Å = chr(197)
    Ä = chr(196)
    Ö = chr(214) --->
<cfset Application.excel_doc_info_author = "Mats Str#chr(246)#mberg" />
<cfset Application.excel_doc_info_subject = "Customer Tablespace Usage" />
<cfset Application.excel_doc_info_title = "My Company Inc. - Tablespace Report" />
<cfset Application.excel_doc_info_lastauthor = "ustr" />
```

Application.company is Your Company Name. This will be displayed on every screen in the application.

Application.excel_doc_info_xxx will be used as document info when generating Excel files. Some character values are provided for foreign character which Excel will understand.

Snapshots

```
<!-- Snapshot Day / Sunday = 1 --->
<cfset Application.snapshot_day = 6 /><!-- 6 = Friday --->
```

It's possible to change the snapshot day but it's not really recommend.

The week starts on Sunday = 1 and stops on Saturday = 7

General Settings

```
<!-- General Application Settings --->
<cfset Application.obd_host = "http://minerva/" />
<cfset Application.obd_desktop_host = "http://localhost:8080/" />

<cfset Application.ogc_logon_url = "http://minerva:4889/em/console/logon/logon" />
<cfset Application.ogc_external_table = "/orascripts/scripts/monitoring/xt/OTR" />
<cfset Application.host_instance_pdf_dir = "/opt/pro/dir/ccr/oracle/" />
```

Application.obd_host is the host of the OTR web server. If Jetty isn't re-configured for port 80 this should contain the correct port number. <http://YourServer:8080/>

Application.obd_desktop_host is the host of the the OpenBD-OTR Application... e.g. your PC.

Application.ogc_login_url is the URL for your Enterprise Manager login screen.

Application.ogc_external_table is the path where your external table source is located. This file contains info about your Customers, Instances and Tablespaces. (See chapter [Tablespaces](#))

Application.host_instance_pdf_dir is the location where the weekly PDF reports will be located.

SFTP Settings

```
<!-- SFTP Settings for the host of the GridControl Repository -->
<cfset Application.sftpHost = "minerva.mbczh.ch">
<cfset Application.sftpUser = "oracle">
<cfset Application.sftpPass = "orambc">
```

The SFTP setting is important for the setup and updates of the External Table (Customer - Instance – Tablespace) relation. This file is located somewhere locally or on a NFS mountpoint where the server for the OTR Repository is installed. This doesn't have to be, and most likely won't be, the same server where the Web GUI for OTR is installed.

Application.sftpHost is name of the server where the access to the external table source file is located.

Application.sftpUser is normally **oracle** since your Oracle Instance most likely is running under the account oracle.

Application.sftpPass is your Oracle OS user password.

Tablespace Warning Settings

```
<!-- Tablespace Warning Levels -->
<cfset Application.tablespace.prc_used = 98 />
<cfset Application.tablespace.mb_left = 1800 />
```


Application.tablespace.prc_used is default set to **98%** (full)

Application.tablespace.mb_left is default set to **1800** MB.

With these settings correctly configured for your environment you are now ready to test the setup of OpenBD-OTR.


Test your OpenBD Installation

Start the OpenBD-OTR from the start menu and you will see a new icon in the system tray.



You can either right-click on the OpenBD Icon and select Open... or manually start your web browser and goto the URL <http://localhost:8080>

You should on the Open BlueDragon Administrator login screen if your Installation was successful.



By default Jetty, like most every Java Server, is configured to use port 8080. You can easily change this to port to something else but be aware of that port 80 most likely will already be in use and you will have a conflict using this port.

Change listener port for Jetty

If you prefer to use port 80 instead of port 8080 simple stop the OpenBD Server again by right-click on the Open BlueDragon Icon and select close.

Go into the C:\Program Files\OpenBD-OTR directory and edit the file openbd-local.ini

```
#
#
#
#
#
#
# http://openbd.org/local/
#
#
# The name of the application
app.title=OpenBD:OTR
#
# The port number of the local server
web.port=8080
#
# Restrict the server to only the local server
web.localonly=true
#
# The path of where the webapp lives
web.root=./webapp/
```

Change the web.port to 80 and start OpenBD-OTR again from the start menu.

From now on your OpenBD should respond on standard port 80


Configuring OpenBD for OTR

First we need to define 2 Datasources for OTR to be able to communicate with the OGC and OTR Repositories.

Login to OpenBD Administrator

Go to the URL, with or without the portnumber depending on if you reconfigured your OpenBD.Local Setup or not, [http://localhost\[:8080\]](http://localhost[:8080])

 Open BlueDragon Administrator



The default Password is **admin**

OpenBD Administrator Main Screen

Welcome to the Open BlueDragon Administrator

Open BlueDragon is an open source (GPLv3), Java-based runtime engine for CFML. For more information on the Open BlueDragon project, please visit the [Open BlueDragon web site](#) and the [Open BlueDragon Google Group](#).

You may use the OpenBD Administrator to manage many OpenBD settings such as datasources, scheduled tasks, mail server settings, directory mappings, custom tag paths, and much more.

For more information on the Open BlueDragon Administrator or to obtain a newer version of the Administrator, please visit the [Open BlueDragon Admin Console project at Google Code](#).

Documentation

For the latest OpenBD documentation you may refer to the [OpenBD Manual](#) that is bundled with OpenBD and runs locally, or the following resources:

- [OpenBD Web Site](#)
- [OpenBD Wiki](#)
- [OpenBD CFML Manual](#) (generated from nightly builds)
- [OpenBD Cookbook](#)


Requesting Features and Reporting Bugs

- [OpenBD Google Group](#)
- [OpenBD Issue Tracker](#)
- [OpenBD Admin Console project at Google Code](#)
- [CFML Conventional Wisdom](#) (general CFML language discussion group)

Copyright © 2008 - 2011 [Open BlueDragon Project](#)

Version 2.0 - Nov 11, 2011 12:00 AM

To add new Datasources select the menu Data & Services



Add Datasource OTR_OTRREP

Manage Datasources

[More Info](#)

Add a Datasource

Datasource Name

Database Type

Datasources

No registered datasources

No datasources configured

Copyright © 2008 - 2011 [Open BlueDragon Project](#)

Version 2.0 - Nov 11, 2011 12:00 AM

Datasource Name: **OTR_OTRREP** and Type is of course **Oracle** and click **Add Datasource**

Adding connection info

Configure Datasource - Oracle (Oracle)

Datasource Details	
OpenBD Datasource Name	<input type="text" value="OTR_OTRREP"/>
Database SID	<input type="text" value="SMO"/>
Database Server	<input type="text" value="theia.mbczh.ch"/>
Server Port	<input type="text" value="1521"/>
User Name	<input type="text" value="OTRREP"/>
Password	<input type="password" value="....."/>
Description	<input type="text" value="OTR Oracle Tablespace Report"/>
<div><input type="button" value="Show Advanced Settings"/> <input type="button" value="Submit"/> <input type="button" value="Cancel"/></div>	

Copyright © 2008 - 2011 Open BlueDragon Project

Version 2.0 - Nov 11, 2011 12:00 AM

Database SID: **<Your OTR OracleSID>**

Database Server: **<Host of your OTR Instance>**

Server Port: **<Listener Port for your OTR Instance>**

User Name: **OTRREP**

Password: **otrrep4otr**

Description: **OTR Oracle Tablespace Report**

Manage Datasources

[More Info](#)

The datasource was created successfully.



Add a Datasource

Datasource Name	<input type="text"/>
Database Type	<input type="text" value="- select -"/>
<input type="button" value="Add Datasource"/>	

Datasources

Actions	Datasource Name	Description	Database Type	Status
	OTR_OTRREP	OTR Oracle Tablespace Report	Oracle (Oracle)	
<input type="button" value="Verify All Datasources"/>				

Add Datasource OTR_SYSMAN

Manage Datasources

[More Info](#)

The datasource was created successfully.



Add a Datasource

Datasource Name

Database Type



Add Datasource

Datasources

Actions	Datasource Name	Description	Database Type	Status
	OTR_OTRREP	OTR Oracle Tablespace Report	Oracle (Oracle)	

Verify All Datasources

Copyright © 2008 - 2011 [Open BlueDragon Project](#)

Version 2.0 - Nov 11, 2011 12:00 AM

Datasource Name: **OTR_SYSMAN** and the type **Oracle** and click **Add Datasource**

Configure Datasource - Oracle (Oracle)

Datasource Details

OpenBD Datasource Name

Database SID

Database Server

Server Port

User Name

Password

Description

Show Advanced Settings

Submit

Cancel

Copyright © 2008 - 2011 [Open BlueDragon Project](#)

Version 2.0 - Nov 11, 2011 12:00 AM

User Name: **SYSMAN** <User on your OGC Instance!!!>

Password: **<SYSMAN Password>**

Description: **Used to generate TBS/NFS Space Usage Reports**

Test the new Datasources

Manage Datasources

[More Info](#)

The datasource was created successfully.



Add a Datasource

Datasource Name

Database Type

- select -

Add Datasource

Datasources

Actions	Datasource Name	Description	Database Type	Status
	OTR_OTRREP	OTR Oracle Tablespace Report	Oracle (Oracle)	
	OTR_SYSMAN	Used to generate TBS/NFS Space Usage Reports	Oracle (Oracle)	
<p>Verify All Datasources</p>				

By clicking on [Verify All Datasources](#) you will get a confirmation of the settings and if they are OK


Datasources

Actions	Datasource Name	Description	Database Type	Status
	OTR_OTRREP	OTR Oracle Tablespace Report	Oracle (Oracle)	✓
	OTR_SYSMAN	Used to generate TBS/NFS Space Usage Reports	Oracle (Oracle)	✓
<p>Verify All Datasources</p>				

Get your OTR ready for use

Now after the datasources are created you goto the <http://localhost:8080> again and the OpenBD-OTR.Local will need some basic setup (If this isn't done from some other client or the OTR Server)

To get your OTR ready to be used we now need to fill it with usable data.



Get Instances from EM Repository

Since this is a new setup you won't have any database Instances in OTR. Start by selecting the menu [1. Get Instances from your EM Repository](#). When this step is done the link will be inactive.

Create your first Customer

There are no customers in your OTR Repository. Select the menu [2. Create at least 1 customer \(Your self\)](#). When this step is done the link will be inactive.

Create the Tablespace relationships

The relation between a Customer, DB Instance and a Tablespace is preferably done using an Excel sheet. As this is a new setup your external table source file doesn't exist yet.

By selecting the menu [3. Create the external table source](#) and the system will create a new file for you that will contain all your instances and the description. Customer ID will be set to the Customer ID of the customer you just created and Tablespace will be set to the value <NOT_DEFINED>.

Export this as XLS and edit this file locally on your PC.

Copy each row for as many Tablespaces you want to monitor for each Instance and customer. Replace the XYZ with correct Customer ID and save the Excel file. Finally upload the file again to OTR and your Tablespace list will now be usable.

Add all your customers

Make sure to add all customers to your system and that the Customer ID is corresponding to your updated Excel file / External table source file. This will be needed when you create your first snapshot, may it be a manually created snapshot or the weekly generated snapshot.

Define a Gather TBS/NFS Space Usage Statistics Job


To get the weekly monitoring to collect the Tablespace usage statistics you should now define a Job in the OpenBD Administrator.

NOTE: Make sure only one workstation is doing this!!!

Login to the Administrator using the URL [http://your_server\[:port\]/bluedragon/administrator/](http://your_server[:port]/bluedragon/administrator/)

If you haven't changed the Administrator Password it will be **admin**.

Select the Menu Data & Services and the Scheduled Tasks



Enter **Gather TBS/NFS Space Usage Statistics** as Task Name.

A screenshot of the 'Edit Scheduled Task' form in the OpenBD Administrator. The form has several fields: 'Task Name' (Gather TBS/NFS Space Usage Statistics), 'Duration' (Start Date: 11/25/2011, End Date:), 'Interval' (One Time, Recurring, Daily), and 'Full URL' (http://minerv...). A calendar widget is open, showing November 2011, with the 25th (Friday) selected. The time 23:30 is entered in the 'to' field.

The Job should be run on a Friday night so select a Date matching a Friday.

A screenshot of the 'Interval' section of the 'Edit Scheduled Task' form. The 'Recurring' radio button is selected. The frequency is set to 'weekly' in a dropdown menu. The time is set to '@ 23:30'. The 'Daily' option is also visible with fields for 'every', 'seconds from', and 'to'.

Define the job as a weekly recurring job starting at **23:30** (11:30 PM)

Enter [http://your_server\[:8080\]/otr/otr_friday_snapshot.cfm](http://your_server[:8080]/otr/otr_friday_snapshot.cfm) as Full URL

Full URL	<input type="text" value="http://minerva/otr/otr_friday_snapshot.cfm"/>
Port	<input type="text"/>

As request Timeout set the value to **120** seconds.

Request Timeout	<input type="text" value="120"/> seconds
<input type="button" value="Submit"/>	

Define Job for creating Host/Instance PDF.

If you could like to have a weekly PDF generated containing info about which Instance is running on which Host, you can create this job over the OpenBD Administrator. The job should be generated on a weekly basis just as the Gather Statistics Job and be run just before or after Friday midnight, shortly after the [Gather TBS/NFS Space Usage Statistics](#) Job.

This step is not required but the information could be handy to have later on...

Define the Scheduling Task

Task Name: [Host Instance Report PDF](#). We'll define the Start Date to be on a Saturday.

Task Name	<input type="text" value="Host Instance Report PDF"/>	
Duration	Start Date: <input type="text"/>	End Date: <input type="text"/>
Interval	<div><input type="radio"/> One Time <input type="radio"/> Recurring <input type="radio"/> Daily every <input type="text"/></div>	
Full URL	<div><input type="text" value="http://"/> Port <input type="text"/></div>	

November 2011

Su	Mo	Tu	We	Th	Fr	Sa
		1	2	3	4	5
6	7	8	9	10	11	12
13	14	15	16	17	18	19
20	21	22	23	24	25	26
27	28	29	30			

Set the Interval to **Weekly** at **01:00** which means that the job will be run on Saturday morning at 01:00 AM

Interval	<input type="radio"/> One Time @ <input type="text"/>	
	<input checked="" type="radio"/> Recurring <input type="text" value="weekly"/> @ <input type="text" value="01:00"/>	
	<input type="radio"/> Daily every <input type="text"/> seconds from <input type="text"/> to <input type="text"/>	

The URL is: [http://your_server\[:port\]/otr/otr_db_host_pdf.cfm](http://your_server[:port]/otr/otr_db_host_pdf.cfm)

Full URL	<input type="text" value="http://your_server[:port]/otr/otr_db_host_pdf.cfm"/>
----------	--

Set the Request Timeout to **60** sec and click the Submit button.

Request Timeout	<input type="text" value="60"/>	seconds
<input type="button" value="Submit"/>		

Your job is now defined. You could test the job but since we don't have any statistical data collected yet it won't generate any PDF.

Test your Setup.

As long as you're not testing your setup on a Friday you could now create your first Manual Snapshot. Required is of course that the relationship between Customer/Instance and Tablespace is done so the snapshot will have something to collect.

In the Web GUI of OTR select the menu option New Snapshot.

The screenshot shows the OTR Web GUI interface. At the top, there is a navigation bar with links: Customers, DB Instances, DB Hosts, Tablespaces, TBS Trend, **New Snapshot**, Del Snapshot, and GridControl. A logo for OTR (Open Tablespace Report) is in the top right corner, with the text 'Last Snapshot: 18.11.2011'.

The main content area is titled 'My Company Inc. - Tablespace Report'. It contains a form with the following fields and options:

- Report Date: 18.11.2011 (dropdown menu)
- Customer: ALL (dropdown menu)
- Include: ☒ Development DB's ☒ Internal DB's (GridControl & SnapManager for Oracle)
- Run Report (button)

A loading spinner is visible in the center of the form area. A tooltip box is overlaid on the 'New Snapshot' menu option, stating: 'This will generate a new snapshot with today's date, containing Tablespace and NFS Storage usage.'

On the right side, there is a 'Current Status' section with a table:

SID	Status
CFIDBT	TBS

Below the status table, it says 'Updated every 5 Minutes For more Info... MouseOver the Status column.' and a link 'All | Trouble'.

At the bottom, there is a footer with copyright information: 'Copyright © 2010 - 2011 NETWORK 23 Powered By: OpenBD Version: 2,1 - OpenBD Build: 2011-11-22 01:00:56 GMT Open BlueDragon Administrator'.

Note: If no snapshots has been made you can't generate any usage reports!!!

If at least 1 Snapshot exists it's possible to run a Report.

First select the Report Date and for which Customer. It can be for All customers or for 1 specific customer. Also select to include (or not) Development DB's and/or Internal DB's like the Enterprise Manager or some other internal type of DB (SMO, RMAN etc.)

My Company Inc. - Oracle Tablespace Report

Report Date: 25.11.2011

Customer: InCore Bank AG

Include:
☒ Development DB's
☒ Internal DB's (GridControl & SnapManager for Oracle)

Run Report

Current Status


SIDStatus

Updated every 5 Minutes
For more Info...
MouseOver
the Status column.

All | Trouble

The report output will contain info about Instance, Tablespace name, Used MB, Free MB, Can Grow To MB, Max Free MB, % Used and % Real used which reflects the Can grow to space.

[Back to Main](#)
[Customers](#)
[DB Instances](#)
[DB Hosts](#)
[Tablespaces](#)
[TBS Trend](#)
[New Snapshot](#)
[Del Snapshot](#)
[GridControl](#)



Last Snapshot: Nov 25, 2011

My Company Inc. - Oracle Tablespace Reports

25.11.2011 - InCore Bank AG

AMCCRI AMCCRP AMDEPOTP CFIDBI CFIDBP CFIDBT HYPCCRP ICBCCRI ICBCCRP LEGCCRT OGC2ICB OTMSCCRT OTMSCCRX OTMSICBI OTMSICBP OTMSICNI OTMSICNX RECOMBCI RECOMBCP SMO SOL XENTISI XENTISP

[customer_report.xls](#)
[as PDF](#)

DB: AMCCRI		Client App(s): Amis CCR INT				
TABLESPACE	Used (MB)	Free (MB)	Can Grow To (MB)	Max Free (MB)	% Used	% Real Used
TSDATLARGE	8,100	2,668.06	12,000	6,568.06	67 %	45 %
TSDATNORM	1,000	398.56	2,000	1,398.56	60 %	30 %
TSDATSN	500	373.44	2,000	1,873.44	25 %	6 %
TSIDX	8,900	3,444.31	10,000	4,544.31	61 %	55 %
Sub Total (MB):	18,500		26,000			Top
NFS Server: kronos	Mount: /u01/oradata/amccri_db	28,672	7,356	74 %		
NFS Server: kronos	Mount: /u02/oradata/amccri_log	6,144	4,621	25 %		
		34,816	11,977			

DB: AMCCRP		Client App(s): Amis CCR PROD				
TABLESPACE	Used (MB)	Free (MB)	Can Grow To (MB)	Max Free (MB)	% Used	% Real Used
TSDATLARGE	8,100	1,916.00	12,000	5,816.00	76 %	52 %
TSDATNORM	1,000	377.31	5,000	4,377.31	62 %	12 %
TSDATSN	500	368.44	2,000	1,868.44	26 %	7 %
TSIDX	8,900	1,317.00	10,000	2,417.00	85 %	76 %
Sub Total (MB):	18,500		29,000			Top

The report also contains NFS space usage in MB. How much space an NFS Volume has and how much free space is still available in MB. It also displays which NFS Server or Storage system is used.

One special feature for volumes created with NetApp's SnapManager for Oracle. The names of these volumes are usually not following your regular volume definition. If such a volume is used, it will be displayed with a dark red color. With a mouse-over on such a Mount name the real name of the volume will be displayed.

For example:

NFS Server: kronos	Mount: /u01/oradata/amccri_db	28,672	7,356	74 %
NFS Server: kronos	Mount: /u02/oradata/amccri_log	6,144	4,621	25 %
	kronos:/vol/SnapManager_20100923141903532_vol_amccrp_db/qamccrp_db	16	11,977	

This concludes the description of the basic Setup and usage of OTR.

Feel free to add functionality to OTR. Get the source code from Google code and join in on the development.

Installing from SVN

Installing the OTR from Subversion

<http://code.google.com/p/oracle-tablespace-report/>

Introduction

Development for the OTR Application is continuously underway, but if you want to try it out now (and we'd love it if you would!), you can grab the code from Subversion (SVN) and run it on your instance of OpenBD.

NOTE: Do NOT run bleeding edge code on a production or otherwise important instance of OpenBD! There is currently no security in place on the OTR, and any bugs that exist in the bleeding edge code could cause problems with your Oracle Databases.

SVN Clients

If you don't have an SVN client, you'll need to get one. If you're a developer and you're already using [Eclipse](#), probably the simplest one to grab is [Subclipse](#). It will work on any platform (Linux, Mac, or Windows).

If you aren't on Eclipse, native clients are available for any platform, or you can run SVN from a terminal or DOS window.

One client that seems to be nice that is available for Linux, Mac, and Windows is [SyncroSVN](#). I haven't personally used it but a few Mac bloggers swear by it.

For Windows, the most popular client is [TortoiseSVN](#), which integrates directly into Windows file explorer.

For Mac, [Versions](#) looks very nice, but again, I haven't personally tried it. [svnX](#) is another popular client for Mac.

Getting the Code from SVN

Once you have an SVN client installed, do a checkout from the SVN repository for this project. Details are available on the [checkout page](#). You'll want to grab the trunk.

Where to Put the OTR

The OTR code resides in the webapps directory at the top of your OpenBD instance.

The easiest way to configure things is to have your local directory for the SVN project be the root of the instance of OpenBD on which you want to try out the OTR.

Reporting Bugs

Since development is still happening rapidly at this point, expect to see a few bugs here and there, and also expect to be pulling the code down regularly to get the latest version of things.

If you do see a bug that's keeping you from using the admin console or think it might be something we aren't aware of, please report it on the [issues page](#).

Requesting Features

If you have ideas for features you'd like to see in the admin console, no matter how big or small, we'd love to hear them! Please create an issue on the [issues page](#) and use the label Type-Enhancement

OTR Philosophy

The group of people behind OTR (so far the group is only me and my dual personality 😊, hopefully this group will increase in the near future and preferably not the way where I have to incorporate a triple personality!), believe strongly in the ideals of the Open Source movement. We believe that software that is made available under an open source model, should always remain under that model, and never be abused or incorporated into products that would result in the harm of the original project.

To that end, we believe that any changes that anyone makes to the core engine should be contributed back to the community, for the benefit of the community as a whole. This is what the GPL license frames.

- How much does OTR cost?
\$0.00 dollars/euros/pounds/yen. Zero. There is no cost for you to download, use, develop and extend OTR, deploy and ship your application.
- Can I sell OTR?
No. You cannot sell OTR as it is not yours to sell. You may sell installation or consultancy services for OTR. You're also allowed to sell added functions to OTR, although we would prefer you would consider supporting the Open Source Project and contributing your added functionality.
- Okay, where's the catch? What features are you not shipping?
There is no catch. All functionality in OTR is available to you the current release, or as and when they are developed. We believe in the power Oracle® and CFML language has to offer and we want to get it into the hands of as many DBA's and/or DB Engineers as possible.

Trademarks

Oracle® and Oracle® Enterprise Manager is Registered Trademarks of Oracle Corporation.

OpenBD/Open BlueDragon is Copyright tagServlet Ltd and aw2.0 Ltd.

OTR is Copyright NETWORK 23.

Credits

OTR Web interface is using Drew Wilson's excellent TipTip jQuery Plugin

<http://code.drewwilson.com/entry/tiptip-jquery-plugin>

OTR Web interface is also using Christian Bach's excellent **tablesorter** jQuery Plugin

<http://tablesorter.com/docs/>

Disclaimer / Warranties

In no event will NETWORK 23 or its officers, directors, employees, agents, suppliers, distributors, and business affiliates be liable to you or any third party for any damages of any kind, including but not limited to, direct, indirect, incidental, special, consequential, punitive, or exemplary damages resulting from or in connection with using this document. Damages include but are not limited to loss of profits, loss of income, loss of business, loss of information, loss of data, or any other kind of loss. You agree that your use of this document and application is based upon your own evaluation and judgment.