

L^AT_EX

Introduction Course

Romain De Groote

October 1, 2026

What will we do today?

Today:

- ▶ No installation
- ▶ Web browser + Overleaf account

What will we do today?

Today:

- ▶ No installation
- ▶ Web browser + Overleaf account

Git repository:

github.com/MatsuneMikuroi/LaTeXCrashCourse

- ▶ This presentation (beamer)
- ▶ Script (article, multiple files)
- ▶ Compiled PDFs

Why LaTeX?

- ▶ Open-Source and free
- ▶ High-quality typesetting
- ▶ Customizability
- ▶ Cross-platform
- ▶ Community and support
- ▶ Integration w other tools
- ▶ Overleaf

Why LaTeX?

- ▶ Open-Source and free
- ▶ High-quality typesetting
- ▶ Customizability
- ▶ Cross-platform
- ▶ Community and support
- ▶ Integration w other tools
- ▶ Overleaf

Handle:

- ▶ Report
- ▶ Presentation
- ▶ Many more

Code your document

Macros for:

Code your document

Macros for:

- ▶ Text
- ▶ Structure
- ▶ Maths
- ▶ Images and tables
 - ▶ Size
 - ▶ Placement
 - ▶ Caption
 - ▶ Label and reference
- ▶ Figures and graphs
- ▶ Bibliography
- ▶ Own commands and environments

Code your document

Macros for:

- ▶ Text
- ▶ Structure
- ▶ Maths
- ▶ Images and tables
 - ▶ Size
 - ▶ Placement
 - ▶ Caption
 - ▶ Label and reference
- ▶ Figures and graphs
- ▶ Bibliography
- ▶ Own commands and environments

Full control $\Rightarrow$ document as you want

Online editor:

Overleaf

Online editor:

- + No installation
- + Collaboration
- + Great UI
- + Lot of docs and templates
 - Limited free features
 - Internet connection
 - Dependency on a third party

Create your account

overleaf.com/register:


- ▶ Personal email (or Google account)
- ▶ Email confirmation

Create your account

overleaf.com/register:

- ▶ Personal email (or Google account)
- ▶ Email confirmation

Dashboard:



- ▶ Blank project: from scratch
- ▶ Example project: main features
- ▶ Upload project: .zip
- ▶ Templates: thesis, report, CV, poster...

The editor

3 panels:

- ▶ File tree: new file, folder, upload
- ▶ Code editor: Code / Visual
- ▶ PDF preview

The editor

3 panels:

- ▶ File tree: new file, folder, upload
- ▶ Code editor: Code / Visual
- ▶ PDF preview

Useful:

- ▶ Recompile: Ctrl+S / Ctrl+Enter
- ▶ Logs: errors, warnings
- ▶ Double-click PDF → code
- ▶ Share, History
- ▶ Menu: compiler, main document, download

Writing

2 types of "text" boxes:

- ▶ Text box: no delimiter
- ▶ Math box:
 - ▶ Inline: $\backslash(\dots\backslash)$ or $\$...\$$
 - ▶ Display: $\backslash[\dots\backslash]$ or $\$...\$$

Writing

2 types of "text" boxes:

- ▶ Text box: no delimiter
- ▶ Math box:
 - ▶ Inline: $\text{\textbackslash}(\dots\text{\textbackslash})$ or $\text{\textbackslash}\dots\text{\textbackslash}$
 - ▶ Display: $\text{\textbackslash}[\dots\text{\textbackslash}]$ or $\text{\textbackslash}\dots\text{\textbackslash}$

2 types of macros:

- ▶ Command: $\text{\textbackslash}\text{LaTeX}$
- ▶ Environment: $\text{\textbackslash}\text{begin}\{\text{itemize}\}\dots\text{\textbackslash}\text{end}\{\text{itemize}\}$

Preamble

Before `\begin{document}`:

- ▶ Class and options: `\documentclass{...}`
- ▶ Packages and options: `\usepackage{...}`
- ▶ Own commands and environments
- ▶ Metadata: `\title{...}`, `\author{...}`, `\date{...}`

Minimal document

```
\documentclass{article} % preamble
\usepackage{graphicx}
\title{My title}
\author{My name}

\begin{document}          % body
\maketitle
\section{Introduction}
Hello world!
\end{document}
```

Minimal document

```
\documentclass{article} % preamble
\usepackage{graphicx}
\title{My title}
\author{My name}
```

```
\begin{document} % body
\maketitle
\section{Introduction}
Hello world!
\end{document}
```

After `\end{document}`: ignored

Special characters

Character	Role	To print it
%	comment	\%
\$	math mode	\\$
&	table column	\&
#	command argument	\#
-	subscript (math)	_
{ }	group	\{ \}
~	non-breaking space	\textasciitilde
\	start of a command	\textbackslash

Special characters

Character	Role	To print it
%	comment	\%
\$	math mode	\\$
&	table column	\&
#	command argument	\#
-	subscript (math)	_
{ }	group	\{ \}
~	non-breaking space	\textasciitilde
\	start of a command	\textbackslash

Spaces:

- ▶ Many spaces = 1 space
- ▶ Line break = 1 space
- ▶ Empty line = new paragraph

When it does not compile

Logs → **first** error first:

- ▶ Undefined control sequence: typo, missing package
- ▶ Missing \$ inserted: math outside math mode
- ▶ File ended while scanning use of...: missing }
- ▶ Environment ... undefined: missing package
- ▶ File ... not found: file name, case sensitive

When it does not compile

Logs → **first** error first:

- ▶ Undefined control sequence: typo, missing package
- ▶ Missing \$ inserted: math outside math mode
- ▶ File ended while scanning use of...: missing }
- ▶ Environment ... undefined: missing package
- ▶ File ... not found: file name, case sensitive

PDF despite errors ⇒ maybe wrong

Document management

Sectioning:

- ▶ `\part{...}`
- ▶ `\chapter{...}` (book, report)
- ▶ `\section{...}`
- ▶ `\subsection{...}`
- ▶ `\subsubsection{...}`
- ▶ `\paragraph{...}`
- ▶ `\subparagraph{...}`

Document management

Sectioning:

- ▶ `\part{...}`
- ▶ `\chapter{...}` (book, report)
- ▶ `\section{...}`
- ▶ `\subsection{...}`
- ▶ `\subsubsection{...}`
- ▶ `\paragraph{...}`
- ▶ `\subparagraph{...}`

Tables of contents:

- ▶ `\tableofcontents, \listoffigures, \listoftables`
- ▶ Depth: `\setcounter{tocdepth}{...}`

Document management (cont.)

Reference:

- ▶ `\label{...}`: sections, figures, tables, equations...
- ▶ `\ref{...}`: number
- ▶ `\pageref{...}`: page

Document management (cont.)

Reference:

- ▶ `\label{...}`: sections, figures, tables, equations...
- ▶ `\ref{...}`: number
- ▶ `\pageref{...}`: page

Multiple files:

- ▶ `\include{...}`: new page
- ▶ `\input{...}`: no new page

Text box

Formatting:

- ▶ **Bold:** `\textbf{...}`
- ▶ *Italic:* `\textit{...}`
- ▶ Underline: `\underline{...}`
- ▶ **Colored:** `\color{red}...`

Text box

Formatting:

- ▶ **Bold:** `\textbf{...}`
- ▶ *Italic:* `\textit{...}`
- ▶ Underline: `\underline{...}`
- ▶ **Colored:** `\color{red}...`

Environments:

- ▶ Itemize: unordered list
- ▶ Enumerate: ordered list
- ▶ Description: description list
- ▶ And many more...

Math box

Symbols:

- ▶ Greek letters: `\alpha`, `\beta`, ...
- ▶ Operators: `\sum`, `\int`, `\frac{\dots}{\dots}`, ...
- ▶ Relations: `\leq`, `\geq`, ...
- ▶ And many more...

Math box

Symbols:

- ▶ Greek letters: `\alpha`, `\beta`, ...
- ▶ Operators: `\sum`, `\int`, `\frac{\dots}{\dots}`, ...
- ▶ Relations: `\leq`, `\geq`, ...
- ▶ And many more...

Environments:

- ▶ Equation: `numbered equation`
- ▶ Align: `aligned equations`
- ▶ And many more...

Math box

Symbols:

- ▶ Greek letters: `\alpha`, `\beta`, ...
- ▶ Operators: `\sum`, `\int`, `\frac{\dots}{\dots}`, ...
- ▶ Relations: `\leq`, `\geq`, ...
- ▶ And many more...

Environments:

- ▶ Equation: `numbered equation`
- ▶ Align: `aligned equations`
- ▶ And many more...

`*`: no numbering (`equation*`, `align*`)

Maths in practice

Code	Result
<code>x^2</code> <code>x_i</code> <code>x_{max}</code>	x^2 x_i x_{max}
<code>\frac{a}{b}</code> <code>\sqrt{x}</code>	$\frac{a}{b}$ $\sqrt{x}$
<code>\sum_{i=1}^N T_i</code>	$\sum_{i=1}^N T_i$
<code>\bar{T}</code> <code>\Delta L</code> <code>\pi</code>	$\bar{T}$ ΔL π

Maths in practice

Code	Result
<code>x^2</code> <code>x_i</code> <code>x_{max}</code>	x^2 x_i x_{max}
<code>\frac{a}{b}</code> <code>\sqrt{x}</code>	$\frac{a}{b}$ $\sqrt{x}$
<code>\sum_{i=1}^N T_i</code>	$\sum_{i=1}^N T_i$
<code>\bar{T}</code> <code>\Delta L</code> <code>\pi</code>	$\bar{T}$ ΔL π

Braces: $x^{10} \rightarrow x^{10}$, $x^{\{10\}} \rightarrow x^{10}$

Maths in practice

Code	Result
<code>x^2</code> <code>x_i</code> <code>x_{max}</code>	x^2 x_i x_{max}
<code>\frac{a}{b}</code> <code>\sqrt{x}</code>	$\frac{a}{b}$ $\sqrt{x}$
<code>\sum_{i=1}^N T_i</code>	$\sum_{i=1}^N T_i$
<code>\bar{T}</code> <code>\Delta L</code> <code>\pi</code>	$\bar{T}$ ΔL π

Braces: $x^{10} \rightarrow x^{10}$, $x^{\{10\}} \rightarrow x^{10}$

Reference: `\label{eq:...}` + `\eqref{eq:...}` (amsmath)

Figures and tables

Figure environment:

- ▶ `\includegraphics{...}`: image
- ▶ `\caption{...}`: caption
- ▶ `\label{...}`: reference

Figures and tables

Figure environment:

- ▶ `\includegraphics{...}`: image
- ▶ `\caption{...}`: caption
- ▶ `\label{...}`: reference

Table environment:

- ▶ Tabular environment: structure
- ▶ `&`: columns, `\\`: rows
- ▶ `\hline`: horizontal line
- ▶ `\caption{...}`, `\label{...}`

Figures and tables

Figure environment:

- ▶ `\includegraphics{...}`: image
- ▶ `\caption{...}`: caption
- ▶ `\label{...}`: reference

Table environment:

- ▶ Tabular environment: structure
- ▶ `&`: columns, `\\`: rows
- ▶ `\hline`: horizontal line
- ▶ `\caption{...}`, `\label{...}`

Array: math tabular

Bibliography

The bibliography environment:

- ▶ `\bibitem{...}`: reference
- ▶ `\cite{...}`: citation

Bibliography

The bibliography environment:

- ▶ `\bibitem{...}`: reference
- ▶ `\cite{...}`: citation

Advanced: BibTeX, BibLaTeX

Create figure and graphes

TikZ package:

- ▶ `tikzpicture` environment: drawing area
- ▶ Shapes, lines, text
- ▶ Flowcharts, diagrams, plots...

Create figure and graphes

TikZ package:

- ▶ `tikzpicture` environment: drawing area
- ▶ Shapes, lines, text
- ▶ Flowcharts, diagrams, plots...


Huge package → doc, online search

TikZ example

```
\begin{tikzpicture}
  \draw[->] (0,0) -- (2.5,0) node[right] {$x$};
  \draw[->] (0,0) -- (0,2) node[above] {$y$};
  \draw[blue, thick, domain=0:2.4]
    plot (\x, {0.3*\x*\x});
  \draw[dashed] (2,0) -- (2,1.2);
  \fill[red] (2,1.2) circle (2pt)
    node[above left] {$A$};
\end{tikzpicture}
```

TikZ example

```
\begin{tikzpicture}
  \draw[->] (0,0) -- (2.5,0) node[right] {$x$};
  \draw[->] (0,0) -- (0,2) node[above] {$y$};
  \draw[blue, thick, domain=0:2.4]
    plot (\x, {0.3*\x*\x});
  \draw[dashed] (2,0) -- (2,1.2);
  \fill[red] (2,1.2) circle (2pt)
    node[above left] {$A$};
\end{tikzpicture}
```



Create your own commands and environments

`\newcommand{...}{...}:`

- ▶ Name + definition
- ▶ Arguments

Create your own commands and environments

`\newcommand{...}{...}:`

- ▶ Name + definition
- ▶ Arguments

`\newenvironment{...}{...}{...}:`

- ▶ Name + begin code + end code
- ▶ Arguments

Create your own commands and environments

`\newcommand{...}{...}`:

- ▶ Name + definition
- ▶ Arguments

`\newenvironment{...}{...}{...}`:

- ▶ Name + begin code + end code
- ▶ Arguments

Arguments:

- ▶ `[n]`: number of arguments
- ▶ `[default]`: optional first argument
- ▶ `#1, #2...`: in the definition

Issue with macros definition

- ▶ Many arguments: hard to follow
- ▶ Definition: hard to read
- ▶ Syntax: hard to input

Issue with macros definition

- ▶ Many arguments: hard to follow
- ▶ Definition: hard to read
- ▶ Syntax: hard to input

xparse package:

- ▶ `\NewDocumentCommand{name}{arguments}{definition}`
- ▶ `\NewDocumentEnvironment{name}{arguments}{begin code}{end code}`

Going further

Resources:

- ▶ [Overleaf Learn](#): docs, tutorials
- ▶ [TeX Stack Exchange](#): Q&A
- ▶ [Detexify](#): drawn symbol $\rightarrow$ command
- ▶ [CTAN](#): packages, documentation

Conclusion

LaTeX:

- ▶ Powerful typesetting
- ▶ Academia and industry
- ▶ Steep learning curve, high-quality documents
- ▶ Online resources, communities

Conclusion

LaTeX:

- ▶ Powerful typesetting
- ▶ Academia and industry
- ▶ Steep learning curve, high-quality documents
- ▶ Online resources, communities

Overleaf:

- ▶ Online editor
- ▶ Collaboration, ease of use
- ▶ Limited free features, internet dependency