

# Lesson 1: Week 1 - Python Programming Fundamentals

Created: 2024-05-27T01:25:36.564438+10:00 | Outline: You'll learn to write and run your first Python program

## Program, language, and Python

A computer program (or code) is a set of instructions for a computer to follow. Computer programming (or coding) is the activity of writing computer programs. When you write a program you must use a language that the computer can understand. There are many such languages - Java, Python, C, Ruby, JavaScript, PHP, and many, many more. Each language has its own advantages and disadvantages, and there is no "best" language that will be the most appropriate choice in all situations. While, for expediency, this course will focus on a single language (Python), many of the fundamental principles you will learn, such as program flow, data manipulation and code modularity, carry over to almost every other language. Like natural languages, such as English and French, programming languages have a specific grammar; this is known as the language's syntax. Unlike natural languages, programming languages require you to be precise and unambiguous. Python has very simple syntax and is considered one of the best designed programming languages in this respect. In this course, you will learn the Python language. Python is one of the most popular languages for several reasons: It is a general-purpose language that can be used in a wide variety of situations. It is mature enough that many comprehensive libraries for many disciplines have been built and extensively tested. It was developed recently enough to be built upon many of the fundamental programming principles that have been developed and fine-tuned over the years. It has a human-friendly syntax that is easy to learn. Python has become one of the most popular languages for working with data. It has data processing and visualisation libraries such as pandas and Matplotlib that make handling data very easy. Even though you will be learning just one language, many of the fundamental principles you will learn, such as controlling program flow, manipulating data, and modularising code, carry over to almost every other language. Like natural languages, programming languages tend to change over time. You'll be using the latest version of Python throughout this course - Python 3. You may encounter some Python 2 code from time to time. The language differences between these two are minor however they can be incompatible with each other. In this course, code will usually be presented in a web interpreter as seen below, the language the code is written in can be seen in the top right corner of the web interpreter, most code will be editable and runnable. Try running the code below to see the exact version of Python 3 we are using (in ed):

```
import sys
print(sys.version)
```

Python nuts and bolts Python is an interpreted language which means that code is passed directly to an interpreter (a program running on the host machine) for execution rather than being compiled into machine-readable instructions to be executed directly by the computer. This means that executing Python code can be as simple as starting an interpreter and typing commands to run. If you installed a version of Python on your computer then there will be an interpreter as part of that installation. Alternatively, you can access an interpreter through the Workspaces and code snippets here on ed platform. Increasing usability by simplifying the process from program writing to execution makes Python a very attractive language for the novice programmer.

## Python Programming Basics

Here is a very simple Python program: 

```
print('Hello, world!')
```

 Execution You can execute the program (i.e., run it) by clicking 'Run'. When you do, the Python interpreter executes each line of the program, one at a time, from beginning to end (in this case there is only one line). When you run a program like this, the Python interpreter executes each line of the program, one at a time, from beginning to end (in this case there is only one line). Whenever you see a runnable piece of code like this you can also modify it yourself. This is a great way for you to experiment with Python (don't worry, you won't break anything, and everything gets restored when you refresh the page). Try modifying the code above to get it to print your name rather than "world". Statements Each line in the program is called a statement. Your programs will typically contain many statements. Here is one with two statements: 

```
print('Hello, world!') print('Goodbye, world!')
```

 The `print()` function `print()` is a Python function, one that you will find yourself using often. 'Hello world!' is an argument of the function - some input that we give to the function. The `print()` function performs the task of printing the argument. Try modifying the program below to make it print your name (you need to use quotation marks): 

```
print()
```

 If you supply `print()` with multiple arguments it will print them all, separated by spaces. You will find this very useful: 

```
print('The value is', 10*2)
```

 A very handy technique when using `print()` is to use an f-string. If you append an 'f' to the start of a quoted string (before the first quote) you can get Python to do things inside the string before it prints, such as perform calculations. You do this

by using curly brackets. Here are some examples: `print(f'The result is {10*2}.')` `print(f'The results are {10*2}, {10*3}, and {10*4}.')` InputGetting user inputAnother Python function that you will use often is `input()`, which you can use to get input from the user. For example: `print(input('What would you like to print? '))` This program asks the user for some input and then prints it. Syntax errorsBefore executing a program the interpreter first checks that it has correct syntax. If it finds any syntax errors it will tell you, and not run the program. The following program contains a syntax error (it's missing a quotation mark) - try running it: `print('Hello, world!)` Runtime errorsSometimes the syntax of a program is fine, but Python raises an error during its execution. These are called runtime errors. When this happens, execution stops, and Python returns some information about the error. For example, the following program asks Python to divide a number by zero, which is impossible. It generates a runtime error: `print(10/0)` Logical errorsSometimes the syntax of a program is fine, and it executes without any runtime errors, but it doesn't do what you intended it to do. This is called a logical error. For example, suppose you write the following program to add 1 and 2 and then multiply the result by 3: `print(1 + 2 * 3)` The result you're expecting is 9, because 1 + 2 is 3, and 3 times 3 is 9. But the program above prints 7. Error! This is not a syntax error, nor a runtime error - it's a logical error. The problem is that Python assumes that you want the multiplication to happen first, then the addition (you will learn more about this). So it calculates  $2 \times 3 = 6$ , then  $1 + 6 = 7$ . You should write your program like this instead: `print((1 + 2) * 3)` This removes the logical error. CommentsIn Python, anything on the same line after a `#` will be ignored by the Python interpreter. This allows you to add comments. It is important that the programs you write are easily understandable by someone who reads them. To help with this it can be a good idea to add comments throughout. Here is an example from above, with an explanatory comment added: `# Ask the user for input and then print it: print(input('What would you like to print? '))` Comments can start anywhere on a line (but use comments on t...

## Importing modules

You won't get far using Python before you need to import a module. A module is just a file that contains Python code, with a ".py" extension. Although the core Python language contains a lot of functionality, some of the functionality you'll want is included in modules, rather than in the core. You can access that functionality by importing those modules. For example, there is a lot of non-core mathematics functionality in the "math.py" module. You can import that module as follows (note that you don't include ".py" - Python will figure it out): `import math` This makes all of the code that has been saved in the math.py file available for use in your program. For example, in math.py there is a function `floor()`, which rounds a number down to the nearest integer. Having imported math.py you can now call this function: `import math`  
`print(math.floor(3.14))` Note that you call the function using `math.floor()`, rather than using just `floor()`. If you'd like to be able to use this function without having to add the prefix, you can do so using the `from` keyword when you import: `from math import floor` `print(floor(3.14))` If you'd like to import more functions then you can just separate their names by commas: `from math import floor, ceil` `print(floor(3.14))`  
`print(ceil(3.14))` You can import everything by using an asterisk: `from math import *` `print(floor(3.14))`  
`print(ceil(3.14))` But you should avoid doing this because you might end up with the same function name being used twice as shown in the examples below: `from math import *` `def ceil(x): # my ceil() doubles the number given return 2*x` `print(ceil(3.14))` # you will get 6.28  
`from math import *` `#def ceil(x): # my ceil() doubles the number given # return 2*x` `print(ceil(3.14))` # you will get 4  
`import math` `def ceil(x): # my ceil() doubles the number given return 2*x` `print(math.ceil(3.14))` # you will get 4  
`print(ceil(3.14))` # you will get 6.28 You can use the `dir()` function to see what is available to you in a module that you have imported: `import math` `print(dir(math))` When you import a module you can give it an alias using the `as` keyword, to save yourself some typing. One module that we will be using a lot in the second half of this course is the pandas module. It is standard to give it the alias "pd" when importing it: `import pandas as pd` `print(dir(pd))` When Python gets installed on a computer many modules are installed with it. These are called built-in modules. These are automatically available for you to import. If you want to import other modules they will first need to be installed on the computer. You can also write your own modules, and import them.

## Objects

When you program with Python (and many other languages) you will work a lot with objects. Objects encapsulate a piece of data (which may be simple, such as a single number; or more complex, such as a collection of smaller objects) and are the building blocks of Python. For example, in the statement `print('The value is', 10*2)`, 'The value is', 10 and 2 are all objects. Indeed, even the `print()` function is an object. TypesEvery object is of a certain type. The type of an object determines how Python interacts with it, for example it makes sense to add two numbers, but it does not make sense to add functions. In Python, the main types are: Integer (int). A whole number, positive or negative, including zero (i.e. ..., -2, -1, 0, 1, 2, ...). Floating-point number (float). A positive or negative number, not necessarily whole, including zero (e.g.

3.14, -0.12, 89.56473).String (str). A sequence of characters (e.g. 'Hello', 'we34t&2\*'). Used to store text.Boolean (bool). A truth value, either true or false.List (list). An ordered container of objects.Tuple (tuple). An immutable list (i.e. one that cannot be changed).Set (set). An unordered container of unique objects.Dictionary (dict). A set of key-object pairs.Function. A piece of code that can be run by calling it.Class. A user-defined type of object.Python also has a special object, None, which represents the absence of an object. It is of type NoneType. It is the only object of this type.You will be learning more about the objects of each type. This week you will learn about integers, floats, strings, and booleans. Next week you will learn about lists, tuples, sets, and dictionaries. In Week 3 you will learn about functions and classes. Checking the type of an objectYou can find out the type of an object by using Python's type() function:print(type(1)) print(type(3.14)) print(type('Hello')) print(type(None)) print(type(print))Notice in the last example above that we have provided the print function as an argument to the type function. You can do that - the print function is an object, just like numbers and strings are, and you can provide it as an argument to the type() function to find out what type of object it is. Most of the time you'll be calling print(), and providing arguments to it, but occasionally you might provide it as an argument to some other function, as we have done above. In fact, you can even provide print as an argument to print() function itself:print(print)When an object is of a certain type we say that it is an instance of that type. You can also use Python's isinstance() function to check whether an object is of a certain type:print(isinstance(1, int)) # True print(isinstance(1, float)) # False print(isinstance(3.14, float)) # True print(isinstance(3.14, int)) # False print(isinstance('Hello', str)) # True print(isinstance('Hello', float)) # FalseAttributesObjects have attributes. Attributes are properties that are specific to the object. For example, the string object 'Hello', has an attribute upper(), which is a function that produces an upper-case version of the string. You can access this attribute of the string by using dot notation:print('Hello'.upper())It can be useful to think of '.' as representing " 's " (i.e. apostrophe-s) - the statement 'Hello'.upper() is instructing Python to execute the upper() function of the 'Hello' object.When an attribute is a function, like this one is, it is also called a method. Attributes which are not methods are also known as fields.Which attributes an object has depends upon what type of object it is. String objects have the upper() attribute (method), but integer objects do not. If you try to access this attribute of an integer you will get an error:print("Hello".upper()) number = 12 print(number.upper())Part of learning Python, and other languages, is learning what attributes the different types of objects have.

## Expressions

To work with an object you need to refer to it, and to refer to it you use an expression. Expressions come in two varieties: simple expressions and complex expressions. We'll consider simple expressions first, and then complex expressions. There are three types of simple expressions:LiteralsVariablesConstantsLiteralsA literal shows explicitly which object they refer to. Here are some examples: Integer literals: 1, 26, -14Floating-point literals: 3.14, 0.06, -9.7String literals: 'Hello', "Goodbye" (you can use single or double quotes, but they must match)Boolean literals: True, False (there are only two)None literal: None (there is only one)You might be wondering whether -14 counts as a literal. The answer is no: Python understands this expression not as a literal for the number -14, but as the application of the - operator to the number 14 (more about number operators in the next slide).VariablesYou can also introduce your own names for objects, and these are called variables. When you introduce a variable you have to specify which object it refers to. This is called assigning the variable, and you do it using the assignment operator =. This is sometimes also called binding the variable - you bind it to an object.Here is an example:message = 'Hello there' print(message)The first line introduces a variable message and assigns it the string object 'Hello there'. The second line uses this variable to print the object.Once you introduce a variable you can use it as many times as you like throughout your program:message = 'Hello there' print(message) print(message) print(message) print(message)The object that the variable refers to is often called the value of the variable. You can change the value of a variable (i.e., change which object the variable refers to) as often as you like:message = 'Hello there' print(message) message = 3.14 # Assign a new value print(message) message = True # Assign a new value print(message)Notice that the variable message in the program refers to different types of object as the program proceeds - first it refers to a string, then to a floating-point number, and then to a boolean. Because variables in Python can do this we say that Python has flexible typing. (Some languages, such as C and Java, do not allow variables to change their reference to a different type of object.)If you want to check the type of the object that a variable refers to, you can use the type() function:x = 'Hello there' print(type(x)) # str x = 3.14 print(type(x)) # float x = True print(type(x)) # bool x = print print(type(x)) # functionAny type of object can be assigned to a variable, not just numbers, strings or booleans. Look at the last example above - we have assigned the print function to the variable x. Having done that, x is then another name for the print function, and we can use it accordingly:x = print x('Hello, world!')You can use variables to assign other variables:message = 'Hello there' new\_message = message print(new\_message)Be careful to understand what's going on here. In line 2 you are getting new\_message

to refer to whatever it is that message refers to at the time. If a different object is later assigned to message, it will not automatically be assigned to new\_message as well - there will be no change in what new\_message refers to. Let's check that: message = 'Hello there' new\_message = message message = 'Goodbye' # Value of new\_message not changed print(new\_message) You must assign a value to a variable before you use it, otherwise Python will generate an error: print(message) # Error - message has no value if you want to introduce a variable but don't yet have any significant value to assign it then you can assign it the value None: message = None print(message) # No error - message has a value You can assign multiple variables the same value: x = y = z = 0 # All get assigned 0 print(x, y, z) Or different values, using a technique called multiple assignment: x, y, z = 1, 2, 3 # x gets 1, y gets 2, z gets 3 print(x...

## Working with numbers

Python has 3 built-in types for numbers: int - representing whole numbers (positive and negative integers) with unlimited precision (i.e. there is no a priori maximum or minimum value an int object can have) float - representing floating point numbers (non-whole numbers) with a limited precision (i.e. a float object is limited to a certain number of significant figures) complex - representing complex numbers. A complex number is a number with two distinct components: a real part and an imaginary part. While numeric types are largely interchangeable (for example you can add an int to a float), a common source of runtime errors is when objects of the wrong type are being used (for example using a float when an int was expected or vice versa). Operating on numbers You can add, subtract, multiply, and divide numbers by using the operators +, -, \*, /, respectively, and combinations of them: print(1 + 2) print(10 - 5) print(3 \* 4) print(20 / 4) print((1 + 2) \* (3 + 4)) print(10 / (3 - 1)) Complex numbers examples: n = 1 + 2j print(n) print(n.real) print(n.imag) a = 1 + 2j b = 3 - 4j print(a + b) print(a - b) print(a \* b) print(a / b) You can raise one number to the power of another number by using the exponentiation operator, \*\*: print(10 \*\* 2) # 10 to the power 2 print(2 \*\* 3) # 2 to the power 3 You can divide one number by another number and round down to the nearest whole number by using the integer division operator, //: print(10 // 3) # 10 divided by 3 and rounded down Note the effect of using // on negative numbers: print(-10 // 3) # -10 divided by 3 and rounded down You can divide one number by another number and get the remainder by using the modulus operator, %: print(10 % 3) # The remainder when 10 is divided by 3 Order of operations Unless you specify the order in which operations are to be performed, by using brackets, Python performs them in a very particular order: First, \*\* is performed, from right to left Next, \*, /, //, and % are performed, from left to right. Next, + and - are performed, from left to right. print(1 + 2 \* 3) # Same as 1 + (2 \* 3) print(2 \*\* 3 \* 4) # Same as (2 \*\* 3) \* 4 print(24 / 6 \* 2) # Same as (24 / 6) \* 2 print(24 / 6 / 2) # Same as (24 / 6) / 2 print(2 \*\* 2 \*\* 3) # Same as 2 \*\* (2 \*\* 3) Augmented assignment operators You will often find yourself wanting to operate on a variable and then re-assign the result to that same variable. Python provides augmented assignment operators to allow for more concise code: +=, -=, \*=, /=, //=, and %= . x += 2 is equivalent to x = x + 2 x -= 2 is equivalent to x = x - 2 x \*= 2 is equivalent to x = x \* 2 x /= 2 is equivalent to x = x / 2 x //= 2 is equivalent to x = x // 2 x %= 2 is equivalent to x = x % 2 x = 12 x += 2 # Equivalent to x = x + 2 (assign to x the result of x + 2) print(x) Comparing numbers Python has a number of comparison operators which you can use to compare numbers: num1 == num2 is True if the value of num1 equals the value of num2, otherwise it is False num1 is num2 is True if the value of num1 equals the value of num2, and num1 and num2 have the same type, otherwise it is False num1 != num2 is True if the value of num1 does not equal the value of num2, otherwise it is False num1 is not num2 is True if the value of num1 does not equal the value of num2, or num1 and num2 have different types, otherwise it is False num1 is True if the value of num1 is less than the value of num2, otherwise it is False num1 is True if the value of num1 is less than or equal to the value of num2, otherwise it is False num1 > num2 is True if the value of num1 is greater than the value of num2, otherwise it is False num1 >= num2 is True if the value of num1 is greater than or equal to the value of num2, otherwise it is False x = 1 y = 1.0 print(1 == 1.0) print(x is y) Floating-point numbers and == Because floating point numbers are stored with limited precision you might experience strange results when attempting to compare them with ==. For example: print(0.1 + 0.2 == 0.3) Why does this comparison return False? Because 0.1...

## Working with strings

A string is a sequence of characters. The characters might be ones you can type on your keyboard, or any of the hundreds of thousands of other unicode characters, including symbols and foreign language letters. String literals As you have seen, string literals have the characters between quotes, either single quotes or double quotes. literal\_one = 'A string' # You can use single quotes literal\_two = "A string" # Or double quotes print(literal\_one) print(literal\_two) The empty string One of the most useful strings is the empty string - a string with no characters. The literal for an empty string is "", or "". Note that the empty string is not the same thing as None - they are different objects: empty\_string = "" print(empty\_string) print(None) print(empty\_string is None) Escaping special characters Sometimes you will need to use a

string literal that contains quote marks or other characters that have special meaning in Python. You can do this by escaping those special characters, which means prefixing them with a backslash \. # Backslash used to escape a quote mark `print('Penny\'s dog')` `print("Penny's dog is called \"Mac\".")` # Backslash used to escape a new line symbol `print('This is one line.\nThis is a second line')` # Backslash used to escape a tab symbol `print('Here\tThere')` This means that the backslash itself has a special meaning in strings, so to include it you must escape it: `print("You can have tea neither\nor coffee")` `print("You can have tea neither\\nor coffee")` If you have a lot of backslashes and no special characters then you can tell Python to ignore the special meaning of the backslash by preceding the string with `r` (for "raw"): `print(r"You can have tea neither\nor coffee")` You can avoid having to escape single quote marks by enclosing the whole string in double quotes. Similarly, you can avoid having to escape double quote marks by enclosing the whole string in single quotes: `print("Penny's dog")` `print('Penny said, "This is my dog".')` If you like to include line breaks in a string then you can either use `\n`, as in the example above, or you can use triple quotes around the string: # Using `\n` `text = 'This is one line.\nThis is a second line'` `print(text)` # Using triple single quotes `text = '''This is one line. This is a second line.'''` `print(text)` # Using triple double quotes `text = """This is one line. This is a second line."""` `print(text)` `text = """\ This is one line. This is a second line."""` `print(text)` You can also use triple quotes around a string that contains both single and double quotes: `text = "She said, 'I don't know how you do it!'"` `print(text)` `text = """She said, 'I don't know what "" means'"""` `print(text)` You'll get an error if you end up with four quotes in a row. Concatenating strings You can concatenate strings (i.e. join them) using the `+` operator: `first_name = 'Leo'` `last_name = 'Tolstoy'` `full_name = first_name + ' ' + last_name` `print(full_name)` You can also use the `+=` augmented assignment operator: `name = 'Leo'` `name += ' Tolstoy'` `print(name)` You can duplicate a string a given number of times by using the `*` operator: `print('a' * 10)` Comparing strings Just as with numbers, you can use Python's comparison operators to compare strings: `str1 == str2` is True if `str1` and `str2` are the same sequence of characters, otherwise it is False `str1 != str2` is True if `str1` and `str2` are not the same sequence of characters, otherwise it is False `str1 in str2` is True if `str1` appears as a substring in `str2`, otherwise it is False `str1 not in str2` is True if `str1` does not appear as a substring in `str2`, otherwise it is False `str1 is True` if `str1` is lexicographically less than (i.e. would appear earlier in the dictionary than) `str2`, otherwise it is False Similarly we have `str1 < str2`, and `str1 >= str2` `print('A' == 'A')` `print('A' == "A")` # Whether you define literals with `'` or `"` does not matter `print('fish' in 'selfishness')` `print('fine' in 'selfishness')` # Substrings have to be contiguous `print('A'` Applying functions to strings Y...

## Working with booleans

Boolean objects are the simplest type of objects in Python, but often they play the most significant role in determining the path that a program takes (as you will see). There are two boolean objects: `True` and `False`. They most commonly appear as the result of the comparison operations we have seen for the other types, for example `3` will evaluate to `True`; and `1 + 1 == 3` will evaluate to `False`: `print(3)` Operating on booleans You can build complex boolean expressions by combining simple boolean expressions with the logical operators `not`, `and`, and `or`: `not x` is true if `x` is false, otherwise it is false. `x and y` is true if `x` is true and `y` is true, otherwise it is false. `x or y` is true if `x` is true or `y` is true or both, otherwise it is false `print(not True)` # `False` `print(not False)` # `True` `print(not 3)` `print(True and True)` # `True` `print(True and False)` # `False` `print(False and True)` # `False` `print(False and False)` # `False` `print((3 < 4) and (3 < 5))` # `True` `print(True or True)` # `True` `print(True or False)` # `True` `print(False or True)` # `True` `print(False or False)` # `False` `print((3 < 4) or (3 < 5))` # `True` `guess = int(input('Enter a number: '))` `print('Your number is between 2 and 5?')` `print(guess > 2 and guess < 5)` Chaining comparisons It is possible to combine comparisons into a chain: `x = 12` # Rather than this `print(5 < x < 10)` Short circuiting The operators `or` and `and` are said to be short circuiting operators, because they only evaluate their second expression if they need to. To illustrate, the program below does not generate an error, even though the variable `var` has not been defined. That's because Python doesn't even look at that variable. It doesn't need to, because the first `True` is enough to make the whole expression true. `print(True or var)` Similarly, the program below does not generate an error, even though the variable `var` has not been defined. That's because Python doesn't need to look at it - the first `False` is enough to make the whole expression false. `print(False and var)` If you swap the order in either case, you get an error: `print(var and False)`

## Controlling program flow

In a simple program, Python executes the statements of the program one-by-one in sequence, from start to finish. However, you will often want your program to deviate from this: Conditional execution. You might want to execute a certain statement only if a certain condition is true. Loops. You might want to loop through a block of code multiple times. Handling exceptions. You might want to run a block of code in a "cautious" way, so that if an error arises you can deal with it without your whole program stopping. We will look at these one-by-one in the next few slides.

## If statements

You will often want Python to execute a certain statement only if a certain condition is true. For this you can use an if statement. The following program uses an if statement:

```
number = int(input('What is your favourite number? '))
if number == 42: print('That is my favourite number too!')
print('Good bye!')
```

If the user enters the number 42 then Python executes line 3, otherwise it skips line 3 and goes straight to line 4.

**Syntax** The syntax for an if statement is: `if` : There are two parts to this statement - the part between `if` and `:` is called the header of the statement; the rest is called the body of the statement. The body of the statement is a block of statements. Notice that the body contains one or more statements (as many as you like), so an if statement contains other statements as part of it. Because of this we call it a compound statement. Also notice that the body is indented. This is required - if you don't use indentation then Python will issue an error:

```
if True: print('Hello')
```

You can use either the tab character or the space character to create the indentation, but you must use the same character for each line, and the same number of those characters, otherwise Python will issue an error. Each of the following will cause an error:

```
if True:
print('Hello') # Indentation using a tab
print('Hello') # Indentation using 4 spaces - Error
if True:
print('Hello') # Indentation using 5 spaces - Error
```

It is standard to use 4 spaces for indentation. You can set this to be the default behaviour in the code editor for `ed` by selecting "Soft tabs" under the settings menu (icon: ) in the top right of an editor window. The statement block after `if` must contain at least one statement. It is common use the `pass` statement as a placeholder for unfinished code - it is a statement that does nothing:

```
if True: pass
```

There must be at least one statement in the body.

**Conditions** Any boolean expression can be used between the `if` and the `:`

```
if True: print('The condition is true')
if 2 > 1: print('The condition is true')
if 2 > 1 and 2 < 2 or 2 > 1: print('The condition is true')
```

If `'cat' == 'cat'`: `print('The condition is true')`

Be careful with variables! If you introduce a variable inside the block of an if statement then that variable will only be defined if the block is executed. This might cause you some unexpected errors. For example:

```
if False: x = 1
print(x) # Error - x does not have a value
```

Since line 2 is not executed the variable `x` does not get assigned a value, so when it is used in line 3 Python issues an error.

**Else clauses** You can add an `else` clause to an if statement, to tell Python what to do if the condition of the if statement is false:

```
number = int(input('What is your favourite number? '))
if number == 42:
    print('That is my favourite number too!')
else:
    print('That is not my favourite number.')
```

**Grade example with multiple conditions** # we assume the user gives a valid mark between 0 and 100 inclusive

```
mark = float(input("Please give your mark: "))
if mark == 50: print("PS")
elif mark == 65: print("CR")
elif mark == 75: print("DN")
elif mark == 85: print("HD")
else:
    print("Error")
```

**Elif clauses** You can add `elif` clauses (short for 'else if') to chain together multiple conditions:

```
number = int(input('What is your favourite number? '))
if number == 42: print('That is my favourite number too!')
elif number == 21: print('That is my second favourite number')
else: print('That is neither of my favourite numbers.')
```

**Grade example with elif** # we assume the user gives a valid mark between 0 and 100 inclusive

```
mark = float(input("Please give your mark: "))
if mark == 50: print("PS")
elif mark == 65: print("CR")
elif mark == 75: print("DN")
else:
    print("Error")
```

**Abbreviations** If you only have one statement in an if body then you can put it on the same line as the header. The same applies to `elif` and `else`. Note that you still need the colon:

```
number = int(input('What is your favourite number? '))
if number == 42: print('That is my favourite number too!')
elif number == 21: print('That is my second favourite number')
```

## While statements

Sometimes you might want to repeat a set of statements for as long as a certain condition is true. For this you can use a while statement. Here's a program that uses a while statement to print the first 10 positive integers:

```
n = 1
while n <= 10:
    print(n)
    n = n + 1
```

When Python gets to line 2 it evaluates the condition `n <= 10`. If the condition is true then it executes the statement block below, in lines 3-4, and then returns to line 2 again. If the condition is false then it skips the block and goes straight to line 5. You could achieve the same effect by using 10 different print statements, but using a while statement is more elegant and less repetitive. And if you don't know in advance how many integers to print, for example if you want to ask the user, then it might be impossible to use just print statements.

**The while block** The while block can contain any statement(s) you like, including if statements and other while statements. For example, here's a program that prints the even numbers between 1 and 10. It uses an if statement inside the while loop:

```
n = 1
while n <= 10:
    if n % 2 == 0:
        print(n)
    n = n + 1
```

Here is an example of a while loop used to iterate through a string, counting the number of times 'e' occurs in it.

```
string = 'The quick brown fox jumped over the lazy dog'
occurrences = 0
i = 0
while i < len(string):
    if string[i] == 'e':
        occurrences = occurrences + 1
    i = i + 1
```

Continuing You can use a `continue` statement to skip to the next iteration of a loop:

```
i = 0
while i < len(string):
    if string[i] == 'e':
        occurrences = occurrences + 1
    i = i + 1
    continue
```

When the value of `i` gets to 5 the `continue` statement is executed, and Python jumps directly back to line 2 and continues. The number 5 does not get printed, but 6 - 10 do. Why might you use `continue`? It can help to keep your code from getting to many levels of indentation. We will see examples of this.

**Breaking** You can use a `break` statement to break out of a loop entirely:

```
i = 0
while i < len(string):
    if string[i] == 'e':
        occurrences = occurrences + 1
    i = i + 1
    break
```

When the value of `i` gets to 5 the `break` statement is executed, and Python jumps directly to line 7. The number 5 does not get printed, and nor do 6 - 10. Note that if the loop is nested inside another loop, the `break` statement terminates only the inner loop.

**Keeping a program**

running When you run the program below it stops after it gets and prints a name. To run it again you have to click 'Run' again: `name = input('What is your name? ') print('Hello', name)` It can be convenient to have the program keep running - getting it to start again automatically after it does its thing. You can get it to do this by adding a while loop, with a condition that always evaluates to true: `while True: name = input('What is your name? ') print('Hello', name)` Now the program will keep running, until you click 'Stop'. If you want to get a bit fancier, you could get your program to stop when the user enters a certain value, such as 'q'. Remember to let the user know that they can do this: `while True: name = input('What is your name? (Enter q to quit) ') if name == 'q': break print('Hello', name)` Nested while loops example # Write a program to display the following: `# ***** # ***** # ***** i = 1 while i`

## Handling exceptions

If your code interacts with the outside world, you may encounter unexpected circumstances. Perhaps a file that you are trying to open doesn't exist, or when you try to save the user's data you find that the disk is full, or perhaps the user enters a non integer value when you are expecting an integer, or maybe you divided by zero. Exceptions are a mechanism for dealing with the unwanted or unexpected situations. The approach in Python is known as structured exception handling. This means that if Python encounters an exception in a block of code, it will search for an exception handler enclosing that block. If none exists, it will look for an exception handler enclosing that outer block, and so on. It is important to understand that exception handling should be used to handle exceptions that are recoverable. If your program cannot handle the exception or recover from it, it should not even try. Instead it should let the exception terminate your program so the user can deal with it instead. For many cases of exceptions, there is no remedy. Try and except You can handle exceptions by using a try statement. Consider the following program, which asks the user to enter a number and then returns the square of that number: `num = input("Please enter a number: ") result = float(num) ** 2 print("The square of the number is", result)` If the user enters a string of letters instead of a number then an error occurs and the program very ungracefully ends. Python complained with a `ValueError`. To handle this, we'd write a `try ...except ...` block around the code that could potentially raise an exception. `num = input("Please enter a number: ") try: result = float(num) ** 2 print("The square of the number is", result) except: print("You did not enter a number.")` In the above code, when control reaches line 2, an exception is raised. Python finds the nearest exception handler and moves control to line 3, which proceeds into the block at line 4. If there was no exception on line 2, then the code in the except block would not be executed. If you don't want to do anything with the exception then you can use the pass statement: `num = input("Please enter a number: ") try: result = float(num) ** 2 print("The square of the number is", result) except: pass` When an exception occurs, there is information about the exception contained in a special Exception object. You can assign that object to a variable and then display that information to the user: `try: int('string') except Exception as err: print('Exception:', err)` Else if you have some code that you want to execute only if the try block succeeds then you can add an else clause: `x = 'Hello' try: x = int(x) except: print('The conversion was not successful.') else: print('The conversion was successful.')`

## Working with files

So far we have seen programs that interact with the external environment via the `input()` and `print()` functions. Another way they can interact is by reading from and writing to files. This is very simple in Python, which is why Python is a popular tool for working with files. This is what you will typically want to do: Open the file Read from the file, or write to the file Close the file Opening a file To work with a file you must first open it. You do so using the `open()` function: `f = open('MyData', 'w')` The function expects a file as the first argument. This can be given as an absolute or relative filename. If given as a relative filename, it is relative to the directory that Python was executed from - in Ed this is always the same directory as the program. You can also supply a mode as the second argument. This indicates whether the file is to be opened for reading (i.e. input) or writing (i.e. output). If you don't specify the mode, Python assumes that you want to open the file for reading. The available options for the mode are: 'r' - Open the file for reading. `open` will throw an exception if the file does not exist. 'w' - Open the file for writing. If the file exists, the contents are completely overwritten. If the file does not exist, it will be created. 'x' - Open the file for writing. If the file already exists this will throw an exception. If the file does not exist, it will be created. 'a' - Open the file for appending. The file is opened at the end and any writes to the file will append to the end. If the file does not exist it is created. This option is useful for adding information to a file - for example a log file. The `open()` function returns a file object (also called a file handle) that represents the file that you have opened. It is this object that allows you to perform operations on the underlying file itself. Reading from and writing to a file The `read()` method of a file object returns a string that contains the entire contents of the file. The `write()` method takes a string and adds it to the file. # Open a file for writing `file = open('myfile', 'w') # Write to the file # If you want a newline anywhere you have to add it, using \n file.write('Line 1: Some text.\n') #`

Write some more to the file `file.write('Line 2: Some more text.')` # Now open the file for reading `file = open('myfile', 'r')` # Print the contents `print(file.read())` Closing a file You can close a file by using its `close()` method. It is important to close a file after you are done working with it, to free up resources back to the system. A program can only have a limited number of files open while it is running. If a running program reaches this limit, it will receive a "Too many open files" error when it attempts to open more files. So the program above should look like this instead: `file = open('myfile', 'w')` `file.write('Line 1: Some text.\n')` `file.write('Line 2: Some more text.')` `file.close()` `file = open('myfile', 'r')` `print(file.read())` `file.close()` Using a `with` block It's a good idea to work with a file inside a `with` statement. This ensures that the file is always closed after use, even if an error occurs inside your program. As soon as control exits the `with` statement the file will be automatically closed. Here is the previous example written with `with` statements: # Open a file for writing # The file is automatically closed after the `with` statement with `open('myfile', 'w')` as file: `file.write('Line 1: Some text.\n')` `file.write('Line 2: Some more text.')` # Open the file again for reading # The file is automatically closed after the `with` statement with `open('myfile', 'r')` as file: `print(file.read())` See Files Example in Ed Workspaces

## Further reading

You might find the following helpful: The Python Tutorial at [w3schools.com](https://www.w3schools.com/python/) Numbers in Python <https://realpython.com/python-numbers/>