

A Comparative Empirical Study of FIDO2 and Its Predecessors

Anderko Máté
Óbuda University
mate.anderko@stud.uni-obuda.hu

Abstract—The FIDO2 standard, introduced by the FIDO Alliance and the World Wide Web Consortium (W3C) in 2018, it has been hailed as the “Kingslayer of User Authentication”. This paper presents the implementation of a FIDO2 + WebAuthn authentication system and shows an analysis on different user authentication philosophies. The analysis assesses a FIDO2, a 2FA and a password only system on their resistance to common security threats using the STRIDE threat modeling framework and evaluates performance based on latency, memory usage, and computational overhead. The objective is to determine how adopting FIDO2 influences the security, usability, and system resource requirements of information systems.

Index Terms—FIDO2, WebAuthn, Passkeys, Passwordless authentication, Multi-factor authentication, STRIDE, Performance

I. Introduction

Since the dawn of computing the weakest link in most information systems has been the people creating and using them. We choose easy to remember password that might be prone to dictionary attacks, then we overcomplicate them just to forget them, so to only have to remember a couple passwords we reuse them across sites, also we are susceptible to social engineering attacks, like phishing. Sufficiently long, unique, and complex passwords with proper rate limiting remain impractical to brute-force, so compromises overwhelmingly exploit human factors and credential leaks rather than cryptographic weakness. Also the use passwords impose nontrivial support costs and friction because of the resets and account recovery.

To mitigate the weaknesses of a password only environment one-time codes (SMS/TOTP) and push prompts were introduced, this is safety standard is commonly referred to as Multi Factor Authentication MFA materially reduces risk from simple credential stuffing, but common forms remain phishable (e.g., OTP relay, look-alike pages) and are vulnerable to SIM-swap or “push fatigue” attacks. Usability trade-offs (codes, prompts, and device availability) also create drop-off during enrollment and sign-in.

FIDO2/WebAuthn addresses these limitations by replacing shared secrets with origin-bound public-key cryptography and local user verification (biometrics or a device PIN). Private keys never leave the authenticator; the server stores only public keys, eliminating password reuse and greatly reducing the value of stolen databases. Because assertions are tied to the requesting origin, generic

phishing and OTP-relay attacks fail by design. In practice, passkeys (discoverable credentials) further streamline the flow across platforms using platform sync or roaming security keys.

This paper adopts that progression—passwords → MFA → FIDO2—and (i) implements a fully passwordless WebAuthn system, and (ii) compares password-only, password+MFA, and FIDO2 across resilience (phishing, stuffing, brute-force), usability (enrollment, recovery, cross-device), and resource usage (compute, storage, support). We show how MFA mitigates many password risks yet remains phishable, and how FIDO2 offers a principled, practical solution that is both more secure and simpler for end users.

II. Similar and Related Work

This section reviews research on the security, usability, and adoption of FIDO2, also shows a comparison with this here work.

A. Formal and Theoretical Analyses

Barbosa and their team [1] offers a formal model of FIDO2 and, through theoretical analysis, show resistance to credential-phishing and replay attacks. In contrast, the present work examines a deployed FIDO2 stack with STRIDE, emphasizing practical security implications and performance (latency, memory, compute).

B. Empirical and Usability Studies

Lyastani and their team [2] created an empirically FIDO2’s usability analyses. The study shows significant usability gains and phishing resistance compared to passwords and 2FA. Their work relied on user studies and perception metrics rather than system-level measurements.

Unlike these human-centered, behavioral studies, this work isolates the technical performance and security aspects of FIDO2.

C. Positioning of This Work

Key contributions:

- 1) Operational implementation of FIDO2/WebAuthn alongside password-only and 2FA baselines.
- 2) Structured STRIDE analysis, grounded in Barbosa’s theoretical model.

- 3) Empirical performance results—latency, memory footprint, computational load—that complement usability-centric studies (e.g., Lyastani).

Unlike work centered on formal guarantees or user experience, this study examines how adopting FIDO2 shifts real-world security posture and runtime efficiency.

III. Common Authentication Vulnerabilities

Bad actors find the most creative ways to attack authentication systems, these are called attack vectors. The goal of this section is to outline how the vulnerabilities work, which the paper will address in later sections, and also to shine a light on why traditional password or even basic MFA schemes struggle against them.

A. Weak Passwords and Brute-Force Attacks

Users often choose simple passwords, making them easy targets for brute-force attacks [3]. A simple brute-force attack tries to crack the user’s password by trying random character combinations. Rate limiting and sufficient password length makes the attack redundant. A dictionary attack is a more sophisticated version of a brute-force attack, where attackers use common wordlists, lists of frequently used passwords or they systematically guess combinations to find the password. In the case of brute-force not cryptographic weaknesses, but bad password hygiene and the site’s lack of password complexity enforcement leads to the compromise.

B. Credential Stuffing and Password Reuse

Credential stuffing exploits password reuse across websites. In the event of a databreach the user’s password may get leaked, this creates an opportunity for bad actors, who then use the credentials on other sites to try to gain access to other accounts.[4]. The process can be well automated, thus the reuse of credentials turns one breach into many.

C. Social Engineering Attacks

Many attacks rely on human gullability instead of technical flaws. Phishing, SIM swap, and push fatigue attacks are such attacks.

1) Phishing and OTP Relay: Phishing deceives users into revealing credentials on fake websites, that mimic the working of the site the user is familiar with. Attackers can proxy the login and capture OTP codes in real time, bypassing traditional 2FA, this is commonly referred to as a real-time phishing proxy. OTP capturing is Adversary-in-the-Middle type attack[5].

2) SIM Swap Attacks: The way SMS based MFA works is that the user gets an SMS containing a secret code, generated by the server, this while may seems bulletproof requires complete trust in the user’s telecommunication service provider. The attackers may be able to impersonate victims and hijack their phone number (with the service provider unknowingly complicit), thus gaining control of SMS-based OTPs[6].




Fig. 1. Phishing with OTP relay

- 3) MFA Push Fatigue: Push-based MFA can be exploited by flooding users with repeated prompts until they approve one, often by mistake or frustration [7].




Fig. 2. Push fatigue attack sequence

IV. How FIDO2 Works

This section offers a quick introduction into the FIDO2 ecosystem. FIDO2 provides an phishing-resistant, origin-bound public-key authentication by combining the W3C WebAuthn API (browser/platform) with the FIDO Alliance CTAP protocol.

A. Core Roles

- 1) Relying Party (RP): The application service that issues authentication challenges and stores each user’s registered public key.
- 2) Client/Platform: The browser or operating system that brokers WebAuthn requests and responses between the RP and the authenticator.
- 3) Authenticator: A platform or roaming device that creates key pairs, enforces user presence/verification, and returns attested assertions.

B. Registration (makeCredential)

- 1) The RP provides options (challenge, RP ID, user handle, algorithm preferences) to the client.

- 2) The authenticator creates a new key pair based on the RP ID, the private key remains within the authenticator, keeping it safe from attackers, the public key and attestation statement are returned.
- 3) The RP verifies attestation and stores the credential public key.

C. Authentication (getAssertion)

- 1) The RP provides options (challenge, RP ID, and an allow list if applicable).
- 2) The authenticator enforces user presence/verification, then signs the challenge together with the RP ID hash, authenticator flags, and a signature counter.
- 3) The RP verifies origin, RP ID, signature, and counter before completing authentication.

D. Security Properties

- Origin binding (via RP ID and client data) mitigates phishing and relay.
- Non-exportable keys reduce the impact of server-side compromise.
- Attestation enables enforcement of device-class policy, lower class untrusted devices can be blocked.




Fig. 3. Registration sequence




Fig. 4. Authentication sequence

E. Real-World example

This example tries to convey how Android devices keep the data secure working with the FIDO2 ecosystem. On

Android, passkeys and cryptographic keys are managed through Credential Manager and the Android Keystore. Where available, StrongBox places KeyMint in a discrete secure element so that keys are generated and stored within a dedicated secure processor rather than solely in the TEE. Private key material is non-exportable and invocable only via Keystore operations under enforced user-authentication and policy.

1) StrongBox isolation: StrongBox uses KeyMint in a separate secure chip. This chip has its own CPU, RAM and secure storage, completely isolating it from the mobile device, thus making it virtually impossible for bad-actors to access the private key stored here. It enables hardware attestation so servers can verify that keys are hardware-backed on a genuine device.

2) Illustrative Flow:

- The registration process begins through the Credential Manager (WebAuthn).
- The Keystore requests a hardware-backed key; on devices with StrongBox, the key pair is generated within the StrongBox KeyMint and marked as non-exportable.
- The public key and attestation chain are returned. The RP may verify the attestation to confirm hardware-backed security.
- During authentication, StrongBox performs the signature after local user verification; the private key never leaves the secure processor.




Fig. 5. Android StrongBox flow

V. STRIDE Threat Modelling Framework

The STRIDE threat modeling framework helps to group real-world attacks into six types. Each type targets a different part of the authentication process. This section maps the vulnerabilities discussed earlier to STRIDE categories and shows how each of the three authentication methods handles them.

STRIDE categories:

- Spoofing: when an attacker pretends to be a valid user to gain access
- Tampering: when an attacker changes messages or data during login
- Repudiation: when a user denies doing an action, like logging in
- Information Disclosure: when sensitive data like passwords or OTPs are leaked

- Denial of Service: when the attacker blocks the user from logging in
- Elevation of Privilege: when someone gets more access than they should

[7] Cybersecurity & Infrastructure Security Agency (CISA), “Implementing phishing-resistant mfa (fact sheet),” <https://www.cisa.gov/sites/default/files/publications/fact-sheet-implementing-phishing-resistant-mfa.pdf>, 2022, accessed 2025-10-29.

Each vulnerability from Section III fits one or more of these categories. Table I shows which threat is mapped where, and what to expect from password-only, 2FA, and FIDO2-based systems.

TABLE I
STRIDE Categories, Real-World Vulnerabilities, and Expected Behavior

STRIDE Category	Mapped Vulnerability	Password-only	2FA	FIDO2/WebAuthn
Spoofing	Phishing and OTP relay attacks	Easy to spoof if password is stolen or phished	OTP relay attacks can still trick users	Origin check and public-key signatures prevent spoofing
Tampering	Adversary-in-the-middle modifying login flow	No strong protection if TLS fails	Relayed OTPs or injected prompts possible	Signed challenge-response blocks message tampering
Repudiation	No way to prove who logged in	Anyone with the password can log in	2FA logs may help but are weak proof	Authenticator signs each login, tied to device and origin
Information Disclosure	Password reuse and data breaches	Password leaks are common and reused across sites	OTP seeds and SMS codes can be stolen	No password or shared secret stored or sent
Denial of Service	Push fatigue and SIM swap	Lockout by brute force or repeated failures	Flood of OTP or push requests can lock out users	Brute-force blocked by design, backup keys help recovery
Elevation of Privilege	Use of weak or reused admin credentials	Admin access can be guessed or reused	OTP can be phished from high-priv users	High-priv accounts tied to secure device credentials

The STRIDE mapping helps compare which attack types are stopped or remain possible in each authentication setup. This forms the basis of the analysis in Section ??, where each system’s real threat resistance is examined in more detail.

VI. Implementation

VII. Performance Testing

References

- [1] M. Barbosa et al., “Provable security analysis of fido2,” in Information Security Theory and Practice (WISTP 2021). Springer, 2021. [Online]. Available: https://dl.acm.org/doi/10.1007/978-3-030-84252-9_5
- [2] S. Lyastani et al., “Is fido2 the kingslayer of user authentication?” in IEEE Symposium on Security and Privacy, 2020. [Online]. Available: <https://trust.cispa.saarland/publication/lyastani-20-sp/lyastani-20-sp.pdf>
- [3] E. Ma, S. Hasama, E. Lumba, and E. Birrell, “Prospects for improving password selection,” arXiv preprint arXiv:2201.01350, 2022.
- [4] A. Nisenoff, M. Golla, M. Wei, J. Hainline, H. Szymanek, A. Braun, A. Hildebrandt, B. Christensen, D. Langenberg, and B. Ur, “A two-decade retrospective analysis of a university’s vulnerability to attacks exploiting reused passwords,” in Proc. USENIX Security Symposium, 2023.
- [5] M. Käsemodel, V. Winterhalter, F. Heisel, F. Alt, and B. Pfleging, “BlueTOTP: Designing phishing-resistant and user-friendly two-factor authentication,” in Proc. IFIP INTERACT 2025 (LNCS 16110). Springer, 2025, pp. 611–634.
- [6] K. Lee, B. Kaiser, J. Mayer, and A. Narayanan, “An empirical study of wireless carrier authentication for SIM swaps,” in Proc. 16th Symposium on Usable Privacy and Security (SOUPS). USENIX Association, 2020, pp. 61–79.