

# *12. Training neural networks for classification problems and project proposal discussion*

M.A.Z. Chowdhury and M.A. Oehlschlaeger

Department of Mechanical, Aerospace and Nuclear Engineering  
Rensselaer Polytechnic Institute  
Troy, New York

*chowdm@rpi.edu*  
*oehlsm@rpi.edu*

MANE 4962 and 6962

# Regular announcement

- 👉 Quiz 4 on Feb 27. ✓
- 👉 Quiz 4 is based on notes from Lecture 10.
- 👉 HW 4 is due Feb 27. ✓ → March 2
- 👉 Initial project proposal due March 2. ✓

## Outline

Log on  
units per layer  $X_1, X_2$   
inclu' learning rate = 0.001  $X_2, \log X_1$

➡ We solved regression problems using a fully connected neural network,  $y \in \mathbb{R} \leftarrow y_1 \in \mathbb{R}, y_2 \in \mathbb{R}$

➡ Solve a binary classification problem using a fully connected neural network  $y \in [0, 1]$

➡ Solve a multi-class classification problem using a fully connected neural network  $y \in \mathbb{R}^K$ ,  $K$  is the number of classes

➡ HW4 Hints

➡ Discussion about the initial and revised project proposal submission

➡ Study the notebooks for today's class

$$\sigma(z) = \frac{1}{1 + e^{-z}} \in [0, 1]$$

lim  $\rightarrow -\infty$     lim  $\rightarrow \infty$

decision

$$\begin{cases} < 0.5 & 0 \\ \geq 0.5 & 1 \end{cases}$$

# MNIST Digits

→ SGD → NN  
batch size = 10  
mini-batch stochastic gradient descent

---

```
from keras.datasets import mnist
```

```
(x_train, y_train), (x_test, y_test) = mnist.load_data()
```

```
print("training images shapes: ", x_train.shape)
```

```
print("testing images shapes: ", x_test.shape)
```

```
print("training targets shapes: ", y_train.shape)
```


```
print("testing targets shapes: ", y_test.shape)
```

```
plt.imshow(x_train[0], cmap=plt.cm.gray_r, interpolation="nearest")
```


```
print(x_train[0])
```

---

# Visualization of MNIST digits





Odds




128 unique number

Even











# Implementation in tensorflow

```
import tensorflow as tf
from tensorflow import keras
from tensorflow.keras.datasets import mnist
from tensorflow.keras.models import Sequential
from tensorflow.keras.layers import Dense
import matplotlib.pyplot as plt

(x_train, y_train), (x_test, y_test) = mnist.load_data()

x_train = x_train.reshape(60000, 784)
x_test = x_test.reshape(10000, 784)
```

```
x_train = x_train.astype('float32') / 255
x_test = x_test.astype('float32') / 255
y_train = y_train % 2
y_test = y_test % 2
```

tags → 0%2 → 0  
the images

1%2 → 1

Normalizing


0-2  
→ 0.5-1.7-

3%2 → 1 5%2 → 1


Step 1: Preprocess the data as required by the problem.

# Implementation in tensorflow (contd.)

ReLU → Stickler  
Sigmoid → Allow -ve features to pass through



```
model = Sequential()
model.add(Dense(512, activation='relu', input_shape=(784,)))
model.add(Dense(256, activation='relu'))
model.add(Dense(128, activation='relu'))
model.add(Dense(1, activation='sigmoid'))
model.compile(optimizer='adam',
              loss='binary_crossentropy',
              metrics=['accuracy'])
model.summary()
```



Hyperparameter

Step 2: Define model. You may need to perform cross-validation to find the optimal architecture.

⇒ Sigmoid → estimated probability

# Implementation in tensorflow (contd.)

$\tanh \rightarrow$  activation , Goodfellow  $\rightarrow 90\%$  ReLU

# Train the model

```
history = model.fit(x_train, y_train, epochs=10,
                    batch_size=64, validation_split=0.3)
```

```
plt.plot(history.history['accuracy'])
plt.plot(history.history['val_accuracy'])
plt.title('Model Loss')
plt.ylabel('Loss')
plt.xlabel('Epoch')
plt.legend(['Train', 'Validation'], loc='upper left')

plt.show()
```

$$\begin{aligned}
 x &= 0 & p &= 0.5 \\
 se &= (-0.5)^2 \\
 &= 0.25 \\
 &= -[0 \ln 0.5 + (1-0) \ln (-0.5)] \\
 &= \ln(-0.5)
 \end{aligned}$$


Step 3: Train model and analyze further. You can add more steps of postprocessing as needed.

validation data

$val\_data = (x\_val, y\_val)$

7  
7


Multi-class  $\rightarrow$  10  
 $K \rightarrow \#$  of classes  $K=10$



component

$\vec{y} = [0, 0, 0, 0, 0, 0, 0, 0, 0, 0]$

$\rightarrow$  OHE vector 1st component  $\rightarrow$  tracking zero



# Implementation in tensorflow

```
import tensorflow as tf ✓  
from tensorflow import keras ✓  
from tensorflow.keras.datasets import mnist ✓  
from tensorflow.keras.models import Sequential ✓  
from tensorflow.keras.layers import Dense ✓  
from tensorflow.keras.utils import to_categorical ←  
import matplotlib.pyplot as plt ←
```

```
(x_train, y_train), (x_test, y_test) = mnist.load_data()
```

```
x_train = x_train.reshape(60000, 784)
```

```
x_test = x_test.reshape(10000, 784)
```

```
x_train = x_train.astype('float32') / 255
```

```
x_test = x_test.astype('float32') / 255
```

```
# Convert the target data into one-hot encoding ← one
```

```
y_train = to_categorical(y_train, 10)
```

```
y_test = to_categorical(y_test, 10)
```

# Implementation in tensorflow (contd.)

$$\text{Softmax, } \sigma(z_i) = \frac{e^{z_i}}{\sum_j e^{z_j}}$$

Soft max scores

```
model = Sequential()
model.add(Dense(512, activation='relu', input_shape=(784,)))
model.add(Dense(256, activation='relu'))
model.add(Dense(128, activation='relu'))
model.add(Dense(10, activation='softmax'))


model.compile(optimizer='adam',
              loss='categorical_crossentropy',
              metrics=['accuracy'])

model.summary()
```

Sigmoid

→ [0, 1]  
→ [0, 1]  
⋮  
⋮  
⋮  
⇒ [0, 1]  
≠ 1

Step 2: Define model. You may need to perform cross-validation to find the optimal architecture.





# Implementation in tensorflow (contd.)

---

```
history = model.fit(x_train, y_train, epochs=10,  
batch_size=64, validation_split=0.3)  
  
plt.plot(history.history['accuracy'])  
plt.plot(history.history['val_accuracy'])  
plt.title('Model Accuracy')  
plt.ylabel('Accuracy')  
plt.xlabel('Epoch')  
plt.legend(['Train', 'Validation'], loc='upper left')  
plt.show()
```

---

Step 3: Train model and analyze further. You can add more steps of postprocessing as needed.

# HW4 hints

- P1. Identify the type of classification problem. Then use these ideas to code and answer the questions.
- P2. It is a regression problem. The question allows you to use any machine learning model to solve it. So, use whichever one you prefer. Try to identify the features and target and the rest should be pretty easy.

# The CIFAR-10 image dataset

P1,

```

1  from keras.datasets import cifar10
2  from keras.utils.np_utils import to_categorical
3  import matplotlib.pyplot as plt
4
5  # First time you run this it will download the data
6  (X_train, y_train), (X_test, y_test) = cifar10.load_data()
7
8  cifar_classes = ['airplane', 'automobile', 'bird', 'cat',
9                  'deer', 'dog', 'frog', 'horse', 'ship', 'truck']
10 print('Example training images and their labels: ' + str([x[0] for x in y_train[0:5]]))
11 print('Corresponding classes for the labels: ' + str([cifar_classes[x[0]] for x in y_train[0:5]]))
12
13 f, axarr = plt.subplots(1, 5)
14 f.set_size_inches(16, 6)
15
16 for i in range(5):
17     img = X_train[i]
18     axarr[i].imshow(img)
19 plt.show()

```

Dataset description <https://www.cs.toronto.edu/~kriz/cifar.html>

# Project proposal

what is my data?

March 2

- Submit your initial project proposal. →
- ~~Revise it based on our feedback~~
- Follow the guidelines posted in LMS
- Work on your project and keep us informed.
- Better to work on something that you find interesting.

