

```

package FileParser;

import List.LNode;

import java.io.File;
import java.io.FileNotFoundException;
import java.util.Scanner;

/**
 * FileToList class is a class written to parse a supplied String input path to a text file into a
 * linear link LNode list. ALL special characters (and subsequent blank words) will be removed. A word
 * can be a number, and they are case-sensitive.
 *
 * ***** Valid Input *****
 *
 * input      A String path to a text input file.
 *
 * ***** Public Operations *****
 *
 * N/A
 *
 * ***** Global Variables *****
 *
 * data      Public variable for header LNode pointer.
 *
 * @author Matt Laidman (5199807)
 * @version 1.0 (October 21, 2014)
 */
public class FileToList {

    public LNode data;                                // Public header LNode pointer

    /**
     * Public constructor to call methods to parse the input file, and clean the words.
     *
     * @param input    The input String path to the file.
     */

    public FileToList ( String input ) {

        data = noBlanks(cleanWords(getWords(getFile(input))));
    }

    /**
     * Private noBlanks function removes any LNodes with blank String keys that may be in the list after
     * removing special characters.
     *
     * @param words    The list of words.
     * @return         The list of words with no blank words.
     */

    private LNode noBlanks (LNode words) {

        LNode prev = null;
        LNode pres = words;

        while (pres != null) {
            if (pres.key.equals("") && prev == null && pres.next != null) {
                words = pres.next;                // If first item in list, move pointer
                pres = pres.next;                  // forward one
            } else if (pres.key.equals("") && prev != null && pres.next != null) {
                prev.next = pres.next;             // If internal LNode, point around
                pres = pres.next;
            } else if (pres.key.equals("") && prev != null && pres.next == null) {
                prev.next = null;                  // If Last LNode, point to null instead
            } else {
                prev = pres;
                pres = pres.next;
            }
        }

        return words;
    }
}

```

```

}

/**
 * Private cleanWords function calls the noSpecialChars function with each word in the list.
 *
 * @param words      The list of words.
 * @return           The cleaned list of words.
 */

private LNode cleanWords (LNode words) {

    LNode ptr = words;

    if(ptr == null) { // If empty list, throw exception
        throw new FileToListException("No data given in file.");
    } else {
        while (ptr != null){ // For each word, call noSpecialChars
            ptr.key = noSpecialChars(ptr.key);
            ptr = ptr.next;
        }
        return words; // Return cleaned words list
    }
}

/**
 * Private noSpecialChars function removes any special characters in the given string. A special
 * character is defined by the validChar function.
 *
 * @param word      The string to remove characters from.
 * @return           The word with no special characters.
 */

private String noSpecialChars (String word) {

    String tWord = "";

    for (char c : word.toCharArray()) { // For each char in word
        if (validChar(c)) { // If char is valid char
            tWord = tWord + c; // Append to new word
        }
    }
    return tWord;
}

/**
 * Private validChar function checks a given char against the invalids array. If the character is in
 * the array; false is returned, otherwise true is returned.
 *
 * Invalid characters are:
 *
 * . , - ( ) ;
 *
 * @param c      The character to check.
 * @return       True if character is valid, false otherwise.
 */

private boolean validChar (char c) {

    char[] invalids = {'.', ',', '-', '(', ')', ';'};

    for (char i : invalids) { // For each char in invalids array
        if (c == i) { // If c is equal to invalid char
            return false; // Return false
        }
    }
    return true; // Otherwise return true.
}

/**
 * Private getWords function uses given Scanner's next function to read in each word in the file

```

```

* to an LNode in the List.
*
* @param fileS      The Scanner of the text file.
* @return           The list of words.
*/

private LNode getWords (Scanner fileS) {

    LNode words = new LNode(fileS.next());           // Read in first word
    LNode ptr = words;

    while (fileS.hasNext()) {                         // While there are words to read in
        ptr.next = new LNode(fileS.next());           // Set next node to word
        ptr = ptr.next;
    }

    return words;
}

/**
 * Private getFile function checks if the supplied String input path is a valid text file and create:
 * a new Scanner from it.
 *
 * @param input      The input String path.
 * @return           The Scanner of the file.
 */

private Scanner getFile (String input) {

    Scanner fileS;

    try {
        fileS = new Scanner(new File(input));           // Try creating Scanner
    } catch (FileNotFoundException e) {                 // Throw exception if bad file or path
        throw new FileToListException("File not found at: \" + input + "\"");
    }

    return fileS;                                       // Return Scanner
}
}

```