Vault Implementation Foundations

Module 7: Deployment Automation

What You Will Learn



Provisioning Infrastructure

- Installation
- Configuration As Code
- Vault Automation Process
- Pipeline Summary
- Routine Automation

Deployment Automation

Vault Automation Considerations



Provisioning Infrastructure

- Terraform
- Native tools (CF, GDM, ARM, VRA/VRo)

Installation


Packer, Chef, Puppet, Ansible, SALT

Configuration as Code

- Vault TFE Provider
- Vault API

Provisioning Tasks





- Load Balancer
- Server Specifications
- Network Connectivity


Provisioning Check List (Consul)



- Load Balancer
- 3 Vault Frontend Entities (Hardware, VM, Container)
- 5 Consul Backend Entities (Hardware, VM, Container)
- Network Configuration
 - Intra-cluster Requirements
 - Inbound Traffic Configuration
 - Replication Configuration

Provisioning Tasks (Integrated Storage)





- Load Balancer
- Server Specifications
- Network Connectivity


Provisioning Check List (Integrated Storage)



- Load Balancer
- 5 Vault Entities (Hardware, VM, Container)
- Network Configuration
 - Intra-cluster Requirements
 - Inbound Traffic Configuration
 - Replication Configuration

Installation Tasks (Consul)





- Install Consul Server
- Install Consul Agent
- Install Vault

Install Check List (Consul)



- Download Vault to 3 Frontends
- Download Consul to all 8 Entities
- Install Consul on all 8 Entities
- Configure Consul
- Start Consul
- Install Vault on 3 Frontends
- Configure Vault
- Start Vault

Install Check List (Integrated Storage)



- Download Vault to 5 Servers
- Install Vault on 5 Servers
- Configure Vault
- Start Vault

Configuration Tasks - API



Once Vault is started and ready to be initialized all of Vault's capabilities are accessible via the HTTP API in addition to the CLI.

When invoking the API, authentication is still required

Important API Endpoints



- /sys/init used to initialize a new Vault.
- /sys/unseal used unseal the Vault
- /sys/license endpoint for license management
- /sys/health health checking and status information for Vault
- /sys/mounts used to manage all secret engines within Vault
- /sys/policies used to manage all policies within Vault
- /sys/replication for tuning, managing and changing replication topologies

Configuration Check List



- Initialize Vault
 - vault operator init
 - Specify encryption keys
 - Specify number of secret shares
 - Specify key qourum size
 - Specify recovery keys (shares, threshold)
- Unseal Vault Manual
 - Does NOT require authentication



Vault supports opt-in automatic unsealing via KMS:

AliCloud KMS



Vault supports opt-in automatic unsealing via KMS:

- AliCloud KMS
- Amazon KMS



Vault supports opt-in automatic unsealing via KMS:

- AliCloud KMS
- Amazon KMS
- Azure Key Vault



Vault supports opt-in automatic unsealing via KMS:

- AliCloud KMS
- Amazon KMS
- Azure Key Vault
- Google Cloud KMS




Vault supports opt-in automatic unsealing via KMS:

- AliCloud KMS
- Amazon KMS
- Azure Key Vault
- Google Cloud KMS
- Vault Transit Unseal

Key Management System Diagram






HSM Unseal



Vault stores its HSM-wrapped master key in storage, allowing for automatic unsealing



Turning On Audit



Audit devices are the components in Vault that keep a detailed log of all requests and response to Vault

Audit Devices:

- File
- Syslog
- Socket

Enabling Authentication Backend




Commonly considered the final **setup** step for a Vault Cluster this step may be considered optional.

Authentication Methods:

- LDAP
- Cloud IAM
- Github
- Okta
- MORE!

Pipeline Overview





Chapter Summary



- Identify all of the components to automate with Vault:
 - Infrastructure
 - Components
 - Configuration
 - Services
- One time events:
 - Initialization
 - Unseal
 - Enable Auth
 - Enable Audit devices
- API Capabilities

Reference links



- Vault API Documentation
- Using the API
- Auth API
- Sys API Endpoint

Vault Deployment Automation Module Complete!