- 1. True or False: It is best practice to automate the failover decision in the event of a Vault primary cluster failure.
 - a. False (can lead to split-brain scenario)
- 2. True or False: A primary Vault cluster can only replicate to either a DR secondary OR a performance secondary, but not both.
 - a. False (a primary can be connected to both)
- 3. Which replication type provides an active-active service?
 - a. Performance replication
- 4. Which type of replication includes tokens and dynamic secrets?
 - a. dr
- 5. What is the API endpoint for Vault health checking and status?
 - a. /sys/health
- 6. What is the API endpoint for unsealing vault?
 - a. /sys/unseal
- 7. True or False: It is best practice to enable multiple audit devices.
 - a. True (if no audit devices are available, Vault will stop servicing requests)
- 8. When troubleshooting hanging or failing connections to Vault, what are the first things to look at?
 - a. Expired ssl certs, exhausted file descriptor limit, depleted memory, all audit devices unavailable
- 9. If an entity has multiple linked multiple policies and one is Read-Only while another is Read/Write, what would the effective policy be?
 - a. Read/Write (policies are additive)
- 10. What policy permission overrides all other permissions?
 - a. Deny
- 11. What language are policies written in?
 - a. HCL
- 12. How could an orchestrator look up the properties of a machine token without actually having the token?
 - a. Token accessor
- 13. What are the two types of tokens?
 - a. Service and Batch

- 14. What are the main differences between a service and batch token?
 - Service tokens are created dynamically and are not replicated over a performance link. Batch tokens are manually created and are replicated over a performance link.
- 15. True or False: When a token is revoked, all static secrets retrieved are revoked as well.
 - a. False (only dynamically generated secrets are revoked)
- 16. What token property determines how long a token is valid?
 - a. TTL
- 17. What auth method can be used when no other auth types are available for an entity?
 - a. AppRole
- 18. What are the two types of supported auth methods for AWS?
 - a. EC2 and IAM
- 19. True or False: GCP auth can be used as a user auth method for G Suite users.
 - a. False (it only authenticates GCP entities)
- 20. What is the recommended method for secrets retrieval in a k8s environment?
 - a. Vault agent (init container for static secrets, sidecar for dynamic)
- 21. What is the best method to authenticate on-prem VMs?
 - a. AppRole