Research Report: A Comprehensive Material and Component Analysis of Humanoid Robots

Report Date: 2026-04-20

Executive Summary

This report provides a comprehensive scientific analysis of the global humanoid robot landscape from a material and component perspective, synthesizing technical data, market trends, and policy developments to present a holistic view of the industry as of early 2026. The analysis finds that humanoid robots are not a revolutionary leap but an evolutionary integration of mature technologies developed across other robotic domains, including industrial manipulators, mobile robots, and quadrupeds [9]. Their progress is intrinsically linked to ongoing advancements in these foundational areas.

From a material science standpoint, the industry is heavily reliant on advanced lightweight materials to balance strength, durability, and energy efficiency. Aerospace-grade aluminum and titanium alloys form the core of structural frames and high-stress joints, while carbon fiber composites are used extensively for limbs and external shells to minimize inertia [77, 78, 79]. The manufacturing of these components is increasingly shifting towards additive manufacturing and topology optimization to create complex, weight-efficient geometries [78]. A detailed component-by-component analysis reveals a sophisticated material palette tailored to specific functional requirements, from high-hardness steels in gear systems to flexible polymers in sensing skins [77].

Actuation systems have undergone a decisive industry-wide shift from complex hydraulics to all-electric solutions [5, 82]. High-torque-density frameless motors paired with high-ratio strain-wave and cycloidal gearboxes have become the standard, enabling the precise and powerful motion required for dynamic tasks [4, 81]. A key design focus is on integrated actuator modules that combine the motor, gearbox, and electronics into compact, reliable units [82]. Degrees of Freedom (DOF) typically range from 40 to 60, with divergent design philosophies emerging: some platforms, like Tesla's Optimus, prioritize manual dexterity with a high concentration of DOF in the hands, while others, like Boston Dynamics' Atlas, focus on whole-body mobility and extreme agility with a higher overall DOF count [10, 84, 85]. Robotic hands are a critical area of development, with tendon-driven and linkage-driven mechanisms being equipped with advanced tactile sensors like ReSkin to enable dexterous manipulation [88, 92].

Power systems remain a significant bottleneck. Customized high-voltage lithium-ion battery packs, primarily using NMC and LFP chemistries, offer limited operational runtimes of 2-4 hours due to the immense power demands of bipedal locomotion [93, 94, 97]. Furthermore, the harsh thermal environment and high-current discharge cycles within the robot's torso lead to rapid battery degradation, potentially reducing a battery pack's service life to as little as 3-5 months under high utilization [96, 121]. Battery swapping has emerged as the most viable near-term solution for continuous operation [93].

The "brain" of the humanoid is a hierarchical control system running on powerful onboard computers equipped with AI accelerators [108]. High-level AI models, including Vision-Language-Action (VLA) models, handle perception and task planning, while mid-level controllers manage whole-body coordination and low-level embedded systems execute precise joint movements [106]. This intelligence is fed by a dense sensor suite, including proprioceptive sensors (IMUs, encoders, force/torque sensors) for

balance and exteroceptive sensors (LiDAR, depth cameras, tactile arrays) for environmental awareness [120].

The global landscape is a four-way race between the United States (AI and innovation leader), China (manufacturing and deployment powerhouse), Japan (social and teleoperated robotics pioneer), and Europe (industrial integration and human-centric contender) [136]. China currently dominates global shipments, leveraging its vertically integrated supply chain [1, 138]. Europe's market is projected to have the fastest growth rate, driven by industrial adoption in its automotive and logistics sectors to combat severe labor shortages [58, 60]. The EU's proactive regulatory framework, centered on the AI Act and Machinery Regulation, prioritizes safety and human oversight, which may foster public trust and accelerate adoption in sensitive sectors [51, 128, 137]. However, Europe faces a strategic vulnerability due to its heavy reliance on the Asian supply chain for critical components like actuators and semiconductors [135, 139].

The 3-5 year outlook indicates a transition from prototypes to targeted commercial deployment [75]. Key developments will include AI-driven improvements in task learning, the integration of more sophisticated multimodal tactile sensing, and a strong industry push to reduce costs and improve reliability [118]. While the vision of a general-purpose robot persists, near-term success will be defined by specialized roles in logistics, manufacturing, and healthcare [127]. The economic viability of humanoid robots is improving, but significant constraints related to battery life, total cost of ownership, and real-world robustness must be overcome for widespread adoption [75, 96, 141].

1. Introduction

Humanoid robots, complex machines engineered to emulate human form and function, stand at a critical inflection point, transitioning from research novelties to commercially viable platforms poised to reshape industries [2, 10, 75]. Their bipedal, bi-manual architecture is a deliberate engineering choice, offering the unique capability to operate within environments built for people, utilize human-scale tools, and perform tasks alongside human workers without requiring extensive and costly infrastructure modifications [8]. The recent and rapid acceleration in humanoid development, fueled by converging breakthroughs in artificial intelligence, material science, actuator technology, and mechatronics, necessitates a deep and detailed examination of the underlying technologies that constitute these sophisticated systems [109].

This report provides a comprehensive scientific analysis of humanoid robots from a material and component perspective. It aims to deconstruct the anatomy of a modern humanoid, detailing the core subsystems that enable its human-like mobility, dexterity, and autonomous behavior. We will explore the structural composition, the science behind material selection, the intricacies of advanced actuation, the dense arrays of multi-modal sensing, and the persistent challenges of power management. This technical deep dive includes a specific focus on the evolution of robotic hands, a crucial frontier where dexterity and sensory feedback converge to unlock the potential for fine manipulation.

To provide a clear technological context, the report will first situate humanoid robots within the broader robotics landscape, analyzing their evolutionary lineage from conventional industrial robots, single- and dual-arm manipulators, mobile manipulators, and quadrupeds. This comparative analysis underscores how humanoids are an integration of mature technologies developed across these diverse domains. Furthermore, the report incorporates a worldwide manufacturer and ecosystem overview with a particular focus on the European Union, assessing regional market dynamics, investment relevance, key adoption sectors, and the distinct, human-centric policy framework that governs the deployment of AI and robotics [51, 58]. The analysis culminates in a forward-looking assessment of the next three

to five years, projecting the technological trajectory, market evolution, and the key constraints that will shape the rollout of these transformative machines.

2. Technological Lineage: The Evolution from Industrial to Humanoid Robotics

Humanoid robots did not emerge from a technological vacuum; they are the sophisticated culmination of decades of research and development across the entire spectrum of robotics. They represent a convergence platform, integrating foundational subsystems that were pioneered, tested, and matured in other, more specialized robotic classes [9]. Understanding this technological lineage is essential for any substantive analysis of humanoid materials and components, as it reveals that their development is evolutionary, not revolutionary. This context clarifies why deep research into non-humanoid platforms is a prerequisite for a comprehensive study of humanoid technology.

The most basic building block is the **conventional industrial robot**, typically a single-armed manipulator fixed to a factory floor [11, 41]. These systems are the workhorses of modern manufacturing, built for extreme rigidity, payload capacity, and repeatability [45, 46]. Often constructed from heavy materials like steel and cast iron, their primary contribution to the humanoid lineage is the perfection of core manipulation components [41]. The high-precision servo motors, robust gearboxes, and a vast array of end-effectors (grippers, welders, etc.) that enable industrial automation are the direct technological ancestors of the components found in a humanoid's arms and torso [47]. However, operating in highly structured environments, they lack the need for dynamic balancing, mobile navigation, or advanced environmental perception.

A key evolutionary step toward the humanoid form is the **dual-arm manipulator** [12, 14]. The introduction of a second arm enables far more complex, coordinated tasks that a single arm cannot perform, such as stabilizing a workpiece with one hand while assembling it with the other [12]. This development necessitated a significant leap in control systems to manage bimanual coordination, avoid self-collision, and execute cooperative motions [15]. These dual-arm systems are direct precursors to the manipulation capabilities of humanoids, sharing core components like electric actuators, joints, and sensors, as well as structural materials like aluminum and carbon fiber [13]. The complex control challenges solved in dual-arm robotics provided a crucial foundation for the even more demanding task of humanoid whole-body control.

The next major advancement was the **mobile manipulator**, or "mobot," which consists of a robotic arm mounted on a mobile base, typically wheeled or tracked [21]. These systems bridge the gap between fixed industrial robots and fully ambulatory humanoids by combining manipulation with locomotion [23]. Mobots introduced the critical challenge of navigating semi-structured or unstructured environments [22]. They rely heavily on the same sensory suites used in modern humanoids, including LiDAR for long-range mapping and 3D cameras for close-quarters navigation and object detection [23, 27]. Their control architectures must integrate mobile base navigation with manipulator control, a prerequisite for enabling a humanoid to perform tasks while in motion [26]. Furthermore, as these robots began to operate in closer proximity to humans, the prioritization of soft, lightweight materials for safety became a more prominent design consideration [24].

Finally, **quadruped robots**, or four-legged "robot dogs," represent a mastery of dynamic mobility over complex and uneven terrain [32]. While not human-like in form, they tackle the same fundamental engineering problem of legged locomotion. To manage ground impacts and store kinetic energy, research into quadrupedal robotics pioneered the use of specialized actuators like Series Elastic Actuators (SEAs), which incorporate a compliant spring into the joint mechanism [33, 83]. Their development has driven innovation in lightweight and robust materials, such as carbon fiber, capable of withstand-

ing the repeated shocks of dynamic movement [36]. The control algorithms for dynamic balance, which rely heavily on IMU feedback and foot-contact sensors to adapt to terrain, have provided invaluable insights directly informing the development of bipedal walking algorithms [38]. Innovations in their power systems, such as structural batteries that serve as both a power source and a load-bearing component, are also highly relevant to the design of compact and efficient humanoids [31].

In synthesizing these lineages, it becomes clear that to study humanoid robots in isolation is to ignore the rich history of proven solutions and persistent challenges that define their components. A thorough material and component analysis requires understanding the de-risked and matured systems—actuators from industrial arms, sensor stacks from mobots, and locomotion principles from quadrupeds—that allow humanoid research to focus on its unique and formidable challenge: integrating these disparate technologies into a stable, functional, and intelligent bipedal system.

3. Humanoid Anatomy: Structural Design and Material Science

The physical form and capabilities of a humanoid robot are fundamentally defined by its structural architecture and the materials from which it is constructed. The primary engineering challenge is a delicate and continuous trade-off: creating a skeletal frame and body that is strong enough to withstand high dynamic loads from walking and lifting, yet lightweight enough to maximize energy efficiency, agility, and operational runtime [77, 78]. Modern full-size humanoids are engineered to achieve a balance, typically weighing between 50 and 70 kilograms, and must be able to support their own mass in addition to the significant payload of motors, batteries, and electronics [9, 78]. The material science behind this balancing act is a critical determinant of a robot’s overall performance.

3.1 Advanced Design and Manufacturing Methodologies

To achieve the optimal balance of strength and weight, humanoid engineers employ sophisticated design and manufacturing techniques that push the boundaries of material science [78]. One of the most powerful tools is **topology optimization**, an algorithmic design approach that uses computer simulations to determine the most efficient distribution of material within a component to meet specific load requirements [78]. This process effectively carves away any non-essential mass, resulting in organic, bone-like structures that provide maximum strength for minimum weight. This method ensures that every gram of material serves a structural purpose, which is critical in a system where weight directly impacts energy consumption.

Additive manufacturing, more commonly known as 3D printing, has become an indispensable technology in humanoid robot development [76, 78]. It allows engineers to fabricate the complex, highly optimized geometries produced by topology optimization, which are often impossible to create using traditional subtractive manufacturing methods like milling or lathing. 3D printing is particularly transformative for working with advanced materials like titanium alloys and carbon fiber-reinforced thermoplastics [76]. It enables the creation of monolithic, integrated parts that reduce assembly complexity and eliminate potential points of failure. This method also facilitates rapid prototyping, allowing for faster design iteration and experimentation.

Furthermore, designers are increasingly using **hybrid materials** to create components that leverage the distinct advantages of multiple substances [78]. This can involve embedding high-strength titanium reinforcements within a lightweight carbon fiber composite structure or co-molding a rigid polymer frame with a soft, impact-absorbing outer skin. By strategically combining materials, engineers can create multifunctional components that are simultaneously strong, lightweight, and safe for human interaction, further optimizing the overall system design.

3.2 Material Selection for Performance and Weight

The choice of materials for a humanoid robot's frame, limbs, and casing is a meticulous process, with each material selected for its specific properties and application within the robotic anatomy [77]. This diverse palette of advanced materials is essential for achieving the required performance characteristics. **Aluminum alloys**, particularly aerospace grades like 6061 and 7075, serve as a foundational material for many humanoid robots [77, 78]. They are widely used for chassis components, structural frames, and link arms due to their excellent strength-to-weight ratio, high corrosion resistance, and relative ease of machining. This combination of properties, along with their cost-effectiveness compared to more exotic materials, makes them a practical choice for a significant portion of the robot's structure.

For components subjected to the highest levels of stress and fatigue, such as the critical joints in the hips, knees, and ankles, as well as elements of the spine support frame, **titanium alloys** are the material of choice [76, 77]. Alloys like Ti-6Al-4V (Grade 5) offer a superior strength-to-weight ratio and outstanding fatigue resistance, making them ideal for load-bearing applications. The use of titanium can lead to significant weight reductions; for example, using a titanium alloy for gear sets can decrease component weight by 40% compared to traditional steel while tripling fatigue life [76]. While historically limited by high cost, the increasing maturity of additive manufacturing techniques is making the production of complex titanium parts more economically viable, fueling their adoption [76]. The growing importance of this material is reflected in market projections, with the global market for titanium alloy in humanoid robots alone expected to reach approximately 18.7 billion yuan by 2030 [76].

Carbon fiber composites are renowned for their exceptional stiffness-to-weight ratio, making them the preferred material for components where minimizing inertia is paramount for dynamic performance [77, 79]. These composites are frequently used for the external panels, shells, and limbs of high-performance robots like Boston Dynamics' Atlas [79]. By strategically using carbon fiber, designers can achieve weight savings of over 40% compared to aluminum for similar parts, which translates directly into enhanced agility, higher speed, and improved energy efficiency [79].

While lightweighting is a primary goal, durability and wear resistance are also critical. For this reason, **steel alloys**, particularly stainless steels, are selectively used for high-wear components such as shafts, pins, fasteners, and localized structural reinforcements where hardness and durability are more important than weight [77]. Finally, a variety of **engineering polymers and plastics** are employed for non-load-bearing parts. Lightweight thermoplastics like PEEK (Polyether Ether Ketone), polycarbonate, and ABS are used for body covers, sensor housings, and joint seals to reduce weight and cost [77, 79]. PEEK, in particular, has been instrumental in the weight reduction efforts for robots like the Tesla Optimus Gen 2 [79]. Soft-touch materials like silicone are also widely used for robotic skins and soft interfaces to enable safer physical interaction with humans and to provide a gripping surface on end-effectors [77].

4. Actuation and Drivetrains: The Robotic Musculoskeletal System

If the frame and shell constitute the skeleton of a humanoid robot, the actuation and drivetrain system serves as its musculoskeletal system, converting stored electrical energy into the precise mechanical motion that animates every joint. This system is responsible for everything from the powerful strides of locomotion to the delicate articulation of a fingertip. The design of these systems represents a continuous engineering compromise between power output, weight, energy efficiency, and control fidelity.

Across the industry, there is a clear and decisive trend away from older hydraulic systems towards sophisticated, all-electric solutions that are lighter, quieter, and more efficient [5, 82].

4.1 The Industry-Wide Shift to Electric Actuation

Early dynamic robots, most famously the hydraulic versions of Boston Dynamics' Atlas, relied on hydraulic actuation to achieve immense power and dynamic response [5]. However, hydraulic systems are notoriously complex, heavy, noisy, and susceptible to fluid leaks, making them impractical for commercial deployment in human-centric environments. Consequently, the entire industry has pivoted to **all-electric actuation** as the dominant architecture [82]. Prominent modern humanoids, including Tesla's Optimus, Figure's 01, Apptronik's APOLLO, and the new generation of Atlas, are all built upon electric motors paired with high-ratio gearboxes [5]. These systems offer superior energy efficiency (often over 80% before gearbox losses), quieter operation, more precise and repeatable control, and greater reliability, which are all critical attributes for commercially viable products [8]. For the major joints providing articulation, such as shoulders, elbows, hips, and knees, **rotary actuators** are the standard, providing direct torque output for rotational movement [82]. **Linear actuators**, which provide pushing and pulling motion, are typically reserved for smaller, secondary movements where their compact form factor is advantageous, such as within the complex mechanics of a robotic hand [82].

4.2 Electric Motors, Reducers, and Gearboxes

In a robotic joint, the electric motor rarely works alone. To generate the immense force needed to lift heavy loads or propel the robot's body, relatively small and lightweight motors are paired with a **reducer or gearbox** [81]. These mechanical transmissions are essential for amplifying motor torque, typically by trading high speed for low-speed, high-force output at ratios often exceeding 100:1 [4]. The quality and design of the gearbox are as critical as the motor itself, defining the joint's precision, strength, and durability. The industry relies on several types of high-performance reducers, each with specific advantages.

Strain-wave gearboxes, often known by the trade name Harmonic Drive, are a dominant technology in modern robotics [4]. They are prized for their ability to provide very high gear ratios in a compact form factor with near-zero backlash (the "slop" or play in a gear system) [4]. This extreme precision is critical for joints involved in fine manipulation and stable balancing, such as those in the ankles and wrists, where even minuscule unwanted movements can compromise performance.

For joints that experience high shock loads, such as those in the legs during walking or running, **cycloidal gearboxes** are often favored [81]. These reducers offer exceptional torque density and a very high tolerance for shock, making them more robust and durable in demanding, high-impact applications. Finally, **planetary gear systems**, valued for their compactness, high efficiency, and ability to handle significant torque loads, are also being increasingly adapted for use in robotic joints, particularly in leg mechanisms and waist rotation [81]. The choice of gearbox technology for each joint is a critical design decision that directly impacts the robot's overall kinematic performance.

4.3 Degrees of Freedom (DOF): Quantifying Articulation and Design Philosophy

A robot's **Degrees of Freedom (DOF)** refers to the number of independent axes of motion it possesses [10]. This metric quantifies the robot's articulation, and the total number and distribution of DOF across the humanoid's body dictate its range of motion, agility, and capacity for performing complex tasks. Modern humanoid robots typically feature between 40 and 60 DOF, with this articulation strategically distributed to prioritize specific capabilities based on the robot's intended application [10, 86]. A significant portion of a humanoid's DOF is consistently concentrated in its arms and hands for

manipulation, and in its legs, torso, and neck for stable locomotion, balancing, and environmental awareness [86].

A comparative analysis of two of the industry's most prominent platforms—Boston dynamics' Atlas and Tesla's Optimus—reveals how differing design philosophies are directly reflected in their DOF counts and distribution. The new, all-electric **Boston Dynamics Atlas** is engineered for extreme agility, strength, and unparalleled mobility [84]. It features an impressive 56 DOF, a significant increase from its hydraulic predecessor's ~28 DOF [84, 86]. A key feature of the new Atlas is its use of fully rotational joints, granting it an extraordinary range of motion that allows it to contort and maneuver in ways that exceed human flexibility [85]. This high level of articulation, combined with its immensely powerful custom electric actuators, positions Atlas as a platform for heavy industrial tasks and work in hazardous environments, prioritizing whole-body mobility and strength [85].

In contrast, the **Tesla Optimus** is designed with mass production, cost-effectiveness, and general-purpose work in mind [85]. The Optimus platform has approximately 40 structural actuators/DOF [86]. Its most notable feature is the heavy concentration of articulation in its hands, which each possess 11 DOF [86]. This design choice underscores a strategic focus on fine motor control and manual dexterity, enabling the robot to perform delicate tasks such as handling fragile objects like eggs [85]. The overall design prioritizes energy efficiency, reliability, and the fine manipulation skills needed for tasks in structured human environments like factory production lines and warehouses [85]. This divergence illustrates two distinct paths in humanoid development: one pursuing hyper-agile, high-performance systems for specialized, physically demanding applications (Atlas), and the other aiming for cost-effective, scalable platforms with high manual dexterity for general-purpose tasks (Optimus) [84, 85].

4.4 Key Trends in Actuator Design

The design of actuators for humanoid robots is evolving rapidly, driven by the relentless pursuit of higher performance in a smaller and lighter package. One of the most significant trends is the move toward **integrated actuator modules** [80]. Instead of assembling a joint from a separate motor, gearbox, encoder, and motor driver, manufacturers are developing compact, self-contained units that integrate all of these components into a single package. This approach reduces complexity, minimizes cabling, saves valuable space within the robot's frame, and ultimately improves overall reliability and performance by ensuring all components are perfectly matched and optimized [82].

The holy grail of actuator design is maximizing **torque density**, which is the ratio of the torque an actuator can produce relative to its own weight [82]. Engineers are constantly striving to achieve a specific torque exceeding 10 Nm/kg for rotary actuators. This metric is critical because of the "mass penalty spiral" inherent in robotic design: heavier components require more powerful (and thus heavier) motors to move them, which in turn require larger (and heavier) batteries to power them, creating a cascade that adds significant weight and reduces energy efficiency. Every gram saved in an actuator directly contributes to a lighter, more agile, and longer-running robot [82].

A third critical trend, particularly for legged robots, is designing for **compliance and backdrivability** [82]. Backdrivability is an actuator's inherent ability to "give way" or be moved by an external force, in contrast to a stiff actuator that resists all external motion [82]. This compliance is essential for absorbing the thousands of high-force impacts that occur at the feet and knee joints during walking and running. An actuator that is too stiff would transfer 100% of these shock loads directly to the delicate teeth of its internal gearbox, leading to catastrophic and premature failure [82]. This has driven research into two main approaches. The first is **Quasi-Direct Drive (QDD)**, which uses motors with very high intrinsic torque paired with low gear ratios (e.g., 6:1 to 30:1 instead of 100:1) [82]. This reduces the reflected inertia from the motor, making the joint feel much more compliant and better able to absorb impacts. The second approach is the **Series Elastic Actuator (SEA)**, used by robots like

Agility's Digit [83]. SEAs intentionally incorporate a physical spring in series with the motor and gearbox [83]. This mechanical elasticity provides excellent shock absorption and allows the system to store and release energy during locomotion, similar to how tendons work in biological systems.

5. Robotic Hands: The Nexus of Sensing and Dexterity

The human hand is a biological marvel, capable of exerting immense force to grip a heavy tool and then executing movements of exquisite delicacy to manipulate a tiny object. Replicating this combination of strength and dexterity is one of the greatest challenges in robotics and is widely considered a critical technology for unlocking the full potential of humanoid robots [88]. The ability to grasp and use human tools is fundamental to their value proposition. As such, the development of robotic hands represents a major focus of research and engineering, combining complex mechanical design with advanced materials and sophisticated sensory feedback.

5.1 Actuation Mechanisms in Hand Design

Several distinct mechanical approaches are used to actuate the multiple joints in a robotic hand, each presenting a different set of trade-offs between compactness, strength, complexity, and cost. One of the most bio-inspired designs is the **tendon-driven** mechanism. In this approach, the actuators (motors) are placed remotely, typically in the forearm, to reduce the weight and inertia of the hand itself. A complex series of strong, flexible tendons are then routed from these motors through the wrist and palm to the finger joints. Pulling on these tendons causes the joints to flex, closely mimicking the way muscles and tendons operate in a human hand [90]. This allows for a very lightweight and compact hand design. Prominent examples of this approach include the Shadow Dexterous Hand and the hand developed for NASA's Robonaut 2 [90]. The primary drawbacks of tendon-driven systems are their mechanical complexity, which can make assembly and maintenance difficult, and the challenge of precisely controlling the force applied at the fingertips due to tendon friction and stretching.

An alternative is the **linkage-driven** approach, which uses a network of rigid links to transmit power from actuators to the joints [88]. This design offers robust, bidirectional control (both opening and closing) and is generally easier to manufacture and maintain than a complex tendon system. The ILDA hand is a prime example of this design philosophy, successfully integrating all 15 of its actuators and sensors entirely within the hand's structure [88]. This high level of integration allows it to achieve remarkable dexterity and a strong fingertip force of 34N, all within a compact, self-contained package [88].

A third method is the **motor-direct-driven** design, which seeks to place very small motors directly at or near the joints they control. This approach can offer high efficiency and greater design flexibility, as it eliminates the need for complex tendons or linkages. However, its performance is highly dependent on the availability of powerful, miniaturized motors and gearboxes that are small enough to fit within the confines of a finger or palm. This can significantly increase the cost, weight, and inertia of the hand itself, potentially compromising its dynamic performance [88].

5.2 The Quest for Affordable Dexterity and Advanced Sensing

Historically, the high cost, complexity, and fragility of dexterous robotic hands have been major barriers to their widespread adoption. A multi-DOF, sensorized hand could easily cost tens or even hundreds of thousands of dollars. A key trend in modern hand development is therefore the focused pursuit of robust, modular, and affordable designs suitable for real-world use. Additive manufacturing is revolutionizing this effort, enabling researchers and companies to rapidly prototype and fabricate complex hand structures from durable polymers and other low-cost materials [89, 91]. This has dramatically reduced development time and manufacturing costs, with some advanced, multi-DOF research

hands now being fabricated for under $350 [89]. By leveraging 3D-printed components, off-the-shelf “smart” actuators, and innovative, low-cost sensors, researchers are creating hands like the D’Manus that are not only highly capable but also inexpensive and easy to repair, a crucial step toward their viable deployment on commercial robots [89].

Modern robotic hands are not merely mechanical manipulators; they are sophisticated sensory organs [92]. The ability to “feel” is crucial for dexterous grasping and manipulation. To this end, advanced hands are being equipped with large-area **tactile sensors** across their palms and fingers [118]. One of the most promising technologies is the **ReSkin** sensor, which consists of a thin elastomer layer embedded with magnetic microparticles [92]. When the skin deforms upon contact with an object, it changes the magnetic field, which can be measured by underlying magnetometers. This provides the robot with a rich, detailed sense of touch, allowing it to measure contact forces, detect object slippage, and infer texture [92]. Other systems integrate miniaturized six-axis force/torque sensors directly into the fingertips to provide precise feedback for controlling grip strength [88, 123].

In addition to feeling the external world, the robot must have a sense of its own posture, known as **proprioceptive sensing** [117]. To control the hand effectively, the robot’s software must know the precise position of every joint and the tension in every tendon. This is typically achieved through integrated encoders in the motors and specialized strain sensors [117]. The Fil3D-Hand, for example, is a 3D-printed hand that integrates 14 nanocomposite filament strain sensors directly into its structure [91]. These sensors provide highly linear feedback that corresponds directly to the bending angle of the finger joints, allowing the control system to have real-time, accurate information about the hand’s posture without the need for additional, bulky encoders [91]. This fusion of advanced mechanical design, affordable manufacturing, and multi-modal sensing is paving the way for a new generation of robotic hands that can finally begin to approach the versatility of their human counterparts.

6. Power Systems: Batteries, Runtime, and Lifetime

Powering a dynamic, bipedal robot is a profound engineering challenge [103]. The high and fluctuating energy consumption required for constant balancing, locomotion, manipulation, and onboard computation makes the battery system a primary limiting factor for a humanoid’s performance, weight, and commercial viability [93]. The battery pack’s capacity, chemistry, and longevity directly dictate the robot’s operational endurance and its total cost of ownership. Consequently, significant research and development efforts are focused on improving every aspect of the power system, from cell chemistry to thermal management.

6.1 Battery Technology and Specifications

Modern commercial humanoids almost exclusively rely on customized, high-voltage battery packs, which are typically housed in the torso to maintain a stable center of gravity and provide protection [93, 102]. These systems generally operate at voltages between 48V and 72V [93]. Using a higher voltage system is more efficient for the drivetrain, as it allows for the delivery of the same amount of power at a lower current, which in turn reduces resistive energy losses (I^2R losses) in the wiring and motor windings. The battery capacities for current-generation humanoids commonly range from 2 to 4 kilowatt-hours (kWh) [93]. For example, both the Tesla Optimus and the Figure 01 utilize a 2.3 kWh battery pack [93].

The choice of battery chemistry involves a critical trade-off between energy density (runtime per unit of weight), safety, cycle life, and cost [94]. The two dominant lithium-based chemistries are **Lithium Nickel Manganese Cobalt Oxide (NMC)** and **Lithium Iron Phosphate (LFP)**. NMC is widely used for its high energy density, which typically ranges from 250–300 Wh/kg [93]. This allows for the maximum possible runtime for a given weight, which is a major advantage in a weight-sensitive system

like a humanoid. However, NMC cells are more susceptible to thermal runaway if damaged or overheated and tend to have a shorter cycle life, especially when subjected to fast charging and high temperatures [96].

In contrast, LFP chemistry offers superior safety and thermal stability, making it far less prone to fire [94]. Its primary advantage is a much longer cycle life, often rated for 3,000 to over 6,000 charge-discharge cycles before significant degradation [94]. The main drawback of LFP is its lower energy density, typically between 100–160 Wh/kg [93]. This imposes a significant weight penalty; for the same energy capacity, an LFP pack can be 20–30% heavier than an equivalent NMC pack. This additional mass increases the load on the robot's actuators, partially offsetting the longevity benefits. Looking to the future, **solid-state batteries** represent a key area of development [95, 98]. This emerging technology promises to eliminate flammable liquid electrolytes, leading to enhanced safety while also offering projected energy densities of 350–450 Wh/kg and a cycle life potentially exceeding 2,000 cycles [95]. Commercial deployment of solid-state batteries in humanoid robots is anticipated around the 2029-2030 timeframe [95].

6.2 The Operational Endurance and Lifetime Challenge

The operational runtime of current-generation humanoids is a major bottleneck for commercial adoption, typically ranging from a mere 1.5 to 4 hours on a single charge [93, 97]. For example, Apptronik's Apollo and 1X's NEO cite a 4-hour runtime per pack, while the Unitree G1 lists approximately 2 hours [93]. This limited endurance is a direct consequence of the exceptionally high power demands of a bipedal system. Continuous dynamic tasks, such as walking, lifting heavy objects, or recovering balance, create intense peak power demands that can surge to 2,500-3,000 watts [96]. While regenerative braking—recovering energy during deceleration or "braking" movements—can help, its practical gains in bipedal robots are often limited to 10-15%, far below the theoretical maximum of 30%, because the robot's movements are typically short, corrective micro-bursts rather than long, smooth decelerations [96]. Consequently, achieving a full eight-hour work shift on a single charge remains a distant goal, with some analyses suggesting it could take up to a decade to achieve [96, 97].

Perhaps the most significant and often overlooked challenge in humanoid power systems is the stark discrepancy between the lab-rated cycle life of a battery and its actual service life in deployment [96]. While an NMC battery might be rated for 800-1,500 cycles under ideal, controlled laboratory conditions (e.g., room temperature, moderate charge/discharge rates), its real-world cycle life in a humanoid robot can plummet to as low as 200-500 effective cycles [96, 121]. This rapid degradation is caused by a confluence of factors inherent to humanoid operation. The battery pack is typically enclosed within the robot's torso, surrounded by heat-generating components like high-power motors and compute hardware. With very limited space for active cooling, the internal cell temperatures can spike to 80–100°C during peak operational loads [96]. This extreme heat dramatically accelerates parasitic chemical reactions within the battery cells, primarily the growth of the Solid Electrolyte Interphase (SEI) layer, which consumes active lithium and permanently reduces the battery's capacity [96]. Furthermore, the operational load profile, characterized by constant high-current (high C-rate) discharge bursts for balancing and movement, combined with the commercial need for fast-charging cycles, places immense stress on the battery's chemistry [96]. This can lead to another degradation mechanism called lithium plating on the anode, which further contributes to permanent capacity loss. In economic terms, this rapid degradation means a costly battery pack may need to be replaced as frequently as every 3-5 months in a high-utilization, two-shift industrial scenario, significantly increasing the robot's total cost of ownership and impacting its economic viability [96, 121].

6.3 Strategies for Continuous Operation and Longevity

To mitigate the severe limitations imposed by battery endurance and degradation, developers are implementing several key strategies. The most practical and widely adopted near-term solution for achieving continuous or near-continuous operation is **battery swapping** [93, 96]. Both manual and automated hot-swappable battery systems are being developed, which allow a robot to exchange a depleted battery pack for a fully charged one in a matter of minutes. This drastically reduces downtime compared to a multi-hour charging cycle. UBTECH's Walker S2, for example, has demonstrated the ability to perform an autonomous battery swap in under three minutes without needing to shut down its systems, enabling seamless operational continuity [93, 96].

Given that heat is a primary driver of battery degradation, effective **thermal management** is a non-negotiable aspect of modern humanoid design [93, 101]. This involves a combination of passive and active cooling solutions. Passive solutions can include using the robot's metal structural housing as a large heat sink to help dissipate thermal energy. However, for high-performance systems, active cooling is essential. This typically involves integrated fans and carefully designed air ducts that provide forced-air cooling directly to the battery pack, as well as to other critical heat-generating components like the main computer and motor drivers [101].

Overseeing the entire power system is a sophisticated **Battery Management System (BMS)** [93, 101]. The BMS is an intelligent electronic controller that continuously monitors the state of every cell in the battery pack, tracking key parameters like voltage, current, and temperature. It performs crucial functions to prolong the battery's life, such as cell balancing, which ensures all cells are charged and discharged evenly to prevent premature failure of individual cells [101]. The BMS also enforces strict safety limits to prevent dangerous conditions like overcharge, over-discharge, and thermal runaway [102]. It communicates with the robot's main controller via a robust communication protocol like CAN-bus, providing real-time data on the battery's State of Charge (SoC) and, importantly, its State of Health (SoH), allowing the robot to predict and manage its own power needs and maintenance schedule [100].

7. Controllers, Compute, and Sensors: The Robotic Nervous System

The ability of a humanoid robot to perceive its environment, make intelligent decisions, and execute complex, coordinated movements stems from its sophisticated control and computation architecture, which functions as its central nervous system [107]. This system is typically organized in a hierarchical structure that processes a massive stream of sensory input, plans actions, and distributes precise commands to dozens of actuators working in concert [2, 108]. This intricate interplay between sensing, computation, and control is what enables autonomy and imbues the robot with its capacity for functional behavior.

7.1 Hierarchical Control Architecture

Inspired by the organization of the human nervous system, the control architecture of a humanoid robot is layered to efficiently manage tasks of varying complexity and required response time [2, 113, 116]. At the highest level is the **AI Control or "Brain,"** which runs on powerful onboard computers, often equipped with high-performance CPUs, GPUs, and other specialized AI accelerators [2, 108]. This cognitive layer is responsible for perception, strategic planning, and decision-making [106]. It is here that advanced AI models interpret the data streams from cameras and microphones, understand natural language commands from humans (e.g., "go to the kitchen and get the blue cup from the table"), and formulate a high-level plan to achieve the goal [106].

This strategic plan is then passed down to the **Mid-Level Motion Controller**, which can be analogized to the human cerebellum. This layer's primary task is to translate abstract, high-level commands into smooth, stable, whole-body movements. It runs computationally intensive algorithms like Whole-Body Control (WBC), which mathematically optimizes the motion of all the robot's limbs simultaneously to maintain balance while performing a task, and Model Predictive Control (MPC), which continuously predicts the robot's future state over a short time horizon to optimize gait, stability, and foot placement during locomotion [110, 113].

Finally, at the lowest level is the **Embedded Control** layer. This consists of distributed microcontrollers located at or near each individual joint [105, 116]. These low-level controllers act as the robot's reflexes, running very high-frequency feedback loops (often at 1 kHz or faster) to execute the final motion commands [105]. They precisely control the position, speed, and torque of each motor based on the targets received from the mid-level controller and feedback from local joint sensors. To manage the complex communication and data flow between these different layers, developers commonly use a middleware framework, with the **Robot Operating System (ROS)** being the de facto industry standard for integrating perception, planning, and control subsystems [2].

7.2 Onboard Compute, Power Electronics, and AI

The "brain" of a modern humanoid is a powerful edge AI computing platform [108]. The onboard computer is responsible for running the entire software stack, from sensor processing to AI inference. The intelligence and adaptability of the robot are driven by a suite of sophisticated AI models. **Convolutional Neural Networks (CNNs)** and, more recently, **Vision Transformers (ViTs)** are used to process the raw pixel data from cameras and other sensors to perform essential perception tasks like object recognition, scene segmentation, and human pose estimation [106].

A transformative development in robot cognition is the rise of **Vision-Language-Action (VLA)** models [106]. These are large, multi-modal models that merge visual input, linguistic commands, and the robot's own internal state (e.g., joint positions, battery level) to generate appropriate actions. This allows the robot to respond to complex, context-aware instructions and exhibit a more general understanding of its tasks. The skills themselves are often developed using advanced machine learning techniques, particularly **Reinforcement Learning (RL)** and **imitation learning** [2, 106]. In this paradigm, robots can learn optimal policies for complex skills like walking, grasping, and manipulation by running millions of trial-and-error attempts in high-fidelity physics-based simulators (such as NVIDIA Isaac Sim or MuJoCo) [2, 112]. Once a skill is perfected in simulation, the learned policy is transferred to the physical robot for real-world execution, a process known as "sim-to-real" transfer [2].

Bridging the gap between the low-voltage signals of the control computer and the high-power demands of the actuators are the **motor drivers**, a critical class of power electronics [105, 107]. These modules convert the logical control signals into the high-power, precisely modulated current needed to drive the brushless DC (BLDC) motors in each joint. Advanced servo drives with high-precision current sensing capabilities are essential for achieving the accurate force and torque control needed for stable locomotion and delicate manipulation [107]. A key technological trend in this area is the adoption of **Gallium Nitride (GaN)**-based power stages [105]. GaN technology allows for much higher switching frequencies and greater power efficiency compared to traditional silicon-based electronics, enabling designers to create motor drivers that are over 50% smaller and more power-dense, a critical advantage in the space- and weight-constrained environment of a humanoid robot [105].

7.3 Sensing and Perception: Awareness of Self and World

A humanoid robot's ability to operate safely and effectively is entirely dependent on its capacity to perceive both its own internal state and the surrounding external environment [119]. This awareness

is achieved through a dense and diverse suite of onboard sensors, which can be broadly categorized into proprioceptive and exteroceptive systems [120].

Proprioceptive sensors provide the robot with crucial information about its own body, posture, and movement, a sense of "self" that is essential for balance and coordinated motion [114, 117]. The most critical proprioceptive sensor is the **Inertial Measurement Unit (IMU)** [116]. Typically located in the robot's torso, the IMU combines accelerometers and gyroscopes to function as the robot's inner ear, constantly measuring its orientation, angular velocity, and linear acceleration [114]. This data provides the core feedback for the dynamic control loops that keep the robot balanced while standing and walking. At every joint, **joint encoders** are integrated to precisely measure the angle and rotational speed of each motor [117]. This data is fundamental for low-level motion control and for the robot's higher-level software to know its exact body posture at all times. For physical interaction, **Force/Torque (F/T) sensors** are strategically placed in critical locations like the wrists and ankles, and sometimes even within the joints themselves [123]. These sensors measure the forces and torques resulting from contact with the environment, enabling the robot to gauge its grip strength, detect the ground reaction forces necessary for stable walking, and perform delicate manipulation tasks without applying excessive force [123]. Some robots also feature arrays of low-profile load cells in the soles of their feet to precisely measure pressure distribution for more sophisticated balance assessment [123].

Exteroceptive sensors gather information about the external world, allowing the robot to navigate, recognize objects, and interact safely with humans and its surroundings [120]. Vision is the primary modality for environmental perception. Humanoids are typically equipped with a head containing multiple cameras, including standard RGB cameras for object recognition and color vision, and **depth sensors** (such as LiDAR or stereo vision cameras) that generate a 3D point cloud of the environment [2, 116]. This 3D data is essential for mapping, navigation, and real-time obstacle avoidance. As discussed previously, **tactile sensors** provide a sense of touch and are a key enabling technology for dexterous manipulation [118]. Advanced tactile arrays on the fingertips and palms allow the robot to detect pressure, texture, and object slippage. Finally, arrays of **microphones** function as the robot's ears, enabling it to detect and localize sounds in its environment, as well as understand spoken commands from humans through speech recognition software [115].

No single sensor can provide a complete and perfect picture of the world. Therefore, a critical task for the robot's onboard computer is **sensor fusion** [114]. Using mathematical techniques like Kalman filters and, more recently, advanced deep learning models, the control system intelligently combines the often noisy, partial, and sometimes conflicting data from this multitude of sensors [116, 122]. By fusing visual data from cameras with motion data from the IMU, for example, the system creates a single, robust, and unified model of its own state and the state of the world around it, enabling more reliable and intelligent behavior.

8. Worldwide Manufacturer and Ecosystem Overview

The global humanoid robot market is rapidly evolving into a dynamic and highly competitive four-way race, with major innovation and industrial hubs consolidating in the United States, China, Japan, and Europe [136]. Each region possesses distinct strategic strengths, key corporate champions, and different approaches to development and deployment. The overall market is projected to experience explosive growth, expanding from an estimated USD 2.92 billion in 2025 to over USD 15.26 billion by 2030, reflecting the immense commercial interest and investment pouring into the sector [60, 61, 131].

The **United States** has firmly established itself as the global leader in cognitive humanoids, a position driven by its unparalleled advancements in generative AI and substantial backing from private venture

capital and major technology corporations [136]. The U.S. ecosystem thrives on a powerful synergy between leading AI research laboratories like OpenAI and Google DeepMind and the robotics companies building the physical hardware platforms. American firms are primarily focused on developing highly intelligent robots capable of reasoning, learning complex coordination from demonstration, and integrating at scale into sectors like logistics and advanced manufacturing [136]. Key representative companies include **Figure AI**, which gained prominence with a massive USD 675 million funding round from a consortium including Nvidia, Microsoft, and Jeff Bezos; **Agility Robotics**, a pioneer in dynamic bipedal locomotion whose Digit robot is being piloted by Amazon; **Tesla**, which is leveraging its vast expertise in AI, battery technology, and mass manufacturing for its Optimus robot; and **Boston Dynamics**, renowned for its high-mobility Atlas platform [60, 70, 74].

China has emerged as the unequivocal manufacturing and deployment powerhouse, accounting for an estimated 90% of global humanoid robot unit sales in 2025 [1, 142]. This staggering dominance is the result of a concerted national strategy involving substantial public investment, aggressive government policies aimed at securing leadership in robotics, a mature and deeply integrated domestic supply chain, and immense internal demand for automation [136, 138]. Chinese companies like **Unitree Robotics**, **AgiBot**, and **UBTECH Robotics** are shipping thousands of units, dwarfing the more R&D-focused production of their Western counterparts [142]. China's primary advantage lies in its supply chain. The Yangtze River Delta hosts a highly concentrated ecosystem of robotic parts suppliers, and the country's dominance in electric vehicle (EV) manufacturing provides a ready source of repurposed components like high-performance actuators and gears [138]. Furthermore, China's control over critical minerals and its significant share of the global actuator market create a formidable competitive moat [138].

Japan, a historical pioneer in robotics, has carved out a niche as the global reference for expressive social robots, advanced teleoperation systems, and specialized retail and service applications [136]. The country's expertise lies in high-precision mechanics, advanced control systems, and human-robot interaction, a focus partly driven by the societal pressures of its rapidly aging population [60]. While China has surpassed Japan in humanoid shipment volumes, Japanese companies like **SoftBank Robotics**, **Kawada Robotics**, and **Toyota** remain influential forces in the industry, particularly in assistive and social robotics [70, 136]. Japan's deep experience in industrial robotics and its strong domestic market for elder care applications position it for significant future humanoid deployment.

Europe holds a strong position as an industrial and human-centric contender, leveraging its deep engineering expertise, powerful manufacturing base, and legacy of producing premium, industrial, and medical-grade robotics [58, 136]. While the European ecosystem is more fragmented than those in the U.S. and China, it is characterized by a focus on high-quality, specialized applications, open-source research platforms, and tight integration with established industries. Germany dominates the European landscape with companies like **Neura Robotics** and **Agile Robots** focusing on industrial and cognitive robotics [136]. France excels in premium and medical robotics through firms like **Enchanted Tools** and **Wandercraft**, while Spain's **PAL Robotics** is a major player in hospitality and research platforms [60, 136]. Europe's key strength lies in its ability to integrate robotics into complex industrial processes and its unwavering emphasis on developing systems that are safe, reliable, and compliant with its uniquely stringent regulatory standards.

8.1 European Usage, Deployment, and Policy

The European humanoid robot market is projected to experience the fastest growth rate of any global region, with a forecast CAGR of 52.5% between 2024 and 2030 [60, 62]. This rapid expansion is fueled by a convergence of acute industrial need, strategic government support, and pressing societal demands. A primary driver is the severe labor shortage affecting the continent, with an estimated 63% of EU Small and Medium-sized Enterprises (SMEs) struggling to find skilled talent [60, 63]. In response,

European industrial giants, particularly in the automotive sector, are becoming anchor customers and key investors. Major manufacturers like **BMW**, **Volkswagen**, and **Mercedes-Benz** are actively conducting humanoid robot trials in their production facilities for tasks like assembly, quality inspection, and material handling [62]. The logistics and healthcare sectors are also key targets for deployment, driven by the demands of e-commerce and an aging population [60].

While Europe has historically lagged behind the U.S. in venture capital funding for robotics startups, its established industrial players, such as Bosch and Schaeffler, are providing crucial “smart money” investments, offering not only capital but also deep domain expertise and a direct path to large-scale industrial deployment [104]. This industry-led approach is complemented by government initiatives like the **Horizon Europe** program, which provides significant funding for robotics research and innovation [63].

The most distinct aspect of the European landscape is its proactive and comprehensive regulatory framework for AI and robotics [50, 58]. This “human-centric” approach is designed to foster public trust and guide technological development in a manner that serves human well-being [53]. The **AI Act**, which entered into force in 2024, is the world’s first comprehensive legal framework for artificial intelligence [128, 143]. Under this act, autonomous robots like humanoids are likely to be classified as “high-risk” systems, subjecting them to strict obligations including rigorous risk assessment, cybersecurity protocols, detailed documentation, and a mandate for effective human oversight [56, 128].

This is further reinforced by the new **Machinery Regulation**, fully applicable in 2027, which modernizes safety rules for autonomous systems [132]. It explicitly requires manufacturers to incorporate lifetime cybersecurity protections and treats software as a safety-critical component subject to rigorous validation [137]. The revised **Product Liability Directive** clarifies that software is a “product,” establishing a clear chain of legal accountability for any damages caused by a faulty AI system, holding manufacturers, importers, and software providers liable [140]. While this complex regulatory environment imposes a significant compliance burden, it also provides a clear pathway for the responsible commercialization of humanoid robots. By mandating safety and establishing clear accountability, the EU may reduce business hesitation and accelerate adoption in sensitive sectors, potentially positioning Europe as a global leader in the ethical deployment of advanced robotics [58].

9. Component-by-Component Material Table

The construction of a humanoid robot is an exercise in applied material science, where every component’s material is carefully selected to optimize performance, weight, durability, and cost. The following table provides a detailed breakdown of the materials used in the key subsystems of a typical modern humanoid robot, tracing the flow from major structural elements down to the specific material families and alloys involved.

Component/Subsystem	Primary Function	Key Materials and Rationale
Main Chassis / Torso Frame	Provides the central structural core, houses batteries, compute, and power electronics; serves as the mounting point for limbs and head.	**Aluminum Alloys (6061, 7075):** The primary choice for the main frame due to its excellent strength-to-weight ratio, ease of machining for complex mounting points, and good thermal conductivity to help dissipate heat from internal electronics [77, 78]. **Topology-Optimized Titanium Alloy (Ti-6Al-4V):** Used in high-end or high-stress designs for the absolute best strength-to-weight performance, especially around major joint connections like the hips and shoulders [76, 77].
Limbs (Arms and Legs)	Provide the articulated levers for manipulation and locomotion; must be lightweight to minimize inertia for dynamic movements.	**Carbon Fiber Composites:** The preferred material for limb segments due to their exceptional stiffness and extremely low weight [79]. This reduces the amount of torque required from the joint motors to accelerate and decelerate the limbs, improving energy efficiency and agility [77]. **Aluminum Alloys:** Often used for the internal structural elements within the carbon fiber shell or as a more cost-effective alternative to carbon fiber in less performance-critical designs [78].
External Shell / Body Panels	Protects internal components from dust and impacts; provides a safe and smooth surface for human interaction; defines the robot's aesthetic.	**Engineering Thermoplastics (Polycarbonate, ABS):** Widely used for their light weight, impact resistance, and ease of molding into complex shapes. They are cost-effective for large body panels [77]. **PEEK**

Component/Subsystem	Primary Function	Key Materials and Rationale
		(Polyether Ether Ketone): A high-performance thermoplastic used in more demanding applications for its superior strength, chemical resistance, and high-temperature tolerance, especially for panels near hot motors or electronics [79]. **Silicone:** Used for soft, flexible outer skins or “bumpers” in areas with high potential for human contact to improve safety and provide a more lifelike feel [77].
Major Joints (Hips, Knees, Shoulders)	Act as the high-load rotational points for the limbs, requiring extreme strength, fatigue resistance, and precision.	**Titanium Alloys (Ti-6Al-4V):** The dominant material for the structural components of major joints due to their unmatched strength-to-weight ratio and resistance to fatigue failure under high cyclical loads [76, 77]. **High-Strength Steel Alloys:** Used for internal components like large shafts, pins, and bearing surfaces where hardness and wear resistance are paramount [77].
Actuator Housings / Motor Casings	Encase the electric motors and gearboxes, providing structural support and heat dissipation.	**Machined Aluminum Alloys:** Most common due to good thermal conductivity, allowing the housing itself to act as a heat sink for the motor [78]. It is also lightweight and strong.
Gearboxes / Reducers (Internal)	Transmit and amplify torque from the motor to the joint; components must withstand immense internal forces and wear.	**High-Hardness Tool Steels / Case-Hardened Steels:** Used for the gear teeth themselves within strain-wave, cycloidal, and planetary gear sets [81]. These materials are heat-

Component/Subsystem	Primary Function	Key Materials and Rationale
		treated to create an extremely hard surface for wear resistance while maintaining a tougher, less brittle core to prevent tooth fracture under shock loads. **Titanium Alloys:** Increasingly used for the structural carriers and casings within high-performance gearboxes to save weight, with some designs showing a 40% weight reduction over steel equivalents [76].
Robotic Hands (Structure)	Provide the frame and fingers for dexterous manipulation; must be lightweight, strong, and often complex in shape.	**3D-Printed Polymers (Nylon, ABS, Onyx):** Revolutionizing hand development by allowing for rapid prototyping and production of lightweight, complex finger and palm structures at low cost [89, 91]. Reinforcement with continuous carbon fiber filaments is common. **Machined Aluminum:** Used for higher-strength hand frames and linkage components where greater rigidity is required [88].
Robotic Hands (Sensing and Grip)	Provide tactile feedback and a high-friction surface for grasping objects.	**Elastomers (Silicone, Urethane):** Used for the outer “skin” of the fingers and palm. These materials provide a compliant, high-friction surface for secure gripping [92]. They also serve as the substrate for embedded tactile sensors.
Sensors and Electronics Housings	Protect delicate sensors (cameras, LiDAR, IMU) and control boards from physical	**Injection-Molded Plastics (ABS, Polycarbonate):** Lightweight and can be molded to precise specifications

Component/Subsystem	Primary Function	Key Materials and Rationale
	damage and electrical interference.	to house custom circuit boards and sensors [77]. **EMI-Shielded Enclosures (Coated Plastics or Aluminum):** Used for sensitive electronics to prevent electromagnetic interference from the high-power motors.
Battery Pack Enclosure	Safely contains the battery cells, BMS, and provides protection from puncture or impact.	**Aluminum or Fire-Retardant Composites:** Provides structural protection and helps dissipate heat [102]. The material must meet stringent safety requirements to help contain a potential thermal runaway event.

10. 3-5 Year Outlook on Development and Rollout

The humanoid robot industry is poised for a period of significant transition over the next three to five years, moving from a phase dominated by research and development and impressive one-off demonstrations to the initial stages of targeted commercial deployment and industrial integration [75, 127]. This evolution will be shaped by concurrent advancements in core component technology, artificial intelligence, and manufacturing economics, alongside the persistent challenges of reliability and cost.

In terms of technology, the evolution of the torso, legs, and locomotion systems will see a strategic divergence. While fully bipedal locomotion will remain the gold standard for navigating complex human environments like multi-story buildings and cluttered workshops, hybrid designs will gain traction for specific industrial applications [72]. These models, often featuring a standard humanoid upper body mounted on a wheeled base, will trade the ability to climb stairs for greatly increased stability, energy efficiency, and payload capacity in the more structured, flat-floored environments of large warehouses and factory logistics [141]. Modularity will become a key design principle, with companies like Apptronik exploring platforms where a single, sophisticated torso and arm system can be deployed on either a bipedal or a wheeled platform depending on the customer’s needs [5]. Critically, extending operational runtime will remain a top priority. Expect the next generation of robots to feature more efficient power management through improved regenerative braking algorithms and, most importantly, the widespread standardization of swappable battery packs to enable near-continuous operation, aiming for favorable work-to-charge ratios like the 4:1 target set by Agility Robotics [5, 8].

The primary driver of increased capability will undoubtedly be advances in **artificial intelligence** [5, 106]. The performance of vision-language models and vision-language-action models will continue to improve, making robots “smarter” and more adaptable. This will enable them to understand more complex, unstructured, and context-aware spoken commands, moving beyond simple instructions to execute multi-step tasks with minimal human oversight [5]. While the long-term vision of a truly general-purpose robot that can perform any human task will remain a distant goal, the near-term focus

will be on **specialization** [75]. We will see the emergence of humanoids designed and trained for specific vertical markets and roles. This includes specialized models for logistics (package handling and palletizing), manufacturing (machine tending and assembly), healthcare (patient assistance and mobility support), and hazardous environments (inspection and maintenance) [72, 75].

From a market dynamics perspective, **cost reduction** will be a critical battleground [75]. For broad adoption to occur, the price of humanoid robots must fall significantly from their current levels. The average selling price is projected to decrease from around $75,000 in 2025 to as low as $25,000 by 2035, a trend driven by fierce competition and economies of scale in manufacturing [72, 129]. This price pressure will be particularly intense from Chinese manufacturers, who benefit from a highly integrated domestic supply chain and are already offering highly affordable models from companies like Unitree [138]. As a result, China is poised to become a dominant force in both the global manufacturing and the large-scale deployment of humanoid robots [1, 138]. To counter high upfront capital costs, the Robot-as-a-Service (RaaS) business model will become increasingly prevalent, allowing companies to lease robotic labor for a monthly or hourly fee, lowering the barrier to entry for adoption [134].

Overall, the 3-5 year horizon will be a crucial period of commercial maturation [127]. The industry's focus will shift from demonstrating impressive physical feats to proving reliability, safety, and a positive return on investment in real-world industrial settings. Success will be determined not just by the sophistication of the AI, but by the durability and cost-effectiveness of the underlying materials and components that constitute the physical robot.

References

1. China leads the world in the humanoid robot market - Verdict (https://www.verdict.co.uk/china-humanoid-market/)
2. What is a humanoid robot - Humanoid.guide (https://humanoid.guide/what-is-a-humanoid/)
3. Introducing Figure 03 - Figure.ai (https://www.figure.ai/news/introducing-figure-03/)
4. Precision in Motion: The Core Components Powering Humanoid Robots - PIB Sales (https://pib-sales.com/robotics/precision-in-motion-the-core-components-powering-humanoid-robots/)
5. AI Humanoid Robots 2026: Technology, Builders & Future - Articsledge (https://www.articsledge.com/post/ai-humanoid-robots/)
6. Humanoid Robots: Understanding the Technology Behind Human-Like Machines - ThinkRobotics.com (https://thinkrobotics.com/blogs/indepths/humanoid-robots-understanding-the-technology-behind-human-like-machines/)
7. The Era of Humanoid Robots: Addressing Emerging End-of-Life Waste Challenges - Environmental Science & Technology (https://pubs.acs.org/doi/10.1021/acs.est.6c02229/)
8. How Humanoid Robots Work: Complete Guide - Qviro Blog (https://qviro.com/blog/how-do-humanoid-robots-work/)
9. Humanoid Robots 2025-2035: Technologies, Markets and Opportunities - IDTechEx (https://www.idtechex.com/en/research-report/humanoid-robots/1093)
10. A Comprehensive Review of Humanoid Robots - Sheng - 2025 - SmartBot - Wiley Online Library (https://onlinelibrary.wiley.com/doi/10.1002/smb2.12008)
11. robotic manipulator - ScienceDirect (https://www.sciencedirect.com/topics/engineering/robotic-manipulator)
12. Two arms are better than one: The benefits of a dual-arm robotic system - dsiac.dtic.mil (https://dsiac.dtic.mil/articles/two-arms-are-better-than-one-the-benefits-of-a-dual-arm-robotic-system/)

13. Robot Manipulator - Wevolver (https://www.wevolver.com/article/robot-manipulator)
14. Dual-Arm Robots - Accio (https://www.accio.com/plp/dual-arm-robots)
15. A bimanual robot for dynamic manipulation - RAI Institute (https://rai-inst.com/resources/blog/bi-manual-robot-for-dynamic-manipulation/)
16. ARM - Robots Guide (https://robotsguide.com/robots/arm)
17. Robot Arm Guide: Types, Applications, and Building Your First Robotic Manipulator - thinkrobotics.com (https://thinkrobotics.com/blogs/tutorials/robot-arm-guide-types-applications-and-building-your-first-robotic-manipulator)
18. robot arm, the most amazing elite power - Liv Hospital (https://int.livhospital.com/robot-arm-the-most-amazing-elite-power/)
19. manipulator arm - ScienceDirect (https://www.sciencedirect.com/topics/computer-science/manipulator-arm)
20. Applied Sciences | Free Full-Text | Enhancing Industrial Robot Control: A Novel Force-Sensing Gripper and Data-Driven Force Estimation Model - MDPI (https://www.mdpi.com/2076-3417/15/6/2976)
21. mobile manipulator - ScienceDirect (https://www.sciencedirect.com/topics/computer-science/mobile-manipulator)
22. Mobile Manipulators - StudySmarter (https://www.studysmarter.co.uk/explanations/engineering/robotics-engineering/mobile-manipulators/)
23. Understanding a mobile manipulator - Mobile Industrial Robots (https://mobile-industrial-robots.com/blog/understanding-a-mobile-manipulator/)
24. Mobile Manipulators - ACM Digital Library (https://dl.acm.org/doi/10.1145/3702468.3702471)
25. Robot Mobility, Manipulation & Attachment - RCA Robotics Laboratory (https://www.rca.ac.uk/research-innovation/research-centres/rca-robotics-laboratory/robot-mobility-manipulation-attachment/)
26. A state of the art on motion control of mobile manipulators - ScienceDirect (https://www.sciencedirect.com/science/article/abs/pii/S1367578820300043)
27. Manipulator Robots: Complete Guide | Benefits and applications | Robotnik (https://robotnik.eu/complete-guide-to-manipulator-robots-benefits-and-applications/)
28. O series - YOUİBOT (https://en.youibot.com/products-category/o-series-19.html)
29. Mobile Manipulators: Dynamic Flexibility In Action - Agile Robots (https://www.agile-robots.com/en/news/detail/mobile-manipulators-dynamic-flexibility-in-action/)
30. Recent advances in the development and control of humanoid robots for dynamic motions - ScienceDirect (https://www.sciencedirect.com/science/article/pii/S2215098625003192)
31. Embodied, flexible, high-power-output, structural batteries for untethered, small-scale robots - ScienceDirect (https://www.sciencedirect.com/science/article/abs/pii/S2405829723003999)
32. Quadruped Robot - an overview - ScienceDirect Topics (https://www.sciencedirect.com/topics/engineering/quadruped-robot)
33. Engineering Quadruped Locomotion: Actuation Systems, ... - IRJET (https://www.irjet.net/archives/V11/i10/IRJET-V11I1046.pdf)
34. Q8bot: Palm-sized quadruped robot jumps, redefines design with no wires - Interesting Engineering (https://interestingengineering.com/innovation/palm-sized-quadruped-robot-redefines-design)
35. Additive design and manufacturing of a quadruped robot actuated by electrothermal effect of shape memory polymer - ScienceDirect (https://www.sciencedirect.com/science/article/abs/pii/S0924424723002509)
36. A Review of Quadruped Robots: Structure, Control, and Autonomous Motion - Wiley Online Library (https://advanced.onlinelibrary.wiley.com/doi/10.1002/aisy.202300783)

37. Review: Advanced Drive Technologies for Bionic Soft Robots - Springer Nature Link (https://link.springer.com/article/10.1007/s42235-025-00664-1)
38. Quadruped Robot: A Complete Guide to Quadruped Robots - Humanoid Robotics Technology (https://humanoidroboticstechnology.com/articles/quadruped-robot-complete-guide/)
39. A Centimeter-Scale Quadruped Piezoelectric Robot with High Integration and Strong Robustness - PMC (https://pmc.ncbi.nlm.nih.gov/articles/PMC12282480/)
40. Quadruped Robots: Bridging Mechanical Design, Control, and Applications - MDPI (https://www.mdpi.com/2218-6581/14/5/57)
41. Robotic Arm Components: An Essential Guide - Standard Bots (https://standardbots.com/blog/robotic-arm-components)
42. Parts of Robot: Understand the Key Components - JEHSON (https://jehson-robot.com/parts-of-robot/)
43. How Do Robotic Arms Work? A Comprehensive Guide - Standard Bots (https://standardbots.com/blog/how-do-robotic-arms-work-a-comprehensive-guide)
44. A Guide To Robotic Arms And All You Need To Know - Universal Robots (https://www.universal-robots.com/in/blog/robotic-arm/)
45. Review on robotic arm performance - IAEME (https://iaeme.com/MasterAdmin/Journal_uploads/IJARET/VOLUME_11_ISSUE_6/IJARET_11_06_125.pdf)
46. Industrial Robot Arms and Cobots - Vention (https://vention.io/blogs/industrial-automation-design/industrial-robot-arms-and-cobots-913)
47. What Components Do Industrial Robotic Arms Include - Ost Bridge (https://www.ostbridge-tech.com/news/what-components-do-industrial-robotic-arms-include.html)
48. What are the Components of Robotic Arms in Industrial Robots? - CUBeMARS (https://www.linkedin.com/pulse/what-components-robotic-arms-industrial-robots-cubemars)
49. Robotic Arm Design Principles - Arctos Robotics (https://arctosrobotics.com/2025/10/19/robotic-arm-design-principles/)
50. Roboethics in Europe - PMC (https://pmc.ncbi.nlm.nih.gov/articles/PMC8572833/)
51. When ‘made in Europe’ meets machines: Humanoid robots, policy and the new industrial paradox - The Senate of Economy Europe (https://senate.economy.ac/t/when-made-in-europe-meets-machines-humanoid-robots-policy-and-the-new-industrial-paradox/1579)
52. Don’t blame it on the machines: Robots and employment in Europe - CEPR (https://cepr.org/voxeu/columns/dont-blame-it-machines-robots-and-employment-europe)
53. Responsible Robotics: a new opportunity for research and policy direction - SpringerLink (https://link.springer.com/article/10.1007/s12369-023-00982-6)
54. A Systematic Literature Review on Ethics in Robotics - SpringerLink (https://link.springer.com/article/10.1007/s42452-021-04853-5)
55. Artificial intelligence, robots, and work: is this time different? - Oslo Law Review (https://www.scup.com/doi/10.18261/olr.11.1.5)
56. Humanoid Robot Compliance - Kite Compliance (https://www.kitecompliance.ai/vertical-compliance/humanoid-robot-compliance)
57. Europe divided over robot ‘personhood’ - POLITICO (https://www.politico.eu/article/europe-divided-over-robot-ai-artificial-intelligence-personhood/)
58. Why Europe Could Win the Humanoid Race, Quietly - Robotics Observer (https://roboticsobserver.com/why-europe-could-win-the-humanoid-races-quietly/)
59. Digital responsibility gaps in the European Union - PMC (https://pmc.ncbi.nlm.nih.gov/articles/PMC8097897/)

60. Humanoid Robot Market - MarketsandMarkets (https://www.marketsandmarkets.com/Market-Reports/humanoid-robot-market-99567653.html)
61. Humanoid Robot Market Size, Share | Industry Report 2024-2030 - Grand View Research (https://www.grandviewresearch.com/industry-analysis/humanoid-robot-market-report)
62. Humanoid Robots Market - Fortune Business Insights (https://www.fortunebusinessinsights.com/humanoid-robots-market-110188)
63. Humanoid Robots: Conquering Industry - Societe Generale Private Banking (https://www.privatebanking.societegenerale.com/en/insights/humanoid-robots-conquering-industry/)
64. Humanoid Robotics Funding Trends - New Market Pitch (https://newmarketpitch.com/blogs/news/humanoid-robotics-funding-trends)
65. The Global Humanoid Robot Market is Expected to Reach $61.2 Billion in 2029 - SkyQuest Technology (https://www.skyquestt.com/report/humanoid-robot-market)
66. Humanoid Robot Market - Roots Analysis (https://www.rootsanalysis.com/humanoid-robot-market)
67. Humanoid Robots Are Evolving | Automate - Automate.org (https://www.automate.org/industry-insights/humanoid-robots-are-evolving)
68. Humanoid Robots Global Market Report 2026 - Yahoo Finance (https://finance.yahoo.com/news/humanoid-robots-global-market-report-153700568.html)
69. Is the Humanoid Robot Market on the Verge of a ‘5 Trillion’ Opportunity? - Morgan Stanley (https://www.morganstanley.com/insights/articles/humanoid-robot-market-5-trillion-by-2050)
70. Top Companies in the Rise of Humanoid Robots - Ross Dawson (https://rossdawson.com/futurist/companies-creating-future/top-companies-rise-humanoid-robots/)
71. Humanoid Robots 2025: The Race to Useful Intelligence - Edge AI and Vision Alliance (https://www.edge-ai-vision.com/2025/11/humanoid-robots-2025-the-race-to-useful-intelligence/)
72. What is a Humanoid Robot? Basics, Applications, Best Models - Top 3D Shop (https://top3d-shop.com/blog/humanoid-robots-types-history-best-models)
73. Robust Balance Control for Quadruped Robots with a Manipulator on Sloped Terrains - Science Partner Journals (https://spj.science.org/doi/10.34133/cbsystems.0201)
74. What does a humanoid robot do? - Standard Bots (https://standardbots.com/blog/humanoid-robot)
75. Humanoid Robots: From Demos to Deployment - Bain & Company (https://www.bain.com/insights/humanoid-robots-from-demos-to-deployment-technology-report-2025/)
76. Star50 | Tesla’s Optimus Robot Fuels Demand for Titanium Alloys, Pushing Price of the Industrial Metal Up 17% in a Week - yicaiglobal.com (https://www.yicaiglobal.com/star50news/2025_03_27680888595355201544)
77. Advanced materials for humanoid robots - Goodfellow (https://www.goodfellow.com/usa/resources/advanced-materials-for-humanoid-robots/)
78. Lightweight Materials for Structural Components of Humanoid Robots - The Future of Things (https://mrratanbajaj.substack.com/p/lightweight-materials-for-structural)
79. The new material revolution of humanoid robots - sbfchem.com (https://www.sbfchem.com/index.php/news/1009/The_new_material_revolution_of_humanoid_robots.html)
80. Recent Advances in Robot Actuators - MDPI (https://www.mdpi.com/2076-0825/14/5/243)
81. Beyond Motors: Gearboxes as the Unsung Heroes in Robotics and Heavy-Duty Machines - Power Transmission Engineering (https://www.powertransmission.com/beyond-motors-gearboxes-as-the-unsung-heroes-in-robotics-and-heavy-duty-machines)
82. Humanoid Robot Actuators - FIRGELLI (https://www.firgelli.com/pages/humanoid-robot-actuators)
83. Actuator With Series Elasticity for Robotic Applications - Frontiers (https://www.frontiersin.org/journals/robotics-and-ai/articles/10.3389/frobt.2020.00103/full)

84. Comparing Boston Dynamics' All-New Atlas to Tesla's Optimus Gen 2 - Interesting Engineering (https://interestingengineering.com/innovation/comparing-boston-dynamics-atlas-optimus-humanoid-robots)
85. Tesla Optimus Vs Boston Dynamics Atlas: Who Will Prevail? - Robozaps Blog (https://blog.robozaps.com/b/tesla-optimus-vs-boston-dynamics-atlas)
86. Humanoidspecs (https://humanoidspecs.com/)
87. Top 10 Most Advanced Humanoid Robots in the World in 2026 - AutoGPT (https://autogpt.net/top-10-humanoid-robots/)
88. A compact and lightweight integrated linkage-driven dexterous anthropomorphic robot hand - Nature Communications (https://www.nature.com/articles/s41467-021-27261-0)
89. D'Manus: An Inexpensive, Modular, and Robust Dexterous Robotic Hand - arXiv (https://arxiv.org/html/2210.15658v3)
90. Robonaut 2 Hand & Arm Dexterous Manipulation - NASA Technology Transfer Program (https://technology.nasa.gov/patent/MSC-TOPS-102)
91. An underactuated, 3D-printed, 17-DOF anthropomorphic robotic hand with integrated nanocomposite filament strain sensors for proprioception - The International Journal of Advanced Manufacturing Technology (https://link.springer.com/article/10.1007/s00170-024-14918-5)
92. A soft robotic hand for dexterous grasping and in-hand manipulation with integrated visual–tactile sensing - PMC (https://pmc.ncbi.nlm.nih.gov/articles/PMC11894155/)
93. Inside a Humanoid Robot Battery Pack Design in 2025 - Ufine Battery (https://www.ufinebattery.com/blog/inside-humanoid-robot-battery-pack-design/)
94. How to Choose the Best Humanoid Robot Lithium Battery? - MANLY Battery (https://manlybattery.com/how-to-choose-the-best-humanoid-robot-lithium-battery/)
95. Humanoid Robot Battery Program Guide: 2026 Outlook and Beyond - MANLY Battery (https://manlybattery.com/humanoid-robot-battery-program-guide-2026-outlook-and-beyond/)
96. Hitting the Battery Wall - The Review from Strange Ventures (https://thereview.strangevc.com/p/hitting-the-battery-wall)
97. Humanoid robots are tripping over their high-energy demands - GlobalSpec (https://insights.globalspec.com/article/24246/humanoid-robots-are-tripping-over-their-high-energy-demands)
98. Powering the Future: How Advanced Batteries Drive Humanoid & Quadrupedal Robots - APA ROBOT (https://www.aparobot.com/articles/powering-the-future-how-advanced-batteries-drive-humanoid-quadrupedal-robots)
99. Humanoid Robot Batteries - PAC (http://www.pacbattery.com/humanoid-robot-batteries.html)
100. Maximize AMR Robot Battery Uptime And Performance For Your Business - Longsing (https://www.longsingtech.com/maximize-amr-robot-battery-uptime/)
101. Revolutionizing Humanoid Robotics: Advanced Battery Protection Systems Explained - Large-Battery.com (https://www.large-battery.com/2025/02/revolutionizing-humanoid-robotics-advanced-battery-protection-systems-explained.html)
102. Humanoid Robot Battery Considerations: Energy, Safety, Integration - Large-Battery.com (https://www.large-battery.com/blog/humanoid-robot-battery-considerations-energy-safety-integration/)
103. Top 5 Technical Challenges in Humanoid Robotics - Simplexity (https://www.simplexitypd.com/blog/top-5-technical-challenges-in-humanoid-robotics/)
104. How Europe's sleepy industrial giants are waking up to humanoid robots - The Europe Says (https://www.europesays.com/europe/3908/)
105. How humanoid robots will coexist with us on- and off-planet - TI.com (https://www.ti.com/applications/industrial/robotics/humanoid-robot/overview.html)

106. Humanoid Robots: Humanoid AI Robots Are the Future - Medium (https://medium.com/@aayushbhatnagar_10462/humanoid-ai-robots-are-the-future-9b44923ba0ce)
107. What is Humanoid Robotics? - Celera Motion (https://www.celeramotion.com/news/articles/what-is-humanoid-robotics/)
108. Humanoid Robot Control System Based on AI - JHC Technology (https://www.jhc-technology.com/humanoid_robot_control)
109. Humanoid robots: From science fiction to industrial reality - ScienceDirect (https://www.sciencedirect.com/science/article/pii/S0306457325003048)
110. Reinforcement Learning Based Whole-Body Control of a Humanoid Robot for Non-Cooperative Physical Human-Robot Interaction - arXiv.org (https://arxiv.org/html/2501.02116v1)
111. Real-time adaptive whole-body motion planning of humanoid robot for dynamic human-robot interaction using deep reinforcement learning - arXiv.org (https://arxiv.org/html/2405.15775v2)
112. Research on dynamic trajectory online generation of humanoid robot turning based on deep reinforcement learning - SpringerLink (https://link.springer.com/article/10.1007/s44163-025-00603-3)
113. Biomimetic emergency response control architecture for Humanoid Robot under sudden disturbance - ScienceDirect (https://www.sciencedirect.com/science/article/abs/pii/S2452414X2500233X)
114. A survey of state estimation for legged robots: from the viewpoint of proprioceptive sensing - SpringerLink (https://link.springer.com/article/10.1007/s43154-023-00107-x)
115. A survey of audio processing for humanoid robots - ScienceDirect (https://www.sciencedirect.com/science/article/pii/S0921889021001196)
116. Humanoid robotics’ nervous system: Perception, balance, and real-time control - Panasonic (https://na.industrial.panasonic.com/blog/humanoid-robotics-nervous-system-perception-balance-and-real-time-control)
117. Proprioceptive sensors in humanoid robots - Wikipedia (https://en.wikipedia.org/wiki/Proprioceptive_sensors_in_humanoid_robots)
118. The Development of Dexterous Housekeeping by a Humanoid Robot with Multimodal Tactile Sensors - Nature (https://www.nature.com/articles/s41467-024-51261-5)
119. Sensors for Humanoid Robots - Humanoid Robotics Technology (https://humanoidroboticstechnology.com/suppliers/modules-components/sensors-for-humanoids/)
120. What Sensors do Humanoid Robots Have? - Humanoid Robotics Technology (https://humanoidroboticstechnology.com/articles/what-sensors-do-humanoid-robots-have/)
121. Why are humanoid robot batteries so short-lived? - PAC (http://www.pacbattery.com/why-are-humanoid-robot-batteries-so-short-lived.html)
122. A survey of multimodal human activity and motion recognition by humanoid robots - SpringerLink (https://link.springer.com/article/10.1007/s10845-024-02341-2)
123. Humanoid Robot Sensors - FUTEK (https://www.futek.com/applications/humanoid-robot-sensors)
124. Humanoid Robot Market - Humanoid.guide (https://humanoid.guide/humanoid-robot-market-report/)
125. Humanoid Robots Will Not Deliver The Future Labour Force, It Will Transform It - Economy.ac (https://economy.ac/review/2026/03/202603288571)
126. Humanoid robots enter a new battlefield of industrial implementation - Gasgoo (https://autonews.gasgoo.com/articles/news/humanoid-robots-enter-a-new-battlefield-2026957094341603329)

127. Humanoid robots: Crossing the chasm from concept to commercial reality - McKinsey (https://www.mckinsey.com/industries/industrials-and-electronics/our-insights/humanoid-robots-crossing-the-chasm-from-concept-to-commercial-reality)
128. Digital framework for AI - European Commission (https://digital-strategy.ec.europa.eu/en/policies/regulatory-framework-ai)
129. Humanoid Robot Market | Global Market Analysis Report - 2035 - Future Market Insights (https://www.futuremarketinsights.com/reports/humanoid-robot-market)
130. Humanoid-robotics-market Growth outlook 2023-2032 - MarketIntelo (https://marketintelo.com/report/humanoid-robotics-market)
131. humanoid-robot-market to increase by USD 59.18 billion between 2024 and 2029 - Technavio (https://www.technavio.com/report/humanoid-robot-market-industry-analysis)
132. Robotics at a Global Regulatory Crossroads - Osborne Clarke (https://www.osborneclarke.com/insights/robotics-global-regulatory-crossroads-compliance-challenges-autonomous-systems)
133. Introduction - DIGITIMES (https://www.digitimes.com/reports/ai/2025_robots/)
134. Humanoid Robot Market Size, CAGR, and Projections | 2024-2030 - RoboZaps (https://blog.robozaps.com/b/market-size-for-humanoid-robots)
135. The Humanoid 100 - Mapping the Humanoid Robot Value Chain - Morgan Stanley (https://advisor.morganstanley.com/john.howard/documents/field/j/jo/john-howard/The_Humanoid_100_-_Mapping_the_Humanoid_Robot_Value_Chain.pdf)
136. 2026 global directory of humanoid robot manufacturers: ranking by country and sector - ROBOT-MAGAZINE.FR (https://www.robot-magazine.fr/en/2026-global-directory-of-humanoid-robot-manufacturers-ranking-by-country-and-sector/)
137. AI Act and Machinery Regulation: What changes for the safety of work equipment? - Wolters Kluwer (https://legalblogs.wolterskluwer.com/global-workplace-law-and-policy/ai-act-and-machinery-regulation-what-changes-for-the-safety-of-work-equipment/)
138. Why China’s humanoid robot industry is winning the early market - TechCrunch (https://techcrunch.com/2026/02/28/why-chinas-humanoid-robot-industry-is-winning-the-early-market/)
139. Humanoid Robot supply chain - a new paradigm in Global manufacturing - Gerra (https://www.gerra.com/insights/humanoid-robot-supply-chain)
140. Navigating the legal maze of AI, autonomous robots, and the EU’s regulatory overhaul - Timelex (https://www.timelex.eu/en/blog/navigating-legal-maze-ai-autonomous-robots-and-eus-regulatory-overhaul)
141. The Value and Limitations of Humanoid Robots in the Warehouse of the Future - SCMR.com (https://www.scmr.com/article/the-value-and-limitations-of-humanoid-robots-in-the-warehouse-of-the-future)
142. Ranked: The Companies Shipping the World’s Humanoid Robots - Visual Capitalist (https://imageio.forbes.com/specials-images/imageserve/69614b2bfc8aa9a0ac8ed196/Top-10-leading-humanoid-robot-manufacturers-globally-for-2025-shipments/0x0.png?format=png&width=480)
143. What is a humanoid robot - The Artificial Intelligence Act (https://artificialintelligenceact.eu/)