Staff answers

Year A | Autumn 2 · Week 1 | 3 November 2026

The starter comparison

A fair start script sets both score variables to zero every time the start event runs. Without explicit reset blocks, points from the previous turn stay in the variables and make the next turn unfair.

Model for project card A

A space maze project

Variables created

FuelScore (pickup variable) and HazardHits (hazard variable).

Start reset script

When start runs: set FuelScore to 0; set HazardHits to 0. Show both readouts at the top of the stage.

Model for project card B

A deep-sea maze project

Variables created

PearlScore (pickup variable) and ReefHits (hazard variable).

Start reset script

When start runs: set PearlScore to 0; set ReefHits to 0. Show both readouts at the top of the stage.

These are models, not the only valid variable labels. Accept accurate, descriptive variable names that match the chosen card. Check that both variables reset to zero under the start event.

Staff checks and next steps

Year A | Autumn 2 · Week 1 | 3 November 2026

Optional stretch variable

Card A adds RoundCount set to 1 on start. Card B adds DiveCount set to 1 on start. A round or dive counter starts at 1 for the first attempt, whereas score and hazard counters start at 0.

Variable and readout checks

Check that two distinct variables exist and that each set-to-zero block selects a different variable name in its drop-down menu. A common fault is setting the same variable to zero twice while leaving the second variable unchanged.

Useful next-step prompts

Which variable tracks pickups and which tracks hazards? Do both set blocks name different variables? What happens when you set a variable to 5 and press start? Can the player see the start zone clearly?

Evidence decisions

Seen: the pupil demonstrates the variable setup and start reset or explains an accurate choice. Supported: record the action and actual prompt or scribing. Not yet seen: the action did not occur or the device was unavailable. Do not award an individual check from a partner's file.

Save and revision

The start script and both variables must appear after reopening the saved file. If using v2, retain v1, open both and identify the specific improvement.