


Test materials and joins

Today: inspect samples, try a cold join and read test evidence.

Choose handling, looking, reading or recording. You do not have to touch a fabric.

How could we check a claim about a material?




Words that help

PROPERTY

A feature of a material that can be observed or tested.

JOIN

A connection between two pieces.




Property plus evidence

“Flexible” means it bends. “Stretchy” means its length changes under a gentle pull.


“This cut edge stays together” is an observation about this sample.

A material’s name does not prove every property.



Property plus evidence — continued

Does a fabric that bends have to stretch?




Compare two samples

Inspect felt sample B and net sample E, or read their property cards.

Choose two property words for each.

Link a choice to the card-pocket job.

Which sample is a better starting point for a card pocket, and why?




Three ways to connect

Glue needs the amount and curing time on its label.

Cold fabric tape is pressed; we are not using iron-on tape.

A prepared stitch sample shows thread joining the layers.

Can we test fresh glue as though it has already cured?




A fair comparison?

Team A tests fresh glue. Team B tests tape that is ready to handle.

Their strip sizes and overlaps are also different.

Can they claim one method is stronger from this comparison?




Make, label, leave to cure

Join two prepared strips using approved cold tape, then make a glue sample if approved.


Label the method and record whether you made or only inspected it.

Leave wet glue to cure; inspect the adult's prepared stitch sample.



Make, label, leave to cure — continued

What should the record say if you observed the stitch sample?




Read the sample results

At the same 100 g load for 10 seconds: glue held 3/3, tape 1/3, stitch 2/3.

These are invented class results.

A holding test at one load does not find the maximum strength.

What claim is supported?




Match the join to the job

For a quick display repair, consider time and surface.

For a hem, consider fabric, movement and washing.

For a bag handle, further load and reinforcement checks are needed.

Can this 100 g test certify a bag handle?



One claim, one limit

Finish: “In this test ____ because ____.”

Name one condition that should stay the same in the comparison.