
Verification of the Blocking and Non-Blocking Michael-Scott Queue Algorithms

Mathias Pedersen, 201808137

Master's Thesis, Computer Science

May 2024

Advisor: Amin Timany



AARHUS
UNIVERSITY

DEPARTMENT OF COMPUTER SCIENCE

Abstract

►in English...◄

Resumé

►in Danish...◄

Acknowledgments



Mathias Pedersen
Aarhus, May 2024.

Contents

Abstract	ii
Resumé	iii
Acknowledgments	iv
1 Introduction	1
2 Preliminaries	2
2.1 HeapLang	2
2.2 The Iris Program Logic Framework	2
2.2.1 Fundamentals of Iris	2
2.2.2 Hoare Triples and Weakest Pre-Condition	2
2.2.3 Later Modality	2
2.2.4 Invariants	3
2.2.5 Resource Algebra	3
2.2.6 Update modality and Viewshift	3
2.3 Formalisation in Coq	3
2.3.1 Compiling the Project	3
3 The Two-Lock Michael Scott Queue	5
3.1 Introduction	5
3.2 Implementation	5
3.2.1 Initialise	6
3.2.2 Enqueue	6
3.2.3 Dequeue	6
4 Sequential Specification	9
4.1 Defining a Sequential Specification	9
4.2 Sequential Queue Predicate	9
4.3 Proof Outline	11
5 Concurrent Specification	14
5.1 Defining a Concurrent Specification	14
5.2 Concurrent Queue Predicate	14
5.3 Linearisation Points	17
5.4 Proof Outline	17
5.4.1 Discussing the need for Old Nodes	20
6 Hocap-Style Specification	22
6.1 Defining a Hocap-Style Specification	22
6.2 Hocap-Style Queue Predicate	23
6.3 Proof Sketch	23
6.4 Deriving Sequential and Concurrent Specifications	25
6.4.1 Deriving the Sequential Specification	25

6.4.2	Deriving the Concurrent Specification	26
7	The Lock-Free Michael Scott Queue	27
7.1	Introduction	27
7.2	Implementation	27
7.2.1	Initialise	27
7.2.2	Enqueue	27
7.2.3	Dequeue	28
7.2.4	Prophecies	28
7.3	Reachability	29
7.3.1	Concrete Reachability	29
7.3.2	Abstract Reachability	30
7.4	Specifications for Lock-Free M&S-Queue	32
7.5	Hocap-style Queue Predicate	32
7.6	Proof Outline	33
7.7	Discussion	38
8	Conclusion and Future Work	39
	Bibliography	40
A	The Technical Details	41

Chapter 1

Introduction

►motivate and explain the problem to be addressed◄

►example of a citation: [4]◄►get your bibtex entries from <https://dblp.org/>◄►Emphasise that specs for two-lock and lock-free are equivalent, with only the queue functions being different. This is even shown in the coq proofs◄►Have a bullet point list of contributions◄

►direct specifications for TL and LF Queues (instead of refinement)◄►Add more contributions◄

Chapter 2

Preliminaries

►Mention that the project uses heaplang and the program logic iris, and hence we need to know about them◄

2.1 HeapLang

►Write about heaplang language: ml like, with a heap, Cas◄ ►Refer to ILN for specification◄
►Talk about Syntactic sugar: i.e. $e1 \;; e2 = (\text{lam } v, e2) \; e1$ where v is fresh, and CAS ... as Snd (CMPXHG ...), and derived rules for them◄ ►also mention prophecies and refer to the section talking about them◄

2.2 The Iris Program Logic Framework

In this section, we give a brief introduction to Iris – the logic we use to reason about the M&S-Queue’s. Iris is quite expressive and supports a myriad of features and derived rules, many of which have been utilised in this project. As such, it will be impossible to cover all facets of Iris in detail, so we limit ourselves to give an overview of the main aspects of Iris. If the reader wishes a more thorough introduction, or wants to see further details of the topics covered, please consult the Iris Lecture Notes [1].

►FOCUS IN THIS SECTION is on explaining the basic ideas of the concepts and showing the notation used. Assume the reader is somewhat familiar with program verification.
◄

2.2.1 Fundamentals of Iris

►program logic framework◄ ►instantiate with a language, here heaplang◄ ►higher order logic◄ ►separation logic◄ ►- exclusive ownership and duplicability◄ ►introduce persistent modality, duplicability◄ ►points-to predicates◄ ►resource oriented◄ ►derivation rules examples...◄

2.2.2 Hoare Triples and Weakest Pre-Condition

►explain hoare triples◄ ►talk about Partial correctness and Adequacy◄ ►explain weakest pre-conditions◄ ►show how they are related◄

2.2.3 Later Modality

►explain concept◄ ►ties propositions to program steps◄ ►Explain the löb induction rule, mention the intuition when P is hoare triple◄

The later modality adds a notion of step indexing to Iris propositions. This step indexing is technically parallel to the notion of taking steps in the programs, but the way we define hoare-triples and weakest-

preconditions tie program steps together with steps in the logic. In other words, a single Later corresponds to a single step in the program.

2.2.4 Invariants

►explain the idea◀ ►open around atomic expression◀ ►only one opening at a time◀
►namespaces◀ ►Show the basic rules. Inv-alloc (FUP), ...◀

2.2.5 Resource Algebra

►Introduce the idea◀ ►Validity◀ ►introduce \cdot and \preceq ◀ ►tying them into the logic◀ ►also
ghost names◀ ►own-allocate own-op, own-valid...◀ ►mention that points-to predicate is
also a resource algebra◀ ►composing resource algebras◀ ►we introduce the resource alge-
bras we use at the point of use◀

2.2.6 Update modality and Viewshift

►explain the ideas◀

2.3 Formalisation in Coq

Iris has been mechanised in the Coq proof assistant¹ – a tool to machine-check proofs of mathematical assertions. All results in this project have been completely machine-verified in the Iris mechanisation in Coq. Specifications in the Coq formalisation of Iris are usually written in terms of hoare-triples but proved by first converting the hoare-triples to equivalent weakest-preconditions, as this is usually easier to work with. The proofs presented in this report will follow suit and give specifications using hoare-triples, but prove them assuming they are weakest-preconditions. The proofs presented in the report thus follow the mechanised proofs very closely, making it possible to “step-through” the mechanised proofs in tandem with reading the paper-proofs presented in this report.

One caveat is that, although the theory discussed in the previous section remain valid, the underlying model of Iris is somewhat more complex than the section presented it to be. Working with the Coq formalisation of Iris thus requires a bit deeper understanding of the model of Iris. [3] explains the underlying model of an older version of Iris, but many of the concepts discussed are still relevant².

Table 2.1 gives an overview over the files developed in the project and how they relate to this report. All files related to the project are available at <https://github.com/MatteP1/thesis>.

2.3.1 Compiling the Project

Compiling the project (on Linux) requires both Coq and Iris to be installed. Once installed, open a terminal and navigate to the project folder, containing `_CoqProject`. Then run the following two commands, which (1) generates a makefile and (2) runs the makefile.

```
1 $ coq_makefile -f _CoqProject -o CoqMakefile
2 $ make -f CoqMakefile
```

The project is known to compile with Coq version 8.19.0 and Iris version 4.2.0.

¹The mechanisation can be found at <https://gitlab.mpi-sws.org/iris/iris/>

²For an up-to-date presentation, please consult the Technical Reference at <https://iris-project.org/>

File Name	Relevant Sections	Description
MSQ_common.v	Chapters 3 - 7	Common definitions and lemmas.
twoLockMSQ_impl.v	Chapter 3	Two-Lock M&S-Queue implementation and proofs of three specifications. Two of them shown to be derivable from the third.
twoLockMSQ_sequential_spec.v	Chapter 4	
twoLockMSQ_concurrent_spec.v	Chapter 5	
twoLockMSQ_hocap_spec.v	Chapter 6	
twoLockMSQ_derived.v	Section 6.4	
lockFreeMSQ_impl.v	Section 7.2	Lock-Free M&S-Queue implementation and Hocap-style + derived specifications.
lockFreeMSQ_hocap_spec.v	Sections 7.3 - 7.6	
lockFreeMSQ_derived.v	Sections 7.4 and 6.4	
lockAndCCFreeMSQ_impl.v	Section 7.7	Consistency-Check-Free version of Lock-Free M&S-Queue.
lockAndCCFreeMSQ_hocap_spec.v	Section 7.7	
queue_specs.v	N/A	Implementation-independent specs.

Table 2.1: Overview of Coq Files

Chapter 3

The Two-Lock Michael Scott Queue

In this chapter, we give an implementation of the blocking version of the M&S-Queue, the Two-Lock M&S-Queue, in HeapLang. This implementation differs slightly from the original, presented in [4], but most changes simply reflect the differences in the two languages.

3.1 Introduction

The underlying data structure making up the queue is a singly-linked list. The linked-list will always contain at least one element, called the *head* node, marking the beginning of the queue. Note that the head node is itself not part of the queue, but all nodes following it are. The queue keeps a head pointer (ℓ_{head}) which always points to the head node, and a tail pointer (ℓ_{tail}) which points to some node in the linked list, denoted the tail node.

In my implementation, a node is a triple $(\ell_{i_in}, w_i, \ell_{i_out})$ satisfying that location ℓ_{i_in} points to the pair (w_i, ℓ_{i_out}) . Here, w_i either contains the value of the node v_i wrapped in a *Some* (i.e. $w_i = \text{Some } v_i$) or it is *None*. ℓ_{i_out} either points to *None* which represents the null pointer, or to the next node in the linked list. When we say that a location ℓ points to a node $(\ell_{i_in}, w_i, \ell_{i_out})$, we mean that $\ell \mapsto \ell_{i_in}$. Hence, if we have two adjacent nodes $(\ell_{i_in}, w_i, \ell_{i_out})$, $(\ell_{i+1_in}, w_{i+1}, \ell_{i+1_out})$ in the linked list, then we have the following structure: $\ell_{i_in} \mapsto (w_i, \ell_{i_out})$, $\ell_{i_out} \mapsto \ell_{i+1_in}$, and $\ell_{i+1_in} \mapsto w_{i+1}, \ell_{i+1_out}$. For a given triple $x = (\ell_{in}, w, \ell_{out})$, we introduce the following notation:

$$\text{in}(x) = \ell_{in} \qquad \text{val}(x) = w \qquad \text{out}(x) = \ell_{out}$$

The reader may wonder why there is an extra, intermediary “in” pointer, between the pairs of the linked list, and why the “out” pointer couldn’t point directly to the next pair. In the original implementation [4], nodes are allocated on the heap. To simulate this in HeapLang, when creating a new node, we create a pointer to a pair making up the node. Now, in the C-like language used in the original specification, an assignment operator is available which is not present in HeapLang. So in order to mimic this behaviour, we model variables as pointers. In this way, we can model a variable x as a location ℓ_x , and the value stored at ℓ_x is the current value of x . This means that the variable “next” in the original implementation becomes a location ℓ_{out} , and the value stored at the location is what it is currently assigned to. Since “next” is supposed to be a variable containing a pointer, then the value that ℓ_{out} points to will also be a pointer.

3.2 Implementation

The queue consists of 3 functions: initialize, enqueue, and dequeue, and as the name of the data structure suggests, the functions rely on two locks. To this end, we shall assume that we have some lock implementation given. In the accompanying Coq mechanisation, a “spin-lock” is used, but the only part we really care about is its specification; this can be found in [1] (Example 8.38 at the time of writing).




Figure 3.1: Queue after initialisation

3.2.1 Initialise

initialize will first create a single node – the head node – marking the start of the linked list. It then creates two locks, h_{lock} and t_{lock} , protecting the head and tail pointers, respectively. Finally, it creates the head and tail pointers, both pointing to the head node. The queue is then a pointer to a structure containing the head and tail pointers, and the two locks.

Figure 3.1 illustrates the structure of the queue after initialisation. Note that one of the pointers is coloured blue. This represents a *persistent* pointer; a pointer that will never be updated again. All “in” pointers ℓ_{i_in} , are persistent, meaning that, once created, they will only ever point to (w_i, ℓ_{i_out}) . We shall use the notation $\ell \mapsto^\square v$ (introduced in [5]) to mean that ℓ points persistently to v .

Note that in the original specification, a queue is a pointer to a 4-tuple $(\ell_{\text{head}}, \ell_{\text{tail}}, h_{\text{lock}}, t_{\text{lock}})$. Since HeapLang doesn’t support 4-tuples, we instead represent the queue as a pointer to a pair of pairs: $((\ell_{\text{head}}, \ell_{\text{tail}}), (h_{\text{lock}}, t_{\text{lock}}))$.

3.2.2 Enqueue

To enqueue a value, we must create a new node, append it to the underlying linked-list, and swing the tail pointer to this new node. These three operations are depicted in figure 3.2.

enqueue takes as argument the value to be enqueued and creates a new node containing this value (corresponding to figure 3.2a). This creation doesn’t interact with the underlying queue data-structure, hence why we don’t acquire t_{lock} first. After creating the new node, we must make the last node in the linked list point to it. Since this operation interacts with the queue, we first acquire t_{lock} . Once we obtain the lock, we make the last node in the linked list point to our new node (figure 3.2b). Following this, we swing ℓ_{tail} to the newly inserted node (figure 3.2c).

Figure 3.2 also illustrates when pointers become persistent; once the previous last node is updated to point to the newly inserted node, that pointer will never be updated again, hence becoming persistent.

3.2.3 Dequeue

It is of course only possible to dequeue an element from the queue if the queue contains at least one element. Hence, the first thing dequeue does is check if the queue is empty. We can detect an empty queue by checking if the head node is the last node in the linked list. Being the last node in the linked list corresponds to having the “out” node be None. If this is the case, then the queue is empty and the function returns None. Otherwise, there is a node just after the head node, which is the first node of the queue. To dequeue it, we first read the associated value, and next we swing the head pointer to it, making it the new head node. Finally, we return the value we read.


Since all of these operations interact with the queue, we shall only perform them after having acquired h_{lock} .

Figure 3.3 illustrates running dequeue on a non-empty queue. Note that the only change is that the head pointer is swung to the next node in the linked list; the old head node is not deleted, it just becomes unreachable from the head pointer. In this way, the linked list only ever grows.


```

1  initialize  $\triangleq$ 
2    let node = ref (None, ref (None)) in
3    let H_lock = newLock() in
4    let T_lock = newLock() in
5    ref ((ref (node), ref (node)), (H_lock, T_lock))


```



(a) Queue after creating the new node $(\ell_{3_in}, w_3, \ell_{3_out})$ to be added to the queue.



(b) Queue after adding the new node to linked list.



(c) Queue after swinging tail pointer to the new node.

Figure 3.2: Enqueuing an element to a queue with one element.




Figure 3.3: Dequeueing an element (w_2) from a queue with two elements (w_2, w_3) . The dotted line represents the state before the dequeue, and the dashed line is the state after dequeuing.

```

1 enqueue  $Q$   $value \triangleq$ 
2   let  $node = \text{ref}(\text{Some } value, \text{ref}(\text{None}))$  in
3   acquire( $\text{snd}(\text{snd}(!Q))$ );
4    $\text{snd}(!(\text{snd}(\text{fst}(!Q)))) \leftarrow node$ ;
5    $\text{snd}(\text{fst}(!Q)) \leftarrow node$ ;
6   release( $\text{snd}(\text{snd}(!Q))$ )

1 dequeue  $Q \triangleq$ 
2   acquire( $\text{fst}(\text{snd}(!Q))$ );
3   let  $node = !(\text{fst}(\text{fst}(!Q)))$  in
4   let  $new\_head = !(\text{snd}(!node))$  in
5   if  $new\_head = \text{None}$  then
6     release( $\text{fst}(\text{snd}(!Q))$ );
7     None
8   else
9     let  $value = \text{fst}(!new\_head)$  in
10     $\text{fst}(\text{fst}(!Q)) \leftarrow new\_head$ ;
11    release( $\text{fst}(\text{snd}(!Q))$ );
12     $value$ 

```

Chapter 4

Sequential Specification

4.1 Defining a Sequential Specification

Let us first prove a specification for the Two-Lock M&S-Queue in the simple case where we don't allow for concurrency. In this case, we know that only a single thread will interact with the queue at any given point in a sequential manner. The specification we give will track the exact contents of the queue. To this end, we shall define the abstract state of the queue, denoted xs_v as a list of HeapLang values. I.e. $xs_v : List\ Val$. We adopt the convention that enqueueing an element is done by adding it to the front of the list, and dequeueing removes the last element of the list (if such an element exists). The reason for this choice is purely technical.

Since the queue uses two locks, we will need two ghost names; one for each lock (see specification of lock). For this specification, these are the only two ghost names we will need. However, for the later specifications, we will use more resource algebra, and will need more ghost names. Thus, to ease notation, we shall define the type “*SeqQnames*” whose purpose is to keep track of the ghost names used for a specific queue. Since we only have two ghost names for this specification, elements of *SeqQnames* will simply be pairs of ghost names. For an element $Q_\gamma \in SeqQnames$, the first element of the pair, written $Q_\gamma.\gamma_{Hlock}$, will contain the ghost name for the head lock, and the second element, $Q_\gamma.\gamma_{Tlock}$, the ghost name for the tail lock.

The sequential specification we wish to prove is the following.

Lemma 1 (Two-Lock M&S-Queue Sequential Specification).

$$\begin{aligned}
& \exists is_queue_seq : Val \rightarrow List\ Val \rightarrow SeqQnames \rightarrow Prop. \\
& \{True\} \text{ initialize } () \{v_q. \exists Q_\gamma. is_queue_seq(v_q, [], Q_\gamma)\} \\
& \wedge \quad \forall v_q, v, xs_v, Q_\gamma. \{is_queue_seq(v_q, xs_v, Q_\gamma)\} \text{ enqueue } v_q\ v \{w. is_queue_seq(v_q, (v :: xs_v), Q_\gamma)\} \\
& \wedge \quad \forall v_q, xs_v, Q_\gamma. \{is_queue_seq(v_q, xs_v, Q_\gamma)\} \\
& \quad \text{dequeue } v_q \\
& \quad \left\{ \begin{array}{l} (xs_v = [] * w = None * is_queue_seq(v_q, xs_v, Q_\gamma)) \vee \\ w. (\exists v, xs'_v. xs_v = xs'_v ++ [v] * w = Some\ v * is_queue_seq(v_q, xs'_v, Q_\gamma)) \end{array} \right\}
\end{aligned}$$

The proposition $is_queue_seq(v_q, xs_v, Q_\gamma)$ captures that the value v_q is a queue, whose content matches that of our abstract representation xs_v , and the queue uses the ghost names described by Q_γ . Note that the is_queue_seq predicate is not required to be persistent, hence it cannot be duplicated and given to multiple threads. This is the sense in which this specification is sequential.

4.2 Sequential Queue Predicate

To prove the specification, we must give a specific is_queue_seq predicate. To help guide us in designing this, we give the following observations about the behaviour of the implementation.

1. The head node always points to the first node in the queue (or None if the queue is empty).

2. The tail node is always either the last or second last node in the linked list.
3. All but the last pointer in the linked list (the pointer to None) never change.

Observation 2 captures the fact that, while enqueueing, a new node is first added to the linked list, and then later the tail pointer is updated to point to the newly added node. Since only one thread can enqueue a node at a time (due to the lock), then the tail pointer will only ever point to the last or second last node. However, in a sequential setting, the tail will always appear to point to the last node, as no one can inspect the queue while the tail points to the second last.

Insight 3 means that we can mark all pointers in the queue, except the pointer to None, as persistent. This is technically not needed in the sequential case, but we will incorporate it now, as we will need it in the concurrent setting anyway.

With these points in mind, we give our definition of the queue predicate for the sequential specification and explain it afterwards.

Definition 4.2.1 (Two-Lock M&S-Queue - `is_queue_seq` Predicate).

$$\begin{aligned}
\text{is_queue_seq}(v_q, xs_v, Q_\gamma) \triangleq & \exists \ell_{\text{queue}}, \ell_{\text{head}}, \ell_{\text{tail}} \in \text{Loc}. \exists h_{\text{lock}}, t_{\text{lock}} \in \text{Val}. \\
& v_q = \ell_{\text{queue}} * \ell_{\text{queue}} \mapsto^\square ((\ell_{\text{head}}, \ell_{\text{tail}}), (h_{\text{lock}}, t_{\text{lock}})) * \\
& \exists xs_{\text{queue}} \in \text{List}(\text{Loc} \times \text{Val} \times \text{Loc}). \exists x_{\text{head}}, x_{\text{tail}} \in (\text{Loc} \times \text{Val} \times \text{Loc}). \\
& \text{proj_val}(xs_{\text{queue}}) = \text{wrap_some}(xs_v) * \\
& \text{isLL}(xs_{\text{queue}} \mathbin{++} [x_{\text{head}}]) * \\
& \ell_{\text{head}} \mapsto \text{in}(x_{\text{head}}) * \\
& \ell_{\text{tail}} \mapsto \text{in}(x_{\text{tail}}) * \text{isLast}(x_{\text{tail}}, (xs_{\text{queue}} \mathbin{++} [x_{\text{head}}])) * \\
& \text{isLock}(Q_\gamma \cdot \gamma_{\text{Hlock}}, h_{\text{lock}}, \text{True}) * \\
& \text{isLock}(Q_\gamma \cdot \gamma_{\text{Tlock}}, t_{\text{lock}}, \text{True})
\end{aligned}$$

This `is_queue_seq` predicate states that the value v_q is a location, which persistently points to the structure containing the head and tail pointers, and the two locks. It also connects the abstract state xs_v with the concrete state by stating that if you strip away the locations in xs_{queue} (achieved by `proj_val`) and wrap the values in the abstract state xs_v in `Some` (achieved by `wrap_some`), then the lists become equal.

Next, the predicate specifies the concrete state. There is some head node x_{head} , which the head points to. This head node and the nodes in xs_{queue} form the underlying linked list (specified using the `isLL` predicate below). There is also a tail node, which is the last node in the linked list, and the tail points to this node. The proposition `isLast`(x, xs) simply asserts the existence of some xs' , so that $xs = x :: xs'$.

Next, we have the `isLock` predicate for our two locks. Since we are in a sequential setting, the locks are superfluous, hence they simply protect `True`.

The `isLL` predicate essentially creates the structure seen in the examples of section 3.2. It is defined in two steps. Firstly, we create all the persistent pointers in the linked list using the `isLL_chain` predicate. Note that this in effect makes `isLL_chain`(xs) persistent for all xs .

Definition 4.2.2 (Linked List Chain Predicate).

$$\begin{aligned}
\text{isLL_chain}([]) & \equiv \text{True} \\
\text{isLL_chain}([x]) & \equiv \text{in}(x) \mapsto^\square (\text{val}(x), \text{out}(x)) \\
\text{isLL_chain}(x :: x' :: xs) & \equiv \text{in}(x) \mapsto^\square (\text{val}(x), \text{out}(x)) * \text{out}(x') \mapsto^\square \text{in}(x') * \text{isLL_chain}(x' :: xs)
\end{aligned}$$

Then, to define `isLL`, we add that the last node in the linked list points to None.

Definition 4.2.3 (Linked List Predicate).

$$\begin{aligned}
\text{isLL}([]) & \equiv \text{True} \\
\text{isLL}(x :: xs) & \equiv \text{out}(x) \mapsto \text{None} * \text{isLL_chain}(x :: xs)
\end{aligned}$$

For instance, if we wanted to capture the linked list in figure 3.2c, we would use the list $xs = [(\ell_{3_in}, w_3, \ell_{3_out}); (\ell_{2_in}, w_2, \ell_{2_out}); (\ell_{1_in}, w_1, \ell_{1_out})]$. $\text{isLL}(xs)$ will expand to $\ell_{3_out} \mapsto \text{None} * \text{isLL_chain}(xs)$, and $\text{isLL_chain}(xs)$ expands to

$$\begin{aligned}\ell_{3_in} &\mapsto^\square (w_3, \ell_{3_out}) * \ell_{2_out} \mapsto^\square \ell_{3_in} * \\ \ell_{2_in} &\mapsto^\square (w_2, \ell_{2_out}) * \ell_{1_out} \mapsto^\square \ell_{2_in} * \\ \ell_{1_in} &\mapsto^\square (w_1, \ell_{1_out})\end{aligned}$$

Note how this matches the structure of the linked list in figure 3.2c.

The proofs require us manipulate specific isLL propositions quite a bit – appendix **►Add appendix and refer to it◄** shows the specific lemmas we will use, but the proof outlines will generally not mention the lemmas explicitly.

4.3 Proof Outline

Initialise

Lemma 2 (Two-Lock M&S-Queue Sequential Specification - Initialise).

$$\{\text{True}\} \text{ initialize } () \{v_q. \exists Q_\gamma. \text{is_queue_seq}(v_q, [], Q_\gamma)\}$$

Proof. Proving the initialise specification amounts to stepping through the code, giving us the required resources, and then using these to create an instance of is_queue_seq with the obtained resources. To begin with, we step through line 2 which creates the first node $x_1 = (\ell_{1_in}, \text{None}, \ell_{1_out})$ with $\ell_{1_out} \mapsto \text{None}$ and $\ell_{1_in} \mapsto (\text{None}, \ell_{1_out})$. We can then update the latter points-to proposition to become persistent, giving us $\ell_{1_in} \mapsto^\square (\text{None}, \ell_{1_out})$. Next, on lines 3 and 4, we create the two locks. We use the specification for newLock for each of its invocations. Both times, we specify that the lock should protect True . This gives us two ghost names, $\gamma_{\text{Hlock}}, \gamma_{\text{Tlock}}$, which we will collect in a SeqQgnames pair, Q_γ . Finally, we step through the allocations of the head, tail, and queue pointers on line 5. This gives us locations $\ell_{\text{head}}, \ell_{\text{tail}}, \ell_{\text{queue}}$, such that both ℓ_{head} and ℓ_{tail} point to node x_1 , and such that ℓ_{queue} points to the structure containing the head and tail pointers, and the two locks. This last points to predicate we update to become persistent. With this, we now have all the resources needed to prove the post-condition. Proving this follows by a sequence of framing away the resources we obtained and instantiating existentials with the values we got above. Most noteworthy, we pick the empty list for xs_{queue} , and node x_1 for x_{head} and x_{tail} . \square

Enqueue

Lemma 3 (Two-Lock M&S-Queue Sequential Specification - Enqueue).

$$\forall v_q, v, xs_v, Q_\gamma. \{\text{is_queue_seq}(v_q, xs_v, Q_\gamma)\} \text{ enqueue } v_q \ v \{w. \text{is_queue_seq}(v_q, (v :: xs_v), Q_\gamma)\}$$

Proof. We assume the pre-condition $\text{is_queue_seq}(v_q, xs_v, Q_\gamma)$ which tells us that v_q is some location ℓ_{queue} , and in particular, we have following:

$$\ell_{\text{queue}} \mapsto^\square ((\ell_{\text{head}}, \ell_{\text{tail}}), (h_{\text{lock}}, t_{\text{lock}})) \quad (4.1)$$

$$\text{proj_val}(xs_{\text{queue}}) = \text{wrap_some}(xs_v) \quad (4.2)$$

$$x_{\text{tail}} \mapsto \text{None} * \text{isLL_chain}(xs_{\text{queue}} ++ [x_{\text{head}}]) \quad (4.3)$$

$$\ell_{\text{tail}} \mapsto \text{in}(x_{\text{tail}}) * \text{isLast}(x_{\text{tail}}, (xs_{\text{queue}} ++ [x_{\text{head}}])) \quad (4.4)$$

$$\text{isLock}(Q_\gamma. \gamma_{\text{Tlock}}, t_{\text{lock}}, \text{True}) \quad (4.5)$$

We proceed to step into the enqueue function. Firstly, on line 2, we create a new node x_{new} , with $\text{val}(x_{\text{new}}) = \text{Some } v$. Next, on line 3 we acquire the tail lock. We step through the dereference and the projections using 4.1. To acquire the lock we use the acquire specification with 4.5. This gives us $\text{locked}(Qg. \gamma_{\text{Tlock}})$ and True .

Line 4 adds node x_{new} to the linked list. We first use 4.1 to step to the dereference of ℓ_{tail} . From 4.4, we know the dereference results in $\text{in}(x_{\text{tail}})$. Because x_{tail} is in the linked list, we can use 4.3 to

conclude that x_{tail} is a node, and hence we can perform the load and the projection to get to the final store operation: $\text{out}(x_{\text{tail}}) \leftarrow \text{in}(x_{\text{new}})$. Using the points-to proposition from 4.3, we perform the store, which in turn gives us $\text{out}(x_{\text{tail}}) \mapsto \text{in}(x_{\text{new}})$. We make this persistent and combine it with the isLL_chain proposition from 4.3 to conclude $\text{isLL}(x_{\text{new}} :: xs_{\text{queue}} ++ [x_{\text{head}}])$.

The next line (line 5) swings the tail pointer to x_{new} . 4.4 and 4.4 gives us all the required resources to step through the code and perform the store. Afterwards, we get $\ell_{\text{tail}} \mapsto \text{in}(x_{\text{new}})$.

Finally, we get to line 6 which releases the lock. We use the specification for release, giving up $\text{locked}(Q_{\gamma}.\gamma_{\text{lock}})$. The only thing left is to prove the postcondition: $\text{is_queue_seq}(v_q, (v :: xs_v), Q_{\gamma})$. For the existentials, we pick $x_{\text{new}} :: xs_{\text{queue}}$ as the queue, and as the tail node, we chose x_{new} . The remaining choices are similar to those we got from the pre-condition. With these choices, the remaining proof obligations become straightforward; we already have the required pointers and the isLL proposition. The relationship between the abstract and concrete states follows from $\text{val}(x_{\text{new}}) = \text{Some } v$ and 4.2. \square

Deque

Lemma 4 (Two-Lock M&S-Queue Sequential Specification - Dequeue).

$$\begin{aligned} & \forall v_q, xs_v, Q_{\gamma}. \{ \text{is_queue_seq}(v_q, xs_v, Q_{\gamma}) \} \\ & \quad \text{dequeue } v_q \\ & \quad \left\{ \begin{array}{l} (xs_v = [] * w = \text{None} * \text{is_queue_seq}(v_q, xs_v, Q_{\gamma})) \vee \\ w. (\exists v, xs'_v. xs_v = xs'_v ++ [v] * w = \text{Some } v * \text{is_queue_seq}(v_q, xs'_v, Q_{\gamma})) \end{array} \right\} \end{aligned}$$

Proof. We assume the pre-condition $\text{is_queue_seq}(v_q, xs_v, Q_{\gamma})$ which gives us that v_q is some location ℓ_{queue} , and the following propositions.

$$\ell_{\text{queue}} \mapsto^{\square} ((\ell_{\text{head}}, \ell_{\text{tail}}), (h_{\text{lock}}, t_{\text{lock}})) \quad (4.6)$$

$$\text{proj_val}(xs_{\text{queue}}) = \text{wrap_some}(xs_v) \quad (4.7)$$

$$x_{\text{tail}} \mapsto \text{None} * \text{isLL_chain}(xs_{\text{queue}} ++ [x_{\text{head}}]) \quad (4.8)$$

$$\ell_{\text{head}} \mapsto \text{in}(x_{\text{head}}) * \quad (4.9)$$

$$\text{isLock}(Q_{\gamma}.\gamma_{\text{Hlock}}, h_{\text{lock}}, \text{True}) \quad (4.10)$$

We perform the function application and step into the function. We first do the superfluous acquire on line 2 using the acquire spec and 4.10. This gives us $\text{locked}(Q_{\gamma}.\gamma_{\text{Hlock}})$.

Next we step to line 3 which dereferences the head node. We perform the loads and projections using 4.6 and 4.9, which tells us that the *node* variable becomes $\text{in}(x_{\text{head}})$. From 4.8, we know that x_{head} is in the linked list, hence it must be a node.

We step to line 4 which finds out what x_{head} points to. As x_{head} is a node, we can step to the load: $!(\text{out}(x_{\text{head}}))$. The result of this load is either None or another node $x_{\text{head_next}}$, depending on whether or not xs_{queue} is empty. So we consider both cases.

Case xs_{queue} is empty: In this case, 4.8 simply asserts $\text{isLL}[x_{\text{head}}]$, which by definition tells us that $x_{\text{head}} \mapsto \text{None}$. Hence, the “if” on line 5 will take the “then” branch, so we step to line 6. Here we release the lock, giving up $\text{locked}(Q_{\gamma}.\gamma_{\text{Hlock}})$, and return None on the next line. What remains is to prove the post-condition with $w = \text{None}$. We can easily do this by proving the first disjunction. From 4.7 with the fact that $xs_{\text{queue}} = []$ we can conclude that xs_v is empty, and since we haven’t modified the queue, we can prove $\text{is_queue_seq}(v_q, xs_v, Q_{\gamma})$ using the same resources we got from the pre-condition.

Case xs_{queue} is not empty: In this case, we can conclude that there must be some node $x_{\text{head_next}}$, which is the first node in xs_{queue} . I.e.

$$xs_{\text{queue}} = xs'_{\text{queue}} ++ [x_{\text{head_next}}] \quad (4.11)$$

We can thus use the isLL predicate to conclude that x_{head} must point to $x_{\text{head_next}}$. Hence the “else” branch will be taken, so we step to line 12. Since $x_{\text{head_next}}$ is part of the linked list, it must be a node, allowing us to extract its value $\text{val}(x_{\text{head_next}})$ in the first line of the else branch.

We step to line 10 which swings the head pointer, ℓ_{head} to $x_{\text{head_next}}$. We perform these steps using 4.6 and 4.9, which then gives us $\ell_{\text{head}} \mapsto \text{in}(x_{\text{head_next}})$. Finally, we release the lock on line 11, giving up $\text{locked}(Q_\gamma.\gamma_{\text{Hlock}})$ and return the value: $\text{val}(x_{\text{head_next}})$. We must now prove the post-condition with $w = \text{val}(x_{\text{head_next}})$, and this time we prove the second disjunct. From 4.7 and 4.11 we can deduce

$$xs_v = xs'_v ++ [v] \quad (4.12)$$

$$\text{proj_val}(xs'_{\text{queue}}) = \text{wrap_some}(xs'_v) \quad (4.13)$$

$$\text{val}(x_{\text{head_next}}) = \text{Some } v \quad (4.14)$$

4.12 and 4.14 proves the first part of the post-condition. What remains is to show $\text{is_queue_seq}(v_q, xs'_v, Q_\gamma)$. For the existentials, we pick xs'_{queue} as the queue and $x_{\text{head_next}}$ as the head node. The rest are similar to the variables we got from the pre-condition. With these choices, we can prove the predicate using the resources we have established.

□

Chapter 5

Concurrent Specification

5.1 Defining a Concurrent Specification

For the concurrent specification, we will need the queue predicate (here denoted `is_queue_conc`) to be duplicable. To achieve this, we shall initially give up on tracking the abstract state of the queue, and instead add a predicate Φ , which we will ensure holds for all elements in the queue. In this way, when dequeuing, we at least know that if we get some value, then Φ holds of this value. The specification we wish to prove is as follows.

Lemma 5 (Two-Lock M&S-Queue Concurrent Specification).

$$\begin{aligned}
& \exists \text{is_queue_conc} : (Val \rightarrow \text{Prop}) \rightarrow Val \rightarrow \text{ConcQghostnames} \rightarrow \text{Prop}. \\
& \forall \Phi : Val \rightarrow \text{Prop}. \\
& \quad \forall v_q, Q_\gamma. \text{is_queue_conc}(\Phi, v_q, Q_\gamma) \implies \Box \text{is_queue_conc}(\Phi, v_q, Q_\gamma) \\
& \quad \wedge \{ \text{True} \} \text{ initialize } () \{ v_q. \exists Q_\gamma. \text{is_queue_conc}(\Phi, v_q, Q_\gamma) \} \\
& \quad \wedge \forall v_q, v, Q_\gamma. \{ \text{is_queue_conc}(\Phi, v_q, Q_\gamma) * \Phi(v) \} \text{ enqueue } v_q \ v \{ w. \text{True} \} \\
& \quad \wedge \forall v_q, Q_\gamma. \{ \text{is_queue_conc}(\Phi, v_q, Q_\gamma) \} \text{ dequeue } v_q \{ w. w = \text{None} \vee (\exists v. w = \text{Some } v * \Phi(v)) \}
\end{aligned}$$

Note that the type of the collection of ghost names here is *ConcQghostnames*, as we will require more ghost names than before. The new ghost names are used for “tokens” which are introduced in the following section.

5.2 Concurrent Queue Predicate

As we did for the sequential specification, we note here some useful observations about the implementation.

1. Nodes in the linked list are never deleted. Hence, the linked list only ever grows.
2. The tail can lag one node behind the head.
3. At any given time, the queue is in one of four states:
 - (a) No threads are interacting with the queue (**Static**)
 - (b) A thread is enqueueing (**Enqueue**)
 - (c) A thread is dequeuing (**Dequeue**)
 - (d) A thread is enqueueing and a thread is dequeuing (**Both**)

Observation 2 might seem a little surprising, and indeed it stands in contrast to property 5 in [4], which states “Tail always points to a node in the linked list, because it never lags behind Head, so it can never point to a deleted node.”. I also didn’t realise this possibility until a proof attempt using a model that “forgot” old nodes lead to an unprovable case (see section 5.4.1). The situation can occur when the

queue is empty, and a thread performs an incomplete enqueue; it attaches the new node to the end, but before it can swing the tail to this new node, another thread performs a dequeue, which dequeues this new node, swinging the head to it. Now the tail is lagging a node behind the head.

It is not possible for the tail to point more than one node behind the head, as in order for this to happen, more nodes must be enqueued, but this can't happen before the current enqueue finishes, which will update the tail and bring it up to speed with the head.

Fortunately, this isn't an issue for safety, but a consequence of this possibility is that when modelling the queue, we must remember at least one "old" node (i.e. a dequeued node), as the tail might be pointing to this node. For the sake of simplicity in the model, the choice is made to remember an arbitrary amount of old nodes, which is represented by the list xs_{old} .

Observation 3 is a simple consequence of the implementation using two locks.

Since we want `is_queue_conc` to be persistent, then we cannot directly state the points-to predicates as we did in the sequential case. However, we will still need all the same resources to be able to prove the specification. The solution is to have an *invariant* which describes the concrete state of the queue. In the proofs, when we need access to some resource, we shall then access it by opening the invariant. We now present the invariant and explain it afterwards.

Definition 5.2.1 (Two-Lock M&S-Queue Concurrent Invariant).

$$\begin{aligned}
& I_{TLC}(\Phi, \ell_{head}, \ell_{tail}, Q_\gamma) \triangleq \\
& \exists xs_v. \text{All}(xs_v, \Phi) * \quad \text{(abstract state)} \\
& \exists xs, xs_{queue}, xs_{old}, x_{head}, x_{tail}. \quad \text{(concrete state)} \\
& xs = xs_{queue} ++ [x_{head}] ++ xs_{old} * \\
& isLL(xs) * \\
& proj_val(xs_{queue}) = wrap_some(xs_v) * \\
& (\\
& \quad \ell_{head} \mapsto in(x_{head}) * \ell_{tail} \mapsto in(x_{tail}) * isLast(x_{tail}, xs) * \quad \text{(Static)} \\
& \quad ToknE \ Q_\gamma * ToknD \ Q_\gamma * TokUpdated \ Q_\gamma \\
& \vee \\
& \quad \ell_{head} \mapsto in(x_{head}) * \ell_{tail} \mapsto \frac{1}{2} in(x_{tail}) * \quad \text{(Enqueue)} \\
& \quad (isLast(x_{tail}, xs) * TokBefore \ Q_\gamma \vee isSndLast(x_{tail}, xs) * TokAfter \ Q_\gamma) * \\
& \quad TokE \ Q_\gamma * ToknD \ Q_\gamma \\
& \vee \\
& \quad \ell_{head} \mapsto \frac{1}{2} in(x_{head}) * \ell_{tail} \mapsto in(x_{tail}) * isLast(x_{tail}, xs) * \quad \text{(Dequeue)} \\
& \quad ToknE \ Q_\gamma * TokD \ Q_\gamma * TokUpdated \ Q_\gamma \\
& \vee \\
& \quad \ell_{head} \mapsto \frac{1}{2} in(x_{head}) * \ell_{tail} \mapsto \frac{1}{2} in(x_{tail}) * \quad \text{(Both)} \\
& \quad (isLast(x_{tail}, xs) * TokBefore \ Q_\gamma \vee isSndLast(x_{tail}, xs) * TokAfter \ Q_\gamma) * \\
& \quad TokE \ Q_\gamma * TokD \ Q_\gamma \\
&)
\end{aligned}$$

In contrast to the sequential specification, the abstract state is now existentially quantified, hence the exact contents of the queue are not tracked. Instead, we have added the proposition $\text{All}(xs_v, \Phi)$, which states that all values in xs_v (i.e. the values currently in the queue) satisfy the predicate Φ . This will allow us to conclude that dequeued values satisfy Φ .

The concrete state of the queue is still reflected in the abstract state through projecting out the values of the nodes (`proj_val`), and wrapping the values in the queue in `Some` (`wrap_some`). Another difference is that we now also keep track of an arbitrary number of "old" nodes; nodes that are behind the head node, x_{head} . As discussed above, this inclusion is due to observation 2.

As before, we also assert that the concrete state forms a linked list, as described by the `isLL` predicate. The final part of the invariant describes the four possible states of the queue, as described in 3. Since the

resources used by the queue are inside an invariant, and enqueueing/dequeueing threads need to access the resources of the queue multiple times (as shown in the sequential specification), then we will have to open and close the invariant multiple times. Each time we open the invariant, the existentially quantified variables will not be the same as those from early accesses of the invariant (as they are existentially quantified). Thus, the threads must be able to “match up” variables from previous accesses to later accesses. The way we shall achieve this is by allowing threads to keep a *fraction* of the points-to predicate that it is using. For instance, an enqueueing thread will have to access the points-to predicate concerning ℓ_{tail} multiple times, and in between accesses of the invariant, it can get to keep half of the points-to predicate. Thus, when it opens the invariant later, it will have $\ell_{\text{tail}} \mapsto \frac{1}{2} \text{in}(x_{\text{tail}})$ from an earlier access, and it will obtain the existence of some new x'_{tail} , such that $\ell_{\text{tail}} \mapsto \frac{1}{2} \text{in}(x'_{\text{tail}})$. Combining the two points-to predicates allows us to conclude that $\text{in}(x_{\text{tail}}) = \text{in}(x'_{\text{tail}})$ and using lemma 28 we can further conclude $x_{\text{tail}} = x'_{\text{tail}}$. In this way, we can match up variables from earlier accesses to variables in later accesses. In the **Static** state where no thread is interacting with the queue, the queue owns all of the points-to predicates concerning the head and tail.

In the **Enqueue** state, the enqueueing thread owns half of the tail pointer, and we distinguish between two cases, as discussed in 2: either the enqueueing thread has yet to add the new node to the linked list and x_{tail} is still the last node, or the new node has been added, but the tail pointer hasn’t been updated, meaning that x_{tail} is the second last node (isSndLast is defined similarly to isLast).

In the **Dequeue** state, the dequeueing thread owns half of the head pointer, and the tail is as in the **Static** state.

Finally, the **Both** state is essentially a combination of the **Enqueue** and **Dequeue** states.

To track which state the queue is in, we use *tokens*. Tokens are defined using the exclusive resource algebra on the singleton set: $\text{EX}()$. This resource algebra only has one valid element, and combining two elements will give the non-valid element \perp . Thus, if we own a particular token, then, upon opening the invariant, we can rule out certain states simply because they mention the token we own.

We will use several tokens, each of which is the valid element of their own instance of $\text{EX}()$. Different instances are distinguish between using ghost names. Hence, each token will be represented by a ghost name. As we did for the sequential specification, we group these ghost names into a tuple Q_γ , and write, for instance $\text{TokE } Q_\gamma$ to refer to the valid element of a particular instance. We proceed to explain the meaning of each of the tokens used in the invariant.

- $\text{ToknE } Q_\gamma$ represents that no threads are enqueueing.
- $\text{TokE } Q_\gamma$ represents that a thread is enqueueing.
- $\text{ToknD } Q_\gamma$ represents that no threads are dequeueing.
- $\text{TokD } Q_\gamma$ represents that a thread is dequeueing.
- $\text{TokBefore } Q_\gamma$ represents that an enqueueing thread has not yet added the new node to the linked list.
- $\text{TokAfter } Q_\gamma$ represents that an enqueueing thread has added the new node to the linked list, but not yet swung the tail.
- $\text{TokUpdated } Q_\gamma$ is defined as $\text{TokBefore } Q_\gamma * \text{TokAfter } Q_\gamma$, and represents that the queue is up to date.

Note: The concurrent specification for the Two-Lock M&S-Queue *can* be proven using queue invariant 5.2.1 directly, and the proof outline below will also be using this. However, a simpler (but arguably less intuitive) queue invariant was discovered. This simpler invariant is equivalent to 5.2.1 and has the benefit of being easier to work with in the mechanised proofs. Thus, in the mechanised proofs, we always rewrite to the simpler invariant when opening the invariant. The simpler invariant can be found in the appendix (A.0.1).

With this, we can now give our definition of `is_queue_conc`. In the below, we let \mathcal{N} be some namespace.

Definition 5.2.2 (Two-Lock M&S-Queue - `is_queue_conc` Predicate).

$$\begin{aligned}
\text{is_queue_conc}(\Psi, v_q, Q_\gamma) &\triangleq \exists \ell_{\text{queue}}, \ell_{\text{head}}, \ell_{\text{tail}} \in \text{Loc}. \exists h_{\text{lock}}, t_{\text{lock}} \in \text{Val}. \\
v_q &= \ell_{\text{queue}} * \ell_{\text{queue}} \mapsto^\square ((\ell_{\text{head}}, \ell_{\text{tail}}), (h_{\text{lock}}, t_{\text{lock}})) * \\
&\boxed{\text{ITLC}(\Phi, \ell_{\text{head}}, \ell_{\text{tail}}, Q_\gamma)}^{\mathcal{N}.\text{queue}} * \\
&\text{isLock}(Q_\gamma.\gamma_{\text{Hlock}}, h_{\text{lock}}, \text{TokD } Q_\gamma) * \\
&\text{isLock}(Q_\gamma.\gamma_{\text{Tlock}}, t_{\text{lock}}, \text{TokE } Q_\gamma).
\end{aligned}$$

In contrast to the sequential specification, the locks now protect `TokE` Q_γ and `TokD` Q_γ . The idea is that, when an enqueueing thread obtains t_{lock} , they will obtain the `TokE` Q_γ token, which allows them to conclude that the queue state is either **Static** or **Dequeue**. Similarly for a dequeuing thread.

5.3 Linearisation Points

An important notion for concurrent algorithms is *linearisability* [2]. Linearisability is a non-blocking property¹ that helps reason about which behaviours are possible. Both versions of the M&S-Queue are linearisable, which rules out undesired behaviours.

One way to characterise linearisability is through the concept of *linearisation points*. We say that a function (such as enqueue or dequeue) is linearisable, if all invocations of the function have a linearisation point somewhere between the invocation and the response. Further, the effects of the function appear to occur instantaneously at the linearisation point; a single, atomic instruction performs the desired change that the function must carry out.

For example, enqueue has a single linearisation point at the instruction that appends the newly created node to the linked list (the store on line 4). At exactly that point, the effect of the enqueue takes place. dequeue is slightly more complicated as it has multiple linearisation points. If the queue is empty when we read the head node's out pointer on line 4, then at that read, the dequeue function is guaranteed to return `None`, interpreting the queue as empty. In this case the dequeue doesn't change the queue but merely observes it, and the observation happens exactly at the read of the head node's out pointer, making it the linearisation point.

On the hand, if the queue was not empty at that point, then the linearisation point is at line 10, when we swing the head pointer. At that very store operation, the effect of dequeue occurs.

Linearisation points are closely tied to updates of the abstract state of the queue. The abstract state of the queue changes only at linearisation points. This is consistent with the notion that the effects of the function takes effect at the linearisation points – updates to the abstract state happen atomically as we would intuitively want it to. This link to the abstract state becomes even more prevalent when we introduce Hocap-style specifications in chapter 6.

5.4 Proof Outline

Firstly, we must show that `is_queue_conc` is persistent. This however follows from the fact that invariants are persistent, the `isLock` predicates are persistent, persistent points-to predicates are persistent, and persistency is preserved by $*$ and quantifications (rules: `persistently-sep`, `persistently- \wedge` , `persistently- \exists`).

The proofs of the three specifications largely have the same structure as the sequential counterparts. The major difference is that we don't have access to the resources all the time; we must get them from the invariant. Further we also have to keep track of which state we are in. For the proof outlines below, these points will be the main focus.

Initialise

Lemma 6 (Two-Lock M&S-Queue Concurrent Specification - Initialise).

$$\frac{\{\text{True}\} \text{ initialize } () \{v_q. \exists Q_\gamma. \text{is_queue_conc}(\Phi, v_q, Q_\gamma)\}}{}$$

¹Other properties, such as serialisability, inherently require implementations to be blocking. Linearisability does not require this, but linearisable algorithms can of course still be blocking.

Proof. We first step through line 2 which gives us the head node of the linked list. Following this, we must create the two locks. As the locks had to protect tokens, we must first create these. To create the two tokens, we use the ghost-alloc $\blacktriangleright\text{ref}\blacktriangleleft$ rule twice, which gives us two ghost names, one for each of the tokens. We put the ghost names into a tuple Q_γ , and write TokE Q_γ and TokD Q_γ for the two ghost resources created by the ghost-alloc $\blacktriangleright\text{ref}\blacktriangleleft$ rule. We then use the newLock specification to step through the code and create the locks, giving up the two tokens. Next, we step to line 5 and create the ℓ_{queue} , ℓ_{head} , and ℓ_{tail} pointers with $\ell_{\text{queue}} \mapsto ((\ell_{\text{head}}, \ell_{\text{tail}}), (h_{\text{lock}}, t_{\text{lock}}))$. We make this persistent.

All that remains then is to prove the postcondition; the `is_queue_conc` predicate. We have both the points-to predicate of ℓ_{queue} and the two `isLock` predicates (from the newLock specification). So all that remains is the invariant.

We create I_{TLC} in the **Static** state, most of which is analogous to the sequential specification. However, we will also need to supply the tokens required by the **Static** state. Thus, we allocate the four tokens ToknE Q_γ , ToknD Q_γ , TokBefore Q_γ , and TokAfter Q_γ in the same way we allocated TokE Q_γ and TokD Q_γ . We combine TokBefore Q_γ and TokAfter Q_γ to get TokUpdated Q_γ , and we now have all the tokens we need to create I_{TLC} in the **Static** state. To create the invariant from I_{TLC} , we use the Inv-alloc rule $\blacktriangleright\text{ref}\blacktriangleleft$. \square

Enqueue

Lemma 7 (Two-Lock M&S-Queue Concurrent Specification - Enqueue).

$$\forall v_q, v, Q_\gamma. \{ \text{is_queue_conc}(\Phi, v_q, Q_\gamma) * \Phi(v) \} \text{ enqueue } v_q \ v \ \{ w.\text{True} \}$$

Proof. We assume the pre-condition, which tells us that v_q is a location ℓ_{queue} , and we have:

$$\Phi(v) \tag{5.1}$$

$$\ell_{\text{queue}} \mapsto^\square ((\ell_{\text{head}}, \ell_{\text{tail}}), (h_{\text{lock}}, t_{\text{lock}})) \tag{5.2}$$

$$\boxed{I_{\text{TLC}}(\Phi, \ell_{\text{head}}, \ell_{\text{tail}}, Q_\gamma)}^{\mathcal{N}.queue} \tag{5.3}$$

$$\text{isLock}(Q_\gamma.\gamma\text{Tlock}, t_{\text{lock}}, \text{TokE } Q_\gamma) \tag{5.4}$$

We perform the function application and step into enqueue to line 2. We create the new node as before, giving us x_{new} , with $\text{val}(x_{\text{new}}) = \text{Some } v$.

On line 3 we then use the acquire specification with 5.4 to acquire $\text{locked}(Q_\gamma.\gamma\text{Tlock})$ and TokE Q_γ .

Following this, we step to line 4. Using 5.2 we can step to the load of ℓ_{tail} . This is where we meet our first challenge; in order to perform the store, we must open the invariant to access the points-to predicate regarding ℓ_{tail} .

As invariants can only be opened if the expression being considered is atomic, we use a bind rule to “focus” on the load of ℓ_{tail} . We proceed to open the invariant, and since we have TokE Q_γ , we know that the queue is in state **Static** or **Dequeue**. In any case, we get that $\ell_{\text{tail}} \mapsto \text{in}(x_{\text{tail}})$, for some x_{tail} which is the last node in the linked list. As x_{tail} is in the linked list, we further deduce that it is a node.

We can now perform the load of ℓ_{tail} which results in $\text{in}(x_{\text{tail}})$. We must now close the invariant. We split up the points-to predicate $\ell_{\text{tail}} \mapsto \text{in}(x_{\text{tail}})$ in two, which leaves us with two of $\ell_{\text{tail}} \mapsto^{\frac{1}{2}} \text{in}(x_{\text{tail}})$. We keep one of them, and use the other to close the invariant in the before case of state **Enqueue** or **Both**, depending on which state we opened the invariant into. By doing this, we give up TokE Q_γ , but we gain ToknE Q_γ and TokAfter Q_γ .

As x_{tail} was a node we can step to $\text{out}(x_{\text{tail}}) \leftarrow \text{in}(x_{\text{new}})$. However, the points-to predicate concerning $\text{out}(x_{\text{tail}})$ isn't persistent, and is hence inside the invariant. We thus have to open the invariant again. Since we have ToknE Q_γ and TokAfter Q_γ , we know that we are in the before case of either state **Enqueue** or **Both**.

The invariant hence gives us $\ell_{\text{tail}} \mapsto^{\frac{1}{2}} \text{in}(x'_{\text{tail}})$ for some x'_{tail} . However, since we kept $\ell_{\text{tail}} \mapsto^{\frac{1}{2}} \text{in}(x_{\text{tail}})$, we can combine these, allowing us to conclude that $\text{in}(x_{\text{tail}}) = \text{in}(x'_{\text{tail}})$. As both x_{tail} and x'_{tail} are nodes, we apply 28 to conclude $x_{\text{tail}} = x'_{\text{tail}}$. This now gives us that $\text{out}(x_{\text{tail}}) \mapsto \text{None}$, allowing us to perform the store. Thus, x_{new} is added to the linked list, and this is a linearisation point. As such we must update the abstract state to reflect the change. We do this by closing the invariant with $v :: x_{s_v}$ as the abstract state, where x_{s_v} is the abstract state we got when we opened the invariant. Note that we have $\Phi(v)$ (from 5.1), hence we will be able to conclude $\text{All}((v :: x_{s_v}), \Phi)$. For the concrete state, we pick $x_{\text{new}} :: xs$,

where xs is the concrete state we got when we opened the invariant. We close the invariant in the after case of either state **Enqueue** or **Both**, giving up TokAfter Q_γ , and obtaining TokBefore Q_γ .

We step to line 5, which swings the tail pointer to x_{new} . Using 5.2 we step to $\ell_{\text{tail}} \leftarrow \text{in}(x_{\text{new}})$. However, to perform this store we must first know that ℓ_{tail} points to something. This resource is inside the invariant, so we open the invariant one last time. Due to having ToknE Q_γ and TokBefore Q_γ , we know that we are in the after case of state **Enqueue** or **Both**. This time we get $\ell_{\text{tail}} \mapsto^{\frac{1}{2}} x''_{\text{tail}}$ for some x''_{tail} , where x''_{tail} is the *second* last node in the linked list. Hence there is some other node x'_{new} , which is the last node, with x''_{tail} pointing to it. As before, we use our half of the points-to predicate of ℓ_{tail} (i.e. $\ell_{\text{tail}} \mapsto^{\frac{1}{2}} \text{in}(x_{\text{tail}})$) to get that $x''_{\text{tail}} = x_{\text{tail}}$. Since x_{tail} points to x_{new} , and x''_{tail} points to x'_{new} , we can further conclude that $x_{\text{new}} = x'_{\text{new}}$. Thus, we can perform the store, which now gives us that ℓ_{tail} points to x_{new} ; the last node in the linked list. With this, we can close the invariant in state **Static** or **Dequeue**, giving up ToknE Q_γ and TokUpdated Q_γ , and getting TokE Q_γ .

Finally, on line 6, we release the lock which we can do since we have TokE Q_γ and locked($Q_\gamma.\gamma_{\text{lock}}$). The postcondition merely asserts **True**, so there is nothing left to prove. \square

Dequeue

Lemma 8 (Two-Lock M&S-Queue Concurrent Specification - Dequeue).

$$\forall v_q, Q_\gamma. \{\text{is_queue_conc}(\Phi, v_q, Q_\gamma)\} \text{ dequeue } v_q \{w.w = \text{None} \vee (\exists v. w = \text{Some } v * \Phi(v))\}$$

Proof. As usual, we assume the pre-condition giving us that v_q is a location ℓ_{queue} with

$$\ell_{\text{queue}} \mapsto^\square ((\ell_{\text{head}}, \ell_{\text{tail}}), (h_{\text{lock}}, t_{\text{lock}})) \quad (5.5)$$

$$\boxed{\text{ITLC}(\Phi, \ell_{\text{head}}, \ell_{\text{tail}}, Q_\gamma)}^{\mathcal{N}.queue} \quad (5.6)$$

$$\text{isLock}(Q_\gamma.\gamma_{\text{Hlock}}, h_{\text{lock}}, \text{True}) \quad (5.7)$$

We do the function application and step into dequeue. First, on line 2, we acquire the lock, which gives us locked($Q_\gamma.\gamma_{\text{Hlock}}$) and TokD Q_γ .

Next, we step to line 3 and using 5.5 we get to $!(\ell_{\text{head}})$. To perform this load, we must open the invariant. We open it in state **Static** or **Enqueue** (as we have TokD Q_γ), which gives us $\ell_{\text{head}} \mapsto \text{in}(x_{\text{head}})$ for some x_{head} . The isLL predicate further tells us that x_{head} is a node: $\text{in}(x_{\text{head}}) \mapsto^\square (\text{val}(x_{\text{head}}), \text{out}(x_{\text{head}}))$. We perform the load, and take half of the points-to predicate: $\ell_{\text{head}} \mapsto^{\frac{1}{2}} \text{in}(x_{\text{head}})$. We use the other half to close the invariant in state **Dequeue** or **Both**, giving up TokD Q_γ , but obtaining ToknD Q_γ .

We proceed to line 4, which finds out what x_{head} is pointing to. As x_{head} is a node we can step to $!(\text{out}(x_{\text{head}}))$. To perform this dereference, we must open the invariant. As we own ToknD Q_γ , the queue must be in state **Dequeue** or **Both**. In any case, we get that there is some x'_{head} with $\ell_{\text{head}} \mapsto^{\frac{1}{2}} x'_{\text{head}}$. Using the fractional points-to predicate we kept from earlier and lemma 28, we can conclude that $x'_{\text{head}} = x_{\text{head}}$. We now perform a case analysis on the contents of the queue: xs_{queue} , similarly to the sequential proof.

Case xs_{queue} is empty: In this case, we use the isLL predicate to conclude $\text{out}(x_{\text{head}}) \mapsto \text{None}$. The expression $!(\text{out}(x_{\text{head}}))$ hence resolves to **None**. At this point, we know dequeue will decide that the queue is empty, so this is a linearisation point. We close the invariant in state **Static** or **Enqueue**, giving up ToknD Q_γ and obtaining TokD Q_γ .

As new_head was set to **None**, the “if” on line 5 takes the “then” branch, so we step to line 6. We release the lock, giving up TokD Q_γ and locked($Q_\gamma.\gamma_{\text{Hlock}}$), and return **None**. We must now prove the postcondition with $w = \text{None}$. We easily prove the first disjunct.

Case xs_{queue} is not empty: As in the sequential proof, we conclude that x_{head} points to $x_{\text{head_next}}$ for some $x_{\text{head_next}}$. That is, we have the following:

$$\text{out}(x_{\text{head}}) \mapsto \text{in}(x_{\text{head_next}}) \quad (5.8)$$

$$\text{in}(x_{\text{head_next}}) \mapsto^\square (\text{val}(x_{\text{head_next}}), \text{out}(x_{\text{head_next}})) \quad (5.9)$$

We perform the dereference, which resolves to $\text{in}(x_{\text{head_next}})$. We close the invariant in **Dequeue** or **Both**, meaning we still have ToknD Q_γ and $\ell_{\text{head}} \mapsto^{\frac{1}{2}} \text{in}(x_{\text{head}})$.

This time, the “if” will take the else branch, so we step to line 12. Using 5.9, we conclude that the return value will be $\text{val}(x_{\text{head_next}})$.

Next, we step to line 10, which swings the head pointer to $x_{\text{head_next}}$. Using 5.5, we step to $\ell_{\text{head}} \leftarrow \text{in}(x_{\text{head_next}})$. Performing this store requires a points-to proposition for ℓ_{head} . Hence, we open the invariant in state **Dequeue** or **Both** (since we have $\text{ToknD } Q_\gamma$), which gives us the following:

$$\text{All}(xs_v, \Phi) \quad (5.10)$$

$$xs = xs_{\text{queue}} ++ [x''_{\text{head}}] ++ xs_{\text{old}} \quad (5.11)$$

$$\text{isLL}(xs) \quad (5.12)$$

$$\text{proj_val}(xs_{\text{queue}}) = \text{wrap_some}(xs_v) \quad (5.13)$$

$$\ell_{\text{head}} \mapsto \frac{1}{2} \text{in}(x''_{\text{head}}) \quad (5.14)$$

for some xs , xs_{queue} , x''_{head} , xs_{old} , and xs_v . We combine 5.14 with our half of the points-to predicate to conclude $\ell_{\text{head}} \mapsto \text{in}(x_{\text{head}})$ and use lemma 28 to conclude $x''_{\text{head}} = x_{\text{head}}$.

We can now perform the store, swinging the head pointer to $x_{\text{head_next}}$, which gives us $\ell_{\text{head}} \mapsto \text{in}(x_{\text{head_next}})$. This is a linearisation point, so we must update the abstract state xs_v , which we got from the invariant opening.

From 5.8 and 5.12, we can deduce that xs_{queue} isn't empty (as otherwise, we would have $x_{\text{head}} \mapsto \text{None}$ which contradicts with 5.8), and in fact, its first element must be $x_{\text{head_next}}$. That is,

$$xs_{\text{queue}} = xs'_{\text{queue}} ++ [x_{\text{head_next}}] \quad (5.15)$$

Combining this with 5.13 allows us to give a similar conclusion to the sequential proof: there exists xs'_v and v such that

$$xs_v = xs'_v ++ [v] \quad (5.16)$$

$$\text{proj_val}(xs'_{\text{queue}}) = \text{wrap_some}(xs'_v) \quad (5.17)$$

$$\text{val}(x_{\text{head_next}}) = \text{Some } v \quad (5.18)$$

By 5.10 and 5.16, we deduce $\text{All}(xs'_v, \Phi)$ and $\Phi(v)$. We are now finally ready to close the invariant. We use xs'_v for the abstract state, giving up $\text{All}(xs'_v, \Phi)$, but allowing us to keep $\Phi(v)$. For the concrete state, we use the same xs . Note that by combining 5.11 and 5.15, we have that $xs = xs'_{\text{queue}} ++ [x_{\text{head_next}}] ++ (x_{\text{head}} :: xs_{\text{old}})$, which allows us to pick xs'_{queue} as the queue, $x_{\text{head_next}}$ as the head node, and $(x_{\text{head}} :: xs_{\text{old}})$ as the old nodes. Since xs hasn't changed, we prove the isLL predicate using 5.12, and the relationship between xs'_v and xs'_{queue} follows from 5.17. Finally, we set the state of the queue to **Static** or **Enqueue**, giving up $\text{ToknD } Q_\gamma$ and $\ell_{\text{head}} \mapsto \text{in}(x_{\text{head_next}})$, and obtaining $\text{TokD } Q_\gamma$.

We step to line 11 and release the lock by giving up $\text{TokD } Q_\gamma$ and $\text{locked}(Q_\gamma.\gamma_{\text{Hlock}})$. Lastly, we return the dequeued value: $\text{val}(x_{\text{head_next}})$, meaning we must prove the post-condition with $w = \text{val}(x_{\text{head_next}})$. Recall that we got to keep $\Phi(v)$, so using 5.18, we can prove the right disjunct. \square

5.4.1 Discussing the need for Old Nodes

As mentioned in the observations, it is possible for the tail to lag one node behind the head. This insight lead to including the old nodes of the queue in the queue invariant: xs_{old} . This addition manifests in the end of the proof of dequeue. When we open the invariant to swing ℓ_{head} to $x_{\text{head_next}}$, we get that the entire linked list is xs . After performing the store, we can then close the invariant with the same xs that we opened the queue to, just written differently to signify that x_{head} is now “old”, and $x_{\text{head_next}}$ is the new head node. Because of this, we can supply the same predicate concerning the location of the x_{tail} in the linked list that we got when we opened the invariant to prove either the **Static** state or the **Enqueue** state.

Had we not used an xs_{old} and essentially just “forgotten” old nodes, we couldn't have done this. Say we defined xs as $xs = xs_{\text{queue}} ++ [x_{\text{head}}]$ instead. Then, once we have to close the invariant, we

cannot supply xs , which we got when we opened the invariant. Our only choice (due to the fact that loc_{head} must point to x_{head_next}) is to close the invariant with $xs' = xs_{queue} = xs'_{queue} ++ [x_{head_next}]$. However, clearly $xs' \neq xs$, so we cannot supply the same predicate concerning the location of x_{tail} that we got when opening the invariant, since this predicate talks about xs , not xs' . Now, if we opened the invariant in the state **Dequeue**, then we could conclude $isLast(x_{tail}, xs')$ from $isLast(x_{tail}, xs)$, due to the relationship between xs and xs' , and still be able close the invariant. However, if we opened the invariant in state **Both**, then we would need to assert $isSndLast(x_{tail}, xs')$ from $isSndLast(x_{tail}, xs)$. This is however not provable, since $isSndLast(x_{tail}, xs)$ allows for the case where xs'_{queue} is empty. In this case $xs' = [x_{head_next}]$ which makes it impossible to prove $isSndLast(x_{tail}, xs')$, as it is impossible to be the second last element in a list of size one.

Chapter 6

Hocap-Style Specification

6.1 Defining a Hocap-Style Specification

When proving the concurrent specification, we were quite careful with tracking the state of the queue, and to some extent, even its contents. The contents may have been existentially quantified, but through saving half a pointer, we could match up the contents of the queue between invariant openings. Given this precision in the proof, the reader may wonder if it is possible to give a more precise specification: one which is both concurrent and allows tracking of the contents of the queue. Indeed, this is possible, and we will explore such a specification in this section. We shall refer to this specification as a hocap-style specification – Higher Order Concurrent Abstract Predicate – since the it will be concurrent and parametrised by abstract predicates. This specification is more general than both the sequential and concurrent specifications in the sense that they are derivable from the hocap-style specification. We prove this in section 6.4.

As before, we cannot simply parametrise the queue predicate (now denoted is_queue) with the abstract state of the queue, as we wish for it to be concurrent. So to allow clients to keep track of the contents of the queue, we will “split” the abstract state into two parts, the authoritative view and the fragmental view. The client will then own the fragmental view, allowing them to keep track of the contents of the queue, whereas the is_queue predicate will own the authoritative view. We will in particular make sure that, if one has both the fragmental and authoritative views, then these agree on the abstract state of the queue. Further, it is only possible to update the abstract state of the queue if one possess both the authoritative and fragmental views.

We shall use the resource algebra $\text{AUTH}((\text{FRAC} \times \text{AG}(\text{List Val}))^?)$ to achieve the above. List Val is the abstract state. It is wrapped in the agreement RA, AG , which ensures that if one owns two elements, then they agree on the abstract state. The fractional RA, FRAC , denotes how much of the fragmental view is owned; the fragmental view can be split up, which is handled by the clients. We collect FRAC and $\text{AG}(\text{List Val})$ in the product RA, whose elements are then pairs of fractions and abstract states. The option RA $?$, makes the product RA unital which is required by the AUTH construction. AUTH is the authoritative resource algebra. It gives us the authoritative and fragmental views and, together with the fractional RA, governs that they can only be updated in unison.

For an abstract state xs_v and a ghost name γ , we shall use the notation $\gamma \models_{\bullet} xs_v$ for the ownership assertion $\left[\bullet \left(\underline{1}, \underline{\text{ag } xs_v} \right) \right]_i^{\gamma}$, meaning that the authoritative view of the abstract state associated with γ is xs_v . Similarly we write $\gamma \models_{\circ} xs_v$ for the assertion $\left[\circ \left(\underline{1}, \underline{\text{ag } xs_v} \right) \right]_i^{\gamma}$.

As before, we collect the ghost names we will need in a tuple, this time of type $Qgnames$. It is similar to ConcQgnames , but has an additional ghost name: γ_{Abst} which is used for elements in the resource algebra we constructed above.

With this, we now give the hocap-style specification, and explain it afterwards.

Lemma 9 (Two-Lock M&S-Queue Hocap Specification).

$$\begin{aligned}
& \exists \text{is_queue} : \text{Val} \rightarrow \text{Qnames} \rightarrow \text{Prop}. \\
& \forall v_q, Q_\gamma. \text{is_queue}(v_q, Q_\gamma) \implies \Box \text{is_queue}(v_q, Q_\gamma) \\
& \wedge \{ \text{True} \} \text{initialize } () \{ v_q. \exists Q_\gamma. \text{is_queue}(v_q, Q_\gamma) * Q_\gamma \cdot \gamma_{\text{Abst}} \mapsto_{\circ} [] \} \\
& \wedge \forall v_q, v, Q_\gamma, P, Q. \left(\forall x s_v. Q_\gamma \cdot \gamma_{\text{Abst}} \mapsto_{\bullet} x s_v * P \Rightarrow_{\mathcal{E} \setminus \mathcal{N}.i \uparrow} \triangleright Q_\gamma \cdot \gamma_{\text{Abst}} \mapsto_{\bullet} v :: x s_v * Q \right) -* \\
& \quad \{ \text{is_queue}(v_q, Q_\gamma) * P \} \text{enqueue } v_q \ v \{ w.Q \} \\
& \wedge \forall v_q, Q_\gamma, P, Q. \left(\forall x s_v. Q_\gamma \cdot \gamma_{\text{Abst}} \mapsto_{\bullet} x s_v * P \Rightarrow_{\mathcal{E} \setminus \mathcal{N}.i \uparrow} \triangleright \left(\begin{aligned} & (x s_v = [] * Q_\gamma \cdot \gamma_{\text{Abst}} \mapsto_{\bullet} x s_v * Q(\text{None})) \\ & \vee \left(\begin{aligned} & \exists v, x s'_v. x s_v = x s'_v ++ [v] * \\ & Q_\gamma \cdot \gamma_{\text{Abst}} \mapsto_{\bullet} x s'_v * Q(\text{Some } v) \end{aligned} \right) \end{aligned} \right) \right) -* \\
& \quad \{ \text{is_queue}(v_q, Q_\gamma) * P \} \text{dequeue } v_q \{ w.Q(w) \}
\end{aligned}$$

Firstly, we require `is_queue` to be persistent, giving us support for concurrent clients.

Next, the specification for `initialize` gives clients an additional resource in the postcondition: the ownership of the fragmental view of the empty list, $Q_\gamma \cdot \gamma_{\text{Abst}} \mapsto_{\circ} []$. As discussed above, this allows them to keep track of the contents of the queue.

Finally, the specifications for `enqueue` and `dequeue` have been parametrised by two predicates: P and Q . The clients get to pick P and Q , and the choice depends on what the client wishes to prove; P describes those resources that the client has before `enqueue` or `dequeue`, and Q the resources it will have after. Hence P is in the precondition and Q in the postcondition of the associated Hoare-triples. However, before the client gets access to the hoare triple for `enqueue` or `dequeue` they must prove a viewshift. This viewshift states how the abstract state of the queue will change as a result of running `enqueue` or `dequeue`, and further shows that P can be updated to Q . Note that the consequent of the viewshift contains a \triangleright . This signifies that the update in the abstract state is tied to a step in the code. The mask on the viewshift further disallows opening of invariants in the namespace $\mathcal{N}.i$. This is because, when proving the specifications, we will use an invariant within this namespace. Thus, to be able to use the viewshift while our invariant is open, we must make sure the viewshift doesn't use our invariant (since invariants can only be opened once, before being closed).

It might seem a bit strange that the client has to prove that the abstract state can be updated, but remember that the client owns the fragmental view, and that both this and the authoritative view, which is owned by the queue, is needed to update the abstract state. When proving the viewshift, clients aren't updating the abstract state of the queue, they are merely showing that they can supply the fragmental view, allowing the abstract state to be updated. This then enables the queue to update the authoritative view of the abstract state (using the proved viewshift) in conjunction with updating the concrete view.

Exactly how the client supplies the fragmental view depends on what the client wants to achieve. We will see two options, when we derive the sequential and concurrent specifications from this Hocap-style specification.

6.2 Hocap-Style Queue Predicate

Our definition of `is_queue` is almost the same as `is_queue_conc`, so we only mention the differences here. The full definition can be found in the appendix (A.0.3). We no longer take the predicate Ψ , and the collection of ghost names is now of type Qnames . Similarly, the queue invariant, now denoted I_{TLH} , doesn't require the Ψ any more and the assertion $\text{All}(x s_v, \Psi)$ is changed to $Q_\gamma \cdot \gamma_{\text{Abst}} \mapsto_{\bullet} x s_v$.

6.3 Proof Sketch

The Hocap-style proofs are largely similar their concurrent counterparts. However, instead of having to handle the Ψ predicate, we must now work with the authoritative and fragmental views of the abstract state. For `initialise`, we must additionally get ownership of the authoritative and fragmental view of the empty abstract state, and for `enqueue` and `dequeue`, the only real changes happen at the linearisation points. We sketch these challenges below.

Initialise

Lemma 10 (Two-Lock M&S-Queue Hocap Specification - Initialise).

$$\{\text{True}\} \text{ initialize } () \{v_q. \exists Q_\gamma. \text{is_queue}(v_q, Q_\gamma) * Q_\gamma.\gamma_{\text{Abst}} \Rightarrow_\circ []\}$$

As discussed, we must obtain $Q_\gamma.\gamma_{\text{Abst}} \Rightarrow_\bullet [] * Q_\gamma.\gamma_{\text{Abst}} \Rightarrow_\circ []$. We achieve this by own-op $\blacktriangleright\text{ref}\blacktriangleleft$ and own-allocate $\blacktriangleright\text{ref}\blacktriangleleft$, which requires us to show $\bullet(1, \text{ag } []) \cdot \circ(1, \text{ag } []) \in \mathcal{V}$. This follows by the definitions of the involved resource algebras. We use $Q_\gamma.\gamma_{\text{Abst}} \Rightarrow_\bullet []$ to establish the queue invariant, and $Q_\gamma.\gamma_{\text{Abst}} \Rightarrow_\circ []$ to prove the post-condition.

Enqueue

Lemma 11 (Two-Lock M&S-Queue Hocap Specification - Enqueue).

$$\forall v_q, v, Q_\gamma, P, Q. \left(\forall x_{s_v}. Q_\gamma.\gamma_{\text{Abst}} \Rightarrow_\bullet x_{s_v} * P \Rightarrow_{\mathcal{E}\backslash\mathcal{N}.i^\dagger} \triangleright Q_\gamma.\gamma_{\text{Abst}} \Rightarrow_\bullet v :: x_{s_v} * Q \right) -* \{ \text{is_queue}(v_q, Q_\gamma) * P \} \text{ enqueue } v_q \ v \{ w.Q \}$$

We start by assuming the viewshift which allows us to update P to Q and $Q_\gamma.\gamma_{\text{Abst}} \Rightarrow_\bullet x_{s_v}$ to $Q_\gamma.\gamma_{\text{Abst}} \Rightarrow_\bullet v :: x_{s_v}$, for any x_{s_v} . The only real change from the previous proof happens the second time we open the invariant; the first and third times, the abstract state doesn't change, hence we simply frame away the newly added authoritative fragment, and continue as we did before. The second time we open the invariant is on line 4, around the expression that adds the newly created node, x_{new} , to the linked list. When opening the invariant, we now get $Q_\gamma.\gamma_{\text{Abst}} \Rightarrow_\bullet x_{s_v}$. And as before, we also get all the resources to match up variables and step through the code, updating the concrete state. To close the invariant, we must make the same choice of abstract state as we did previously: $v :: x_{s_v}$. This, however, requires us to obtain $Q_\gamma.\gamma_{\text{Abst}} \Rightarrow_\bullet v :: x_{s_v}$. However, since we have $Q_\gamma.\gamma_{\text{Abst}} \Rightarrow_\bullet x_{s_v}$ and P (from the pre-condition), we can apply the viewshift to obtain it, along with Q . This then allows us to close the invariant, and the proof proceeds as previously. At the end, we must now additionally prove the post-condition Q , but this is no issue as we obtained that from the viewshift.

Dequeue

Lemma 12 (Two-Lock M&S-Queue Hocap Specification - Dequeue).

$$\forall v_q, Q_\gamma, P, Q. \left(\forall x_{s_v}. Q_\gamma.\gamma_{\text{Abst}} \Rightarrow_\bullet x_{s_v} * P \Rightarrow_{\mathcal{E}\backslash\mathcal{N}.i^\dagger} \triangleright \left(\begin{array}{l} (x_{s_v} = [] * Q_\gamma.\gamma_{\text{Abst}} \Rightarrow_\bullet x_{s_v} * Q(\text{None})) \\ \vee \left(\begin{array}{l} \exists v, x_{s'_v}. x_{s_v} = x_{s'_v} ++ [v] * \\ Q_\gamma.\gamma_{\text{Abst}} \Rightarrow_\bullet x_{s'_v} * Q(\text{Some } v) \end{array} \right) \end{array} \right) \right) -* \{ \text{is_queue}(v_q, Q_\gamma) * P \} \text{ dequeue } v_q \ {w.Q(w)}$$

We assume the viewshift and proceed as in the concurrent proof until we get to the second time we open the invariant. This invariant opening is on line 4 around the expression that reads the head node's out pointer. It is here that we figure out whether or not the queue is empty by doing case analysis on $x_{s_{\text{queue}}}$. We open the invariant and do the same case analysis here.

Case $x_{s_{\text{queue}}}$ is empty: In the case that the queue is empty, the abstract state of the queue will not change. We thus apply the viewshift (we have P from the precondition and $Q_\gamma.\gamma_{\text{Abst}} \Rightarrow_\bullet x_{s_v}$ from the invariant), which gives us the consequent of the viewshift. The right disjunct states that the abstract state, x_{s_v} , is non-empty, but since the abstract state is reflected in $x_{s_{\text{queue}}}$, which *is* empty, then we know that the right disjunct is impossible. Hence we may assume the left disjunct. I.e. $x_{s_v} = [] * Q_\gamma.\gamma_{\text{Abst}} \Rightarrow_\bullet x_{s_v} * Q(\text{None})$. We now proceed as before, this time giving up $Q_\gamma.\gamma_{\text{Abst}} \Rightarrow_\bullet x_{s_v}$ to close the invariant. After stepping through the code, we are left with proving the postcondition: $Q(\text{None})$, which we got from the viewshift.

Case $x_{s_{\text{queue}}}$ is not empty: If the queue is not empty, then we do not apply the viewshift (as the abstract state doesn't change within this invariant opening), and simply continue as we did previously. The next time we open the invariant is on line 10, around the expression that swings ℓ_{head} to $x_{\text{head_next}}$. It is this store operation that updates the abstract state of the queue, so it is within this invariant opening that we apply the viewshift (again, we have P from the pre-condition and $Q_\gamma.\gamma_{\text{Abst}} \Rightarrow_\bullet x_{s_v}$

from the invariant). As we did previously, we deduce that the current xs_{queue} is non-empty, and since xs_v is reflected in xs_{queue} , then we can conclude that the first disjunct is impossible, so the viewshift gives us $\exists v, xs'_v. xs_v = xs'_v ++ [v] * Q_{\gamma}.\gamma_{\text{Abst}} \Rightarrow \bullet xs'_v * Q(\text{Some } v)$. As before, we conclude that $\text{Some } v$ is the return value (through the reflection between xs_{queue} and xs_v), and proceed to close the invariant, this time giving up $Q_{\gamma}.\gamma_{\text{Abst}} \Rightarrow \bullet xs'_v$. Stepping through the code, we end up having to prove the post-condition $Q(\text{Some } v)$, which we got from the viewshift.

6.4 Deriving Sequential and Concurrent Specifications

In this section we show that we can derive the sequential and concurrent specifications from chapters 4 and 5 from the Hocap-style specification. The derivations will need to show how to update the abstract state of the queue. We introduce two lemmas to help with this. The first shows that the authoritative and fragmental views of the abstract state agree.

Lemma 13 (Abstract state agree). $\forall \gamma, xs_v, xs'_v.$
 $\gamma \Rightarrow \bullet xs'_v * \gamma \Rightarrow_{\circ} xs_v \vdash xs_v = xs'_v$

Proof. Since we own both $\gamma \Rightarrow \bullet xs_v$ and $\gamma \Rightarrow_{\circ} xs'_v$, and they have the same ghost name, we can use rules **own-op**►**ref**◄ and **own-valid**►**ref**◄ to conclude that the element $\bullet(1, \text{ag } xs_v) \cdot \circ(1, \text{ag } xs'_v)$ is valid. By the authoritative RA, this means that $\text{ag } xs'_v \preceq \text{ag } xs_v$. By definition of the agreement RA, this means that $xs'_v = xs_v$, which is what we wanted. \square

The second lemma shows that, if we own both the authoritative and fragmental views, we are allowed to update the abstract state to whatever we like.

Lemma 14 (Abstract state update). $\forall \gamma, xs_v, xs'_v, xs''_v.$
 $\gamma \Rightarrow \bullet xs'_v * \gamma \Rightarrow_{\circ} xs_v \Rightarrow \gamma \Rightarrow \bullet xs''_v * \gamma \Rightarrow_{\circ} xs''_v$

Proof. This time, we use **own-op**►**ref**◄ to conclude $\bullet(1, \text{ag } xs_v) \cdot \circ(1, \text{ag } xs'_v)$. Further, by **own-op**►**ref**◄, it suffices to prove $\Rightarrow \bullet(1, \text{ag } xs'_v) \cdot \circ(1, \text{ag } xs''_v)$. We do this by applying the ghost-update►**ref**◄ rule, which requires us to prove $\bullet(1, \text{ag } xs_v) \cdot \circ(1, \text{ag } xs'_v) \rightsquigarrow \bullet(1, \text{ag } xs'_v) \cdot \circ(1, \text{ag } xs''_v)$. Firstly by the product, fractional, and agreement RA, the element $(1, \text{ag } xs'_v)$ is valid, so the product of the authoritative and fragmental parts of it is also valid. Next, note that we own the entire fraction of the fragmental element. Hence, there can be no other valid fragments. It hence follows that we can do the frame-preserving update. \square

6.4.1 Deriving the Sequential Specification

We define the `is_queue_seq` predicate as follows.

Definition 6.4.1 (Two-Lock M&S-Queue - `is_queue_seq` Predicate (Derive)).

$$\begin{aligned} \text{is_queue_seq}(v_q, xs_v, Q_{\gamma S}) &\triangleq \exists Q_{\gamma H} \in Qgnames. \\ &\quad \text{proj_Qgnames_seq}(Q_{\gamma H}) = Q_{\gamma S} * \\ &\quad \text{is_queue}(v_q, Q_{\gamma H}) * \\ &\quad Q_{\gamma H}.\gamma_{\text{Abst}} \Rightarrow_{\circ} xs_v \end{aligned}$$

Here, `proj_Qgnames_seq`($Q_{\gamma H}$) simply creates an element of $SeqQgnames$, with ghost names matching those of $Q_{\gamma H}$. `is_queue` is the predicate from the Hocap-style specification.

►reformat proofs◄

The **sequential initialise specification** follows almost directly from hocap-style initialise specification. They only differ in the post-condition. The post-condition in the hocap-style spec states $\exists Q_{\gamma H}. \text{is_queue}(v_q, Q_{\gamma H}) * Q_{\gamma H}.\gamma_{\text{Abst}} \Rightarrow_{\circ} []$, whereas we have to prove $\exists Q_{\gamma S}. \text{is_queue_seq}(v_q, [], Q_{\gamma S})$. If we choose `proj_Qgnames_seq`($Q_{\gamma H}$) for $Q_{\gamma S}$, then the equality in `is_queue_seq` becomes trivially true, and the post-condition we must prove follows from the hocap-style post-condition.

To prove the **sequential enqueue specification**, assume some v_q, v, xs_v , and $Q_{\gamma S}$. We must then show the Hoare-triple concerning the expression: `enqueue vq v`. To do this, we shall use the Hocap-style

specification for enqueue. This requires us to pick P and Q , and prove the resulting viewshift. We choose $P \triangleq Q_{\gamma H} \cdot \gamma_{\text{Abst}} \mapsto_{\circ} xs_v$ and $Q \triangleq Q_{\gamma H} \cdot \gamma_{\text{Abst}} \mapsto_{\circ} (v :: xs_v)$. Note that with this choice, the hoare triple we get after proving the viewshift almost matches the hoare triple we have to prove. The main thing we need is $\text{is_queue}(v_q, Q_{\gamma H})$ in the postcondition. However, since is_queue is persistent, and it is present in the precondition, we may assume it in the postcondition. Hence, all we have to prove is the viewshift:

$$\forall xs'_v. Q_{\gamma} \cdot \gamma_{\text{Abst}} \mapsto_{\bullet} xs'_v * Q_{\gamma H} \cdot \gamma_{\text{Abst}} \mapsto_{\circ} xs_v \Rightarrow_{\mathcal{E} \setminus \mathcal{N}.i^{\uparrow}} \triangleright Q_{\gamma} \cdot \gamma_{\text{Abst}} \mapsto_{\bullet} v :: xs'_v * Q_{\gamma H} \cdot \gamma_{\text{Abst}} \mapsto_{\circ} (v :: xs_v)$$

So assume some xs'_v , $Q_{\gamma} \cdot \gamma_{\text{Abst}} \mapsto_{\bullet} xs'_v$ and $Q_{\gamma H} \cdot \gamma_{\text{Abst}} \mapsto_{\circ} xs_v$. We must then prove $\mapsto_{\mathcal{E} \setminus \mathcal{N}.i^{\uparrow}} \triangleright Q_{\gamma} \cdot \gamma_{\text{Abst}} \mapsto_{\bullet} (v :: xs'_v) * Q_{\gamma H} \cdot \gamma_{\text{Abst}} \mapsto_{\circ} (v :: xs_v)$. By property 13, $xs_v = xs'_v$, hence, we can apply property 14 to update the authoritative and fragmental views to $(v :: xs_v)$, which is what we wanted.

We use a similar approach to above to prove the **sequential dequeue specification**. So we assume some v_q , xs_v , and $Q_{\gamma S}$, and must then prove the hoare-triple concerning the expression: dequeue v_q . This time, we use the hcap-style dequeue spec, with the following choices: $P \triangleq Q_{\gamma H} \cdot \gamma_{\text{Abst}} \mapsto_{\circ} xs_v$, and $Q(w) \triangleq (xs_v = [] * w = \text{None} * Q_{\gamma H} \cdot \gamma_{\text{Abst}} \mapsto_{\circ} xs_v) \vee (\exists v, xs'_v. xs_v = xs'_v ++ [v] * w = \text{Some } v * Q_{\gamma H} \cdot \gamma_{\text{Abst}} \mapsto_{\circ} xs'_v)$. In the same way as above, the hoare triple we get matches the one we have to prove (after a bit of manipulation). So we only have to prove the viewshift. First we conclude that the abstract states in the authoritative and fragmental views are equal. Then we do a case analysis on the abstract state, xs_v . If xs_v is empty, we prove the left disjunct in the consequent of the viewshift, *without* updating the authoritative and fragmental views. If xs_v is non-empty, i.e. $xs_v = xs'_v ++ [v]$ for some xs'_v and v , then we prove the right-side of the consequent in the viewshift, using property 14 to update the authoritative and fragmental views to the new abstract state, xs'_v .

6.4.2 Deriving the Concurrent Specification

Remember that we need the is_queue_conc predicate to be persistent, hence we cannot simply assert $Q_{\gamma H} \cdot \gamma_{\text{Abst}} \mapsto_{\circ} xs_v$ as we did for is_queue_seq . Instead we will put it into an invariant. The predicate we will use looks as follows.

Definition 6.4.2 (Two-Lock M&S-Queue - is_queue_conc Predicate (Derive)).

$$\begin{aligned} \text{is_queue_conc}(\Psi, v_q, Q_{\gamma C}) &\triangleq \exists Q_{\gamma H} \in Q_{\text{gnames}}. \\ &\quad \text{proj_Qgnames_conc}(Q_{\gamma H}) = Q_{\gamma C} * \\ &\quad \text{is_queue}(v_q, Q_{\gamma H}) * \\ &\quad \boxed{\exists xs_v. Q_{\gamma H} \cdot \gamma_{\text{Abst}} \mapsto_{\circ} xs_v * \text{All}(xs_v, \Psi)}^{\mathcal{N}.c} \end{aligned}$$

Persistency of is_queue_conc follows by the persistency of is_queue and the fact that invariants and equalities are persistent.

►**reformat proof**◄

The **concurrent initialise specification** follows from the hcap-style initialise spec, after allocating the invariant in the post-condition. We achieve this by applying the rules Ht-csq-vs and inv-alloc, to put the assertions $Q_{\gamma H} \cdot \gamma_{\text{Abst}} \mapsto_{\circ} xs_v$ and $\text{All}([], \Psi)$ (which is trivially true) in the postcondition of the hcap style spec into an invariant.

Next, to prove the **concurrent enqueue specification**, we assume some v_q , v , and $Q_{\gamma C}$, and must then prove the hoare triple concerning the expression: enqueue v_q v . We specialise the hcap-style enqueue spec with $P \triangleq \Psi(v)$ and $Q \triangleq \text{True}$. The hoare triple we get after proving the viewshift matches the hoare triple we must prove, except that its precondition is weaker: it doesn't mention the invariant or the equality. Hence, the hoare triple we have to prove simply follows by the rule of consequence. To prove the viewshift, we must supply the full fragmental view. When deriving the sequential spec, we had this available through P . But this time we shall get it by opening the invariant in is_queue_conc . Proving the viewshift is then similar to what we did for the sequential spec.

To derive the **concurrent dequeue specification**, we pick $P \triangleq \text{True}$ and $Q(w) \triangleq w = \text{None} \vee (\exists v. w = \text{Some } v * \Psi(v))$. Again, the hoare triple we get after proving the viewshift is exactly the hoare triple we must prove, except that its precondition is weaker. Hence, we only have to prove the viewshift. This is done analogously to the sequential case (i.e. case distinction on xs_v), except this time we get $Q_{\gamma H} \cdot \gamma_{\text{Abst}} \mapsto_{\circ} xs_v$ through the invariant, and in the case where xs_v is not empty, i.e. $xs_v = xs'_v ++ [v]$ for some xs'_v and v , we extract $\Psi(v)$ from $\text{All}(xs_v, \Psi)$, and use this to prove the right disjunct in Q .

Chapter 7

The Lock-Free Michael Scott Queue

7.1 Introduction

In this chapter we will study the non-blocking version of the M&S-Queue, the Lock-Free M&S-Queue. As with the two-lock version, the original implementation can be found in [4]. As the name “Lock-Free” suggests, the implementation doesn’t rely on locks to achieve correct behaviour. Instead, it uses the atomic operation: [CAS](#) which we discussed in section 2.1.

Section 7.2 implements the Lock-Free M&S-Queue in HeapLang. Next, we move towards proving a hocap-style specification for it. Section 7.3 introduces the notion of *Reachability* which we will need in the proofs. In section 7.4 we discuss the specification we will be proving, and in sections 7.5 and 7.6 we give the proofs. Finally, in section 7.7, we discuss a simplification to the Lock-Free M&S-Queue algorithm and its implications.

7.2 Implementation

The implementation shares many commonalities with the two-lock variant, most importantly, the underlying queue is still a linked list. The major differences are how we manipulate the linked list and the head and tail pointers.

7.2.1 Initialise

As the implementation doesn’t use locks, the queue data structure is now just a pointer to a pair consisting of the head and tail pointers.

7.2.2 Enqueue

Enqueueing a node consists of the same two steps as before: add the newly created node to the linked list, and swing the tail pointer. In this way, figures 3.2a, 3.2b, and 3.2c still accurately reflect the state changes that the queue goes through during an enqueue. However, one big difference is that swinging the tail pointer to the newly inserted node is not necessarily done by the thread that enqueued it. We discuss this below.

Since other threads can work on the linked list at the same time, we must do some extra checks when enqueueing a new node.

Firstly, we must ensure that the tail pointer is actually pointing to the last node. We ensure this on line 7. If it isn’t, that means that another enqueueing thread has added a new node to the linked list, but hasn’t yet swung the tail pointer. So instead of waiting for it, we *help* it by trying to swing the tail pointer for it. Afterwards, we try to enqueue our node again.

Secondly, before we can add the node, we must ensure that no thread has performed an enqueue while we have been working, so that we don’t overwrite another threads enqueue. This is ensured with the [CAS](#) instruction on line 8 – it adds the new node to the linked list only if our tail node is still the last, and hence points to None. After adding the node, we attempt to swing the tail pointer to it. This may fail,

but that simply means that another thread has already swung it for us. Finally, we have an additional *consistency check* on line 6. We discuss the purpose of this extra check in section 7.7.

7.2.3 Dequeue

Fundamentally, a dequeue operation still consists of swinging the head pointer to the next node in the linked list. The original authors decided that the tail pointer shouldn't lag behind the head pointer, hence dequeue also accesses the tail node and checks ensures it won't lag behind as result of the dequeue. on line 8, we check whether the head and tail nodes are the same. If this is the case, then the queue is either empty or the tail pointer is lagging behind. We distinguish between these two cases on line 9. If the tail node is indeed lagging behind, then some thread has enqueued a node, but not yet swung the tail pointer, so we help it out by swinging the pointer.

If the head and tail nodes are not the same, then it must be safe to dequeue, which we attempt in the else block on line 13.

7.2.4 Prophecies

On line 5 in dequeue, we create a “prophecy variable” which is resolved on line 7. Prophecies are a part of Iris and allow us to reason about the result of future expressions. They are only used in the logic and do not alter the semantics of the code. The reason we need it is because the load on line 6 is a possible linearisation point – if the load resolves to None (i.e. the queue is empty) and the consistency check on the next line passes, the dequeue will conclude the queue is empty and return None. So when we are at the load, we need to know whether or not the consistency check passes; if it does, we should apply the viewshift, and if it doesn't, we shouldn't apply it. The prophecy variable allows us to reason about the result of the consistency check already at the load, allowing us to make the correct choice.

```

1  initialize  $\triangleq$ 
2    let node = ref (None, ref (None)) in
3    ref (ref (node), ref (node))

1  enqueue Q value  $\triangleq$ 
2    let node = ref (Some value, ref (None)) in
3    (rec loop_ =
4      let tail = !(snd(!Q)) in
5      let next = !(snd(!tail)) in
6      if tail = !(snd(!Q)) then
7        if next = None then
8          if CAS (snd(!tail)) next node then
9            CAS (snd(!Q)) tail node
10           else loop ()
11          else CAS (snd(!Q)) tail next; loop ()
12         else loop ()
13    ) ()

1  dequeue Q  $\triangleq$ 
2    (rec loop_ =
3      let head = !(fst(!Q)) in
4      let tail = !(snd(!Q)) in
5      let p = newproph in
6      let next = !(snd(!head)) in
7      if head = Resolve(!(fst(!Q)), p, ()) then
8        if head = tail then
9          if next = None then
10             None
11          else
12             CAS(snd(!Q)) tail next; loop ()
13         else

```

```

14         let value = fst(!next) in
15         if CAS (fst(!Q)) head next then
16             value
17         else loop ()
18     else loop ()
19 )()

```

7.3 Reachability

An important aspect in the correctness of the Lock-Free M&S-Queue is which nodes a particular node is able to *reach* through the linked list (i.e. by following the chain of pointers), and how the head and tail pointers change during the lifetime of the queue.

Firstly, the underlying linked list still only ever grows, and it does so only at the end. Hence, the set of nodes that a given node can reach only ever grows. Further, all nodes can always reach the last node in the linked list.

Secondly, similarly to the two-lock variant, the correctness of the queue relies on the fact that the head and tail pointers are only ever swung towards the end of the linked list. That is, if a node can reach, say, the tail node at one point during the program, then it can reach any future tail nodes.

Thirdly, whereas it was possible for the tail node to lag behind the head node in the two-lock version, it is not possible in the lock-free version. Indeed, if such a scenario could happen, dequeue could crash! Consider the scenario where the head node is the last node in the linked list (hence the queue is empty), and the tail is lagging behind the head. If someone invokes dequeue, the check on line 8, which is supposed to detect an empty queue or a lagging tail will result to false, and hence, incorrectly, take the “else” branch, which assumes that there is something to dequeue. But since the queue is empty, then *next* – the node after head – is None, and when we try to dereference *next* on line 14, we will crash. Therefore, our invariant must ensure that the tail never lags behind the head.

To capture these properties, we introduce two notions of reachability: concrete reachability and abstract reachability, which we introduce in the following sections. This way of modelling the queue was originally introduced in [5]. The presentation here borrows the same ideas, but the presentation differs in the sense that it is node-oriented instead of location-oriented. Moreover, we prove some additional properties of reachability which allows us to simplify the queue invariant slightly.

7.3.1 Concrete Reachability

We say that a node x_n in a linked list can concretely reach a node x_m when, if we start traversing succeeding nodes (by following the out and in pointers starting from x_n), we will eventually get to x_m . If this is the case, we write $x_n \leadsto x_m$. We allow for traversing zero nodes to reach x_m , which essentially means that all nodes can reach themselves. Formally, we define $x_n \leadsto x_m$ inductively as follows.

Definition 7.3.1 (Concrete Reachability). $x_n \leadsto x_m \triangleq \text{in}(x_n) \mapsto^\square (\text{val}(x_n), \text{out}(x_n)) * (x_n = x_m \vee \exists x_p. \text{out}(x_n) \mapsto^\square \text{in}(x_p) * x_p \leadsto x_m)$

This definition firstly states that x_n is a node: $\text{in}(x_n) \mapsto^\square (\text{val}(x_n), \text{out}(x_n))$. Secondly, x_n is either the node to be reached x_m , or it has a succeeding node x_p , which can reach x_m . Note that the points-to propositions are all persistent, which mimics the fact that the linked list is only ever changed by appending new nodes to the end. This in turn makes concrete reachability a persistent predicate.

We proceed to prove some useful lemmas about concrete reachability.

Lemma 15 (reach-reflexive). $x_n \leadsto x_n ** \text{in}(x_n) \mapsto^\square (\text{val}(x_n), \text{out}(x_n))$

Proof. The \rightarrow^* direction follows directly by the definition. To prove the $*$ - direction, it suffices to show $(x_n = x_n \vee \exists x_p. \text{out}(x_n) \mapsto^\square \text{in}(x_p) * x_p \leadsto x_n)$. Clearly, this follows as the left disjunction holds. \square

Lemma 16 (reach-transitive). $x_n \leadsto x_m \rightarrow^* x_m \leadsto x_o \rightarrow^* x_n \leadsto x_o$

Proof. We proceed by induction in $x_n \leadsto x_m$.

B.C. In the base case, $x_n = x_m$. We get to assume that $x_m \rightsquigarrow x_o$, and must prove $x_n \rightsquigarrow x_o$. Since $x_n = x_m$, we are done.

I.C. In the inductive case, we assume that x_n is a node that points to some x_p , which satisfies $x_m \rightsquigarrow x_o \multimap x_p \rightsquigarrow x_o$. Assuming $x_m \rightsquigarrow x_o$, we must prove $x_n \rightsquigarrow x_o$.

To prove $x_n \rightsquigarrow x_o$ we must first show that x_n is a node, which we have already established. Next, we must show that either $x_n = x_o$, or x_n steps to some x'_p which can reach x_o . We prove the second case by choosing our x_p for x'_p . Thus, we have to show $x_p \rightsquigarrow x_o$. This then follow by the induction hypothesis together with our assumption that $x_m \rightsquigarrow x_o$.

□

Lemma 17 (reach-from-is-node). $x_n \rightsquigarrow x_m \multimap \text{in}(x_n) \mapsto^\square (\text{val}(x_n), \text{out}(x_n))$

Proof. This follow immediately from the definition or concrete reachability. □

Lemma 18 (reach-to-is-node). $x_n \rightsquigarrow x_m \multimap \text{in}(x_m) \mapsto^\square (\text{val}(x_m), \text{out}(x_m))$

Proof. We proceed by induction in $x_n \rightsquigarrow x_m$. The base case follows by lemma 17 above. In the inductive case, we assume that x_n points to some x_p , which reaches x_m . Our induction hypothesis is $\text{in}(x_m) \mapsto^\square (\text{val}(x_m), \text{out}(x_m))$, which is also our proof obligation, so we are done. □

Lemma 19 (reach-last). $x_n \rightsquigarrow x_m \multimap \text{out}(x_n) \mapsto \text{None} \multimap x_n = x_m \multimap \text{out}(x_n) \mapsto \text{None}$

Proof. Assuming $x_n \rightsquigarrow x_m$ and $\text{out}(x_n) \mapsto \text{None}$, we must prove that $x_n = x_m$ and $\text{out}(x_n) \mapsto \text{None}$. By $x_n \rightsquigarrow x_m$, we know that either $x_n = x_m$, or x_n points to some x_p and $x_p \rightsquigarrow x_m$. The first case immediately gives us everything we need to prove both goals. If we are in the second case, then we know that $\text{out}(x_n) \mapsto^\square \text{in}(x_p)$. But by our initial assumption, $\text{out}(x_n) \mapsto \text{None}$. Since $\text{in}(x_p)$ is a location, then this is clearly a contradiction. □

7.3.2 Abstract Reachability

As discussed, we wish to capture that if a node can reach either the head or tail node at one point during the program, then it can reach any future head or tail nodes. To do this we introduce the notion of abstract reachability. The idea is to introduce ghost variables that can “point” to nodes in the linked list, just as the head and tail pointers do. We shall write $\gamma \rightsquigarrow x$ to mean that the ghost variable γ *abstractly points* to the node x . We shall construct the abstract points-to predicate so that we can update $\gamma \rightsquigarrow x$ to $\gamma \rightsquigarrow y$ only if x can concretely reach y , i.e. $x \rightsquigarrow y$. This additional restriction compared to the normal points-to predicate is what allows us to capture the property described above. We write $x \dashrightarrow \gamma$ to mean that the node x can *abstractly reach* the ghost variable γ . The idea is that, if we have established $x \dashrightarrow \gamma$, then no matter what node γ abstractly points to, for instance $\gamma \rightsquigarrow y$, we can conclude $x \rightsquigarrow y$. This means that if we update $\gamma \rightsquigarrow y$ in the future to, say $\gamma \rightsquigarrow z$, then we can conclude that $x \rightsquigarrow z$.

To define the abstract points-to predicate and the abstract reach predicate, we create the following resource algebra: $\text{AUTH}(\mathcal{P}(\text{Node}))$, where $\text{Node} = (\text{Loc} \times \text{Val}) \times \text{Loc}$. Here, the resource algebra $\mathcal{P}(\text{Node})$ denotes the set of subsets of Node , with union as the operation. The empty set is the unit element, meaning that $\mathcal{P}(\text{Node})$ is unital. We may now define abstract reach and abstract points-to as follows.

Definition 7.3.2 (Abstract Reach). $x \dashrightarrow \gamma \triangleq [\![\circ \{x\}]^{\gamma}]$

Definition 7.3.3 (Abstract Points to). $\gamma \rightsquigarrow x \triangleq \exists s. [\![\bullet s]^{\gamma}] \multimap \bigstar_{x_m \in s} x_m \rightsquigarrow x$

One should think of sets $s \in \mathcal{P}(\text{Node})$ as specifying which nodes can abstractly reach a certain ghost variable. Due to how the authoritative resource algebra work, the assertion $[\![\circ \{x\}]^{\gamma}]$ essentially states that x is *one* of the nodes that can reach the node that γ points to. This is because, when combining a fragmental element s and authoritative element t , we get that the fragmental element is “smaller” than the authoritative, $s \preceq t$. In this case, “smaller” amounts to “subset”. Hence, $[\![\circ \{x\}]^{\gamma}]$ means that, whatever the authoritative set is, it will contain the node x .

The authoritative set is existentially quantified as it can change over time, but whatever it is, we assert that all the nodes it contains *can* concretely reach the node that the ghost name is currently pointing to.

This choice of definitions enables us to prove the properties we desired of abstract reachability above. The four lemmas below are all we need for abstract reachability when we prove the specification for the Lock-Free M&S-Queue later.

Firstly, if we have a node, we may allocate some ghost variable γ which points to it and assert that the node can reach γ .

Lemma 20 (Abs-Reach-Alloc). $x \leadsto x \Rightarrow (\exists \gamma. \gamma \mapsto x * x \dashv\vdash \gamma)$

Proof. We assume $x \leadsto x$ and must show $\models \exists \gamma'. \gamma' \mapsto x * x \dashv\vdash \gamma'$. By definition or the authoritative RA, the element $\bullet\{x\} \cdot \circ\{x\}$ is valid. Hence by the Ghost-alloc rule, we may get $\models \exists \gamma. [\bullet\{x\} \cdot \circ\{x\}]^\gamma$. By Upd-mono, we may strip away the update modality on the goal and the previous assertion. Thus, we must prove $\exists \gamma'. \gamma' \mapsto x * x \dashv\vdash \gamma'$, and we have that $\exists \gamma. [\bullet\{x\} \cdot \circ\{x\}]^\gamma$. We use γ as the witness in the goal meaning we must prove $\gamma \mapsto x * x \dashv\vdash \gamma$. We can split the ownership of the authoritative and fragmental parts up using Own-op, giving us $[\bullet\{x\}]^\gamma$ and $[\circ\{x\}]^\gamma$. The latter assertion is equivalent to $x \dashv\vdash \gamma$, which matches the second obligation in the goal. To prove the first obligation, we must give some set as witness, and show that all nodes in the set can reach x . We of course choose $\{x\}$ as the witness, and must then prove that $x \leadsto x$, which we assumed in the beginning. \square

The second lemma allows us to get a *concrete* reachability predicate out of an abstract one. If a ghost name γ_m currently points abstractly to some node x_m , then any node that can abstractly reach γ , can also *concretely* reach x_m .

Lemma 21 (Abs-Reach-Concr). $x_n \dashv\vdash \gamma_m \multimap \gamma_m \mapsto x_m \multimap x_n \leadsto x_m * \gamma_m \mapsto x_m$

Proof. Assuming $x_n \dashv\vdash \gamma_m$ and $\gamma_m \mapsto x_m$, we must show $x_n \leadsto x_m$ without “consuming” $\gamma_m \mapsto x_m$. From $\gamma_m \mapsto x_m$ we can deduce that there is some set s so that $[\bullet s]^\gamma_m$ and $\bigstar_{x' \in s} x' \leadsto x_m$. Since we own both $[\bullet s]^\gamma_m$ and $[\circ\{x_n\}]^\gamma_m$ (from $x_n \dashv\vdash \gamma_m$), we may conclude that their product is valid, which in our instantiation of the authoritative RA equates to $x_n \in s$. We may now frame away the second part of the goal, $\gamma_m \mapsto x_m$, using $[\bullet s]^\gamma_m$ and $\bigstar_{x' \in s} x' \leadsto x_m$. Note that we get to keep the latter assertion as reach is persistent. Thus, from that assertion and by $x_n \in s$, we can deduce that $x_n \leadsto x_m$, which is what we had to prove. \square

We can also go the other way, and get an abstract reachability predicate out of a concrete one. If a ghost variable γ_m points abstractly to some node x_m , and a node x_n can *concretely* reach x_m , then we may deduce that x_n can *abstractly* reach γ_m , meaning that x_n can reach any node that γ_m will ever point to in the future.

Lemma 22 (Abs-Reach-Abs). $x_n \leadsto x_m \multimap \gamma_m \mapsto x_m \Rightarrow x_n \dashv\vdash \gamma_m \multimap \gamma_m \mapsto x_m$

Proof. Assuming $x_n \leadsto x_m$ and $\gamma_m \mapsto x_m$ we must conclude $\models x_n \dashv\vdash \gamma_m$. From $\gamma_m \mapsto x_m$ we know that there is some set s so that $[\bullet s]^\gamma_m$ and $\bigstar_{x' \in s} x' \leadsto x_m$. There are now two cases to consider: either $x_n \in s$ or $x_n \notin s$.

$x_n \in s$ By the definition of our authoritative RA, if a set y is a subset of s , then we may update our ghost resources to obtain ownership of the fragment y . In our case, since $x_n \in s$, we may update our resources to additionally get $[\circ\{x_n\}]^\gamma_m$, which is exactly what we wanted. Since we still have $[\bullet s]^\gamma_m$, we can also prove $\gamma_m \mapsto x_m$.

$x_n \notin s$ In this case we may update $[\bullet s]^\gamma_m$ so that the set also includes x_n . The reason we may do this, is because, according to the $\mathcal{P}(\text{Node})$ RA, we may update a set X to Y , as long as $X \subseteq Y$. Thus, we can update our resource to get $[\bullet\{x_n\} \cup s]^\gamma_m$. As in the previous case, we can further get $[\circ\{x_n\}]^\gamma_m$ out of this, which we use to frame away the goal $x_n \dashv\vdash \gamma_m$.

To prove $\gamma_m \mapsto x_m$, we use the set $\{x_n\} \cup s$, and immediately frame away the authoritative part, which we owned. We are left with having to prove $\bigstar_{x' \in \{x_n\} \cup s} x' \leadsto x_m$. However, by $\bigstar_{x' \in s} x' \leadsto x_m$ and our assumption that $x_n \leadsto x_m$, we can easily conclude this. \square

The final lemma allows us update abstract pointers. As discussed above, we will require that whatever node we update the pointer to is a successor of the current node. That is, if a ghost variable γ_m currently points to x_m , then we must show that x_m can reach x_o , before we can update γ to point abstractly to x_o . After the update we additionally get that x_o can abstractly reach γ .

Lemma 23 (Abs-Reach-Advance). $\gamma_m \mapsto x_m \ast x_m \leadsto x_o \Rightarrow \gamma_m \mapsto x_o \ast x_o \dashrightarrow \gamma_m$

Proof. Assuming $\gamma_m \mapsto x_m$ and $x_m \leadsto x_o$ we must prove $\Rightarrow \gamma_m \mapsto x_o \ast x_o \dashrightarrow \gamma_m$. From $\gamma_m \mapsto x_m$, we get some set s so that $\llbracket \bullet s \rrbracket^{\gamma_m}$ and $\ast_{x' \in s} x' \leadsto x_m$. As we did in previous proof (lemma 22), we update $\llbracket \bullet s \rrbracket^{\gamma_m}$ so that the set additionally contains x_o . Thus, we get $\llbracket \bullet \{x_o\} \cup s \rrbracket^{\gamma_m}$. From this, we may extract ownership of the fragmental part: $\llbracket \bullet \{x_o\} \rrbracket^{\gamma_m}$, which we use to prove the second part of the goal.

We are thus left with proving $\gamma_m \mapsto x_o$. We use $\{x_o\} \cup s$ as witness for the authoritative set, and immediately frame away the ownership assertion of the authoritative part. We are left with proving $\ast_{x' \in \{x_o\} \cup s} x' \leadsto x_o$. We already know that $\ast_{x' \in s} x' \leadsto x_m$ and $x_m \leadsto x_o$. Thus, by transitivity of reach (lemma 16), we may conclude $\ast_{x' \in \{x_o\} \cup s} x' \leadsto x_o$. Thus, we are done if we can prove that $x_o \leadsto x_o$, which by 15 amount to showing that x_o is a node. However, since $x_m \leadsto x_o$, then, by 18, we know that this is the case. \square

7.4 Specifications for Lock-Free M&S-Queue

From the perspective of a client, the Two-Lock M&S-Queue and the Lock-Free M&S-Queue should behave similarly – they should both behave as a concurrent queue. Hence, in this section, we will prove specifications that are almost identical to those we proved for the Two-Lock M&S-Queue; a sequential, a concurrent, and a hocap-style spec.

As we showed in section 6.4, the sequential and concurrent specifications can be derived from the hocap-style spec *without* referring to the actual implementation. Thus, in this chapter we will only focus on proving the hocap-style spec – the derivations of the sequential and concurrent specs will be practically identical to that of the previous chapter.

The only two differences between the hocap spec we prove for the lock-free version compared to the two-lock version (lemma 9) is the collection of ghost names, and the fact that the expressions in our hoare-triples – initialize, enqueue, and dequeue – refer to the lock-free versions from section 7.2.

The collection $Qnames$ will contain γ_{Abst} whose purpose is the same as before; to keep track of the abstract state of the queue. Additionally, we will have γ_{Head} , γ_{Tail} , and γ_{Last} , which will abstractly point to the head, tail, and last node, respectively.

7.5 Hocap-style Queue Predicate

We will again be needing an invariant to make the predicate persistent. The invariant we define has some commonalities with the invariant we used for the two-lock variant, but it incorporates the differences we discussed earlier in the chapter. In particular, it is important for the correctness of the queue that the tail doesn't lag behind the head. As such, our invariant will not allow for this behaviour. This has the extra implication that the head node is always the oldest node, meaning that we do not need to keep track of older nodes, xs_{old} .

Unlike the two-lock variant, we assert the existence of an additional node x_{last} , which invariantly is the last (newest added) node in the linked list. This helps us reason about where the head and tail nodes are located; enqueue distinguishes between the cases where the tail is last and not last, and similarly for dequeue and head.

In this way, x_{head} is the first node, x_{last} is the last node, and x_{tail} either lies somewhere in between, is one of them, or, in the case where the queue is empty, is both of them. To force this structure, we use our abstract reachability predicate from the previous section.

We proceed to define the invariant.

Definition 7.5.1 (Lock-Free M&S-Queue Invariant).

$$\begin{aligned}
& I_{\text{LFH}}(\ell_{\text{head}}, \ell_{\text{tail}}, Q_\gamma) \triangleq \\
& \exists xs_v. Q_\gamma \cdot \gamma_{\text{Abst}} \Rightarrow_\bullet xs_v * \quad (\text{abstract state}) \\
& \exists xs, xs_{\text{queue}}, x_{\text{head}}, x_{\text{tail}}, x_{\text{last}}. \quad (\text{concrete state}) \\
& xs = xs_{\text{queue}} ++ [x_{\text{head}}] * \\
& \text{isLL}(xs) * \\
& \text{isLast}(x_{\text{last}}, xs) \\
& \text{proj_val}(xs_{\text{queue}}) = \text{wrap_some}(xs_v) * \\
& \ell_{\text{head}} \mapsto \text{in}(x_{\text{head}}) * \\
& \ell_{\text{tail}} \mapsto \text{in}(x_{\text{tail}}) * \\
& Q_\gamma \cdot \gamma_{\text{Head}} \succ \rightarrow x_{\text{head}} * x_{\text{head}} \dashrightarrow Q_\gamma \cdot \gamma_{\text{Tail}} * \\
& Q_\gamma \cdot \gamma_{\text{Tail}} \succ \rightarrow x_{\text{tail}} * x_{\text{tail}} \dashrightarrow Q_\gamma \cdot \gamma_{\text{Last}} * \\
& Q_\gamma \cdot \gamma_{\text{Last}} \succ \rightarrow x_{\text{last}}
\end{aligned}$$

The `is_queue` predicate is now quite simple: it states that the value representing the queue is a location which points persistently to a pair of locations, the head and tail pointers, which satisfy the invariant we defined above.

Definition 7.5.2 (Lock-Free M&S-Queue- `is_queue` Predicate).

$$\begin{aligned}
\text{is_queue}(v_q, Q_\gamma) & \triangleq \exists \ell_{\text{queue}}, \ell_{\text{head}}, \ell_{\text{tail}} \in \text{Loc}. \\
& v_q = \ell_{\text{queue}} * \ell_{\text{queue}} \mapsto^\square (\ell_{\text{head}}, \ell_{\text{tail}}) * \\
& \boxed{I_{\text{LFH}}(\ell_{\text{head}}, \ell_{\text{tail}}, Q_\gamma)}^{\mathcal{N}.\text{queue}}
\end{aligned}$$

7.6 Proof Outline

We instantiate the specification with our definition of `is_queue` (7.5.2). By the definition of `is_queue` we easily show that `is_queue` is persistent. What remains to be shown is the specifications for `initialize`, `enqueue`, and `dequeue`. Both `enqueue` and `dequeue` has code that attempt to swing the tail pointer forward (for `enqueue`, lines 9 and 11, and for `dequeue`, line 12). These all behave similarly, so we additionally prove a specification for swinging the tail.

Initialise

Lemma 24 (Lock-Free M&S-Queue Specification - Initialise).

$$\{\text{True}\} \text{ initialize } () \{v_q. \exists Q_\gamma. \text{is_queue}(v_q, Q_\gamma) * Q_\gamma \cdot \gamma_{\text{Abst}} \Rightarrow_\circ []\}$$

Proof. We first step through line 2 which creates a new node: $x_1 = (\ell_{1_in}, \text{None}, \ell_{1_out})$, with $\ell_{1_out} \mapsto \text{None}$ and $\ell_{1_in} \mapsto (\text{None}, \ell_{1_out})$, the latter of which we make persistent. Next, we step through line 3 which gives us some locations ℓ_{head} , ℓ_{tail} , and ℓ_{queue} , with $\ell_{\text{head}} \mapsto \text{in}(x_1)$ and $\ell_{\text{tail}} \mapsto \text{in}(x_1)$, and finally $\ell_{\text{queue}} \mapsto (\ell_{\text{head}}, \ell_{\text{tail}})$.

As we did for the two-lock version, we allocate an empty abstract queue, giving us some ghost name γ_{Abst} that we put into Q_γ , and the resources $Q_\gamma \cdot \gamma_{\text{Abst}} \Rightarrow_\bullet [] * Q_\gamma \cdot \gamma_{\text{Abst}} \Rightarrow_\circ []$. To allocate the invariant, we must additionally obtain abstract reach propositions. Since x_1 is a node, we may use lemma 15 to conclude $x_1 \rightsquigarrow x_1$. We can now use lemma 20 three times, giving us ghost names γ_{Head} , γ_{Tail} , γ_{Last} which we again put into Q_γ , and the resources

$$Q_\gamma \cdot \gamma_{\text{Head}} \succ \rightarrow x_1 * Q_\gamma \cdot \gamma_{\text{Tail}} \succ \rightarrow x_1 * x_1 \dashrightarrow Q_\gamma \cdot \gamma_{\text{Tail}} * Q_\gamma \cdot \gamma_{\text{Last}} \succ \rightarrow x_1 * x_1 \dashrightarrow Q_\gamma \cdot \gamma_{\text{Last}}$$

We now have all the resources we need to allocate the invariant with the head, tail, and last node being x_1 .

With the invariant allocated, proving the post-condition becomes straightforward. \square

Swing Tail

The specification we wish to prove is the following.

Lemma 25 (Swing Tail). $\forall \ell_{\text{head}}, \ell_{\text{tail}}, x_{\text{tail}}, x_{\text{newtail}}, Q_\gamma.$
 $\left\{ \boxed{\text{LFH}(\ell_{\text{head}}, \ell_{\text{tail}}, Q_\gamma)}^{\mathcal{N}.queue} * x_{\text{tail}} \rightsquigarrow x_{\text{newtail}} * x_{\text{newtail}} \dashrightarrow Q_\gamma.\gamma_{\text{Last}} \right\}$
CAS $\ell_{\text{tail}} \text{ in}(x_{\text{tail}}) \text{ in}(x_{\text{newtail}})$
 $\{w.w = \text{true} \vee w = \text{false}\}$

Proof. The rule for **CAS** demands that we have a points-to predicate for ℓ_{tail} . This is available inside the invariant, so we proceed to open it. This tells us that there is some x'_{tail} so that $\ell_{\text{tail}} \mapsto x'_{\text{tail}}$. We consider both cases of the CAS:

Case CAS succeeds. It must then have been the case that $\text{in}(x'_{\text{tail}}) = \text{in}(x_{\text{tail}})$. Since we have $x_{\text{tail}} \rightsquigarrow x_{\text{newtail}}$, we know that x_{tail} is a node (lemma 17). From the invariant, we additionally got that $Q_\gamma.\gamma_{\text{Tail}} \mapsto x'_{\text{tail}}$ and $x_{\text{head}} \dashrightarrow Q_\gamma.\gamma_{\text{Tail}}$, which by lemma 21 means that $x_{\text{head}} \rightsquigarrow x'_{\text{tail}}$. We can thus also conclude that x'_{tail} is a node (lemma 18). So since both x_{tail} and x'_{tail} are nodes, and $\text{in}(x'_{\text{tail}}) = \text{in}(x_{\text{tail}})$, then it must be that $x_{\text{tail}} = x'_{\text{tail}}$. In other words, we have now know that $Q_\gamma.\gamma_{\text{Tail}} \mapsto x_{\text{tail}}$.

Since the **CAS** succeeded, we now have that $\ell_{\text{tail}} \mapsto \text{in}(x_{\text{newtail}})$. Since the invariant demands that $Q_\gamma.\gamma_{\text{Tail}}$ and ℓ_{tail} agree on the node they point to, we must update $Q_\gamma.\gamma_{\text{Tail}} \mapsto x_{\text{tail}}$ to $Q_\gamma.\gamma_{\text{Tail}} \mapsto x_{\text{newtail}}$. We can do this using lemma 23 as we assumed $x_{\text{tail}} \rightsquigarrow x_{\text{newtail}}$. With this, we can close the invariant again, using x_{newtail} as the tail node.

The **CAS** evaluates to **true** which we use to prove the first disjunct of the post-condition.

Case CAS Fails. Since the **CAS** failed, nothing was updated, and we can close the invariant again with the same resources we got out of it. The **CAS** evaluates to **false**, hence we can prove the second disjunct in the post-condition.

□

Enqueue

Lemma 26 (Lock-Free M&S-Queue Specification - Enqueue).

$$\forall v_q, v, Q_\gamma, P, Q. (\forall x s_v. Q_\gamma.\gamma_{\text{Abst}} \mapsto_\bullet x s_v * P \Rightarrow_{\mathcal{E} \setminus \mathcal{N}.i^\dagger} \triangleright Q_\gamma.\gamma_{\text{Abst}} \mapsto_\bullet v :: x s_v * Q) \multimap \{ \text{is_queue}(v_q, Q_\gamma) * P \} \text{ enqueue } v_q \ v \ \{w.Q\}$$

Proof. We assume the viewshift and proceed to prove the hoare triple. By definition of is_queue , we know that the queue v_q is a location ℓ_{queue} and there are locations ℓ_{head} and ℓ_{tail} so that

$$\ell_{\text{queue}} \mapsto^\square (\ell_{\text{head}}, \ell_{\text{tail}}) * \boxed{\text{LFH}(\ell_{\text{head}}, \ell_{\text{tail}}, Q_\gamma)}^{\mathcal{N}.queue} \quad (7.1)$$

We first step through line 2 which creates a new node x_{new} , so that

$$\text{in}(x_{\text{new}}) \mapsto^\square (\text{Some } v, \text{out}(x_{\text{new}})) \quad (7.2)$$

$$\text{out}(x_{\text{new}}) \mapsto \text{None} \quad (7.3)$$

The next line is the beginning of the looping function. We proceed by löb induction, which allows us to assume the hoare triple we wish to prove *later*. This means that, if we reach a recursive call, we will have the hoare triple that we must prove – the later will be immediately stripped when we apply $()$ and “step into” the recursive function.

Line 4 first dereferences to the tail pointer ℓ_{tail} using the resources in 7.1. We open the invariant to obtain the points-to predicate concerning ℓ_{tail} . We get that ℓ_{tail} points to some x_{tail} . Using the resources from the invariant, we may conclude the following persistent information:

$$x_{\text{tail}} \dashrightarrow Q_\gamma.\gamma_{\text{Last}} \quad (7.4)$$

$$\text{in}(x_{\text{tail}}) \mapsto^\square (\text{val}(x_{\text{tail}}), \text{out}(x_{\text{tail}})) \quad (7.5)$$

The first part is directly from the invariant, and the second we may derive using lemmas 21 and 18. We perform the load, and close the invariant.

The next line (line 5) finds out what x_{tail} points to. Using 7.5 we step to $!(\text{out}(x_{\text{tail}}))$. The points-to predicate required to perform this dereference is owned by the invariant (as it might be non-persistent), so we open the invariant again. We get that there is some x_{last} , with $Q_{\gamma}.\gamma_{\text{Last}} \rightsquigarrow x_{\text{last}}$. From this, 7.4, and lemma 21 we conclude $x_{\text{tail}} \rightsquigarrow x_{\text{last}}$. This gives us two cases to consider: either x_{tail} is x_{last} (meaning that x_{tail} is not lagging behind), or it points to some node $x_{\text{tail_next}}$ which can reach x_{last} (meaning that x_{tail} is lagging behind).

Case $x_{\text{tail}} = x_{\text{last}}$. Since we had $\text{isLast}(x_{\text{last}}, xs)$, we know that x_{tail} is the last node in the linked list, hence it points to None. We perform the load which sets next to None, and close the invariant.

We proceed to the consistency check on line 6. As before, the points-to predicate for ℓ_{tail} is in the invariant, so we open it. We get $\ell_{\text{tail}} \mapsto x'_{\text{tail}}$, for some x'_{tail} . Using this, we perform the dereference and close the invariant. The branch taken now depends on whether or not x'_{tail} is consistent with x_{tail} . In case they aren't, we take the "else" branch on line 12, which simply consists of a recursive call to the looping function. We are done by the induction hypothesis (from the l b induction).

If they are consistent, we take the "then" branch and step to line 7. Here we check whether or not next is None. We already know this is the case, so we proceed to line 8. This consists of a CAS instruction which attempts to add x_{new} to the linked list. The CAS will succeed if and only if ℓ_{tail} still points to None. We open the invariant to gain access to the relevant points-to predicate. Similarly to what we did earlier, we apply lemma 21 to conclude $x_{\text{tail}} \rightsquigarrow x'_{\text{last}}$, where x'_{last} is the current last node of the linked list (according to the invariant). As before, we perform case analysis on $x_{\text{tail}} \rightsquigarrow x'_{\text{last}}$.

Case $x_{\text{tail}} = x'_{\text{last}}$. We now know that x_{tail} is still the last node in the linked list, hence $\text{out}(x_{\text{tail}}) \mapsto \text{None}$, and the CAS will succeed. This instruction makes x_{tail} point to x_{new} , which essentially adds it to the linked list. Thus, the value in x_{new} becomes enqueued. In other words, this is a linearisation point, so we must apply the viewshift. We instantiate the viewshift with the abstract state of the queue xs_v from the invariant opening, and supply $Q_{\gamma}.\gamma_{\text{Abst}} \models_{\bullet} xs_v$ from the invariant and the P from the pre-condition. We hence get $Q_{\gamma}.\gamma_{\text{Abst}} \models_{\bullet} v :: xs_v$ and Q . When closing the invariant, we use $(v :: xs_v)$ for the abstract state, $(x_{\text{new}} :: xs)$ for the concrete state, $x_{\text{new}} :: xs_{\text{queue}}$ for the queue, and we take x_{new} to be the last node. The head and tail nodes remain the same. This means we give up $Q_{\gamma}.\gamma_{\text{Abst}} \models_{\bullet} v :: xs_v$ that we got from the viewshift, and the points-to predicate 7.3 (used to assert $\text{isLL}(x_{\text{new}} :: xs)$). The only thing left to prove is $Q_{\gamma}.\gamma_{\text{Last}} \rightsquigarrow x_{\text{new}}$. From the invariant opening, we have $Q_{\gamma}.\gamma_{\text{Last}} \rightsquigarrow x_{\text{tail}}$. Since $x_{\text{tail}} \rightsquigarrow x_{\text{new}}$, we may apply lemma 23 to update the abstract points-to resource to $Q_{\gamma}.\gamma_{\text{Last}} \rightsquigarrow x_{\text{new}}$ and additionally obtain $x_{\text{new}} \dashrightarrow Q_{\gamma}.\gamma_{\text{Last}}$. With this, we can close the invariant, and step to line 9. This line attempts to swing the tail, so we apply our swing-tail lemma (lemma 25) by supplying our invariant, $x_{\text{tail}} \rightsquigarrow x_{\text{new}}$, and $x_{\text{new}} \dashrightarrow Q_{\gamma}.\gamma_{\text{Last}}$. This tells us that the CAS is safe, and it either succeeds or fails. The resulting value is the returned value of the enqueue function, but since the post-condition is simply Q , which we own, we are done.

Case $\text{out}(x_{\text{tail}}) \mapsto^{\square} \text{in}(x_{\text{tail_next}}) * x_{\text{tail_next}} \rightsquigarrow x_{\text{last}}$. Since x_{tail} doesn't point to None, the CAS will fail. We close the invariant and step to line 10. We finish by applying the induction hypothesis.

Case $\text{out}(x_{\text{tail}}) \mapsto^{\square} \text{in}(x_{\text{tail_next}}) * x_{\text{tail_next}} \rightsquigarrow x_{\text{last}}$. Using this we perform the load, which sets next to $\text{in}(x_{\text{tail_next}})$. Before closing the invariant, we apply lemma 22 with $x_{\text{tail_next}} \rightsquigarrow x_{\text{last}}$ and $Q_{\gamma}.\gamma_{\text{Last}} \rightsquigarrow x_{\text{last}}$ to obtain $x_{\text{tail_next}} \dashrightarrow Q_{\gamma}.\gamma_{\text{Last}}$. We now proceed to close the invariant. Next, we reach the consistency check. We handle it similarly to the previous case: open the invariant, get some x'_{tail} , close the invariant, and in case of inconsistency, apply induction hypothesis. If the nodes are consistent, we step to line 7. This time, the check will fail as next is $\text{in}(x_{\text{tail_next}})$ which is not None. Hence we step to line 11 which attempts to swing the tail pointer. We here apply lemma 25 which we can do as we own the invariant, $x_{\text{tail}} \rightsquigarrow x_{\text{tail_next}}$, and $x_{\text{tail_next}} \dashrightarrow Q_{\gamma}.\gamma_{\text{Last}}$. We step through to the recursive call and finish by applying the induction hypothesis.

□

Deque

Lemma 27 (Lock-Free M&S-Queue Specification - Dequeue).

$$\forall v_q, Q_\gamma, P, Q. \left(\forall xs_v. Q_\gamma \cdot \gamma_{\text{Abst}} \Rightarrow_\bullet xs_v * P \Rightarrow_{\mathcal{E} \setminus \mathcal{N}.i} \triangleright \left(\begin{array}{l} (xs_v = [] * Q_\gamma \cdot \gamma_{\text{Abst}} \Rightarrow_\bullet xs_v * Q(\text{None})) \\ \vee \left(\begin{array}{l} \exists v, xs'_v. xs_v = xs'_v ++ [v] * \\ Q_\gamma \cdot \gamma_{\text{Abst}} \Rightarrow_\bullet xs'_v * Q(\text{Some } v) \end{array} \right) \end{array} \right) \right) \right) \rightarrow^* \\ \{\text{is_queue}(v_q, Q_\gamma) * P\} \text{ dequeue } v_q \{w. Q(w)\}$$

Proof. We assume the viewshift and must prove the hoare triple. As before, we know from `is_queue` that the queue v_q is a location ℓ_{queue} and there are locations ℓ_{head} and ℓ_{tail} so that

$$\ell_{\text{queue}} \mapsto^\square (\ell_{\text{head}}, \ell_{\text{tail}}) * \boxed{\text{LFH}(\ell_{\text{head}}, \ell_{\text{tail}}, Q_\gamma)}^{\mathcal{N}.queue} \quad (7.6)$$

The body of `dequeue` is the loop, so we immediately apply l\"ob induction. We step through the function application, and into the looping function to line 3. This line dereferences ℓ_{head} , so we open the invariant to access the associated points-to predicate. We obtain that ℓ_{head} points to some x_{head} , meaning the load results to $\text{in}(x_{\text{head}})$. We also derive the following information

$$\text{in}(x_{\text{head}}) \mapsto^\square (\text{val}(x_{\text{head}}), \text{out}(x_{\text{head}})) \quad (7.7)$$

$$x_{\text{head}} \dashrightarrow Q_\gamma \cdot \gamma_{\text{Head}} \quad (7.8)$$

$$x_{\text{head}} \dashrightarrow Q_\gamma \cdot \gamma_{\text{Tail}} \quad (7.9)$$

$$x_{\text{head}} \dashrightarrow Q_\gamma \cdot \gamma_{\text{Last}} \quad (7.10)$$

From the abstract points-to predicates from the invariant and lemma 21 we get that $x_{\text{head}} \rightsquigarrow x_{\text{tail}}$, so by lemma 17, we know that x_{head} is a node. This shows 7.7. By reflexivity of `reach` (lemma 15) we additionally know that $x_{\text{head}} \rightsquigarrow x_{\text{head}}$. Lemma 22 then gives us 7.8 and 7.9.

Lastly, we use lemma 21 to deduce that $x_{\text{tail}} \rightsquigarrow x_{\text{last}}$. By transitivity of `reach` (lemma 16) we have that $x_{\text{head}} \rightsquigarrow x_{\text{last}}$, which we use with lemma 22 to get 7.10.

We now close the invariant and step to line 4 which attempts to read ℓ_{tail} . We open the invariant, which tells us that ℓ_{tail} points to some x_{tail} (not necessarily the same as the previous invariant opening), and we perform the load. From the abstract points-to and `reach` predicates from the invariant together with 7.9 and lemmas 21, 18, and 22 we get the following

$$\text{in}(x_{\text{tail}}) \mapsto^\square (\text{val}(x_{\text{tail}}), \text{out}(x_{\text{tail}})) \quad (7.11)$$

$$x_{\text{head}} \rightsquigarrow x_{\text{tail}} \quad (7.12)$$

$$x_{\text{tail}} \dashrightarrow Q_\gamma \cdot \gamma_{\text{Tail}} \quad (7.13)$$

$$(7.14)$$

We close the invariant and step to line 5. This line creates our *prophecy variable* p , which will be resolved on line 7. This allows us to reason about the result of the consistency check: we will later show that the expression associated with p (i.e. `!(fst(!Q))`) evaluates to some value v_p , but we can already now case on whether v_p will be equal to $\text{in}(x_{\text{head}})$ – the left hand side of the equality check on line 7.

Case $\text{in}(x_{\text{head}}) = v_p$. We continue to line 6, which finds out what x_{head} points to. As x_{head} could be the last node in the linked list, we don't have the relevant points-to predicate. We therefore open the invariant. We get the three nodes x'_{head} , x'_{tail} , and x_{last} . Specifically, x_{last} is the last node in the linked list, and

$$Q_\gamma \cdot \gamma_{\text{Last}} \rightsquigarrow x_{\text{last}} \quad (7.15)$$

Combining this with 7.10 and lemma 21 we conclude $x_{\text{head}} \rightsquigarrow x_{\text{last}}$. This gives us two cases to consider: either $x_{\text{head}} = x_{\text{last}}$ or x_{head} points to some $x_{\text{head_next}}$, which reaches x_{last} .

Case $x_{\text{head}} = x_{\text{last}}$. This corresponds to the queue being empty, which we derive below.

As x_{last} is the last node, we have that $\text{out}(x_{\text{head}}) \mapsto \text{None}$, hence the load resolves to `None`.

Using the abstract points-to predicates from the invariant together with 7.8, 7.9, and lemma 21 we get $x_{\text{head}} \rightsquigarrow x'_{\text{head}}$ and $x_{\text{head}} \rightsquigarrow x'_{\text{tail}}$. We can now apply lemma 19 three times to conclude

$x_{\text{head}} = x'_{\text{head}} = x'_{\text{tail}} = x_{\text{tail}}$. Since x'_{head} points to None, then x_{queue} has to be empty (if it wasn't we could deduce that x'_{head} pointed to a node). This also implies that abstract state of the queue x_{s_v} , is empty, $x_{s_v} = []$.

Because the load resolved to None, then the variable next in the code will be None, and since we are in the case where the consistency check passes, and since we have derived that $x_{\text{head}} = x_{\text{tail}}$, we already know now that dequeue will return None. In other words, this is a linearisation point.

Since $x_{s_v} = []$, then our abstract state predicate from the invariant states $Q_{\gamma} \cdot \gamma_{\text{Abst}} \models_{\bullet} []$. We thus instantiate the viewshift with $[]$, and supply the P from the pre-condition. As $x_{s_v} = []$ we can conclude that the first disjunct must be true (the second contains a contradiction), so we get $Q(\text{None})$ and $Q_{\gamma} \cdot \gamma_{\text{Abst}} \models_{\bullet} []$. As we haven't changed any resources, we can close the invariant again.

We reach the consistency check on line 7. By 7.6, we know that $!(\text{fst}(!Q))$ steps to $!(\ell_{\text{head}})$, but to resolve the prophecy, we must first show what $!(\ell_{\text{head}})$ evaluates to. This resource is inside the invariant so we open it. We get that $\ell_{\text{head}} \mapsto \text{in}(x''_{\text{head}})$ for some node x''_{head} . We close the invariant and resolve the prophecy: $!(\text{fst}(!Q))$ evaluated to $\text{in}(x''_{\text{head}})$. In other words, $v_p = \text{in}(x''_{\text{head}})$, and therefore $\text{in}(x_{\text{head}}) = \text{in}(x''_{\text{head}})$. Since the remaining if statement on line 7 compares $\text{in}(x_{\text{head}})$ to $\text{in}(x''_{\text{head}})$, we know that we will take the “then” branch, so we step to line 8. Since $x_{\text{head}} = x_{\text{tail}}$ and next was set to None, we step to line 10 which returns None. The post-condition thus requires us to prove $Q(\text{None})$, which we already have.

Case $\text{out}(x_{\text{head}}) \mapsto^{\square} \text{in}(x_{\text{head_next}}) * x_{\text{head_next}} \rightsquigarrow x_{\text{last}}$. This means that the queue is not empty, and there is an element to be dequeued: the value in $x_{\text{head_next}}$. The load resolves to $\text{in}(x_{\text{head_next}})$, and the program variable next is set to this. Using lemmas 17 and 22 with 7.15 we get

$$\text{in}(x_{\text{head_next}}) \mapsto^{\square} (\text{val}(x_{\text{head_next}}), \text{out}(x_{\text{head_next}})) \quad (7.16)$$

$$x_{\text{head_next}} \dashrightarrow Q_{\gamma} \cdot \gamma_{\text{Last}} \quad (7.17)$$

We close the invariant and step to the consistency check on line 7. We handle this similarly to the previous case, and conclude that the consistency check succeeds and we take the “then” branch to line 8. This line ensures that the dequeue will not make the tail node lag behind the head node. We can simply consider both cases of the check.

The case where the “if” succeeds takes us to the **CAS** on line 12, which attempts to swing the tail, and try dequeuing again. We handle the **CAS** with our swing-tail lemma (lemma 25), and the recursive call by the induction hypothesis.

If the “if” fails, then the tail node will not lag behind as a result of the dequeue, so we step to the else block on line 13 which attempts to dequeue. We first read the value out of $x_{\text{head_next}}$ on line 14. Next, we attempt to swing the head pointer on line 15. The rule for **CAS** demands a points-to predicate for ℓ_{head} , so we open the invariant which gives us fresh nodes x'_{head} , x'_{tail} , and x'_{last} , so that $\ell_{\text{head}} \mapsto \text{in}(x'_{\text{head}})$. The success of the **CAS** depends on whether $\text{in}(x'_{\text{head}})$ equals $\text{in}(x_{\text{head}})$. If they aren't equal, the **CAS** fails and nothing is updated. We can thus close the invariant and we step to the recursive call on line 17 and apply the induction hypothesis. So for the remainder, we assume they are equal and the **CAS** succeeds. Since the **CAS** moved the head pointer to $x_{\text{head_next}}$, the queue data structure changed, so this is a linearisation point.

Using the abstract points-to and reachability propositions from the invariant together with lemmas 21 and 17, we may deduce that x'_{head} is a node. As we already know that x_{head} is a node (from 7.7), we get that $x_{\text{head}} = x'_{\text{head}}$ from lemma 28. From the invariant (specifically isLL x_s) we know that x'_{head} points to the first element of x_{queue} . But since $x_{\text{head}} = x'_{\text{head}}$, then this element must be our $x_{\text{head_next}}$. In other words, $x_{\text{queue}} = x_{\text{queue}} ++ [x_{\text{head_next}}]$, for some x_{queue} . This means that, when we apply the viewshift (giving up P and $Q_{\gamma} \cdot \gamma_{\text{Abst}} \models_{\bullet} x_{s_v}$ as usual), only the second case of the resulting disjunct is possible: x_{s_v} cannot be empty as x_{queue} isn't. We therefore get that there are some $x_{s'_v}$ and v so that

$$x_{s_v} = x_{s'_v} ++ [v] \quad (7.18)$$

$$Q_{\gamma} \cdot \gamma_{\text{Abst}} \models_{\bullet} x_{s'_v} \quad (7.19)$$

$$Q(\text{Some } v) \quad (7.20)$$

Since xs_v is reflected in xs_{queue} (according to the invariant), we may additionally conclude that xs'_v is reflected in xs'_{queue} and $\text{Some } v = \text{val}(x_{\text{head_next}})$.

To close the invariant, we must update some of our resources. Since we now have $\ell_{\text{head}} \mapsto \text{in}(x_{\text{head_next}})$, we must pick $x_{\text{head_next}}$ for the head node. But currently $Q_{\gamma}.\gamma_{\text{Head}} \mapsto x_{\text{head}}$. So we use lemma 23 to advance the pointer, and we get $Q_{\gamma}.\gamma_{\text{Head}} \mapsto x_{\text{head_next}}$.

We are now required to show that $x_{\text{head_next}} \dashrightarrow Q_{\gamma}.\gamma_{\text{Tail}}$. Since $x_{\text{head}} \leadsto x_{\text{tail}}$, and $x_{\text{head}} \neq x_{\text{tail}}$, then it must be the case that $x_{\text{head_next}} \leadsto x_{\text{tail}}$. Lemma 21 with 7.13 now tells us that x_{tail} can reach the current tail node, x'_{tail} . By transitivity (lemma 16), we get $x_{\text{head_next}} \leadsto x'_{\text{tail}}$, and hence by lemma 22, we get the desired $x_{\text{head_next}} \dashrightarrow Q_{\gamma}.\gamma_{\text{Tail}}$.

We now own all the resources required to close the invariant. As the CAS succeed, we step to line 16 which simply returns $\text{val}(x_{\text{head_next}})$. Thus, we must prove the post-condition $Q(\text{val}(x_{\text{head_next}}))$. We can do this since we still own 7.20 and we deduced that $\text{Some } v = \text{val}(x_{\text{head_next}})$.

Case $\text{in}(x_{\text{head}}) \neq v_p$. We step to line 6 which finds out what x_{head} points to. To access the relevant points-to predicate, open the invariant. Importantly, we get that there is some last node of the linked list, x_{last} , with $Q_{\gamma}.\gamma_{\text{Last}} \mapsto x_{\text{last}}$. By combining this with 7.10 and lemma 21 we deduce that $x_{\text{head}} \leadsto x_{\text{last}}$ which means that either x_{head} is the last node, and hence $\text{out}(x_{\text{head}}) \mapsto \text{None}$, or there is some other node $x_{\text{head_next}}$ and $\text{out}(x_{\text{head}}) \mapsto^{\square} x_{\text{head_next}}$. This shows that the load is safe. The actual value that the load resolves to is unimportant, as it won't be used in this case. We thus perform the load, close the invariant and step to line 7.

By 7.6, we know that $!(\text{fst}(!Q))$ steps to $!(\ell_{\text{head}})$, so to resolve the prophecy, we show what $!(\ell_{\text{head}})$ evaluates to. We open the invariant, which gives us that $\ell_{\text{head}} \mapsto \text{in}(x'_{\text{head}})$ for some node x'_{head} . We close the invariant again, and resolve the prophecy: $!(\text{fst}(!Q))$ evaluated to $\text{in}(x'_{\text{head}})$. That is, $v_p = \text{in}(x'_{\text{head}})$, and therefore $\text{in}(x_{\text{head}}) \neq \text{in}(x'_{\text{head}})$. We hence take the “else” branch and step to line 18. This consists of a recursive call to the loop function, hence we are done by the induction hypothesis. □

7.7 Discussion

It was shown in [5] that a version of the Lock-Free M&S-Queue with the consistency checks is contextually equivalent to a version without consistency checks. In the original presentation ([4]) the implementation language was assumed to not have a garbage collector. This meant that the ABA problem was an issue; if a node is freed by a dequeue, and afterwards a new node is allocated at the same location with the same value through an enqueue, it will look as though it is the exact same node. This can cause inconsistencies for threads that read the original node, went to sleep, and continued after the new allocation. To fix the issue, the authors added *modification counters* to their pointers, which means that the pointer to the newly allocated node will have a higher counter, and we can hence tell that it isn't the same node as the original. The essence of the consistency checks is to ensure that previously read nodes are the exact same nodes as from before, by ensuring that the counter is the same. We do this check *after* reading any “next” nodes to ensure that they are indeed the next of the node we originally read – the original node and its next node are consistent.

However, the language that both we and [5] have used, HeapLang, is a garbage collected language. This means that we do not need to worry about freeing nodes, and the ABA problem doesn't occur. In other words, when we read the “next” of a node, we can be certain that it is the next of the node we originally read – no one could have freed it in a dequeue it and subsequently allocated a similar looking node in an enqueue. This then means that the consistency checks are no longer needed.

Indeed, in the Coq formalisations, we prove the Hocap-style specification for an implementation that doesn't have the consistency checks. As an additional benefit, removing the consistency check means that in dequeue, we know already when we read the “next” of the head node on line 6 whether or not the dequeue will conclude that the queue is empty, and hence whether or not the load is a linearisation point. The prophecy variable is thus not needed, which further simplifies the proof of the specification.

Chapter 8

Conclusion and Future Work

►conclude on the problem statement from the introduction◄

►Mention the possibility of simplifying queue invariant for lock-free by removing isLL (and adding x_last -> None)◄

Bibliography

- [1] Lars Birkedal and Aleš Bizjak. Lecture notes on iris: Higher-order concurrent separation logic. <http://iris-project.org/tutorial-pdfs/iris-lecture-notes.pdf>, 2017.
- [2] Maurice Herlihy and Jeannette M. Wing. Linearizability: A correctness condition for concurrent objects. *ACM Trans. Program. Lang. Syst.*, 12(3):463–492, 1990.
- [3] Ralf Jung, Robbert Krebbers, Jacques-Henri Jourdan, Ales Bizjak, Lars Birkedal, and Derek Dreyer. Iris from the ground up: A modular foundation for higher-order concurrent separation logic. *J. Funct. Program.*, 28:e20, 2018.
- [4] Maged M. Michael and Michael L. Scott. Simple, fast, and practical non-blocking and blocking concurrent queue algorithms. In James E. Burns and Yoram Moses, editors, *Proceedings of the Fifteenth Annual ACM Symposium on Principles of Distributed Computing, Philadelphia, Pennsylvania, USA, May 23-26, 1996*, pages 267–275. ACM, 1996.
- [5] Simon Friis Vindum and Lars Birkedal. Contextual refinement of the michael-scott queue (proof pearl). In Catalin Hritcu and Andrei Popescu, editors, *CPP '21: 10th ACM SIGPLAN International Conference on Certified Programs and Proofs, Virtual Event, Denmark, January 17-19, 2021*, pages 76–90. ACM, 2021.

Appendix A

The Technical Details

Lemma 28 (Node equality).

$$\begin{aligned}
& \forall x, y. \\
& \text{in}(x) = \text{in}(y) \multimap \\
& \text{in}(x) \mapsto^\square (\text{val}(x), \text{out}(x)) \multimap \\
& \text{in}(y) \mapsto^\square (\text{val}(y), \text{out}(y)) \multimap \\
& x = y
\end{aligned}$$

Definition A.0.1 (Simplified Two-Lock M&S-Queue Invariant).

$$\begin{aligned}
& \text{I}_{\text{TLC}}(\Phi, \ell_{\text{head}}, \ell_{\text{tail}}, Q_\gamma) \triangleq \\
& \exists xs_v. \text{All}(xs_v, \Phi) * \tag{abstract state} \\
& \exists xs, xs_{\text{queue}}, xs_{\text{old}}, x_{\text{head}}, x_{\text{tail}}. \tag{concrete state} \\
& xs = xs_{\text{queue}} ++ [x_{\text{head}}] ++ xs_{\text{old}} * \\
& \text{isLL}(xs) * \\
& \text{proj_val}(xs_{\text{queue}}) = \text{wrap_some}(xs_v) * \\
& ((\ell_{\text{head}} \mapsto \text{in}(x_{\text{head}}) * \text{ToknD } Q_\gamma) \vee (\ell_{\text{head}} \mapsto^{\frac{1}{2}} \text{in}(x_{\text{head}}) * \text{TokD } Q_\gamma)) * \\
& (\\
& (\ell_{\text{tail}} \mapsto \text{in}(x_{\text{tail}}) * \text{isLast}(x_{\text{tail}}, xs) * \text{ToknE } Q_\gamma * \text{TokUpdated } Q_\gamma) \vee \\
& (\\
& \ell_{\text{tail}} \mapsto^{\frac{1}{2}} \text{in}(x_{\text{tail}}) * \text{TokE } Q_\gamma * \\
& ((\text{isLast}(x_{\text{tail}}, xs) * \text{TokBefore } Q_\gamma) \vee (\text{isSndLast}(x_{\text{tail}}, xs) * \text{TokAfter } Q_\gamma)) \\
&) \\
&)
\end{aligned}$$

Definition A.0.2 (Two-Lock M&S-Queue Hocap Invariant).

$$\begin{aligned}
& \text{ITLH}(\ell_{\text{head}}, \ell_{\text{tail}}, Q_\gamma) \triangleq \\
& \exists xs_v. Q_\gamma.\gamma_{\text{Abst}} \mapsto_\bullet xs_v * \quad (\text{abstract state}) \\
& \exists xs, xs_{\text{queue}}, xs_{\text{old}}, x_{\text{head}}, x_{\text{tail}}. \quad (\text{concrete state}) \\
& xs = xs_{\text{queue}} ++ [x_{\text{head}}] ++ xs_{\text{old}} * \\
& \text{isLL}(xs) * \\
& \text{proj_val}(xs_{\text{queue}}) = \text{wrap_some}(xs_v) * \\
& (\\
& \quad \ell_{\text{head}} \mapsto \text{in}(x_{\text{head}}) * \ell_{\text{tail}} \mapsto \text{in}(x_{\text{tail}}) * \text{isLast}(x_{\text{tail}}, xs) * \quad (\text{Static}) \\
& \quad \text{ToknE } Q_\gamma * \text{ToknD } Q_\gamma * \text{TokUpdated } Q_\gamma \\
& \vee \\
& \quad \ell_{\text{head}} \mapsto \text{in}(x_{\text{head}}) * \ell_{\text{tail}} \mapsto^{\frac{1}{2}} \text{in}(x_{\text{tail}}) * \quad (\text{Enqueue}) \\
& \quad (\text{isLast}(x_{\text{tail}}, xs) * \text{TokBefore } Q_\gamma \vee \text{isSndLast}(x_{\text{tail}}, xs) * \text{TokAfter } Q_\gamma) * \\
& \quad \text{TokE } Q_\gamma * \text{ToknD } Q_\gamma \\
& \vee \\
& \quad \ell_{\text{head}} \mapsto^{\frac{1}{2}} \text{in}(x_{\text{head}}) * \ell_{\text{tail}} \mapsto \text{in}(x_{\text{tail}}) * \text{isLast}(x_{\text{tail}}, xs) * \quad (\text{Dequeue}) \\
& \quad \text{ToknE } Q_\gamma * \text{TokD } Q_\gamma * \text{TokUpdated } Q_\gamma \\
& \vee \\
& \quad \ell_{\text{head}} \mapsto^{\frac{1}{2}} \text{in}(x_{\text{head}}) * \ell_{\text{tail}} \mapsto^{\frac{1}{2}} \text{in}(x_{\text{tail}}) * \quad (\text{Both}) \\
& \quad (\text{isLast}(x_{\text{tail}}, xs) * \text{TokBefore } Q_\gamma \vee \text{isSndLast}(x_{\text{tail}}, xs) * \text{TokAfter } Q_\gamma) * \\
& \quad \text{TokE } Q_\gamma * \text{TokD } Q_\gamma \\
&)
\end{aligned}$$

Definition A.0.3 (Two-Lock M&S-Queue - is_queue Predicate (Hocap)).

$$\begin{aligned}
& \text{is_queue_conc}(v_q, Q_\gamma) \triangleq \exists \ell_{\text{queue}}, \ell_{\text{head}}, \ell_{\text{tail}} \in \text{Loc}. \exists h_{\text{lock}}, t_{\text{lock}} \in \text{Val}. \\
& v_q = \ell_{\text{queue}} * \ell_{\text{queue}} \mapsto^\square ((\ell_{\text{head}}, \ell_{\text{tail}}), (h_{\text{lock}}, t_{\text{lock}})) * \\
& \boxed{\text{ITLH}(\Phi, \ell_{\text{head}}, \ell_{\text{tail}}, Q_\gamma)}^{\mathcal{N}.\text{queue}} * \\
& \text{isLock}(Q_\gamma.\gamma_{\text{Hlock}}, h_{\text{lock}}, \text{TokD } Q_\gamma) * \\
& \text{isLock}(Q_\gamma.\gamma_{\text{Tlock}}, t_{\text{lock}}, \text{TokE } Q_\gamma).
\end{aligned}$$