9 – Segment

Segment is a feature of Cilium's eBPF data plane that can be used to enforce policy based on arbitrary labels that can be defined dynamically at deployment time using environment variables rather than being statically defined in the policy definition.

This is useful for example when deploying the same application multiple times in the same cluster (e.g. blue/green deployments) or when deploying multiple applications that expect the same network policy labels to be present.

- **Segment Identifier**: The segment identifier is the value that is stored in the `io.cilium.k8s.policy.segment` label.
- **Segment Isolation**: This option enables the isolation for workloads within the same segment, while allowing communication between workloads not assigned any segment.

- **Segment Exclusive**: This option enables exclusive segment behavior, meaning that workloads not belonging to a segment cannot communicate with workloads that belong to a segment.

Helm Installation

```
helm repo add isovalent https://helm.isovalent.com

helm install cilium isovalent/cilium \
  --set cni.chainingMode=generic-veth \
  --set cni.customConf=true \
  --set policyEnforcementMode=never \
  --set bpf.vlanBypass={0,1,2,3,4,5,6,7,8,9,10,11,12,13,14,15,16,17,18,19,20,21,22,23,24,25,26,27,28,29,30,31,32,33,34,35,36,37,38,39,40,41,42,43,44,45,46,47,48,49,50,51,52,53,54,55,56,57,58,59,60,61,62,63,64,65,66,67,68,69,70,71,72,73,74,75,76,77,78,79,80,81,82,83,84,85,86,87,88,89,90,91,92,93,94,95,96,97,98,99,100} \
  --set ipam.mode=kubernetes \
  --set enableIPv4Masquerade=false \
  --set devices=eth+ \
  --set nodeinit.enabled=true \
  --set nodeinit.reconfigureKubelet=true \
  --set nodeinit.removeCbrBridge=true \
  --set cni.binPath=/home/kubernetes/bin \
  --set nodeinit.restartPods=true \
  --set hubble.relay.enabled=true \
  --set hubble.ui.enabled=true \
  --set segment.enabled=true \
  --set segment.segmentIsolation=true \
  --set segment.segmentExclusive=true \
  --set segment.segmentIdentifier=io.cilium.k8s.policy.segment \
  --set segment.segmentIsolationExclusion="{kube-system,cilium-monitoring}" \
  --set segment.segmentIsolationInclusion="{}" \
  --set segment.segmentExclusiveExclusion="{kube-system,cilium-monitoring}" \
  --set segment.segmentExclusiveInclusion="{}"
```

CNP Examples

```
apiVersion: "cilium.io/v2"
kind: CiliumNetworkPolicy
metadata:
  name: "segment-example-1"
spec:
  endpointSelector:
    matchLabels:
      app: tiefighter
      io.cilium.k8s.policy.segment: blue
  egress:
  - toEndpoints:
    - matchLabels:
        app: deathstar
        io.cilium.k8s.policy.segment: blue
    toPorts:
    - ports:
      - port: "80"
        protocol: TCP
```

Setting the Public IP and Local BGA Setup

Before you start, make sure that the Cilium agent is running on your node. You can check the current status of Cilium in a Kubernetes cluster with the following command:

```
cilium-dbg status
```

Next, you need to configure the Cilium BGP Control Plane by creating a `CiliumBGPClusterConfig` resource. This resource defines the BGP peers and the local ASN (Autonomous System Number) for your node. Here's an example configuration:

```
apiVersion: cilium.io/v2alpha1
kind: CiliumBGPClusterConfig
metadata:
  name: cilium-bgp
spec:
  nodeSelector:
    matchLabels:
      kubernetes.io/hostname: node1
  bgpInstances:
  - name: "instance-65001"
    localASN: 65001
    peers:
    - name: "peer-65001-192-168-1-1"
      peerASN: 65001
      peerAddress: 192.168.1.1
      peerConfigRef:
        name: "cilium-peer"
```

In this configuration, `nodeSelector` specifies that this configuration applies to the node named `node1`. The `localASN` is set to `65001`, and there is one BGP peer with the IP address `192.168.1.1` and ASN `65001`.

Apply the configuration using `kubectl`:

```
kubectl apply -f cilium-bgp-config.yaml
```

Verify that the BGP session is established by checking the Cilium agent logs:

```
kubectl -n kube-system logs -l k8s-app=cilium | grep "BGP session established"
```

Public and Private IP Address Ranges

Type	Description	Starting Address
Class A	126 networks, 16,777,214 hosts each	10.0.0.0 to 10.255.255.255
Class B	16,384 networks, 65,534 hosts each	172.16.0.0 to 172.31.255.255
Class C	2,097,152 networks, 254 hosts each	192.168.0.0 to 192.168.255.255