# Kubernetes and Istio

10 - Istio observability

Generated: June 2026
Version 1.0

# 10 – helix observability

In this exercise we'll explore the Helix observability stack, which includes a local instance of Grafana, Loki, Prometheus, and Tempo. We'll start by looking at the Grafana dashboards that are provisioned automatically when you run `./stack start`, then move on to writing our own queries. Finally, we'll add some custom metrics and tracing to the Helix code, and see how they appear in the dashboards.

## 1. Grafana

Grafana is an open-source visualization platform for metrics, logs, and traces. It's the central place for us to observe what the Helix system is doing, and we've provisioned a number of dashboards for you automatically.

Open Grafana at http://localhost:3000.

**What kinds of questions can you ask here?**

- **Runner utilization** — How many runners are busy? Are they close to their memory limits?
- **Traffic** — Requests per second, error rates, latency percentiles, slow queries
- **Session activity** — How many sessions are active? How long are they waiting in the queue?
- **Scheduler health** — How long does it take to make a scheduling decision? Are there errors?
- **Database performance** — Slow queries, connection pool usage, transaction rates

**Server Overview** — Host-level metrics for the machine running Helix: CPU, memory, disk I/O, and network. Useful for spotting resource exhaustion that might affect Helix indirectly (e.g. the OOM killer terminating a runner).

**Helix Logs** — Application logs from the Helix API server, searchable by level, component, and free text. Logs are shipped to Loki automatically.

**Helix Runners** — Per-runner metrics: GPU utilization, VRAM usage, model load times, and inference throughput. Each runner is identified by its hostname.

**Helix Scheduler** — Deep dive into the scheduler's behavior: decision latency histograms, queue depths, and counts of scheduling outcomes (assigned, rejected, preempted).

**Helix Traces** — Distributed traces for individual requests, showing how time is spent across the API server, scheduler, and runners. Click through from a slow request in the logs to see exactly where it spent its time.

## 2. Logs

Helix writes structured logs to `/tmp/helix.log`. Each line is a JSON object with a timestamp, level, message, and a set of key-value fields. For example:

```
{"time":"2026-04-07T14:23:01.482Z","level":"INFO","msg":"session started","session_id":"ses_01HXYZ","runner":"runner-3","model":"llama-3.1-8b"}
```

Promtail (running in the background) tails this file and ships the entries to Loki. You can then query them in Grafana's Explore view using LogQL.

Open Grafana Explore at http://localhost:3000/explore.

**Useful LogQL queries:**

```
{job="helix"} | json | level="ERROR"
```

Show all error-level log lines.

```
{job="helix"} | json | component="scheduler"
```

Show only logs from the scheduler component.

```
{job="helix"} | json | session_id="ses_01HXYZ"
```

Show all log lines for a specific session.

```
rate({job="helix"} | json | level="ERROR" [5m])
```

Error rate over the last 5 minutes.

```
{job="helix"} | json | duration_ms > 1000
```

Slow operations (more than 1 second).

## 3. Prometheus

Prometheus scrapes metrics from the Helix API server every 15 seconds. Browse the raw metrics at http://localhost:8080/metrics.

**Key metrics to look for:**

- **`helix_scheduler_decision_duration_seconds`** — How long each scheduling decision takes. A histogram, so you can see p50, p95, and p99.
- **`helix_scheduler_queue_depth`** — Number of sessions waiting for a runner. Should usually be near zero.
- **`helix_runner_memory_bytes`** — Memory usage per runner, labeled by runner ID.
- **`helix_runner_gpu_utilization_ratio`** — GPU utilization per runner, from 0.0 to 1.0.
- **`helix_session_total`** — Counter of sessions started, labeled by model and outcome.
- **`helix_http_request_duration_seconds`** — API request latency, labeled by route and status code.

**Try these PromQL queries:**

```
rate(helix_session_total[5m])
```

Sessions started per second, averaged over the last 5 minutes.

```
histogram_quantile(0.95, rate(helix_scheduler_decision_duration_seconds_bucket[5m]))
```

95th percentile scheduler decision latency.

```
sum by (runner) (helix_runner_memory_bytes)
```

Total memory usage broken down by runner.

## 4. Traces

Tempo receives distributed traces from the Helix API server. Each HTTP request gets a trace, and the scheduler and runner interactions are recorded as spans within that trace.

Open Grafana Explore at http://localhost:3000/explore and select the Tempo data source.

**How to find a trace:**

- **Search by service** — Select `helix-api` and look for recent traces.
- **Search by duration** — Find slow requests by filtering for traces longer than a threshold.
- **Search by error** — Filter for traces with error status.
- **Follow from logs** — If a log line includes a `trace_id` field, click it to jump directly to the trace.

**What you'll see in a trace:**

- **HTTP request span** — The top-level span for the incoming request.
- **Scheduler decision span** — How long the scheduler spent finding a runner for the session.
- **Runner RPC span** — The call to the runner to start inference.
- **Inference span** — The actual model inference, including token generation.

## 5. Your turn

Now that you've seen how the existing observability stack works, let's add some of our own. Pick one of the following exercises and work through it. Each one touches a different part of the system.

**Exercise 1: Add a custom metric**

Add a new Prometheus counter that tracks how many times a user has clicked the "Retry" button in the UI. Then write a PromQL query to display the rate of retries per minute.

**Exercise 2: Add a trace span**

Add a new span around the function that assembles the system prompt. Record the number of tokens in the assembled prompt as a span attribute.

**Exercise 3: Build a dashboard**

Create a new Grafana dashboard called "My Dashboard" with at least three panels. Export it as JSON and save it to `grafana/dashboards/my-dashboard.json` so it's provisioned automatically next time.

**Exercise 4: Write an alert**

Write a Prometheus alerting rule that fires when the scheduler decision latency p95 exceeds 500ms for more than 2 minutes. Add it to `prometheus/rules/helix.yml` and verify it appears in the Prometheus UI at http://localhost:8080/alerts.

**Exercise 5: Correlate logs and traces**

Find a slow request in Tempo, then navigate to the corresponding log lines in Loki. Add a `trace_id` field to the relevant log statements in the Helix code if it's not already there.

**Exercise 6: Investigate a real problem**

Run `./stack start`, then open a few sessions and let them run for a while. Look for anything unexpected in the dashboards, logs, or traces. Write up what you found and what you think should be done about it.