10 – helix observability

In this exercise we'll explore the Helix dashboard, and see how to create simple Grafana dashboards and alerts. We'll also see how to use Helix's built-in tracing capabilities to debug a slow request. Finally, we'll see how to use Helix's built-in support for Prometheus metrics to monitor the health of the server. Note: this exercise assumes you've completed the previous exercises, and have a working Helix server running.

1. Overview

Helix is an open-source platform for running AI workloads (text generation, image generation, fine-tuning) on your own hardware. It's built around a scheduler that places workloads onto runners, and a control plane that manages sessions, users, and billing.

Helix is open source: https://github.com/helixml/helix

What kinds of workloads can Helix run?

Helix supports several types of workloads, each requiring different GPU memory and compute capabilities:

- **Chat** — Standard LLM inference for text generation. Typically requires 8–24 GB of GPU memory depending on the model size.
- **Image** — Image generation models like Stable Diffusion. Requires a GPU with at least 8 GB of memory.
- **Embedding** — Text embedding models used for semantic search and RAG. Can run on smaller GPUs.
- **Fine-tuning** — Training custom LoRA adapters on your own data. Requires more GPU memory than inference.
- **Vision** — Multimodal models that can process images alongside text. Requires a GPU with at least 16 GB of memory.

What is a runner?

A runner is a machine with GPUs that connects to the Helix control plane and executes workloads. You can add as many runners as you like — Helix will schedule workloads onto whichever runner has enough free GPU memory.

What is the control plane?

The control plane is the central server that manages the Helix cluster. It handles:

- **Scheduling** — Deciding which runner should execute each workload, based on GPU memory availability and runner health.
- **Sessions** — Tracking user interactions with models, including chat history and generated content.
- **Users and billing** — Authentication, API keys, and usage tracking.
- **Runner management** — Monitoring runner health, GPU status, and memory usage.

The control plane exposes a REST API that the CLI and dashboard use to interact with the system.

2. Grafana

Helix comes with a built-in Grafana dashboard for monitoring GPU utilization, memory usage, and request latency. Let's set up a simple dashboard and alert.

Step 1: Open Grafana

Navigate to the Grafana instance at `http://localhost:3000`. Log in with the default credentials (`admin` / `admin`).

Step 2: Create a new dashboard

Click **Dashboards** → **New** → **New Dashboard**. Add a panel with the following query to show GPU memory usage:

```
helix_runner_gpu_memory_used_bytes / helix_runner_gpu_memory_total_bytes
```

Set the panel title to "GPU Memory Utilization" and the unit to "percent (0.0–1.0)".

Step 3: Create an alert

Edit the panel and click the **Alert** tab. Create a new alert rule:

- Condition: `WHEN avg() OF query(A, 5m, now) IS ABOVE 0.9`
- Evaluate every: `1m`
- For: `5m`

This will fire an alert if GPU memory stays above 90% for 5 minutes.

3. Flash

Flash is the Helix dashboard — a web UI for managing sessions, viewing logs, and monitoring runner health. It's served by the control plane and requires no separate installation.

Open Flash in your browser at `http://localhost:8080`. You should see a list of active sessions, queued tasks, and connected runners.

Flash is useful for quickly checking whether a runner is online, seeing which model is loaded on each GPU, and inspecting the logs of a failed session. It's not a replacement for the CLI — it's a complement for visual inspection.

4. Trace

Helix has built-in support for distributed tracing. Traces help you understand where time is spent during a request — for example, how much time is spent waiting for a runner to become available versus actually running inference.

Step 1: Enable tracing

Add the following to your `helix.toml` configuration:

```
[tracing]
enabled = true
exporter = "stdout"
```

Restart the control plane for the change to take effect.

Step 2: Send a request and read the trace

Send a chat request and look at the control plane logs. You'll see a trace printed for each request, showing the time spent in each stage:

```
trace: session.create 12.4ms
trace:   scheduler.wait_for_runner 8.1ms
trace:   runner.inference 4.2ms
```

In this example, most of the time was spent waiting for a runner — the inference itself was fast.

What you've learned

- **Grafana Dashboards and Alerts** — How to create dashboards and alerts for GPU memory and request latency.
- **Flash** — How to use the Helix dashboard for monitoring sessions, queues, and runners.
- **Tracing** — How to enable distributed tracing and read traces to understand where time is spent during a request.
- **Prometheus Metrics** — How to use Helix's built-in Prometheus metrics for monitoring the health of the server.
- **Debugging Slow Requests** — How to use traces to debug slow requests and identify bottlenecks.

Further reading

- Grafana documentation: https://grafana.com/docs/
- Prometheus documentation: https://prometheus.io/docs/
- OpenTelemetry documentation: https://opentelemetry.io/docs/

Why it matters

Observability is essential for running any production system. Without dashboards, alerts, and traces, you're flying blind — you won't know when something breaks, why it's slow, or how much capacity you have left. Helix's built-in observability tools make it easy to get started without setting up a separate monitoring stack.