Measuring latency

Load Testing Overview

- Use load testing tools to test performance under expected traffic
- Locust
  - Define behavior using Python code
  - Web UI
  - Web-based
  - Can be run headless
  - Can be distributed
- Vegeta
  - Command line tool
  - Can be used as a library

Vegeta - REST Load Testing

- Command line tool and library

```
$ echo "GET http://localhost:8080/health" | vegeta attack -duration=30s | tee results.bin | vegeta report
Requests      [total, rate, throughput]         3000, 100.03, 100.02
Duration      [total, attack, wait]             29.99s, 29.99s, 1.332ms
Latencies     [min, mean, 50, 90, 95, 99, max]  1.103ms, 1.705ms, 1.569ms, 2.183ms, 2.539ms, 3.906ms, 12.483ms
Bytes In      [total, mean]                     24000, 8.00
Bytes Out     [total, mean]                     0, 0.00
Success       [ratio]                           100.00%
Status Codes  [code:count]                      200:3000
Error Set:
$ vegeta report -type=hist[0,2ms,4ms,6ms,8ms,10ms,12ms,14ms] < results.bin
Bucket           #    %       Histogram
[0s,     2ms]    2999 99.97%  ###############################################################
[2ms,    4ms]    0    0.00%
[4ms,    6ms]    0    0.00%
[6ms,    8ms]    0    0.00%
[8ms,    10ms]   0    0.00%
[10ms,   12ms]   0    0.00%
[12ms,   14ms]   1    0.03%
```

Vegeta - REST Load Testing

- Can be used as a library to write more powerful tests

```
package main

import (
    "fmt"
    "time"

    vegeta "github.com/tsenart/vegeta/lib"
)

func main() {
    rate := vegeta.Rate{Freq: 100, Per: time.Second}
    duration := 30 * time.Second
    targeter := vegeta.NewStaticTargeter(vegeta.Target{
        Method: "GET",
        URL:    "http://localhost:8080/health",
    })
    attacker := vegeta.NewAttacker()

    var metrics vegeta.Metrics
    for res := range attacker.Attack(targeter, rate, duration, "Big Bang!") {
        metrics.Add(res)
    }
    metrics.Close()

    fmt.Println("99th percentile:", metrics.Latencies.P99)
}
```

```
$ go run vegeta.go
99th percentile: 2.539ms
```

Vegeta - gRPC Load Testing

- Command line tool and library
- Protocol buffers and gRPC

```
$ echo '{"service": "Health"}' | vegeta attack -format=grpc -proto=health.proto -call=grpc.health.v1.Health.Check -duration=30s | tee results.bin | vegeta report
Requests      [total, rate, throughput]         3000, 100.03, 100.02
Duration      [total, attack, wait]             29.99s, 29.99s, 1.332ms
Latencies     [min, mean, 50, 90, 95, 99, max]  1.103ms, 1.705ms, 1.569ms, 2.183ms, 2.539ms, 3.906ms, 12.483ms
Bytes In      [total, mean]                     24000, 8.00
Bytes Out     [total, mean]                     0, 0.00
Success       [ratio]                           100.00%
Status Codes  [code:count]                      200:3000
Error Set:
```

gRPC - gRPC API

- Use in-built
- Use grpcurl

```
$ grpcurl -plaintext -d '{"service": "Health"}' localhost:8080 grpc.health.v1.Health.Check
{
  "status": "SERVING"
}
```

Locust - Customizable Load Testing

- Customizable load testing using Python code
- Web UI

```
pip install locust
locust -f locustfile.py
```

- Locust **task**

```
from locust import HttpUser, task

class QuickstartUser(HttpUser):
    @task
    def hello_world(self):
        self.client.get("/hello")
        self.client.get("/world")
```

- Running Locust **headless**

```
locust -f locustfile.py --headless --users 10 --spawn-rate 1 -H http://localhost:8080
```

- Locust **distributed** load testing

```
locust -f locustfile.py --master --expect-workers 4
locust -f locustfile.py --worker --master-host 192.168.0.14
locust -f locustfile.py --worker --master-host 192.168.0.14
locust -f locustfile.py --worker --master-host 192.168.0.14
locust -f locustfile.py --worker --master-host 192.168.0.14
```

Resources