

Chassis LoadBalancer lab

In this lab experience, you will add a `LoadBalancer` to the system defined in [chassis-kubernetes lab](#).

To add the `LoadBalancer` run

```
kubectl apply -f chassis-loadbalancer.yaml
```

We would expect that an External IP is given to the LoadBalancer. After running `kubectl get services` you will notice that External IP is stuck to `pending`.

? Why?

No external IP can be assigned to it because `k3d` lacks the controllers that provide them.

✓ Solutions

1. **Switch to Ingress**, if you need to use the LoadBalancer internally you can use Cluster IP; if you want to make a service accessible externally, consider using **Ingress** which is much more feature rich than vanilla LoadBalancer implementation.
2. **Install a LoadBalancer provider**, if you need to use LoadBalancer anyways (e.g., required from an external tool), follow the guide in the Addendum below.

Please refer to the [lesson content](#) for details.

Addendum: Install MetalLB

MetalLB is the most used LoadBalancer provider in custom installations.

`k3d` conflicts with it by default because it uses `traefik` in its control plane. To successfully install MetalLB you need to start a fresh cluster with `traefik` disabled.

```
k3d cluster create --api-port 6550 --agents 2 --k3s-arg '--disable=traefik@server:*' metallb-cluster
```

It is suggested to install MetalLB via **Helm**, a "packet manager" for your cluster. To install Helm follow the installation guide on their [website](#).

After the installation run the following commands to install MetalLB.

```
helm repo add metallb https://metallb.github.io/metallb
helm repo update
helm install metallb metallb/metallb -n metallb-system --wait --create-namespace
```

Finally, configure MetalLB:

1. get the IPs related with the cluster docker network

```
docker network inspect k3d-metallb-cluster | grep Subnet
```

2. Create a file named `metallb-config.yaml` and edit the IP range accordingly to what you saw in the previous step

```
apiVersion: metallb.io/v1beta1
kind: IPAddressPool
metadata:
  name: first-pool
  namespace: metallb-system
spec:
  addresses:
    - 172.21.0.200-172.21.0.250 # Update this range to match your k3d subnet!
---
```

```
kind: L2Advertisement
metadata:
  name: homework
  namespace: metallb-system
```

3. Apply the YAML configuration

```
kubectl apply -f metallb-config.yaml
```

Now the cluster is ready to create LoadBalancer with a working external IP.