# 10 – helix observability

In this exercise we'll explore the Helix dashboard, and see how to create simple Grafana dashboards and alerts. We'll also see how to use Helix's built-in tracing capabilities to debug a slow request. Finally, we'll see how to use Helix's built-in support for Prometheus metrics to monitor the health of the server. Note: this exercise assumes you've completed the previous exercises, and have a working Helix server running.

## 1. Overview

Helix is an open-source platform for running AI workloads (text generation, image generation, fine-tuning) on your own hardware. It's built around a scheduler that places workloads onto runners, and a control plane that manages sessions, users, and billing.

Helix is open source: https://github.com/helixml/helix

**What kinds of workloads can Helix run?**

Helix supports several types of workloads, each requiring different GPU memory and compute capabilities:

- **Chat** — Standard LLM inference for text generation. Typically requires 8–24 GB of GPU memory depending on the model size.
- **Image** — Image generation models like Stable Diffusion. Requires a GPU with at least 8 GB of memory.
- **Embedding** — Text embedding models used for semantic search and RAG. Can run on smaller GPUs.
- **Fine-tuning** — Training custom LoRA adapters on your own data. Requires more GPU memory than inference.
- **Vision** — Multimodal models that can process images alongside text. Requires a GPU with at least 16 GB of memory.

**What is a runner?**

A runner is a machine with GPUs that connects to the Helix control plane and executes workloads. You can add as many runners as you like — Helix will schedule workloads onto whichever runner has enough free GPU memory.

**What is the control plane?**

The control plane is the central server that manages the Helix cluster. It handles:

- **Scheduling** — Deciding which runner should execute each workload, based on GPU memory availability and runner health.
- **Sessions** — Tracking user interactions with models, including chat history and generated content.
- **Users and billing** — Authentication, API keys, and usage tracking.
- **Runner management** — Monitoring runner health, GPU status, and memory usage.

The control plane exposes a REST API that the CLI and dashboard use to interact with the system.

## 2. Grafana

Helix comes with a built-in Grafana dashboard for monitoring GPU utilization, memory usage, and request latency. Let's set up a simple dashboard and alert.

**Step 1: Open Grafana**

Navigate to the Grafana instance at `http://localhost:3000`. Log in with the default credentials (`admin` / `admin`).

**Step 2: Create a new dashboard**

Click **Dashboards** → **New** → **New Dashboard**. Add a panel with the following query to show GPU memory usage:

```
helix_runner_gpu_memory_used_bytes / helix_runner_gpu_memory_total_bytes
```

Set the panel title to "GPU Memory Utilization" and the unit to "percent (0.0–1.0)".

**Step 3: Create an alert**

Edit the panel and click the **Alert** tab. Create a new alert rule:

- Condition: `WHEN avg() OF query(A, 5m, now) IS ABOVE 0.9`
- Evaluate every: `1m`
- For: `5m`

This will fire an alert if GPU memory stays above 90% for 5 minutes.

## 3. Flash




Flash is the Helix dashboard — a web UI for managing sessions, viewing logs, and monitoring runner health. It's served by the control plane and requires no separate installation.

Open Flash in your browser at `http://localhost:8080`. You should see a list of active sessions, queued tasks, and connected runners.

Flash is useful for quickly checking whether a runner is online, seeing which model is loaded on each GPU, and inspecting the logs of a failed session. It's not a replacement for the CLI — it's a complement for visual inspection.

## 4. Trace

Helix has built-in support for distributed tracing. Traces help you understand where time is spent during a request — for example, how much time is spent waiting for a runner to become available versus actually running inference.

**Step 1: Enable tracing**

Add the following to your `helix.toml` configuration:

```
[tracing]
enabled = true
exporter = "stdout"
```

Restart the control plane for the change to take effect.

**Step 2: Send a request and read the trace**

Send a chat request and look at the control plane logs. You'll see a trace printed for each request, showing the time spent in each stage:

```
trace: session.create 12.4ms
trace:   scheduler.wait_for_runner 8.1ms
trace:   runner.inference 4.2ms
```

In this example, most of the time was spent waiting for a runner — the inference itself was fast.

**What you've learned**

- **Grafana Dashboards and Alerts** — How to create dashboards and alerts for GPU memory and request latency.
- **Flash** — How to use the Helix dashboard for monitoring sessions, queues, and runners.
- **Tracing** — How to enable distributed tracing and read traces to understand where time is spent during a request.
- **Prometheus Metrics** — How to use Helix's built-in Prometheus metrics for monitoring the health of the server.
- **Debugging Slow Requests** — How to use traces to debug slow requests and identify bottlenecks.

**Further reading**

- Grafana documentation: https://grafana.com/docs/
- Prometheus documentation: https://prometheus.io/docs/
- OpenTelemetry documentation: https://opentelemetry.io/docs/

**Why it matters**

Observability is essential for running any production system. Without dashboards, alerts, and traces, you're flying blind — you won't know when something breaks, why it's slow, or how much capacity you have left. Helix's built-in observability tools make it easy to get started without setting up a separate monitoring stack.