13 – Istio traffic management

Istio is the most popular open-source service mesh platform used to control, secure, and observe microservices communication. It provides a dedicated infrastructure layer that handles service-to-service communication, offering features like traffic management, security, and observability without requiring changes to application code.

Istio Architecture

Istio's architecture is divided into two main components: the **data plane** and the **control plane**.

- **Data Plane**: The data plane is composed of a set of intelligent proxies (Envoy proxies) deployed as sidecars. These proxies mediate and control all network communication between microservices. They are responsible for tasks like load balancing, service discovery, health checking, and implementing traffic management policies.
- **Control Plane**: The control plane manages and configures the proxies to route traffic. It also enforces policies and collects telemetry data. The control plane is responsible for configuring the data plane and providing a unified interface for managing the service mesh.

Istio Components

Istio's architecture is composed of several key components that work together to provide its functionality:

- **Envoy Proxy**: Envoy is a high-performance proxy that is deployed as a sidecar to each service instance. It handles all inbound and outbound traffic for the service, enforcing policies and collecting telemetry data.
- **Istiod**: Istiod is the control plane component that manages and configures the Envoy proxies. It provides service discovery, configuration management, and certificate management.
- **Ingress Gateway**: The ingress gateway is an Envoy proxy that handles incoming traffic from outside the service mesh. It routes traffic to the appropriate services based on configured rules.
- **Egress Gateway**: The egress gateway is an Envoy proxy that handles outgoing traffic from the service mesh. It can be used to enforce policies and monitor traffic leaving the mesh.

Istio Traffic Management

Istio's traffic management capabilities allow you to control the flow of traffic between services. You can use Istio's configuration API to set up rules that route traffic to different versions of a service, inject delays or failures for testing, and apply circuit breakers to limit the impact of failures.

Istio's traffic management model relies on the following Custom Resource Definitions (CRDs):

- **VirtualService**: Defines a set of traffic routing rules to apply when a host is addressed. Each routing rule defines matching criteria for traffic of a specific protocol and a destination for the traffic that matches the criteria.
- **DestinationRule**: Defines policies that apply to traffic intended for a service after routing has occurred. These rules specify configuration for load balancing, connection pool size, and outlier detection.
- **Gateway**: Configures a load balancer for HTTP/TCP traffic, most commonly operating at the edge of the mesh to enable ingress or egress traffic.
- **ServiceEntry**: Adds additional entries to Istio's internal service registry, so that auto-discovered services in the mesh can access/route to these manually specified services.

Virtual Services

Virtual services are the core Istio resource that defines the routing rules that control how requests for a service are routed within an Istio service mesh. Virtual services are what make Istio's traffic management capabilities so flexible and powerful.

Istio Architecture

Istio's architecture is divided into two main components: the **data plane** and the **control plane**.

```yaml
apiVersion: networking.istio.io/v1
kind: VirtualService
metadata:
  name: reviews
spec:
  hosts:
  - reviews
  http:
  - match:
    - headers:
        end-user:
          exact: jason
    route:
    - destination:
        host: reviews
        subset: v2
  - route:
    - destination:
        host: reviews
        subset: v3
```

Istio