3.3 - Infra observability

Infrastructure observability is the practice of monitoring the underlying hardware and platforms that run your applications. While application observability tells you what your code is doing, infra observability tells you whether the machines, containers, and networks it runs on are healthy. Without it, you're blind to resource exhaustion, hardware failures, and capacity problems until they cause outages.

3.3.1 - Grafana

Grafana is the open-source platform for visualizing and alerting on metrics, logs, and traces. It connects to dozens of data sources and lets you build dashboards that turn raw numbers into actionable insights.

Grafana Cloud is the managed version — you get Grafana, Prometheus, Loki, and Tempo hosted for you, with a generous free tier. Perfect for learning and small projects.

Dashboards are collections of panels arranged on a grid. Each panel queries a data source and renders a visualization — time series graphs, gauges, stat panels, tables, heatmaps, and more. Dashboards can be shared as JSON, which makes them easy to version control and reproduce.

Data sources are where Grafana pulls its data from. Grafana itself doesn't store metrics — it queries backends like Prometheus, Loki, or CloudWatch and renders the results. You can mix multiple data sources in a single dashboard.

Alerting lets you define rules that fire when a query crosses a threshold. Grafana supports multi-dimensional alerts, notification policies, and integrations with PagerDuty, Slack, email, and webhooks.

Variables make dashboards dynamic. Instead of hardcoding a server name, you can use a variable like `$instance` and let users switch between servers from a dropdown. One dashboard can serve your entire fleet.

Provisioning lets you define dashboards, data sources, and alerts as YAML files checked into Git. This is the infrastructure-as-code approach to Grafana — reproducible, reviewable, and automated.

Above is a screenshot of a Grafana dashboard monitoring a Kubernetes cluster. The cluster selector at the top lets you switch between clusters, and the panels below show CPU usage, memory usage, and pod counts.

Grafana Cloud Free Tier Limits

Grafana Cloud's free tier is generous enough for learning and small projects:

- **10,000 active series** for Prometheus metrics
- **50 GB** of log ingestion per month
- **50 GB** of trace ingestion per month
- **14 days** retention
- **3 users** with access to the stack

Active series is the one you'll hit first. It's the number of unique time series (metric name + label combinations) your Prometheus is storing. Each unique combination of labels counts as one series. For example, `http_requests_total{method="GET", status="200"}` and `http_requests_total{method="POST", status="200"}` are two separate series.

Grafana Alloy

Grafana Alloy is Grafana Labs' distribution of the OpenTelemetry Collector. It's a vendor-neutral pipeline for collecting, processing, and shipping telemetry data — metrics, logs, traces, and profiles — to any backend. Alloy is the recommended way to send data to Grafana Cloud, but it works with any OpenTelemetry-compatible backend.

Alloy uses a component-based configuration language called River. You define components for receiving, processing, and exporting data, and wire them together in a pipeline.

```
prometheus.scrape "node" {
  targets = [{"__address__" = "localhost:9100"}]
  forward_to = [prometheus.remote_write.grafana_cloud.receiver]
}

prometheus.remote_write "grafana_cloud" {
  endpoint {
    url = "https://prometheus-prod-13-gb-south-1.grafana.net/api/prom/push"
    basic_auth {
      username = "123456"
      password = sys.env("GRAFANA_CLOUD_API_KEY")
    }
  }
}
```

This config scrapes node_exporter metrics on localhost and ships them to Grafana Cloud. The credentials are read from environment variables, not hardcoded.

Above is a screenshot of Grafana Alloy's built-in UI. The graph view shows how components are wired together — data flows from left to right. Each box is a component, and you can click on them to see their current state and debug output.

Installation

Alloy is distributed as a standalone binary. On Linux, you download the binary:

```
curl -O -L "https://github.com/grafana/alloy/releases/latest/download/alloy-linux-amd64.zip"
unzip alloy-linux-amd64.zip
chmod +x alloy-linux-amd64
./alloy-linux-amd64 run config.alloy
```

It's also available as a Docker image and Helm chart.

What you can find

- **Monitoring Grafana Alloy itself** — Alloy exposes its own metrics on port 12345 by default. Import the official dashboard to see component health, queue sizes, and throughput.
- **Node Exporter Full** — The most popular dashboard for Linux server metrics. Shows CPU, memory, disk, network, and system load. Import ID: 1860.
- **Loki Dashboard quick search** — If you're using Grafana Alloy to ship logs to Loki, this dashboard lets you search and filter logs directly in Grafana.
- **Kubernetes / Compute Resources / Cluster** — Shows CPU and memory usage across your entire Kubernetes cluster.
- **Prometheus Remote Write** — Monitors the health of your remote write pipeline, including failed samples and retry rates.

Browse the full catalog at grafana.com/grafana/dashboards.

What's next

Now that you understand what Grafana Alloy can collect, the next step is learning how to write River configurations that process and filter your telemetry before it reaches your backend. That's where the real power of Alloy's pipeline model shows up.

3.3.2 - Node Exporter

Node Exporter is the standard way to collect hardware and OS metrics from Linux machines. It exposes CPU, memory, disk, network, and filesystem metrics on an HTTP endpoint that Prometheus can scrape. Nearly every Linux monitoring setup starts here.

Installation

Download the binary and run it:

```
curl -O -L "https://github.com/prometheus/node_exporter/releases/latest/download/node_exporter-linux-amd64.tar.gz"
tar xzf node_exporter-linux-amd64.tar.gz
./node_exporter-linux-amd64/node_exporter
```

It listens on port 9100 by default. Verify it's working:

```
curl http://localhost:9100/metrics
```

You'll see a wall of metrics in Prometheus format.

Running as a systemd service

For production, run it as a service so it starts on boot:

```
sudo useradd --no-create-home --shell /bin/false node_exporter
sudo cp node_exporter-linux-amd64/node_exporter /usr/local/bin/
```

Create `/etc/systemd/system/node_exporter.service`:

```
[Unit]
Description=Node Exporter
After=network.target

[Service]
User=node_exporter
ExecStart=/usr/local/bin/node_exporter
Restart=always

[Install]
WantedBy=multi-user.target
```

Then enable and start it:

```
sudo systemctl daemon-reload
sudo systemctl enable --now node_exporter
```

Key metrics to know

- `node_cpu_seconds_total` — CPU time spent in each mode (idle, user, system, iowait, etc.)
- `node_memory_MemAvailable_bytes` — Memory available for new processes
- `node_filesystem_avail_bytes` — Disk space remaining per mount point
- `node_network_receive_bytes_total` / `node_network_transmit_bytes_total` — Network throughput
- `node_load1` / `node_load5` / `node_load15` — System load averages

Useful PromQL queries

CPU usage percentage:

```
100 - (avg by (instance) (rate(node_cpu_seconds_total{mode="idle"}[5m])) * 100)
```

Memory usage percentage:

```
(1 - node_memory_MemAvailable_bytes / node_memory_MemTotal_bytes) * 100
```

Disk usage percentage:

```
(1 - node_filesystem_avail_bytes / node_filesystem_size_bytes) * 100
```

What you can find

- **Node Exporter Full** — The most popular dashboard for Linux server metrics. Shows CPU, memory, disk, network, and system load. Import ID: 1860.
- **Node Exporter Quickstart and Dashboard** — Simpler dashboard with the essentials. Import ID: 13978.
- **USE Method / Node** — Focuses on Utilization, Saturation, and Errors for each resource. Import ID: 12966.

Browse the full catalog at grafana.com/grafana/dashboards.

What's next

Now that you're collecting hardware metrics, the next step is learning how to write PromQL queries to build your own dashboards and alerts. That's where the real power of Prometheus shows up.

3.3.3 - Prometheus

Prometheus is the open-source monitoring system that pulls metrics from your services and stores them as time series data. It's the backbone of most Kubernetes monitoring setups and the default data source for Grafana.

Pull-based scraping is how Prometheus collects data. Instead of your services pushing metrics to a central server, Prometheus reaches out to each target on a configured interval and scrapes its `/metrics` endpoint. This means your services don't need to know where Prometheus is — they just expose an HTTP endpoint and wait to be scraped.

Time series data is the core concept. Every metric is identified by a name and a set of key-value labels. For example, `http_requests_total{method="GET", status="200"}` and `http_requests_total{method="POST", status="500"}` are two separate time series. Labels are what make Prometheus queries powerful — you can filter, group, and aggregate by any label combination.

PromQL is the query language for Prometheus. It's purpose-built for working with time series data — rates, aggregations, percentiles, and predictions. You'll use it in Grafana dashboards, alerting rules, and the Prometheus UI itself.

Exporters are small programs that translate third-party metrics into Prometheus format. Node Exporter for hardware and OS metrics, MySQL Exporter for database stats, Blackbox Exporter for probing endpoints — there's an exporter for almost everything.

Alertmanager handles alerts that Prometheus fires. It deduplicates, groups, routes, and silences alerts, then sends notifications to PagerDuty, Slack, email, or webhooks. Prometheus evaluates the rules; Alertmanager decides what to do about them.

Service discovery tells Prometheus what to scrape. Instead of hardcoding IP addresses, Prometheus can discover targets automatically from Kubernetes, AWS, Consul, DNS, and more. As your infrastructure changes, Prometheus adapts.

Recording rules pre-compute expensive queries and store the results as new time series. If a dashboard query is slow because it aggregates millions of samples, a recording rule can do that work ahead of time.

Federation lets one Prometheus server scrape selected metrics from another. This is useful for building a global view across multiple clusters or regions.

Long-term storage is where Prometheus struggles on its own. By default it keeps data for 15 days on local disk. For longer retention, you'll need to integrate with Thanos, Cortex, Mimir, or a managed service like Grafana Cloud.

Above is a screenshot of the Prometheus web UI showing the graph view. You can type PromQL queries, see the results as a table or graph, and check the status of your scrape targets.

Installation

Download the binary and run it:

```
curl -O -L "https://github.com/prometheus/prometheus/releases/latest/download/prometheus-linux-amd64.tar.gz"
tar xzf prometheus-linux-amd64.tar.gz
./prometheus-linux-amd64/prometheus
```

It listens on port 9090 by default. Open `http://localhost:9090` in your browser to access the web UI.

Configuration

Prometheus is configured via `prometheus.yml`. Here's a minimal example that scrapes itself and Node Exporter:

```
global:
  scrape_interval: 15s

scrape_configs:
  - job_name: "prometheus"
    static_configs:
      - targets: ["localhost:9090"]

  - job_name: "node_exporter"
    static_configs:
      - targets: ["localhost:9100"]
```

Running as a systemd service

For production, run it as a service so it starts on boot:

```
sudo useradd --no-create-home --shell /bin/false prometheus
sudo mkdir /etc/prometheus /var/lib/prometheus
sudo cp prometheus-linux-amd64/prometheus /usr/local/bin/
sudo cp prometheus-linux-amd64/prometheus.yml /etc/prometheus/
sudo chown -R prometheus:prometheus /etc/prometheus /var/lib/prometheus
```

Create `/etc/systemd/system/prometheus.service`:

```
[Unit]
Description=Prometheus
After=network.target

[Service]
User=prometheus
ExecStart=/usr/local/bin/prometheus \
  --config.file=/etc/prometheus/prometheus.yml \
  --storage.tsdb.path=/var/lib/prometheus
Restart=always

[Install]
WantedBy=multi-user.target
```

Then enable and start it:

```
sudo systemctl daemon-reload
sudo systemctl enable --now prometheus
```

Key PromQL queries to know

- `rate(http_requests_total[5m])` — Per-second request rate over the last 5 minutes
- `histogram_quantile(0.95, rate(http_request_duration_seconds_bucket[5m]))` — 95th percentile latency
- `sum by (status) (rate(http_requests_total[5m]))` — Request rate grouped by status code
- `up` — Which targets are currently being scraped successfully

What you can find

- **Prometheus 2.0 Overview** — Official dashboard for monitoring Prometheus itself. Import ID: 3662.
- **Node Exporter Full** — The most popular dashboard for Linux server metrics. Import ID: 1860.
- **Kubernetes / Compute Resources / Cluster** — Shows CPU and memory usage across your entire Kubernetes cluster.
- **Prometheus Remote Write** — Monitors the health of your remote write pipeline, including failed samples and retry rates.

Browse the full catalog at grafana.com/grafana/dashboards.

What's next

Now that you're collecting metrics, the next step is learning how to write PromQL queries to build your own dashboards and alerts. That's where the real power of Prometheus shows up.