

Design Document

November 21, 2016

Document Version 0.1

Matteo Frosi (mat. 875393)
Luca Costa (mat. 808109)

Contents

1	Introduction	3
1.1	Purpose	3
1.2	Scope	3
1.3	Definitions, acronyms, abbreviations	3
2	Document further information	5
2.1	ChangeLog	5
2.2	Hours of work	5

1 Introduction

1.1 Purpose

This document, addressed mainly to developers, aims to go into further details regarding the specification of the project, described in the RASD. Here more technical features will be described, including:

- The high level architecture
- Some possible design patterns
- The description of the main components and their interaction (Runtime View)
- A brief description of the algorithms on which the software relies
- A more detailed overview of the user interfaces

Although these are the main topics of the document, other minor details will be touched and discussed, such as the architectural style and a brief comparison with other styles and the mapping between the requirements defined in the RASD and the designed elements described in this document.

1.2 Scope

PowerEnJoy is an electrical car sharing service, based on a mobile application. The targets of the service, intended as users, are people that needs to move from a place to another within a city and requires a conveyance to move (because they don't have their own or simply can't use it).

A user can make a reservation for a car, using the mobile app and his/her account, and check for the availability and status of all the cars within his/her position, identified using GPS localization, or a specific one, inserted manually by the user. As stated before, to access the service, the user must possess a private account, so a registration is needed.

The system provides the users a safe way (identification code) to access the cars, and the riding service and keeps trace of the status of all the cars.

Moreover, the system prizes or punishes a respectively good or bad behavior from the users, applying a discount or an overcharge on the cost of a ride. As example, if the user leaves the car without much battery, he/she will have to pay more than the standard cost of the ride, because the car will need to be charged and this operation has a cost. On the other hand, if a user plugs the car before ending the service, it receives a discount.

The system includes other functionality, such as GPS based maps available in every car, an emergency procedure in case an accident occur during a ride and the notification of a car status if the user requested it.

1.3 Definitions, acronyms, abbreviations

- RASD: document about the requirements analysis of the project.
- DD: document about the design choices and the components description of the project.
- GPS: global navigation satellite system that provides location and time information in all weather conditions, anywhere on or near the Earth where there is an unobstructed line of sight to four or more GPS satellites.

- SMS: short message service; it is a notification sent to a mobile phone, we need a GSM gateway to use it.
- GMS gateway: device that allows SMS text messages to be sent and/or received by email, from Web pages or from other software applications by acquiring a unique identifier from the mobile phone's Subscriber Identity Module, or SIM card.
- Push notification/ push message: it is a notification sent to a smartphone using the mobile application.
- API: application programming interface; it is a common way to communicate with another system.
- REST: representational state transfer, it's one way of providing interoperability between computer systems on the Internet.
- RESTFul: REST with no session.
- URL: uniform resource locator.
- MVC: model view controller, it's a design pattern.
- SOA: service oriented architecture, it's a style of software design where services are provided to the other components by application components, through a communication protocol over a network.
- Layer: way of organizing code in sections sharing a common goal. The highest partition includes Presentation Layer, Business or Logic Layer and Data Layer.
- Tier: physical deployment of layers.
- Safe area: it is a specific area where the electric cars of PowerEnjoy service can park. The set of safe areas is pre-defined and owned by the company/society that requested the management system for the service.
- Special safe area: it is a safe area where power grid stations are installed.
- Power grid station: it is an installation that allows the recharge of an electric car.
- Communication primitives: set of instructions and procedure that allow a communication between machines and devices over a network.
- Sensor data retrieval: procedure that consists in getting all the information collected by the sensors of the car.

2 Document further information

2.1 ChangeLog

- [21/11/2016] [**Version 0.1**] :: Added first part of the document introduction, including preface, Purpose, Scope and Definitions. ChangeLog and Hours of work sections also introduced.

2.2 Hours of work

Matteo Frosi

[Before 21/11/2016]: 3.00 hours (spent in analyzing well known architectures, to study and apply them at our problem).

[21/11/2016]: 2.00 hours (further analysis of an applicable architecture to our problem, alleging to the classic 3 Tier architectures).