

STRUCTURA: A Bayesian Network Framework for Information-Theoretic Scoring and Behavioral Anomaly Detection

Dr. Matteo Orsoni¹, Prof. Mariagrazia Benassi¹, Prof. Giovanni Briganti², Dr. Marco Scutari³

¹ Department of Psychology, University of Bologna · ² Department of Computational Medicine and Neuropsychiatry, University of Mons · ³ Dalle Molle Institute for Artificial Intelligence (IDSIA), Lugano, Switzerland

01 · INTRODUCTION

Under network psychometrics, constructs are modeled as interacting nodes linked by explicit dependencies. Bayesian Networks enable exact person-level inference^{1,2}, but their use in cognitive assessment remains limited. **No validated framework currently turns a single response pattern into a reliable, interpretable, and clinically meaningful score³.** STRUCTURA would address this gap.

03 · RESULTS — THE GUTTMAN SCALE PARADOX

A Guttman paradox⁷: failing easy items while solving difficult ones.





Fig. 1 — Learned normative BN of Raven's CPM, adapted from Orsoni et al. (2025)⁵.

02 · METHODS

Normative sample & instrument. Normative data: 32 kindergarten children (M age = 4.72, SD = 0.30; 46.9% male) from Orsoni et al. (2025). Raven's CPM, a non-verbal measure of fluid intelligence and analogical reasoning, includes 36 dichotomous items across subscales A, Ab, and B; after excluding zero-variance items, 26 items were analysed.

- 2 Compilation & local evidence.** The BN was compiled into a junction tree for exact inference, with Laplace-smoothed CPTs (α = 0.5). For each item, local evidence was defined by its Markov Blanket: $E_i = \text{MB}(X_i)$. Only structurally relevant neighbours informed person-level inference.
- 3 TESS.** $\sum_i P(X_i = 1 \mid E_i)$, normalised to 0–100. Equal raw accuracy can yield different TESS values.
- 4 Global SI (GSI).** $\sum_i -\log_2 P(X_i = x_i \mid E_i)$, mapped onto an empirical 0–100 normative centile scale.
- 5 Local SI (LSI).** $\text{SI}_{\pm, i} = (x_i - E[X_i \mid E_i]) \cdot I(x_i)$: signed item-level anomaly; flagged at the 5th/95th normative percentiles.
- 6 Uncertainty.** Parametric bootstrap (95% CI): each CPT perturbed via Dirichlet sampling (ISS as hyperparameter).

04 · DISCUSSION & CONCLUSIONS

These three metrics capture complementary aspects of anomaly: **TESS** adjusts the ability estimate for structural inconsistency, **GSI** quantifies how improbable the overall response pattern is, and **LSI** identifies the specific items driving the anomaly.

STRUCTURA translates BN topology into individual-level scoring.

Uncertainty is rigorously quantified via Dirichlet bootstrap CIs.

Generalizable to any assessment where a DAG is theoretically or empirically justified.

Next steps: Formally validate TESS, GSI, and LSI; integrating contextual nodes and evaluating clinical feasibility in psychiatric populations.

03B · RESULTS — LOCAL SI PROFILE (GUTTMAN CASE)




Fig. 2 — Signed SI per item; flags at normative P05 = -0.929 and P95 = 0.430.

QR CODE



Scan for full references, and poster PDF.