

# Mr.CAS- A Minimalistic (pure) *Ruby* CAS for Fast Prototyping and Code Generation

Matteo Ragni<sup>a</sup>

<sup>a</sup>*Department of Industrial Engineering, University of Trento, 9, Sommarive, Povo di Trento, Italy*

---

## Abstract

There are complete **Computer Algebra System** (CAS) systems on the market with complete solutions for manipulation of analytical models. But exporting a model to a given target language is often a rigid procedure that requires some manual post-processing, even with a good software. This work presents a *Ruby* library that exposes core CAS capabilities—i.e. simplification, substitution, evaluation, etc. The library aims at rapid prototyping of numerical interfaces, and code generation for different target languages, separating mathematical expression from code generation rules supporting best practices for numerical conditioning. The library is implemented in pure *Ruby* language and is compatible with most *Ruby* interpreters.

*Keywords:* CAS, code-generation, Ruby

---

## 1. Motivation and significance

*Ruby* [1] is a purely object-oriented scripting language designed in the mid-1990s by Yukihiro Matsumoto, internationally standardized since 2012 as ISO/IEC 30170.

With the advent of the *Internet of Things*, a compact version of the *Ruby* interpreter called *mRuby* (*eMbedded Ruby*) [2] has been published on *GitHub* by Matsumoto, in 2014. The new interpreter is a lightweight implementation, aimed at both low power devices and PC, and complies with the standard[3]. *mRuby* has a completely new API, and it is designed to be embedded in complex projects as a front-end interface—e.g., a numerical optimization suite may use *mRuby* to for problem definition.

The *Ruby* code-base exposes a large set of utilities in core and standard libraries, that can be furthermore expanded through third party libraries,

---

*Email address:* `matteo.ragni@unitn.it` (Matteo Ragni)

14 or *gems*. Among the large number of available gems, *Ruby* still lacks an  
15 **automatic symbolic differentiation** (ASD) [4] engine that handles basic  
16 computer algebra routines, compatible with all different *Ruby* interpreters.

17 Nowadays *Ruby* is mainly known thanks to the web-oriented *Rails* frame-  
18 work, Its expressiveness and elegance though make it intriguing for use in the  
19 scientific/technical field. An ASD-capable gem would prove a fundamental  
20 step in this direction, including the support for flexible code generation for  
21 high-level software—e.g., IPOPT [5, 6].

22 *Mr.CAS*<sup>1</sup> is a gem implemented in pure *Ruby* that supports symbolic  
23 differentiation (SD) and some computer algebra operations [7]. The library  
24 aims at:

- 25 • support rapid prototyping of numerical algorithms and code generation  
26 to different target languages;
- 27 • when dealing with mathematical models, support a clean and separate  
28 formulation of conditioning rules for numerical issues, in order to sup-  
29 port more robust code generation;
- 30 • create a complete open-source CAS system for the standard *Ruby* lan-  
31 guage, as a long-term effort.

32 Other CAS libraries for *Ruby* are available:

33 ***Rucas*** [8], ***Symbolic*** [9] : milestone gems, yet at early stage and with dis-  
34 continued development status. Both offer basic simplification routines,  
35 although they lack differentiation.

36 ***Symengine*** [10] : is a wrapper of the *symengine* C++ library. The back-  
37 end library is very complete, but it is compatible only with the *vanilla*  
38 *C Ruby* interpreter and has several dependencies. At best of Author  
39 knowledge, at the moment it seems not working using the *Ruby 2.x*  
40 interpreter.

41 In Section 2, *Mr.CAS* container and tree structure is explained in detail  
42 and applied to basic CAS tasks. In Section 3, two examples on how to  
43 use the library as code generator or as interface are described. Finally, the  
44 reasons behind the implementation and the long term desired impact are  
45 depicted in Section 4. All code listings are available at [http://bit.ly/Mr\\_](http://bit.ly/Mr_CAS_examples)  
46 [CAS\\_examples](http://bit.ly/Mr_CAS_examples).

---

<sup>1</sup>Minimalistic Ruby Computer Algebra System

## 2. Software description

### 2.1. Software Architecture

*Mr.CAS* is an object oriented ASD gem that supports some computer algebra routines such as *simplifications* and *substitutions*. When gem is required, it overloads methods of `Fixnum` and `Float` classes, making them compatible with fundamental symbolic classes.

Each symbolic expression (or operation) is the instance of an object, that inherits from a common virtual ancestor: `CAS::Op`. An operation encapsulates sub-operations recursively, building a tree, that is the mathematical equivalent of function composition:

$$(f \circ g) \tag{1}$$




Figure 1: Tree of the expression derived in Listing 1

57 When a new operation is created, it is appended to the tree. The num-  
 58 ber of branches are determined by the parent container class of the current  
 59 symbolic function. There are three possible containers:

60 **CAS::Op** single sub-tree operation — e.g.  $\sin(\cdot)$ .

61 **CAS::BinaryOp** dual sub-tree operation — e.g. exponent  $x^y$  — that inherits  
 62 from **CAS::Op**.

63 **CAS::NaryOp** operation with arbitrary number of sub-tree — e.g.  $\text{sum } x_1 +$   
 64  $\dots + x_N$  — that inherits from **CAS::Op**.

65 Figure 1 contains a graphical representation. The different kind of contain-  
 66 ers allows to introduce some properties — i.e. *associativity* and *commutativ-*  
 67 *ity* for sums and multiplications [11]. Each container exposes the sub-tree  
 68 as instance properties. Containers interfaces and inheritances are shown in  
 69 Figure 2.

70 Terminal leaves of the graph are the classes **CAS::Constant**, **CAS::Va-**  
 71 **riable** and **CAS::Function**. The first models a simple numerical value,  
 72 while the second represents an independent variable, that can be used to  
 73 perform derivatives and evaluations, and the latter is a prototype of implicit  
 74 functions. As for now, those leaves exemplify only real scalar expressions,  
 75 with definition of complex, vectorial and matricial extensions as milestones  
 76 for the next major release.

77 SD (**CAS::Op#diff**) crosses the graph until it reaches ending nodes. A  
 78 terminal node is the starting point for derivatives accumulation, the mathe-  
 79 matical equivalent of the chain rule:

$$(f \circ g)' = (f' \circ g) g' \quad (2)$$

80 The recursiveness is used also for simplifications (**CAS::Op#simplify**), sub-  
 81 stitutions (**CAS::Op#subs**), evaluations (**CAS::Op#call**) and code genera-  
 82 tion.

## 83 2.2. Software Functionalities

### 84 2.2.1. Basic Functionalities

85 No additional dependencies are required. The gem can be installed through  
 86 *rubygems.org* provider<sup>2</sup>. Functionalities must be required runtime using the  
 87 Kernel method: `require r.CAS`. All methods and classes are encapsulated  
 88 in the module **CAS**.

---

<sup>2</sup>gem install Mr.CAS




Figure 2: Simplified version of classes interface and inheritance

89 **SD** is performed with respect to independent variables (`CAS::Variable`)  
 90 through forward accumulation, even for implicit functions. The differentiation  
 91 is done by the method `CAS::Op#diff`, having a `CAS::Variable`  
 92 as argument:

Listing 1: Differentiation example

---

```

93
94 z = CAS.vars 'z'          # creates a variable
95 f = z ** 2 + 1           # define a symbolic expression
96 f.diff(z)                # derivative w.r.t. z
97 # => (((z)^((2-1)) * 2 * 1) + 0)
98 g = CAS.declare :g, f     # creates implicit expression
99 g.diff(z)                # derivative w.r.t. z
100 # => (((z)^((2-1)) * 2 * 1) + 0) * Dg[0](((z)^(2) + 1)))
101

```

---

102 **Automatic differentiation** (AD) is included as plugin and exploits  
103 properties of dual numbers to efficiently perform differentiation, see [12] de-  
104 tails. This differentiation strategy is useful in case of complex expressions,  
105 when explicit derivative's tree may exceed the call stack depth, that is plat-  
106 form dependent.

107 **Simplifications** are not executed automatically, after differentiations.  
108 Each node of the tree knows rules for simplify itself, and rules are called  
109 recursively, exactly like ASD. Simplifications that require an *heuristic expan-*  
110 *sion* of the subgraph — i.e. some trigonometric identities — are not defined  
111 for now, but can be easily achieved through **substitutions**:

Listing 2: Simplification example

---

```

112
113 x, y = CAS::vars 'x', 'y' # creates two variables
114 f = CAS.log( CAS.sin( y ) ) # symbolic expression
115 f.subs y => CAS.asin(CAS.exp(x)) # performs substitution
116 f.simplify                # simplifies expression
117 # => x
118

```

---

119 The tree is numerically **evaluated** when independent variables values are  
120 provided in a feed dictionary. The graph is reduced recursively to a single  
121 numeric value:

Listing 3: Tree evaluation example

---

```

122
123 x = CAS.vars 'x'          # creates a variable
124 f = x ** 2 + 1           # defines a symbolic expression
125 f.call x => 2            # evaluates for x = 2
126 # => 5.0
127

```

---

128 Symbolic expressions can be used to create comparative expressions, that  
129 are stored in special container classes, modeled by the ancestor **CAS::Con-**  
130 **dition** — e.g.  $f(\cdot) \geq g(\cdot)$ . This allow the definition of piecewise functions  
131 — e.g.  $\max(f(\cdot), g(\cdot))$ .

Listing 4: Expressions and Piecewise functions

---

```

132
133 x, y = CAS.vars 'x', 'y'
134 f = CAS.declare :f, x
135 g = CAS.declare :g, x, y

```

---

```

136     f.greater_equal g
137     # => (f(x) >= g(x, y))
138     CAS::max f, g
139     # => ((f(x) >= g(x, y)) ? f(x) : g(x, y))
140

```

---

### 141 2.2.2. Metaprogramming and Code-Generation

142 *Mr.CAS* is developed explicitly for **metaprogramming** and **code gen-**  
143 **eration**. Expressions can be exported as source code or used as prototypes  
144 for callable *closures* (Proc objects):

Listing 5: Graph evaluation example

```

145
146 x = CAS::vars 'x'           # creates a variable
147 f = CAS::log(CAS::sin(x))   # define a symbolic function
148
149 proc = f.as_proc            # exports callable lambda
150 proc.call 'x' => Math::PI/2
151 # => 0.0
152

```

---

153 Compiling a closure of a tree is like making its snapshot, thus any fur-  
154 ther manipulation of the expression do not update the callable object. This  
155 drawback is balanced by the faster execution time of a Proc: when a graph  
156 needs *only to be evaluated* in a iterative algorithm, transforming it in a *clo-*  
157 *sure* reduces the execution time per iteration.

158 Code generation should be flexible enough to export expressions' trees  
159 in a user's target language. Generation methods for common languages are  
160 included in specific **plugins**. Users can furthermore expand exporting capa-  
161 bilities by writing specific exportation rules, overriding method for existing  
162 plugin, or desining their own exporter:

Listing 6: Example of Ruby code generation plugin

```

163
164 # Rules definition for Fortran Language
165 module CAS
166   {
167     # . . .
168     CAS::Variable => Proc.new { "#{name}" }
169     CAS::Sin      => Proc.new { "sin(#{x.to_fortran})" },
170     # . . .
171   }.each do |cls, prc|
172     cls.send(:define_method, :to_fortran, &prc)
173   end
174 end
175
176 # Usage
177 x = CAS.vars 'x'
178 code = (CAS.sin(x)).to_fortran
179 # => sin(x)
180

```

---

### 181 3. Illustrative Examples

#### 182 3.1. Code Generation as C Library

183 In this example a model is exported as C library. `c-opt` plugin implements  
184 advanced features such as code optimization and generation of libraries.

185 The library `example` implements the model:

$$f(x, y) = x^y + g(x) \log(\sin(x^y)) \quad (3)$$

186 Expression  $g(x)$  belongs to a external object, declared as `g_impl`, and its  
187 interface is described in `g_impl.h` header. The code is optimized: the inter-  
188 mediate operation  $x^y$  is evaluated once, even if appears twice in our model.  
189 The C function that implements our model  $f(x, y)$  is declared with the token  
190 `f_impl`. The exporter uses as default type `double` for variables and function  
191 returned values.

Listing 7: Calling optimized-C exporter for library generation

```
192  
193 # Model  
194 x, y = CAS.vars :x, :y  
195 g = CAS.declare :g, x  
196  
197 f = x ** y + g * CAS.log(CAS.sin(x ** y))  
198  
199 # Code Generation  
200 g.c_name = 'g_impl'          # g token  
201  
202 CAS::CLib.create "example" do  
203   include_local "g_impl"      # g header  
204   implements_as "f_impl", f   # token for f  
205 end
```

207 Library created by `CLib` contains the following code:



Listing 8: C Header

```

// Header file for library: example.c

#ifndef example_H
#define example_H

// Standard Libraries
#include <math.h>

208 // Local Libraries
#include "g_impl"

// Definitions

// Functions
double f_impl(double x, double y);

#endif // example_H

```

Listing 9: C Source

```

// Source file for library: example.c

#include "example.h"

double f_impl(double x, double y) {
    double __t_0 = pow(x, y);
    double __t_1 = g_impl(x);
    double __t_2 = sin(__t_0);
    double __t_3 = log(__t_2);
    double __t_4 = (__t_1 + __t_3);
    double __t_5 = (__t_0 + __t_4);

    return __t_5;
}

// end of example.c

```

209 The function  $g(x)$  models the following operation:

$$g(x) = (\sqrt{x+a} - \sqrt{x}) + \sqrt{\pi+x} \quad (4)$$

210 and may suffer from *catastrophic cancellation* [13]. Users can specialize code  
 211 generation rules for this particular expression, conditioned through rational-  
 212 ization and instead of modifying the model  $g(x)$ , in Listing 10, the rational-  
 213 ization is extended to all differences of square roots<sup>3</sup>. For more insight about  
 214 `__to_c` and `__to_c_impl` please refer to the software manual.

Listing 10: Conditioning in exporting function

```

215 # Model
216 a = CAS.declare "PARAM_A"
217
218
219 g = (CAS.sqrt(x + a) - CAS.sqrt(x)) + CAS.sqrt(CAS::Pi + x)
220
221 # Particular Code Generation for difference between square roots.
222 module CAS
223   class Diff
224     alias :__to_c_impl_old :__to_c_impl
225
226     def __to_c_impl(v)
227       if @x.is_a? CAS::Sqrt and @y.is_a? CAS::Sqrt
228         "(#{@x.x.__to_c(v)} + #{@y.x.__to_c(v)}) / " +
229         "( #{@x.__to_c(v)} + #{@y.__to_c(v)} )"

```

<sup>3</sup>i.e.:  $\sqrt{\phi(\cdot)} - \sqrt{\psi(\cdot)} = \frac{\phi(\cdot) - \psi(\cdot)}{\sqrt{\phi(\cdot)} + \sqrt{\psi(\cdot)}}$

```

230         else
231             self.__to_c_impl_old(v)
232         end
233     end
234 end
235 end
236
237 CAS::Clib.create "g_impl" do
238     define "PARAM_A()", 1.0 # Arbitrary value for PARAM_A
239     define "M_PI", Math::Pi
240     implements_as "g_impl", g
241 end
242

```

It should be noted the **separation between the model** — that does not contain conditioning — **and the code generation rule** — that overloads, for this particular case and this particular language, the predefined code generation rule. Obviously, a user can decide to apply directly the conditioning on the model. The result of Listing 10 is reported:

Listing 11: `g_impl` Header

```

// Header file for library: g_impl.c

#ifndef g_impl_H
#define g_impl_H

// Standard Libraries
#include <math.h>

// Local Libraries

// Definitions
#define PARAM_A() 1.0
#define M_PI 3.141592653589793

// Functions
double g_impl(double x);

#endif // g_impl_H

```

Listing 12: `g_impl` Source

```

// Source file for library: g_impl.c

#include "g_impl.h"

double g_impl(double x) {
    double __t_0 = PARAM_A();
    double __t_1 = (x + __t_0);
    double __t_2 = sqrt(__t_1);
    double __t_3 = sqrt(x);
    double __t_4 = (__t_1 + x) / ( __t_2 +
        __t_3 );
    double __t_5 = (M_PI + x);
    double __t_6 = sqrt(__t_5);
    double __t_7 = (__t_4 + __t_6);

    return __t_7;
}

// end of g_impl.c

```

### 3.2. Using the module as interface

As example, an implementation of an algorithm that estimates the *order of convergence* for trapezoidal integration scheme [14] is provided, using the symbolic differentiation as interface.

Given a function  $f(x)$ , the trapezoidal rule for primitive estimation in the

254 interval  $[a, b]$  is:

$$I_n(a, b) = h \left( \frac{f(a) + f(b)}{2} + \sum_{k=1}^{n-1} f(a + k h) \right) \quad (5)$$

255 with  $h = (b - a)/n$ , where  $n$  mediates the integration's step size. When exact  
 256 primitive  $F(x)$  is known, approximation error is:

$$E[n] = F(b) - F(a) - I_n(a, b) \quad (6)$$

257 The error has an asymptotic expansion of the form:

$$E[n] \propto C n^{-p} \quad (7)$$

258 where  $p$  is the convergence order. Using a different value for  $n$ , for example  
 259  $2n$ , the ratio 8 takes the approximate vale:

$$\frac{E[n]}{E[2n]} \approx 2^p \quad \rightarrow \quad p \approx \log_2 \left( \frac{E[n]}{E[2n]} \right) \quad (8)$$

260 Following Listings contain the implementation of the described procedure  
 261 using the proposed gem and the well known *Python* [15] library *SymPy* [16].

Listing 13: Ruby version

```

require 'Mr.CAS'

def integrate(f, a, b, n)
  h = (b - a) / n

  func = f.as_proc

  sum = ((func.call 'x' => a) +
        (func.call 'x' => b)) / 2.0

  for i in (1..n)
    sum += (func.call 'x' => (a + i*h))
  end
  return sum * h
end

262 def order(f, a, b, n)
  x = CAS.vars 'x'

  f_ab = (f.call x => b) -
        (f.call x => a)
  df = f.diff(x).simplify
  f_1n = integrate(df, a, b, n)
  f_2n = integrate(df, a, b, 2 * n)

  return Math.log(
    (f_ab - f_1n) /
    (f_ab - f_2n),
    2)
end

x = CAS.vars 'x'
f = CAS.arctan x

puts(order f, -1.0, 1.0, 100)
# => 1.9999999974244451

```

Listing 14: Python version

```

import sympy
import math

def integrate(f, a, b, n):
  h = (b - a)/n
  x = sympy.symbols('x')
  func = sympy.lambdify((x), f)

  sums = (func(a) +
        func(b)) / 2.0

  for i in range(1, n):
    sums += func(a + i*h)

  return sums * h

def order(f, a, b, n):
  x = sympy.symbols('x')

  f_ab = sympy.Subs(f, (x), (b)).n() - \
        sympy.Subs(f, (x), (a)).n()
  df = f.diff(x)
  f_1n = integrate(df, a, b, n)
  f_2n = integrate(df, a, b, 2 * n)

  return math.log(
    (f_ab - f_1n) /
    (f_ab - f_2n),
    2)

x = sympy.symbols('x')
f = sympy.atan(x)

print(order(f, -1.0, 1.0, 100))
# => 1.9999999974244451

```

263

#### 264 4. Impact

265 *Mr.CAS* is a midpoint between a CAS and an ASD library. It allows  
 266 to manipulate expressions while maintaining the complete control on how  
 267 the code is exported. Each rule is overloaded and applied runtime, without  
 268 the need of compilation. Each user's model may include the mathematical  
 269 description, code generation rules and high level logic that should be intrinsic

270 to such a rule — e.g. exporting gradients as **patterns** instead of matrices.

271 Our research group is including **Mr.CAS** in a solver for optimal control  
272 problem with indirect methods, as interface for problems' description [17].

273 As a long term ambitious impact, this library will become a complete CAS  
274 for *Ruby* language, filling the empty space reported by *SciRuby* for symbolic  
275 math engines.

## 276 5. Conclusions

277 This work presents a pure *Ruby* library that implements a minimalis-  
278 tics CAS with automatic and symbolic differentiation that is aimed at code  
279 generation and metaprogramming. Although at an early developing stage,  
280 *Mr.CAS* has promising feature, some of them shown in Section 3. Also, this  
281 is the only gem that implements symbolic manipulation for this language.

282 Language features and lack of dependencies simplify the use of the module  
283 as interface, extending model definition capabilities for numerical algorithms.  
284 All core functionalities and basic mathematics are defined, with the plan to  
285 include more features in next releases. Reopening a class guarantees a *liquid*  
286 behaviour, in which users are free to modify core methods and their needs.

287 Library is published in *rubygems.org* repository and versioned on *github.com*,  
288 under MIT license. It can be included easily in projects and in inline inter-  
289 preter, or installed as a standalone gem.

## 290 Acknowledgements

291 This research did not receive any specific grant from funding agencies in  
292 the public, commercial, or not-for-profit sectors.

- 293 [1] D. Flanagan, Y. Matsumoto, The ruby programming language, O'Reilly  
294 Media, Inc., 2008.
- 295 [2] K. Tanaka, A. D. Nagumanthri, Y. Matsumoto, mruby-rapid software  
296 development for embedded systems, in: 15th International Conference  
297 on Computational Science and Its Applications (ICCSA), IEEE, 2015,  
298 pp. 27–32.
- 299 [3] ISO/IEC 30170 – Information technology – Programming languages  
300 – Ruby, Standard, International Organization for Standardization,  
301 Geneva, CH (april 2000).
- 302 [4] J. E. Tolsma, P. I. Barton, On computational differentiation, Computers  
303 & chemical engineering 22 (4) (1998) 475–490.

- [5] A. Wächter, C. Laird, Ipopt-an interior point optimizer, <https://projects.coin-or.org/Ipopt>, online; accessed: 2016-11-28 (2009).
- [6] A. Wächter, L. T. Biegler, On the implementation of an interior-point filter line-search algorithm for large-scale nonlinear programming, *Mathematical Programming* 106 (1) (2006) 25–57.
- [7] J. Von Zur Gathen, J. Gerhard, *Modern computer algebra*, Cambridge university press, 2013.
- [8] J. Lees-Miller, Rucas, <https://github.com/jdleesmilller/rucas>, online; commit: 047a38b541966482d1ad0d40d2549683cf193082 (2010).
- [9] R. Bayramgalin, Symbolic, <https://github.com/brainopia/symbolic>, online; commit: bbd588e8676d5bed0017a3e1900ebc392cfe35c3 (2012).
- [10] O. Certik, D. L. Peterson, T. B. Rathnayake, et al., Symengine, <https://github.com/symengine/symengine.rb>, online; commit: 8cf9e08c972085788c17da9f4e9f22898e79d93b (2016).
- [11] J. S. Cohen, *Computer algebra and symbolic computation: Mathematical methods*, Universities Press, 2003.
- [12] M. Bartholomew-Biggs, S. Brown, B. Christianson, L. Dixon, Automatic differentiation of algorithms, *Journal of Computational and Applied Mathematics* 124 (1) (2000) 171–190.
- [13] N. Higham, *Accuracy and Stability of Numerical Algorithms*, Society for Industrial and Applied Mathematics, 2002.
- [14] J. A. C. Weideman, Numerical integration of periodic functions: A few examples, *The American mathematical monthly* 109 (1) (2002) 21–36.
- [15] G. Van Rossum, F. L. Drake, *The python language reference manual*, Network Theory Ltd., 2011.
- [16] C. Smith, A. Meurer, M. Paprocki, et al., Sympy 1.0, <https://doi.org/10.5281/zenodo.47274>, online; accessed: 2016-10-15 (2016).
- [17] F. Biral, E. Bertolazzi, P. Bosetti, Notes on numerical methods for solving optimal control problems, *IEEJ Journal of Industry Applications* 5 (2) (2016) 154–166.

**Current code version**

Nr.	Code metadata description	Please fill in this column
C1	Current code version	0.2.7
C2	Permanent link to code/repository used for this code version	github.com/MatteoRagni/cas-rb & rubygems.org/gems/Mr.CAS
C3	Legal Code License	MIT
C4	Code versioning system used	<i>git</i> (GitHub)
C5	Software code languages, tools, and services used	<i>Ruby</i> language
C6	Compilation requirements, operating environments	<i>Ruby</i> $\geq 2.x$
C7	If available Link to developer documentation/manual	rubydoc.info/gems/Mr.CAS
C8	Support email for questions	info@ragni.me

Table 1: Code metadata (mandatory)