

ragni-cas - A Pure *Ruby* Automatic Differentiation Library for Fast Prototyping of Interfaces

Matteo Ragni^a

^a*Department of Industrial Engineering, University of Trento, 9, Sommarive, Povo di
Trento, Italy*

Abstract

Ca. 100 words

Keywords: CAS, code-generation, Ruby

1. Motivation and significance

Ruby is a purely object-oriented scripting language that allows to express several programming paradigms. It was designed in the mid-1990s by Yukihiro Matsumoto (also known as *Matz*), and it is internationally standardized since 2012 as ISO/IEC 30170.

With the advent of the *Internet of Things*, a written from scratch version of the *Ruby* interpreter called *mRuby* (*eMbedded Ruby*) has been published on *GitHub* by Matsumoto in 2014. The new interpreter is a lightweight implementation aimed at both low power devices and personal computer that complies with the standard. *mRuby* has a completely new API, and it is designed to be embedded in a complex project as a front-end interface — e.g. a numerical optimization suite may use *mRuby* to get problem input definitions.

The *Ruby* code-base exposes a a large set of utilities in core and standard library. This set of tool can be furthermore expanded through libraries, also

Email address: `matteo.ragni@unitn.it` (Matteo Ragni)

16 known as *gems*. Even the high number of gems deployed and available, there
17 is no library that implements a **symbolic automatic differentiation** (AD)
18 engine that also handles some basic computer algebra routines that is cross
19 compatible with all the different *Ruby* interpreter.

20 *Ruby* has matured its fame as a web oriented language with *Rails*, and
21 can efficiently generate code in other languages. An AD-capable gem is the
22 fundamental step to develop rapidly a specific code generator for well known
23 software — e.g. IPOPT.

24 The library that is described in this work, is a gem implemented in pure
25 *Ruby* code and thus compatible with all interpreter that complies with the
26 standard, that is able to perform symbolic AD and some simple computer
27 algebra operations. In particular the library aims at:

- 28 • be an instrument for rapid development of prototype interface for nu-
29 merical algorithms — including the *mRuby* engine or exporting gener-
30 ated code — that can be in different languages;
- 31 • rapidly generate descriptions of mathematical models, with easy to
32 implement workaround for numerical issues, changing on request how
33 the code is exported, and how functions are formulated in the target
34 language;
- 35 • creating a complete open-source CAS system for the *Ruby* language,
36 that is be compatible with all the interpreters that comply with the
37 standard, as a long-term ambitious impact.

38 This is not the first gem that tries to implement a CAS. The available
39 computer algebra library for *Ruby* are:

40 ***Rucas*** gem at early stage and with discontinued developing status; it im-
41 plements basic simplification routines. There is no AD method, but it

42 is one of the milestones. The development is discontinued since 2010.

43 ***Symengine*** is a wrapper for the C++ library *symengine*. The back-end
 44 library is very complete, but it is compatible only with the mainstream
 45 *Ruby* interpreter. At the moment, the *SciRuby* project reports the gem
 46 as broken, and removed it from its codebase. From a direct test, when
 47 performing AD of a function, the engine returns always `nil`.

48 2. Software description

49 2.1. Software Architecture

50 *ragni-cas* is an object oriented AD gem that supports some simple com-
 51 puter algebra routines such as *simplifications* and *substitutions*. When gem
 52 is required, automatically overloads some methods of the `Fixnum` and `Flo-`
 53 `at` classes, to make them compatible with the fundamental symbolic objects.

54 Each symbolic function is an object modeled by a class, that inherits from
 55 a common virtual ancestor: `CAS::Op(operation)`. An operation encapsulates
 56 sub-operations recursively, building a linked graph, that is the mathematical
 57 equivalent of function composition:

$$(f \circ g) \tag{1}$$

58 When a new operation is created, it is appended to the graph. The num-
 59 ber of branches are determined by the parent container class of the current
 60 symbolic function. There are three possible containers. Single argument
 61 functions — e.g. `sin(·)` — have as closest parent the `CAS::Op` class, that
 62 links to one sub-graph. Functions with two arguments — e.g. difference
 63 or exponential function — inherit from `CAS::BinaryOp`, that links to two
 64 subgraphs. Functions with arbitrary number of arguments — e.g. sum and




Figure 1: Example graph from the first function reported in script ??

65 product — have as parent the `CAS::NaryOp`¹, that links to an arbitrary num-
 66 ber of subgraph. Figure 2.1 contains an example of graph. The different
 67 kind of containers allows to introduce some properties like *associativity* and
 68 *commutativity*. Each container exposes the subgraphs as instance properties.
 69 Containers structure is shown in Figure 2.1.

70 Terminal leaf of the graph are the two classes `CAS::Constant` and `CAS::Va-`
 71 `riable`. The first is a node for a simple numerical value, while the latter

¹Please note that this container is still at experimental stage

72 represents an independent variable, that can be used to perform derivatives
73 and evaluations. As for now, those nodes are only scalar numbers, with plans
74 to define also the vectorial and matricial extensions in the next major release.

75 Automatic differentiation (`CAS::Op#diff`) crosses the graph until it reaches
76 the ending node. The terminal node is the starting point for derivatives
77 accumulation, the mathematical equivalent of the chain rule:

$$(f \circ g)' = (f' \circ g) g' \quad (2)$$

78 The recursiveness is used also for simplifications (`CAS::Op#simplify`), sub-
79 stitutions (`CAS::Op#subs`) and evaluations (`CAS::Op#call`).

80 2.2. Software Functionalities

81 The main functionality of the library is the **AD**, that can be performed
82 with respect to an independent variable (`CAS::Variable`), even for implicit
83 functions. The differentiation is done by a method of the `CAS::Op`, having a
84 `CAS::Variable` as argument:

```
85 \label{code:example-diff}
86 x = CAS.vars 'x'           # creates a variable
87 f = x ** 2 + 1             # define a symbolic expression
88 f.diff(x)                  # derivative w.r.t. x
89 # => 2 * x ^ (2 - 1) + 0
90 g = CAS.declare :g, f      # creates implicit function
91 g.diff(x)                  # derivative w.r.t. x
92 # => (2 * x ^ (2 - 1) + 0) * Dg[0](x ^ 2)
```

93 Resulting graph still contains a zero, since **simplifications** are not ex-
94 ecuted automatically. Each node of the graph contains some rules for sim-
95 plify itself. Simplification are called recursively inside the graph, exactly like
96 AD, bringing the strong limitation of not handling simplifications that come
97 from *heuristic expansion* of sub-graphs — e.g. simplification through the use




Figure 2: Simplified version of classes interface and inheritance

98 of trigonometric identities. Those simplification can be achieved manually
 99 using **substitutions**.

```

100 \label{code:example-subs}
101 x, y = CAS::vars 'x', 'y'          # creates two variables
102 f = CAS.log( CAS.sin( y ) )        # symbolic expression
103 f.subs y: CAS.asin(CAS.exp(x))     # perform substitution
104 f.simplify                          # simplify expression
105 # => x

```

106 The graph can be **evaluated** substituting defining some values for the
 107 independent variable in a feed dictionary. The graph is recursively reduced
 108 to a single numeric value:

```

109 \label{code:example-call}
110 x = CAS::vars 'x'                  # creates a variable
111 f = x ** 2 + 1                     # define a symbolic expression
112 f.call x: 2                        # evaluate for x = 2
113 # => 5

```

114 Symbolic functions can be used to create expressions — e.g. $f(\cdot) \geq g(\cdot)$
 115 — or piecewise functions — e.g. $\max(f(\cdot), g(\cdot))$:

```

116 x = CAS::vars 'x'
117 f = x ** 2
118 g = 2 * x + 1
119 f.greater_equal g
120 # => ((x)^(3) >= ((2 * x) + 1))
121 CAS::max f, g
122 # => (((x)^(3) >= ((2 * x) + 1)) ? (x)^(3) : ((2 * x) + 1))

```

123 Expression are stored in a special container class, called `CAS::Condition`.

124 The library is developed explicitly for **generation of code**, and in some
 125 case also **metaprogramming**. Expressions, once manipulated, can be easily
 126 exported as source code (in a defined language —i.e. the following example
 127 in standard *Ruby* code):

```

128 x = CAS::vars 'x'                  # creates a variable

```

```
129 f = CAS::log(CAS::sin(x))      # define a symbolic function
130 # => Math::log(Math::sin(x))
```

131 the same function can be also used to create directly a callable *closure*, as a
132 **Proc** object:

```
133 proc = f.as_proc                # exports callable lambda
134 proc.call 'x' => Math::PI/2
135 # => 0.0
```

136 Must be noted that parsing the graph creates a snapshot, and any further
137 modification to the expression will not update the callable object. This draw-
138 back is balanced by faster execution time of the **Proc**: when a graph needs
139 only to be evaluated in a iterative algorithm, and not to be manipulated,
140 transforming it in a *closure* reduces the execution time per loop.

141 **3. Illustrative Examples**

142 **4. Impact**

143 **5. Conclusions**

144 **Acknowledgements**

145 This research did not receive any specific grant from funding agencies in
146 the public, commercial, or not-for-profit sectors.

147 **Current code version**

Nr.	Code metadata description	Please fill in this column
C1	Current code version	0.0.0
C2	Permanent link to code/repository used for this code version	github.com/MatteoRagni/cas-rb & rubygems.org/gems/ragni-cas
C3	Legal Code License	MIT
C4	Code versioning system used	<i>git</i> (GitHub)
C5	Software code languages, tools, and services used	<i>Ruby</i>
C6	Compilation requirements, operating environments	<i>Ruby</i> $\geq 2.x$, <i>pry</i> for testing console (optional)
C7	If available Link to developer documentation/manual	rubydoc.info/gems/ragni-cas
C8	Support email for questions	info@ragni.me

Table 1: Code metadata (mandatory)