

# Real-time error mitigation for variational optimization on quantum hardware

Alejandro Sopena<sup>1</sup>, Matteo Robbiati<sup>2 3</sup>, Andrea Papaluca<sup>4 5</sup> and Stefano Carrazza<sup>2 3 5</sup>

<sup>2</sup> TIF Lab, Dipartimento di Fisica, Università degli Studi di Milano, Milan, Italy.

<sup>3</sup> CERN, Theoretical Physics Department, CH-1211 Geneva 23, Switzerland.

<sup>1</sup> Instituto de Física Teórica, UAM-CSIC, Universidad Autónoma de Madrid, Cantoblanco, Madrid, Spain.

<sup>4</sup> School of Computing, The Australian National University, Canberra, ACT, Australia.

<sup>5</sup> Quantum Research Center, Technology Innovation Institute, Abu Dhabi, UAE.




## References

### Aim


we put forward the inclusion of error mitigation routines in the process of training Variational Quantum Circuit (VQC) models. In detail, we define a Real Time Quantum Error Mitigation (RTQEM) algorithm to coadiuvate the task of fitting functions on quantum chips with VQCs.

### Schematic pipeline of the RTQEM algorithm



### Ansatz

We tackle multi-dimensional regression problems using a VQC as Quantum Machine Learning (QML) model. The data  $x$  are encoded into the circuit via Data Reuploading:



where we use the following definition of the uploading channel:

$$L(x_j|\theta_{l,j}) = R_z(\theta_3 x_j + \theta_4) R_y(\theta_1 \kappa(x_j) + \theta_2), \quad (1)$$

which uploads the  $j$ -th component of  $x$  at the circuit layer  $l$ .

### Noise of a quantum hardware

We consider a quantum system affected by local pauli noise with parameters  $q = (q_X, q_Y, q_Z)$  and readout noise parametrized by flip probability  $q_M$ .