

# Density estimation via quantum adiabatic computing

Based on  [arXiv:2303.11346](https://arxiv.org/abs/2303.11346)


---

Matteo Robbiati, Juan Manuel Cruz-Martinez, Stefano Carrazza

20 April 2023



# A screenshot of Quantum Machine Learning (QML)



## Introduction

---

- ➔ QML to tackle **Monte Carlo** Integration (MCI).

- ➔ QML to tackle **Monte Carlo** Integration (MCI).
- ➔ Let's consider the integrand  $g(x)$  and a dataset  $\Omega$  sampled from a distribution  $\rho(x)$ . We are interested in calculating:

$$E[g(x)] = \int_{\Omega} g(x)\rho(x)dx. \quad (1)$$

- ➔ QML to tackle **Monte Carlo** Integration (MCI).
- ➔ Let's consider the integrand  $g(x)$  and a dataset  $\Omega$  sampled from a distribution  $\rho(x)$ . We are interested in calculating:

$$E[g(x)] = \int_{\Omega} g(x)\rho(x)dx. \quad (1)$$

- ➔ Thus we need:

- ➔ QML to tackle **Monte Carlo** Integration (MCI).
- ➔ Let's consider the integrand  $g(x)$  and a dataset  $\Omega$  sampled from a distribution  $\rho(x)$ . We are interested in calculating:

$$E[g(x)] = \int_{\Omega} g(x)\rho(x)dx. \quad (1)$$

- ➔ Thus we need:
  - ☰ a sample of data  $\Omega$  to be used for evaluating the integral;

- ➡ QML to tackle **Monte Carlo** Integration (MCI).
- ➡ Let's consider the integrand  $g(x)$  and a dataset  $\Omega$  sampled from a distribution  $\rho(x)$ . We are interested in calculating:

$$E[g(x)] = \int_{\Omega} g(x)\rho(x)dx. \quad (1)$$

- ➡ Thus we need:
  - 📊 a sample of data  $\Omega$  to be used for evaluating the integral;
  - ⚙️ a way for estimating the Probability Density Function (PDF) value for each given data  $\rho(x)$ .



- ➡ QML to tackle **Monte Carlo** Integration (MCI).
- ➡ Let's consider the integrand  $g(x)$  and a dataset  $\Omega$  sampled from a distribution  $\rho(x)$ . We are interested in calculating:

$$E[g(x)] = \int_{\Omega} g(x)\rho(x)dx. \quad (1)$$

- ➡ Thus we need:
  - 🗄 a sample of data  $\Omega$  to be used for evaluating the integral;
  - ⚙ a way for estimating the Probability Density Function (PDF) value for each given data  $\rho(x)$ .


In this work

We focus on to find a **density estimation** strategy.

- ➔ Several HEP deployments exist:



➡ Several HEP deployments exist:

⚙ **Monte Carlo** integration requires density estimation techniques;






➡ Several HEP deployments exist:

- ⚙ **Monte Carlo** integration requires density estimation techniques;
- ⚙ **Parton density function** estimation (TH already worked on this<sup>1</sup>);



<sup>1</sup>[arXiv:2011.13934](https://arxiv.org/abs/2011.13934)

- ➡ Several HEP deployments exist:
- ⚙ **Monte Carlo** integration requires density estimation techniques;
- ⚙ **Parton density function** estimation (TH already worked on this<sup>1</sup>);
- ⚙ **Anomaly detection**: if a PDF is known and punctually evaluable we can use this for hypothesis testing.



<sup>1</sup>[arXiv:2011.13934](https://arxiv.org/abs/2011.13934)

- ➔ We are going to follow these steps:

- ➔ We are going to follow these steps:
  - we target the **Cumulative Density Function** (CDF) of a sampled  $\Omega$ ;

- ➔ We are going to follow these steps:
  - we target the **Cumulative Density Function** (CDF) of a sampled  $\Omega$ ;
  - we define a new **Quantum Adiabatic Machine Learning** (QAML) strategy for tackling 1d fitting problems;



- ➔ We are going to follow these steps:
  - we target the **Cumulative Density Function** (CDF) of a sampled  $\Omega$ ;
  - we define a new **Quantum Adiabatic Machine Learning** (QAML) strategy for tackling 1d fitting problems;
  - we fit the CDF via QAML;

- ➔ We are going to follow these steps:
  - we target the **Cumulative Density Function** (CDF) of a sampled  $\Omega$ ;
  - ▣ we define a new **Quantum Adiabatic Machine Learning** (QAML) strategy for tackling 1d fitting problems;
  - ▣ we fit the CDF via QAML;
  - ▣ we use parameter-shift rules for calculating the PDF as derivative of the CDF;

- ➔ We are going to follow these steps:
  - we target the **Cumulative Density Function** (CDF) of a sampled  $\Omega$ ;
  - ▣ we define a new **Quantum Adiabatic Machine Learning** (QAML) strategy for tackling 1d fitting problems;
  - ▣ we fit the CDF via QAML;
  - ▣ we use parameter-shift rules for calculating the PDF as derivative of the CDF;
  - ▣ we validate the procedure on some test cases.

- ➡ We are going to follow these steps:
  - ☐ we target the **Cumulative Density Function** (CDF) of a sampled  $\Omega$ ;
  - ☐ we define a new **Quantum Adiabatic Machine Learning** (QAML) strategy for tackling 1d fitting problems;
  - ☐ we fit the CDF via QAML;
  - ☐ we use parameter-shift rules for calculating the PDF as derivative of the CDF;
  - ☐ we validate the procedure on some test cases.

```
1 import qibo
2
3 # in some boxes like this
4 # we will show how to implement the QAML strategy
```


🔗 [Code here: qiboteam/adiabatic-fit](https://github.com/qiboteam/adiabatic-fit)

METHOD: **CDF fit with a VQC**

---

## Simple case: 1d data in $\mathcal{D} = [0, 1]$ .

➔ Each  $x \in \Omega$  can be labeled with its empirical CDF<sup>2</sup> value  $F(x)$ , which is related to the PDF value via  $\rho(x) = \frac{dF(x)}{dx}$ .



<sup>2</sup>**Cumulative Density Function:** after sorting the data,  $F(x)$  is calculated by counting how many elements are smaller than the target one.

- ➔ It is great to use a VQC as model for estimating  $F$ :

---

➔ It is great to use a VQC as model for estimating  $F$ :

$$\hat{F}(x; \theta) \equiv \langle \psi_i | \mathcal{C}^\dagger(x; \theta) \hat{\mathcal{O}} \mathcal{C}(x; \theta) | \psi_i \rangle, \quad (2)$$

where  $\mathcal{C}(x; \theta)$ ,  $\mathcal{O}$  and  $\psi_i$  are the respectively the VQC, a target observable and the initial state on which we apply  $\mathcal{C}$ .

---



- ➡ It is great to use a VQC as model for estimating  $F$ :

$$\hat{F}(x; \theta) \equiv \langle \psi_i | \mathcal{C}^\dagger(x; \theta) \hat{\mathcal{O}} \mathcal{C}(x; \theta) | \psi_i \rangle, \quad (2)$$

where  $\mathcal{C}(x; \theta)$ ,  $\mathcal{O}$  and  $\psi_i$  are the respectively the VQC, a target observable and the initial state on which we apply  $\mathcal{C}$ .

- ➡ We know how to derivate circuits, e.g. using the Parameter Shift Rule (PSR)<sup>3</sup>, thanks to which we can calculate:

$$\partial_\mu \hat{F} = r [\hat{F}(\mu^+) - \hat{F}(\mu^-)]. \quad (3)$$

---

<sup>3</sup>[arXiv:1811.11184](#)

- ➡ It is great to use a VQC as model for estimating  $F$ :

$$\hat{F}(x; \theta) \equiv \langle \psi_i | \mathcal{C}^\dagger(x; \theta) \hat{\mathcal{O}} \mathcal{C}(x; \theta) | \psi_i \rangle, \quad (2)$$

where  $\mathcal{C}(x; \theta)$ ,  $\mathcal{O}$  and  $\psi_i$  are the respectively the VQC, a target observable and the initial state on which we apply  $\mathcal{C}$ .

- ➡ We know how to derivate circuits, e.g. using the Parameter Shift Rule (PSR)<sup>3</sup>, thanks to which we can calculate:

$$\partial_\mu \hat{F} = r [\hat{F}(\mu^+) - \hat{F}(\mu^-)]. \quad (3)$$

- ➡ In case of rotational gates<sup>4</sup>  $\exp\{-i\mu\hat{\sigma}\}$  we have  $r = 0.5$ ,  $\mu^\pm = \mu \pm s$  and  $s = \pi/2$ .

---

<sup>3</sup>[arXiv:1811.11184](#)

<sup>4</sup>[arXiv:1803.00745](#)

➔ We can upload  $x$  into a rotation angle and calculate  $\partial_x \hat{F}$ .

```

1 from qibo import models, gates, hamiltonians, derivative
2
3 # here you define a parametric circuit c as explained during the tutorials
4 # in which you upload x into the p-th rotation angle, as theta = x*PAR
5 # then you define an observable
6 h = hamiltonians.Z(nqubits=1)
7
8 # derivative with respect to x of < h >
9 derivative = derivative.parameter_shift(
10     circuit = c,                # parametric circuit
11     hamiltonian = h,            # target observable
12     parameter_index = p,        # parameter index
13     initial_state = initial_state, # initial state (before applying c)
14     scale_factor = scale_factor) # in this case PAR

```

➔ We can upload  $x$  into a rotation angle and calculate  $\partial_x \hat{F}$ .

```

1 from qibo import models, gates, hamiltonians, derivative
2
3 # here you define a parametric circuit c as explained during the tutorials
4 # in which you upload x into the p-th rotation angle, as theta = x*PAR
5 # then you define an observable
6 h = hamiltonians.Z(nqubits=1)
7
8 # derivative with respect to x of < h >
9 derivative = derivative.parameter_shift(
10     circuit = c,                # parametric circuit
11     hamiltonian = h,            # target observable
12     parameter_index = p,        # parameter index
13     initial_state = initial_state, # initial state (before applying c)
14     scale_factor = scale_factor) # in this case PAR


```

### In a nutshell

We estimate the CDF using a VQC and we derivate it with the PSR for calculating the PDF.

## Two problems

- ➡ We tried to fit CDFs using a VQC as QML model, but we had two problems:
  - 📈 by encoding  $x$  into the rotation angles, our results often did not retain a **strictly increasing monotony**.
  - 🔗 we need to fix  $\hat{F}(0) = 0$  and  $\hat{F}(1) = 1$ , so we need to manipulate  $\hat{F}$  in order to follow these constraints.
- ➡ These conditions are needed if we deal with CDFs.



**METHOD: Quantum Adiabatic ML**

---

- ➔ Let's use an Adiabatic Evolution (AE) as model:

$$H_{ad} = H_0[1 - s(\tau; \theta)] + s(\tau; \theta)H_1, \quad (4)$$

- ➔ following a scheduling  $s$ , depending on the evolution time  $\tau \in [0, 1]$  and on some variational parameters  $\theta$ .

## Adiabatic Evolution (AE) as QML model

➔ Let's use an Adiabatic Evolution (AE) as model:

$$H_{ad} = H_0[1 - s(\tau; \theta)] + s(\tau; \theta)H_1, \quad (4)$$

➔ following a scheduling  $s$ , depending on the evolution time  $\tau \in [0, 1]$  and on some variational parameters  $\theta$ .

```
1 # with qibo we can implement an Adiabatic Evolution via trotter formula
2 from qibo import models, hamiltonians, callbacks
3
4 # problem's parameters
5 nqubits = 1
6 h0 = hamiltonians.X(nqubits)
7 h1 = hamiltonians.Z(nqubits)
8 target_observable = h1
9
10 # we track the energy of h1 on the evolved ground state
11 energies = callbacks.Energy(target_observable)
12 evolution = models.AdiabaticEvolution(
13     h0=h0, h1=h1, s = lambda t : t, dt=0.1, callbacks = [energies])
14
15 # calculate the evolved final state at time t=final_time
16 evolved_state = evolution(final_time = final_time)
```



- ➔ We encode our problem into an AE by mapping  $(x, F)$  into  $(\tau, E)$ : evolution time  $\tau$  and target observable's energy  $E$ .

- ➔ We encode our problem into an AE by mapping  $(x, F)$  into  $(\tau, E)$ : evolution time  $\tau$  and target observable's energy  $E$ .
- ➔ An AE **naturally** solves the two problems:

- ➡ We encode our problem into an AE by mapping  $(x, F)$  into  $(\tau, E)$ : evolution time  $\tau$  and target observable's energy  $E$ .
- ➡ An AE **naturally** solves the two problems:
  - 📈 the evolution is naturally monotonic.

- ➔ We encode our problem into an AE by mapping  $(x, F)$  into  $(\tau, E)$ : evolution time  $\tau$  and target observable's energy  $E$ .
- ➔ An AE **naturally** solves the two problems:
  - 📈 the evolution is naturally monotonic.
  - 🔗 we can fix  $\hat{F}(0) = 0$  and  $\hat{F}(1) = 1$  by choosing  $H_0$  and  $H_1$  such that their ground-state energies are zero and one.

## Adiabatic Evolution (AE) as QML model

- ➔ We encode our problem into an AE by mapping  $(x, F)$  into  $(\tau, E)$ : evolution time  $\tau$  and target observable's energy  $E$ .
- ➔ An AE **naturally** solves the two problems:
  - 📈 the evolution is naturally monotonic.
  - 🔗 we can fix  $\hat{F}(0) = 0$  and  $\hat{F}(1) = 1$  by choosing  $H_0$  and  $H_1$  such that their ground-state energies are zero and one.
- ➔ We want to push the Energy of  $\mathcal{O}$  to approximate the target  $F$  value when  $\tau$  corresponds to the target variable  $x$ .

## Adiabatic Evolution (AE) as QML model

- ➔ We encode our problem into an AE by mapping  $(x, F)$  into  $(\tau, E)$ : evolution time  $\tau$  and target observable's energy  $E$ .
- ➔ An AE **naturally** solves the two problems:
  - 📈 the evolution is naturally monotonic.
  - 🔗 we can fix  $\hat{F}(0) = 0$  and  $\hat{F}(1) = 1$  by choosing  $H_0$  and  $H_1$  such that their ground-state energies are zero and one.
- ➔ We want to push the Energy of  $\mathcal{O}$  to approximate the target  $F$  value when  $\tau$  corresponds to the target variable  $x$ .

### Optimizing the AE

The task becomes to optimize the scheduling parameters in order to let the AE pass through the training points.

## METHOD: **Optimizing the AE**

---

➔ We use a **CMA-ES**<sup>5</sup> genetic algorithm and the following loss function:

$$J_{\text{MSE}} = \frac{1}{N_{\text{train}}} \sum_{k=1}^{N_{\text{train}}} [F(x_k) - E_k(\theta)]^2. \quad (5)$$

---

<sup>5</sup>[arXiv:1604.00772](#)



- ➔ We use a **CMA-ES**<sup>5</sup> genetic algorithm and the following loss function:

$$J_{\text{MSE}} = \frac{1}{N_{\text{train}}} \sum_{k=1}^{N_{\text{train}}} [F(x_k) - E_k(\theta)]^2. \quad (5)$$

- ➔ Thus we evolve the system using a **polynomial scheduling** function<sup>6</sup>:

$$s(t; \theta) = \frac{1}{\eta} \sum_{i=1}^p \theta_i x^i, \quad \text{with} \quad \eta = \sum_{i=1}^p \theta_i, \quad (6)$$

---

<sup>5</sup>[arXiv:1604.00772](https://arxiv.org/abs/1604.00772)

<sup>6</sup>One is free to set a custom ansatz, e.g. a neural network. With qibo an  $s$  function is required such as  $s(0) = 0$  and  $s(1) = 1$ .

- ➔ We use a **CMA-ES**<sup>5</sup> genetic algorithm and the following loss function:

$$J_{\text{MSE}} = \frac{1}{N_{\text{train}}} \sum_{k=1}^{N_{\text{train}}} [F(x_k) - E_k(\theta)]^2. \quad (5)$$

- ➔ Thus we evolve the system using a **polynomial scheduling** function<sup>6</sup>:

$$s(t; \theta) = \frac{1}{\eta} \sum_{i=1}^p \theta_i x^i, \quad \text{with} \quad \eta = \sum_{i=1}^p \theta_i, \quad (6)$$

In each optimization step

We execute the evolution collecting  $\{E_k\}$ , thanks to which we evaluate  $J_{\text{MSE}}$ . Then, we update  $\theta$  according to the chosen technique.

<sup>5</sup>[arXiv:1604.00772](https://arxiv.org/abs/1604.00772)


<sup>6</sup>One is free to set a custom ansatz, e.g. a neural network. With qibo an  $s$  function is required such as  $s(0) = 0$  and  $s(1) = 1$ .

➡ The optimization step is performed using qibo:

```
1 import qibo
2
3 # before we define a loss_evaluation function as J_MSE
4 def loss_evaluation(parameters): {...}
5
6 # then we use the cma optimizer provided by qibo
7 def optimize(force_positive=False, method="cma"):
8     """Use qibo to optimize the parameters of the schedule function"""
9
10    options = {
11        "ftarget": target,          # Target loss function
12        "maxiter": max_iterations,   # Maximum number of iterations
13        "maxfeval": max_evals,      # Maximum number of function evaluations
14    }
15
16    # forcing the parameters to be positive; unused in this case.
17    if force_positive:
18        options["bounds"] = [0, 1e5]
19
20    result = qibo.optimizers.optimize(loss_evaluation, parameters, method=method,
21        options=options)
22    return result
```


## A toy example with $n_{\text{qubits}}=1$ - starting point

➡  $n_{\text{params}}=20$ ,  $dt=0.1$ ,  $\text{final\_time}=50$ ,  $\text{target\_loss}=\text{None}$




## A toy example - until $J_{\text{MSE}} = 10^{-1}$

➡ `nparams=20, dt=0.1, final_time=50, target_loss=1e-1`




## A toy example - until $J_{\text{MSE}} = 10^{-2}$

➡ `nparams=20, dt=0.1, final_time=50, target_loss=1e-2`



## A toy example - ending at $J_{\text{MSE}} = 10^{-4}$

➡ `nparams=20, dt=0.1, final_time=50, target_loss=1e-4`



DERIVATION: **from  $\{H_j\}$  to a circuit**

---



- ➔ As previously said, we want to apply some **derivation rules**.

- ➔ As previously said, we want to apply some **derivation rules**.
- ➔ During an `nsteps`-AE, we get `nsteps` “**local time**” adiabatic hamiltonians  $\{H_j\}$ .

- ➡ As previously said, we want to apply some **derivation rules**.
- ➡ During an `nsteps`-AE, we get `nsteps` “**local time**” adiabatic hamiltonians  $\{H_j\}$ .
- ➡ Each of these can be associated with an **instantaneous** time evolution operator  $U_j$ , which at  $\tau_j = j \, dt$  should be applied on to the state obtained in  $\tau_{j-1}$ .

- ➡ As previously said, we want to apply some **derivation rules**.
- ➡ During an `nsteps`-AE, we get `nsteps` “**local time**” adiabatic hamiltonians  $\{H_j\}$ .
- ➡ Each of these can be associated with an **instantaneous** time evolution operator  $U_j$ , which at  $\tau_j = j \, dt$  should be applied on to the state obtained in  $\tau_{j-1}$ .
- ➡ The time-evolved state  $\tau_n$  is obtained as follows:

$$|\psi(\tau_n)\rangle = \prod_{j=0}^n U(\tau_j) |\psi(\tau_0)\rangle, \quad (7)$$

where the initial state is the ground state of  $H_0$  by construction.

➡ To calculate the derivative of (7) is not trivial, is better to have a **single unitary**  $\mathcal{C}(\tau)$  which sums up all the sequence needed to get the evolved state at  $\tau$ .

- ➡ To calculate the derivative of (7) is not trivial, is better to have a **single unitary**  $\mathcal{C}(\tau)$  which sums up all the sequence needed to get the evolved state at  $\tau$ .
- ➡ For doing this:

➡ To calculate the derivative of (7) is not trivial, is better to have a **single unitary**  $\mathcal{C}(\tau)$  which sums up all the sequence needed to get the evolved state at  $\tau$ .

➡ For doing this:

1. we noticed that each  $U_j = \exp\{-iH_j d\tau\}$  can be diagonalized;

➡ To calculate the derivative of (7) is not trivial, is better to have a **single unitary**  $\mathcal{C}(\tau)$  which sums up all the sequence needed to get the evolved state at  $\tau$ .

➡ For doing this:

1. we noticed that each  $U_j = \exp\{-iH_j d\tau\}$  can be diagonalized;
2. once diagonalized  $\forall j$ , we consider the limit such that  $d\tau \rightarrow 0$ ;



➡ To calculate the derivative of (7) is not trivial, is better to have a **single unitary**  $\mathcal{C}(\tau)$  which sums up all the sequence needed to get the evolved state at  $\tau$ .

➡ For doing this:

1. we noticed that each  $U_j = \exp\{-iH_j d\tau\}$  can be diagonalized;
2. once diagonalized  $\forall j$ , we consider the limit such that  $d\tau \rightarrow 0$ ;
3. thanks to which the diagonalizing element  $P_j P_{j-1}^{-1} \rightarrow I$  and we get:

$$\mathcal{C}(\tau) = \Lambda_{t0} P_t \exp \left\{ -it \int_0^t \hat{D}(t) dt \right\} P_0^{-1}, \quad (8)$$

Where the  $\Lambda$  factor is used to make the determinant of  $P$  be one and  $\hat{D}$  is the diagonalized hamiltonian.

➡ To calculate the derivative of (7) is not trivial, is better to have a **single unitary**  $\mathcal{C}(\tau)$  which sums up all the sequence needed to get the evolved state at  $\tau$ .

➡ For doing this:

1. we noticed that each  $U_j = \exp\{-iH_j d\tau\}$  can be diagonalized;
2. once diagonalized  $\forall j$ , we consider the limit such that  $d\tau \rightarrow 0$ ;
3. thanks to which the diagonalizing element  $P_j P_{j-1}^{-1} \rightarrow I$  and we get:

$$\mathcal{C}(\tau) = \Lambda_{t0} P_t \exp \left\{ -it \int_0^t \hat{D}(t) dt \right\} P_0^{-1}, \quad (8)$$

Where the  $\Lambda$  factor is used to make the determinant of  $P$  be one and  $\hat{D}$  is the diagonalized hamiltonian.

4. Now we have a circuit  $\mathcal{C}$  after which evaluate  $\hat{Z}$ .

- ➡ We have a unitary  $\mathcal{C}$ , of which we can calculate the elements  $c_{ij}$ .

- ➡ We have a unitary  $\mathcal{C}$ , of which we can calculate the elements  $c_{ij}$ .
- ➡ The final step is to re-write this unitary in a form on which we can use the **parameter shift rule**.

- ➡ We have a unitary  $\mathcal{C}$ , of which we can calculate the elements  $c_{ij}$ .
- ➡ The final step is to re-write this unitary in a form on which we can use the **parameter shift rule**.
- ➡ Each unitary  $\mathcal{C} \in SU(2)$  can be written as sequence of **three rotations** using the Euler angles:

$$\mathcal{C} \equiv R_z(\phi)R_x(\theta)R_z(\psi), \quad (9)$$

- ➡ We have a unitary  $\mathcal{C}$ , of which we can calculate the elements  $c_{ij}$ .
- ➡ The final step is to re-write this unitary in a form on which we can use the **parameter shift rule**.
- ➡ Each unitary  $\mathcal{C} \in SU(2)$  can be written as sequence of **three rotations** using the Euler angles:

$$\mathcal{C} \equiv R_z(\phi)R_x(\theta)R_z(\psi), \quad (9)$$

in which the relationships between the angles and the elements of  $\mathcal{C}$  are:

$$\begin{cases} \phi = \pi/2 - \arg(c_{01}) - \arg(c_{00}) \\ \theta = -2 \arccos(|c_{00}|) \\ \psi = \arg(c_{01}) - \pi/2 - \arg(c_{00}). \end{cases} \quad (10)$$

- ➡ We have a unitary  $\mathcal{C}$ , of which we can calculate the elements  $c_{ij}$ .
- ➡ The final step is to re-write this unitary in a form on which we can use the **parameter shift rule**.
- ➡ Each unitary  $\mathcal{C} \in SU(2)$  can be written as sequence of **three rotations** using the Euler angles:

$$\mathcal{C} \equiv R_z(\phi)R_x(\theta)R_z(\psi), \quad (9)$$

in which the relationships between the angles and the elements of  $\mathcal{C}$  are:

$$\begin{cases} \phi = \pi/2 - \arg(c_{01}) - \arg(c_{00}) \\ \theta = -2 \arccos(|c_{00}|) \\ \psi = \arg(c_{01}) - \pi/2 - \arg(c_{00}). \end{cases} \quad (10)$$

- ➡ Now we can derivate with respect to the rotation angles!

DERIVATION: **derivating  $\mathcal{C}_R$  via PSR**

---



➡ If we call  $\theta$  one of the three angles, we get  $\partial_\tau \hat{F}$  by calculating:

$$\partial_\tau \hat{F}(\tau; \boldsymbol{\theta}) = \sum_{i=1}^3 \frac{\partial \hat{F}}{\partial \theta_i} \frac{\partial \theta_i}{\partial s} \frac{\partial s}{\partial \tau}, \quad (11)$$

➡ If we call  $\theta$  one of the three angles, we get  $\partial_\tau \hat{F}$  by calculating:

$$\partial_\tau \hat{F}(\tau; \theta) = \sum_{i=1}^3 \frac{\partial \hat{F}}{\partial \theta_i} \frac{\partial \theta_i}{\partial s} \frac{\partial s}{\partial \tau}, \quad (11)$$

➡ where the **first term** is calculated via parameter shift rule, and the remaining twos can be obtained **analytically** if we use an analytical ansatz for  $s$ .

➡ If we call  $\theta$  one of the three angles, we get  $\partial_\tau \hat{F}$  by calculating:

$$\partial_\tau \hat{F}(\tau; \theta) = \sum_{i=1}^3 \frac{\partial \hat{F}}{\partial \theta_i} \frac{\partial \theta_i}{\partial s} \frac{\partial s}{\partial \tau}, \quad (11)$$

➡ where the **first term** is calculated via parameter shift rule, and the remaining twos can be obtained **analytically** if we use an analytical ansatz for  $s$ .

### Summary

- We fit the eCDF via QAML;
- we translate  $\{H_j\}$  into  $\mathcal{C}_R$ ;
- we derivate the result via chain rule.

VALIDATION: **test cases**

---

- ➔ We performed the QAML strategy to some test cases.

- ➔ We performed the QAML strategy to some test cases.
- ➔ We did it by simulating circuits both in ideal<sup>7</sup> and shot-noisy<sup>8</sup> way.

---

<sup>7</sup>Exact state vector simulation

<sup>8</sup>Sampling the frequencies from the simulated state

- ➔ We performed the QAML strategy to some test cases.
- ➔ We did it by simulating circuits both in ideal<sup>7</sup> and shot-noisy<sup>8</sup> way.
- ➔ In the following table we collect realistic results in which we used  $N_{\text{shots}} = 2 \cdot 10^5$  shots for evaluating  $\hat{F}$ .

Fit function	$N_{\text{sample}}$	$p$	$J_f$	$N_{\text{ratio}}$	$\chi^2$
Gamma	$5 \cdot 10^4$	25	$2.9 \cdot 10^{-6}$	31	$2.2 \cdot 10^{-4}$
Gaussian mix	$2 \cdot 10^5$	30	$2.75 \cdot 10^{-5}$	31	$4.39 \cdot 10^{-3}$
$t$	$5 \cdot 10^4$	20	$2.1 \cdot 10^{-6}$	34	$3.4 \cdot 10^{-4}$
$s$	$5 \cdot 10^4$	20	$7.9 \cdot 10^{-6}$	34	$1.20 \cdot 10^{-3}$
$y$	$5 \cdot 10^4$	8	$3.7 \cdot 10^{-6}$	34	$1.45 \cdot 10^{-3}$

**Table 1:** Summary.  $N_{\text{shots}} = 5 \cdot 10^4$ .

---

<sup>7</sup>Exact state vector simulation

<sup>8</sup>Sampling the frequencies from the simulated state

- ➔ We performed the QAML strategy to some test cases.
- ➔ We did it by simulating circuits both in ideal<sup>7</sup> and shot-noisy<sup>8</sup> way.
- ➔ In the following table we collect realistic results in which we used  $N_{\text{shots}} = 2 \cdot 10^5$  shots for evaluating  $\hat{F}$ .

Fit function	$N_{\text{sample}}$	$p$	$J_f$	$N_{\text{ratio}}$	$\chi^2$
Gamma	$5 \cdot 10^4$	25	$2.9 \cdot 10^{-6}$	31	$2.2 \cdot 10^{-4}$
Gaussian mix	$2 \cdot 10^5$	30	$2.75 \cdot 10^{-5}$	31	$4.39 \cdot 10^{-3}$
$t$	$5 \cdot 10^4$	20	$2.1 \cdot 10^{-6}$	34	$3.4 \cdot 10^{-4}$
$s$	$5 \cdot 10^4$	20	$7.9 \cdot 10^{-6}$	34	$1.20 \cdot 10^{-3}$
$y$	$5 \cdot 10^4$	8	$3.7 \cdot 10^{-6}$	34	$1.45 \cdot 10^{-3}$

**Table 1:** Summary.  $N_{\text{shots}} = 5 \cdot 10^4$ .


- ➔ The last three elements in the table refers to a  $pp \rightarrow t\bar{t}$  production.

<sup>7</sup>Exact state vector simulation

<sup>8</sup>Sampling the frequencies from the simulated state




## Test 1: Gamma CDF




**Figure 1:** We show the sample (grey hist), ideal (red line) and realistic (blue line) simulation, theoretical CDF of the gamma distribution (dashed black line).

## Test 1: Gamma PDF



**Figure 2:** Above: data (grey hist), ideal (red) and realistic (blue) simulation, theoretical PDF law (dashed black line). Below: same quantities but normalized with respect to the true law with the addition of a second realistic simulation (yellow) line.


## Test 2: gaussian mixture CDF



**Figure 3:** We show the sample (grey hist), ideal (red line) and realistic (blue line) simulation, theoretical CDF of the gamma distribution (dashed black line).

## Test 2: gaussian mixture PDF


PDF estimation -  $\rho(x) = 0.6\mathcal{N}(x; -10, 4) + 0.4\mathcal{N}(x; 5, 5)$



**Figure 4:** Above: data (grey hist), ideal (red) and realistic (blue) simulation, theoretical PDF law (dashed black line). Below: same quantities but normalized with respect to the true law with the addition of a second realistic simulation (yellow) line.


## Test 3: quantum generation of $pp \rightarrow t\bar{t}$

➡ In a previous TH work<sup>9</sup> a sample of  $10^5$  events for  $pp \rightarrow t\bar{t}$  at a center of mass  $\sqrt{s} = 13$  TeV for LHC configuration was generated<sup>10</sup>.




<sup>9</sup> [arXiv:2110.06933](https://arxiv.org/abs/2110.06933)


<sup>10</sup>  $s$  and  $t$  Mandelstam variables,  $y$  rapidity.



**Figure 5:** We show the sample (grey hist), ideal (red line) and realistic (blue line) simulation, quantum GAN eCDF (yellow).




**Figure 6:** Above: data (grey hist), ideal (red) and realistic (blue) simulation. Below: same quantities but normalized with respect to the true law with the addition of a second realistic simulation (yellow) line.




**Figure 7:** We show the sample (grey hist), ideal (red line) and realistic (blue line) simulation, quantum GAN eCDF (yellow).






**Figure 8:** Above: data (grey hist), ideal (red) and realistic (blue) simulation. Below: same quantities but normalized with respect to the true law with the addition of a second realistic simulation (yellow) line.



**Figure 9:** We show the sample (grey hist), ideal (red line) and realistic (blue line) simulation, quantum GAN eCDF (yellow).



**Figure 10:** Above: data (grey hist), ideal (red) and realistic (blue) simulation. Below: same quantities but normalized with respect to the true law with the addition of a second realistic simulation (yellow) line.

## Outlook and references

---

➔ Open roads:

---

➡ Open roads:

↗ improve QAML validation: *try more general scheduling functions (e.g. ANNs), benchmarking with other density estimation techniques;*

---

<sup>11</sup>In case of *iid* random variables this model can be used individually for each dimension.

## ➡ Open roads:

- 🔗 improve QAML validation: *try more general scheduling functions (e.g. ANNs), benchmarking with other density estimation techniques;*
- 🔗 hardware deployment: *can a NISQ device be used for this? what is the speed-up advantage when running the QAML on annealers?*
- 🔗 multi-dimensional<sup>11</sup> PDFs : *how to preserve correlations? how to exploit multi-qubits hamiltonians?*

---

<sup>11</sup>In case of *iid* random variables this model can be used individually for each dimension.

## ➡ Open roads:

- 🔗 improve QAML validation: *try more general scheduling functions (e.g. ANNs), benchmarking with other density estimation techniques;*
- 🔗 hardware deployment: *can a NISQ device be used for this? what is the speed-up advantage when running the QAML on annealers?*
- 🔗 multi-dimensional<sup>11</sup> PDFs : *how to preserve correlations? how to exploit multi-qubits hamiltonians?*
- 🔗 use the QAML strategy for integrating, e.g. deploying of a new NNPDF feature;

---

<sup>11</sup>In case of *iid* random variables this model can be used individually for each dimension.



## ➡ Open roads:




- ✍ improve QAML validation: *try more general scheduling functions (e.g. ANNs), benchmarking with other density estimation techniques;*
- ✍ hardware deployment: *can a NISQ device be used for this? what is the speed-up advantage when running the QAML on annealers?*
- ✍ multi-dimensional<sup>11</sup> PDFs : *how to preserve correlations? how to exploit multi-qubits hamiltonians?*
- ✍ use the QAML strategy for integrating, e.g. deploying of a new NNPDF feature;
- ✍ anomaly detection applications of the QAML algorithm.


---




<sup>11</sup>In case of *iid* random variables this model can be used individually for each dimension.

➡ We leave some references and links thanks to which you can use our codes and read more about the project:

</> open-access codes for personal coding or contributing:

-  [the qibo package](#);
-  [the qibolab package](#);
-  [the qibocal package](#);

 our official [webpage](#), with the following documentations:

-  [the qibo docs](#);
-  [the qibolab docs](#);
-  [the qibocal docs](#);

The code is open-source and available [here](#)!