

Syntax Mini-Guide for Parsley Documentation Format

Pattern for all special tags: `# [a-z]{2} [a-z0-9]{1}`

All tags need an opening and closing tag.

In the rendered HTML there will be one space removed right of the opening tag and one space left of the closing tag.

Example:

This is `#str` bold `#str`.

renders:

This is `bold`.

1. Structure:

There are 4 levels of section headers (in practice only 3 are used currently):

`#sc1`, `#sc2`, `#sc3`, `#sc4`

Example:

`#sc1` `pageId_sectionId` Title of the Section `#sc1`

`sectionId` can have additional underscores.

References to other sections:

`#ref` `pageId_sectionId` `#ref`

This will render a link and insert the title of the section as the link text.

The tags `#sc1` to `#sc4` will also be used to auto-generate the navigation tree.

2. Tables:

```
#tbl    <table>
#tbr    <tr>
#        Delimiter for cells (<td>)
```

Example:

```
#tbl
#tbr First cell # Second cell #tbr
#tbr Foo # Bar #tbr
#tbl
```

3. Lists:

```
#lst    short for "list"           <ul>
#lse    short for "list element"   <li>
```

Example:

```
#lst
#lse First bullet #lse
#lse Second bullet #lse
#lst
```

4. Links:

#url `http://www.foo.com/` Some text #url

renders:

```
<a href="http://www.foo.com/" target="_blank">Some text</a>
```

Do not use this for cross-references (see #ref under 1.)

5. Images:

#img `doc_img` someDiagram.jpg #img

renders:

```

```

`doc_img` is currently the only style getting used.

6. Other markup:

| | | | |
|------|-------------|-------------------------------|--|
| #str | strong | | |
| #par | paragraph | <p class="paragraph"> | |
| #sub | subheadline | <p class="subheadline"> | (This will not make it into the tree navigation) |
| #cdi | code inline | <code> | |
| #cdb | code block | <pre><code> | (those are the white code boxes) |
| #hlt | highlight | | (currently only used in code snippets) |
| #nbr | no break | <nobr> | |