KABELKAMP 2 - D-30179 HANNOVER

TELEFON: +49 511 67 69 99-188/ -182/ -183/ -186/ -189/ -190

TELEFAX: +49 511 67 69 99-185

E-MAIL: cellulare@mc-technologies.net - Homepage: www.mc-technologies.net



## MC0114027-SMA-ST Magnetfuß-Antenne

## **Magnetic GSM-UMTS Antenna**



## **Specifications**

Material: Nylon 6
Colour: Black
Net weight (g): 65

Dimensions (mm): 88+2\*=029Temperature (°C): -40 to +80

## **Technical Data Telephone**

Antenna type: 1/4l mobile antenna

Frequency range

GSM Europe/USA 824 - 960 MHz DCS-PCS Europe/USA 1710 - 1990 MHz

UMTS 1920 -1990 MHz (uplink tr.)

2110 - 2170 MHz (downlink ric.) 1900 - 1920 MHz (uplink tr.) 2010 - 2025 MHz (downlink ric.)

Impendance (Ohms): 50 Max. Power (W) 20

V.S.W.R.

824 - 960: less than 1.6 1710 - 1990: less than 1.5 1900 - 2170: less than 2.0 Polarisation: vertical Emission: omnidirectional

Rod section: 2 Gain (dBi): 2.14

Cable: RG174, 2,5m with SMA (male)

capacity: 100 pF/m



SWR CURVE

