

Features and Components

Use: To prime JM EPDM membrane surfaces for adhering JM EPDM Tape and Peel and Stick products.

Type: One-part, solvent-based membrane primer.

Color: Grey

Features: Tack-Back functionality for detail work in vertical applications and seam work in horizontal applications.



Component

PR
Primer

Type

M
Membrane
Single Ply

System Compatibility This product may be used as a component in the following systems. Please reference product application for specific installation methods and information.

Multi-Ply	BUR		APP		SBS				
	HA	CA	HW	HA	CA	HW	SA	MF	
									<i>Do not use in multi-ply systems</i>

Single Ply	TPO				PVC			EPDM		
	MF	AD	SA	IW	MF	AD	IW	MF	AD	BA
										<i>Used to prime membranes in EPDM single ply systems</i>

Key: HA = Hot Applied CA = Cold Applied HW = Heat Weldable SA = Self Adhered MF = Mechanically Fastened IW = Induction Weld BA = Ballasted AD = Adhered

Energy and the Environment

Maximum VOC	<250 g/l (EPA Method 24)
This product may be used in jurisdictions limiting VOC (volatile organic compounds) content of single ply roofing adhesive to no greater than 250 g/l.	

Precautions

Johns Manville EPDM Tape Primer Plus (Low VOC) is a combustible material and should be shipped and stored away from open flames, heat or sources of ignition. Keep all pails tightly sealed while in storage. It should be used only in well-ventilated areas. It may cause eye, skin and respiratory irritation, and is harmful or fatal if swallowed. Avoid contact with skin. Use impervious clothing and rubber gloves to avoid prolonged or repeated contact with skin. Read the container label and follow all safety instructions.

Installation/Application



Scrubber Pad

- Do not install in direct contact with asphalt or coal tar pitch.
- Refer to the application instructions guidelines for proper utilization of this primer.
- Recommended for use with Black EPDM Membrane.

Packaging and Coverage

Container Sizes	4 – 1 gal (3.8 l) cans per box	3 gal (11.4 l) pail
Shipping Weight (approx.)	42.5 lb (19.28 kg) / box	30 lb (13.61 kg) / pail
Containers per Pallet	54	45
Pallets per Truck	24	24
Coverage Rate*	150 - 225 ft ² /gal (3.68 - 5.52 m ² /l)	

conditions. Coverage rates stated herein are approximate only.

Storage

Shelf Life	12 months from manufacture date
Storage Conditions	Clean, dry, indoor environment, out of direct sunlight, in the original unopened container.
Temperature Range	60°F – 80°F (16°C – 27°C) - Protect from freezing

Exposure Window

Keep can or pail tightly closed when not in use and protect from moisture contamination. Once exposed to moisture in the air, JM EPDM Tape Primer Plus (Low VOC) begins to cure and may gel within 24 hours.