

Features and Components

Use: JM EPDM/PVC Pourable Sealer is used as a penetration pocket filler.

Type: Two-part polyurethane sealant.

Colors: Part A: Black
Part B: Amber



Component

Sealant

Type

FP
Penetration

Single Ply

System Compatibility This product may be used as a component in the following systems. Please reference product application for specific installation methods and information.

Multi-Ply	BUR		APP		SBS			
	HA	CA	HW	HA	CA	HW	SA	MF
Compatible with the selected multi-ply systems above								

Single Ply	TPO				PVC			EPDM		
	MF	AD	SA	IW	MF	AD	IW	MF	AD	BA
Do not use in single ply systems										

Key: HA = Hot Applied CA = Cold Applied HW = Heat Weldable SA = Self Adhered MF = Mechanically Fastened IW = Induction Weld BA = Ballasted AD = Adhered

Energy and the Environment

Maximum VOC	Part A & B: 0 g/l
-------------	-------------------

Physical Properties

Property		JM EPDM/PVC Pourable Sealer
Percent Volatile	Part A	0%
	Part B	0%
Specific Gravity @ 77°F (25°C)	Part A	1.51
	Part B	1.24
Vapor Pressure	Part A	< 0.001 @ 68°F (20°C)
	Part B	< 1x10 ⁻⁵ mm Hg @ 77°F (25°C)

Precautions

Johns Manville EPDM/PVC Pourable Sealer is a combustible material and should be shipped and stored away from open flames, heat or sources of ignition. Keep all cans tightly sealed while in storage. It should be used only in well-ventilated areas. It may cause eye, skin and respiratory irritation, and is harmful or fatal if swallowed. Avoid contact with skin. Use impervious clothing and rubber gloves to avoid prolonged or repeated contact with skin. Read the container label and follow all safety instructions.

Technical specifications as shown in this literature are intended to be used as general guidelines only. Please refer to the Safety Data Sheet and product label prior to using this product. The Safety Data Sheet is available by calling (800) 922-5922 or on the web at www.jm.com/roofing. The physical and chemical properties of the product listed herein represent typical, average values obtained in accordance with accepted test methods and are subject to normal manufacturing variations. They are supplied as a technical service and are subject to change without notice. Check with the regional sales representative nearest you for current information.

All Johns Manville products are sold subject to Johns Manville's standard Terms and Conditions, which includes a Limited Warranty and Limitation of Remedy. For a copy of the Johns Manville standard Terms and Conditions or for information on other Johns Manville roofing products and systems, visit www.jm.com/terms-conditions.

Installation/Application



Pour

- Apply between temperatures of: 40° to 90° Do Not Thin.
- Refer to the application instructions guidelines for proper utilization of this sealant.

Packaging and Coverage

Container Sizes	Box of three kits: Part A: 0.75 gal (2.84 l) can Part B: 0.5 pint (0.24 l) can
Weight per Can	Part A: 8.7 lb (3.95 kg) Part B: 0.57 lb (0.26 kg)
Shipping Weight (approx.)	32 lb (14.5 kg)/box
Boxes per Pallet	45
Pallet Weight (approx.)	1,500 lb (681.8 kg)
Pallets per Truck	8 (depends on order size)

Storage

Shelf Life	12 months from manufacture date
Storage Conditions	Clean, dry, indoor environment in an unopened container
Temperature Range	60°F – 75°F (16°C – 24°C) - Protect from freezing

Exposure Window

Workable pot life after mixing is approximately 30 minutes at 72°F (22°C). The material begins to cure firmly 2 hours after mixing.