


Features and Components

- Use:** To seal seam laps where perimeter and/or header sheets intersect (T-Joint) in PVC systems.
- Material:** Flexible, non-reinforced, UV-resistant PVC (polyvinyl chloride) with Elvaloy®* KEE (ketone ethylene ester).
- Colors:** White; Grey; and Sandstone

* Elvaloy® KEE is a registered trademark of Dow.



Component

A
Accessory

Single Ply

Type

MS
Membrane Seaming

System Compatibility This product may be used as a component in the following systems. Please reference product application for specific installation methods and information.

Multi-Ply	BUR		APP		SBS				
	HA	CA	CA	HW	HA	CA	HW	SA	MF
Do not use in Multi-Ply systems									

Single Ply	TPO		PVC		EPDM		
	MF	AD	MF	AD	MF	AD	BA
Compatible with the selected Single Ply systems above							

Key: HA = Hot Applied CA = Cold Applied HW = Heat Weldable SA = Self Adhered MF = Mechanically Fastened AD = Adhered BA = Ballasted

Peak Advantage® Guarantee Information

Systems
Approved for use in any JM Peak Advantage Guarantee System

Installation/Application



Hot Air Weld

Refer to JM PVC applicator guides or detail drawings for instructions.

Packaging and Dimensions

Size (diameter)	4.5" (11.4 cm)
Patches per Box	100
Weight per Box	6.4 lb (2.9 kg)
Thickness	0.060" (1.52 mm)

Storage

Storage Conditions	Store indoors, out of direct sunlight, and keep clean and dry prior to application.
--------------------	---