


Features and Components

Use: Provides a safe, stable and maintenance-free walkway for quick and easy access to rooftop equipment in high traffic areas.

Material: 72 mil (1.83 mm) thick, textured, reinforced, UV-resistant PVC (polyvinyl chloride) with Elvaloy® KEE (Ketone Ethylene Ester).

Color: Grey

* Elvaloy is a registered trademark of Dow.



Component

A
Accessory

Single Ply

Type

PT
Protection

System Compatibility

This product may be used as a component in the following systems. Please reference product application for specific installation methods and information.

Multi-Ply	BUR		APP		SBS				
	HA	CA	HW	HA	CA	HW	SA	MF	
Do not use in multi-ply systems									

Single Ply	TPO				PVC			EPDM		
	MF	AD	SA	IW	MF	AD	IW	MF	AD	BA
Compatible with the selected single ply systems above										

Key: HA = Hot Applied CA = Cold Applied HW = Heat Weldable SA = Self Adhered MF = Mechanically Fastened IW = Induction Weld BA = Ballasted AD = Adhered

Peak Advantage® Guarantee Information

Systems
Approved for use in any JM Peak Advantage Guarantee System

Installation/Application



Hot Air Weld

When installing JM PVC Walkpads be sure to:

- Achieve full weld around perimeter of the material
- Install textured side up
- Minimize installing over seams and membrane splices whenever possible
- On mechanically fastened systems, avoid installing over the disc
- Refer to JM PVC applicator guides or detail drawings for instructions

Packaging and Dimensions

Roll Size (width x length)	36" x 60' (91.44 cm x 18.29 m)
Nominal Thickness	0.072" (1.83 mm)
Coverage per Roll (gross)	180 ft² (16.72 m²)
Weight per Roll	78 lb (35.4 kg)

Storage

Storage Conditions	Store indoors, out of direct sunlight, and keep clean and dry prior to application.
--------------------	---

Technical specifications as shown in this literature are intended to be used as general guidelines only. Please refer to the Safety Data Sheet and product label prior to using this product. The Safety Data Sheet is available by calling (800) 922-5922 or on the web at www.jm.com/roofing. The physical and chemical properties of the product listed herein represent typical, average values obtained in accordance with accepted test methods and are subject to normal manufacturing variations. They are supplied as a technical service and are subject to change without notice. Check with the regional sales representative nearest you for current information.

All Johns Manville products are sold subject to Johns Manville's standard Terms and Conditions, which includes a Limited Warranty and Limitation of Remedy. For a copy of the Johns Manville standard Terms and Conditions or for information on other Johns Manville roofing products and systems, visit www.jm.com/terms-conditions.