

JM TPO 6" REINFORCED TERMINATION STRIP (RTS)

Features and Components

Use: To secure the field membrane at any angle change greater than 2 in/ft (167 mm/m). JM TPO 6" RTS can be used in lieu of fastening through the field membrane with screws and plates at angle changes.

Materials: 45 mil (1.14 mm) thick reinforced TPO (thermoplastic polyolefin) membrane with 30 mil (0.76 mm) thick, factory-applied peel and stick adhesive tape.

Color: White



Component

A
Accessory

Single Ply

Type

PR
Perimeter Reinforcement

System Compatibility This product may be used as a component in the following systems. Please reference product application for specific installation methods and information.

Multi-Ply	BUR		APP		SBS				
	HA	CA	CA	HW	HA	CA	HW	SA	MF
Do not use with multi-ply systems									

Single Ply	TPO				PVC			EPDM		
	MF	AD	SA	IW	MF	AD	IW	MF	AD	BA
Compatible with the selected single ply systems above										

Key: HA = Hot Applied CA = Cold Applied HW = Heat Weldable SA = Self Adhered MF = Mechanically Fastened IW = Induction Weld BA = Ballasted AD = Adhered

Peak Advantage® Guarantee Information

Systems
Approved for use in any JM Peak Advantage Guarantee System

Installation/Application



Self-Adhered



Mechanically Fastened

- This product must be both self-adhered and mechanically fastened to properly function.
- Do not install in direct contact with asphalt or coal tar pitch.
- Refer to JM TPO applicator guides or detail drawings for instructions.

Packaging and Dimensions

Roll Size	6" x 100' (15.2 cm x 30.48 m)
Thickness:	
Membrane	0.045" (1.14 mm)
Tape	0.030" (0.76 mm)
Total	0.075" (1.90 mm)
Coverage	50 ft ² (4.65 m ²)
Linear ft (m) per Roll	100 (30.48)
Rolls per Box	2

Storage

Shelf Life	18 months from manufacture date
Storage Conditions	Store indoors, out of direct sunlight, in original unopened containers
Temperature Range	60°F – 80°F (16°C – 27°C)

Technical specifications as shown in this literature are intended to be used as general guidelines only. Please refer to the Safety Data Sheet and product label prior to using this product. The Safety Data Sheet is available by calling (800) 922-5922 or on the web at www.jm.com/roofing. The physical and chemical properties of the product listed herein represent typical, average values obtained in accordance with accepted test methods and are subject to normal manufacturing variations. They are supplied as a technical service and are subject to change without notice. Check with the regional sales representative nearest you for current information. All Johns Manville products are sold subject to Johns Manville's standard Terms and Conditions, which includes a Limited Warranty and Limitation of Remedy. For a copy of the Johns Manville standard Terms and Conditions or for information on other Johns Manville roofing products and systems, visit www.jm.com/terms-conditions.