

Features and Components

Use: To strip in metal flanges on JM TPO Membrane systems with a Heat Weldable detail on one side, or as directed by JM technical services.

Materials: 60 mil (1.52 mm) thick, reinforced TPO (thermoplastic polyolefin) membrane with a 3" wide by 30 mil (0.76 mm) thick, factory-applied peel and stick adhesive tape

Colors: White



Component

A
Accessory

Single Ply

Type

FE
Flashing Edge

Single Ply

System Compatibility This product may be used as a component in the following systems. Please reference product application for specific installation methods and information.

Multi-Ply	BUR		APP			SBS			
	HA	CA	HW	HA	CA	HW	SA	MF	
Do not use in multi-ply systems									

Single Ply	TPO				PVC			EPDM		
	MF	AD	SA	IW	MF	AD	IW	MF	AD	BA
Compatible with the selected single ply systems above										

Key: HA = Hot Applied CA = Cold Applied HW = Heat Weldable SA = Self Adhered MF = Mechanically Fastened IW = Induction Weld BA = Ballasted AD = Adhered

Peak Advantage® Guarantee Information

Systems
Approved for use in any JM Peak Advantage® Guarantee System up to 25 years.

Installation/Application



Self-Adhered



Hot AirWeld

- Prime Metal with JM TPO Membrane Primer or JM Single Ply Membrane Primer (Low VOC) before applying JM TPO Heat Weldable Cover Tape.
- Apply peel & stick tape to primed metal surface then heat weld the TPO membrane to ensure the "uphill" side of the detail remains water tight over the long term.
- Refer to JM TPO application guides or detail drawings for instructions.

Packaging and Dimensions

Roll Size		Coverage
6" x 100' (15.24 cm x 30.48 m)		50 ft² (4.65 m²)
Thickness:		
Membrane		0.060" (1.52 mm)
Tape		0.030" (0.76 mm)
Total		0.090" (2.28 mm)
Roll Width		6"
Rolls per Box		2
Linear ft (m) per Box		200 (60.96)

Storage

Shelf Life	18 months from manufacture date
Storage Conditions	Store indoors, out of direct sunlight, in original unopened containers
Temperature Range	60°F – 80°F (16°C – 27°C)

Technical specifications as shown in this literature are intended to be used as general guidelines only. Please refer to the Safety Data Sheet and product label prior to using this product. The Safety Data Sheet is available by calling (800) 922-5922 or on the web at www.jm.com/roofing. The physical and chemical properties of the product listed herein represent typical, average values obtained in accordance with accepted test methods and are subject to normal manufacturing variations. They are supplied as a technical service and are subject to change without notice. Check with the regional sales representative nearest you for current information.

All Johns Manville products are sold subject to Johns Manville's standard Terms and Conditions, which includes a Limited Warranty and Limitation of Remedy. For a copy of the Johns Manville standard Terms and Conditions or for information on other Johns Manville roofing products and systems, visit www.jm.com/terms-conditions.