

Features and Components

- Use:** A smooth, cone-shaped boot, for traditional or split-pipe flashing applications to securely seal the penetration. Pipe boots eliminate the need for field fabrication.
- Material:** Flexible, smooth, non-reinforced TPO (thermoplastic polyolefin) cone-shaped boot with preformed flange.
- Colors:** White; Grey; and Tan



Component

A
Accessory

Single Ply

Type

FP
Penetration

System Compatibility This product may be used as a component in the following systems. Please reference product application for specific installation methods and information.

Multi-Ply	BUR		APP		SBS				
	HA	CA	HW	HA	CA	HW	SA	MF	
									Not compatible with Multi-ply systems

Single Ply	TPO				PVC			EPDM		
	MF	AD	SA	IW	MF	AD	IW	MF	AD	BA
										Compatible with the selected Single Ply systems above

Key: HA = Hot Applied CA = Cold Applied HW = Heat Weldable SA = Self Adhered MF = Mechanically Fastened IW = Induction Weld BA = Ballasted AD = Adhered

Peak Advantage® Guarantee Information

Systems
Approved for use in any JM Peak Advantage Guarantee System

Installation/Application



Hot Air Weld

- Each boot has a cutting guide for easy reference and diameter measurements.
- Do not install JM TPO Pipe Boots in direct contact with asphalt.
- Refer to JM TPO applicator guides or detail drawings for instructions.

Packaging and Dimensions

Sizes*	1" to 6" (2.5 cm to 15.2 cm)
Boots per Box	10
Weight per Boot	0.85 lb (0.38 kg)
Weight per Box	9 lb (4.1 kg)
Thickness	0.060" (1.52 mm)

* Standard size pipe clamps covering the largest possible range (6" diameter) are included for each pipe boot. Dimensions less than 1.5" (3.8 cm) diameter may require alternative clamps.

Storage

Storage Conditions	Store indoors, out of direct sunlight, and keep clean and dry prior to application.
--------------------	---

Technical specifications as shown in this literature are intended to be used as general guidelines only. Please refer to the Safety Data Sheet and product label prior to using this product. The Safety Data Sheet is available by calling (800) 922-5922 or on the web at www.jm.com/roofing. The physical and chemical properties of the product listed herein represent typical, average values obtained in accordance with accepted test methods and are subject to normal manufacturing variations. They are supplied as a technical service and are subject to change without notice. Check with the regional sales representative nearest you for current information.

All Johns Manville products are sold subject to Johns Manville's standard Terms and Conditions, which includes a Limited Warranty and Limitation of Remedy. For a copy of the Johns Manville standard Terms and Conditions or for information on other Johns Manville roofing products and systems, visit www.jm.com/terms-conditions.