

JM White EPDM Peel & Stick Inside/Outside Corners

Features and Components

Use: Use universally for either an inside or outside corner. Quick and easy to install on either TPO or EPDM.

Materials: 60 mil (1.52 mm) thick, uncured EPDM (ethylene propylene diene monomer) and a factory laminated, self-adhering EPDM tape.

Color: White



Component

A
Accessory

Single Ply

Type

FC
Curb/Corner

System Compatibility This product may be used as a component in the following systems. Please reference product application for specific installation methods and information.

Multi-Ply	BUR		APP		SBS				
	HA	CA	HW	HA	CA	HW	SA	MF	
									<i>Do not use in multi-ply systems</i>

Key: HA = Hot Applied CA = Cold Applied HW = Heat Weldable SA = Self Adhered MF = Mechanically Fastened IW = Induction Weld BA = Ballasted AD = Adhered

Single Ply	TPO				PVC			EPDM		
	MF	AD	SA	IW	MF	AD	IW	MF	AD	BA
										<i>Compatible with the selected single ply systems above</i>

Peak Advantage® Guarantee Information

Systems
Approved for use in any JM Peak Advantage Guarantee System

Installation/Application



Self-Adhered

- Clean all surfaces to be flashed with either JM TPO Membrane Cleaner or JM Weathered Membrane Cleaner.
- Prime the membrane with JM Single Ply Membrane Primer - LVOC or JM TPO Membrane Primer before applying JM White EPDM Peel & Stick Inside/Outside Corners.
- Do not install in direct contact with asphalt or coal tar pitch.
- Refer to JM TPO or EPDM detail drawings for instructions.
- Be sure to caulk all flashing edges with JM Single Ply Low VOC white caulk.

Packaging and Dimensions

Size	7" x 9" (17.78 cm x 22.86 cm)
Thickness:	
Membrane	0.060" (1.52 mm)
Tape	0.030" (0.76 mm)
Total	0.090" (2.28 mm)
Number per Box	20
Coverage per Box	8.75 ft² (0.81 m²)
Weight per Box	5 lb (2.26 kg)

Storage

Shelf Life	6 months from manufacture date
Storage Conditions	Store indoors, out of direct sunlight, keep clean and dry prior to use.
Temperature Range	60°F – 80°F (16°C – 27°C)

Technical specifications as shown in this literature are intended to be used as general guidelines only. Please refer to the Safety Data Sheet and product label prior to using this product. The Safety Data Sheet is available by calling (800) 922-5922 or on the web at www.jm.com/roofing. The physical and chemical properties of the product listed herein represent typical, average values obtained in accordance with accepted test methods and are subject to normal manufacturing variations. They are supplied as a technical service and are subject to change without notice. Check with the regional sales representative nearest you for current information.

All Johns Manville products are sold subject to Johns Manville's standard Terms and Conditions, which includes a Limited Warranty and Limitation of Remedy. For a copy of the Johns Manville standard Terms and Conditions or for information on other Johns Manville roofing products and systems, visit www.jm.com/terms-conditions.