

## Features and Components

**Use:** JM Roofing System Urethane Adhesive is a two-component polyurethane adhesive used for attaching fleece-backed single ply membranes to insulation boards or various deck types as well as insulation boards to the roof deck or to other insulation boards.

**Type:** Two-part, cold application insulation adhesive.

**Substrates:** Compatible with the following insulations, cover boards, and substrates<sup>1</sup>: polyisocyanurate; HD wood fiber; perlite; ProtectoR® HD; gypsum; concrete<sup>2</sup> (*Lightweight structural, poured-in-place structural, precast, and insulating*); treated plywood (5/8" [1.58 cm] min. thickness); cementitious wood fiber; gypsum; smooth or granulated BUR, APP or SBS.

1. Ensure that all insulation boards are 4' x 4' or smaller.
2. Ensure that the concrete is adequately dry for adhesion.



**Color:** Part 1 - Brown, Part 2 - Colorless, Combined/foamed adhesive - Light Amber

**Features:** Solvent free, and HCFC or CFC free. Universal adhesive for adhering fleece-backed membranes and insulation boards. Sets in minutes.

Component

**AD**  
Adhesive

Type

**I**  
Insulation

**B**  
Cover Board

Multi-Ply  
Single Ply

**M**  
Membrane

Single Ply

**System Compatibility** This product may be used as a component in the following systems. Please reference product application for specific installation methods and information.

| Multi-Ply | BUR                                                 |    | APP |    | SBS |    |    |    |  |
|-----------|-----------------------------------------------------|----|-----|----|-----|----|----|----|--|
|           | HA                                                  | CA | HW  | HA | CA  | HW | SA | MF |  |
|           | Used to adhere insulation in all multi-ply systems* |    |     |    |     |    |    |    |  |

| Single Ply | TPO                                                   |    |    |    | PVC |    |    | EPDM |    |    |
|------------|-------------------------------------------------------|----|----|----|-----|----|----|------|----|----|
|            | MF                                                    | AD | SA | IW | MF  | AD | IW | MF   | AD | BA |
|            | Used to adhere insulation in all single ply systems** |    |    |    |     |    |    |      |    |    |

**Key:** HA = Hot Applied CA = Cold Applied HW = Heat Weldable SA = Self Adhered MF = Mechanically Fastened IW = Induction Weld BA = Ballasted AD = Adhered

\* For smooth modified membranes contact JM Technical Services for specific approval. \*\* May also be used to adhere fleece-backed TPO and PVC Membranes to Insulation and Cover Boards.

## Energy and the Environment

|             |                                                |
|-------------|------------------------------------------------|
| Maximum VOC | 32 g/l as applied after mixing (EPA method 24) |
|-------------|------------------------------------------------|

## Physical Properties

| Property                      |        | ASTM Test Method | JM Roofing System Urethane Adhesive |
|-------------------------------|--------|------------------|-------------------------------------|
| Weight (liquid components)    | Part 1 | —                | 10.18 lb/gal (1.2 kg/l)             |
|                               | Part 2 | —                | 8.34 lb/gal (1.0 kg/l)              |
| Viscosity (liquid components) | Part 1 | —                | 250 cps                             |
|                               | Part 2 | —                | 370 cps                             |

## Codes and Approvals



## Installation/Application



- Apply when ambient temperature is 25°F (-3.9°C) and rising.
- Ensure all insulation boards are 4' x 4' (1.22 m x 1.22 m) or smaller.
- Ensure all surfaces are dry and free of any debris, dirt, oil and grease before using JM Roofing System Urethane Adhesive.
- Refer to the application instructions and guidelines for proper utilization and coverages rates of this adhesive.
- Ambient temperature must remain at 25°F (-4°C) or higher for a minimum of 24 hours after applying or the adhesive may not cure properly.

## Packaging and Coverage

|                           | Container Type                |                                                    |                                                    |                                                      |
|---------------------------|-------------------------------|----------------------------------------------------|----------------------------------------------------|------------------------------------------------------|
|                           | Cartridges                    | 5 gal (18.9 l) Boxes                               | 15 gal (57 l) Drums                                | 50 gal (189 l) Drums                                 |
| Items per Case/Set*       | 4 per case with 5 mixing tips | 1 Set with 5 mixing tips                           | 1 Drum                                             | 1 Drum                                               |
| Shipping Weight (approx.) | 20 lb (9 kg)                  | Part 1 = 54 lb (24.5 kg)<br>Part 2 = 46 lb (21 kg) | Part 1 = 155 lb (70 kg)<br>Part 2 = 132 lb (60 kg) | Part 1 = 552 lb (250 kg)<br>Part 2 = 472 lb (214 kg) |
| Cases/Sets per Pallet     | 48 Cases                      | 18 Sets                                            | 4 Sets                                             | 2 Sets                                               |
| Coverage                  | See tables on back page       |                                                    |                                                    |                                                      |

\* A set is defined as an equal Part 1 and Part 2.

## Storage

|                    |                                                                                                                             |
|--------------------|-----------------------------------------------------------------------------------------------------------------------------|
| Shelf Life         | 18 months from manufacture date                                                                                             |
| Storage Conditions | Clean, dry, well-ventilated indoor environment in an un-opened container.                                                   |
| Temperature Range  |                                                                                                                             |
| Long Term:         | 45°F to 95°F (7°C to 35°C) - Protect from freezing.                                                                         |
| Short Term:        | 24 hours prior to use, store between 70°F (21°C) and 85°F (29°C). Adhesive must be at least 70°F (21°C) before application. |

RS-7373 10-25 (Replaces 9-24)

Refer to the Safety Data Sheet and product label prior to using this product. The Safety Data Sheet is available by calling (800) 922-5922 or on the Web at [www.jm.com/roofing](http://www.jm.com/roofing).

## Coverage – Fleece Backed Membranes, Insulation, and Substrates (see Installation Guide for Approved Substrates)

Bead spacing: 12" o.c. • Applied bead size: ½" - ¾" min.

| Packaging   | Typical Coverage Rates*              |                      |                         |
|-------------|--------------------------------------|----------------------|-------------------------|
|             | per package                          | ft <sup>2</sup> /gal | gal/100 ft <sup>2</sup> |
| Cartridge   | 600-800 ft <sup>2</sup> /case        | 189-250              | 0.33-0.4                |
| 5 gal box   | 2,500-3,000 ft <sup>2</sup> /set**   | 250-300              |                         |
| 15 gal drum | 7,500-9,000 ft <sup>2</sup> /set**   |                      |                         |
| 50 gal drum | 25,000-30,000 ft <sup>2</sup> /set** |                      |                         |

Bead spacing: 6" o.c. • Applied bead size: ½" - ¾" min.

| Packaging   | Typical Coverage Rates*              |                      |                         |
|-------------|--------------------------------------|----------------------|-------------------------|
|             | per package                          | ft <sup>2</sup> /gal | gal/100 ft <sup>2</sup> |
| Cartridge   | 300-400 ft <sup>2</sup> /case        | 94-125               | 0.8-1.1                 |
| 5 gal box   | 1,250-1,500 ft <sup>2</sup> /set**   | 125-150              | 0.66-0.8                |
| 15 gal drum | 3,750-4,500 ft <sup>2</sup> /set**   |                      |                         |
| 50 gal drum | 12,500-15,000 ft <sup>2</sup> /set** |                      |                         |

Bead spacing: 4" o.c. • Applied bead size: ½" - ¾" min.

| Packaging   | Typical Coverage Rates*             |                      |                         |
|-------------|-------------------------------------|----------------------|-------------------------|
|             | per package                         | ft <sup>2</sup> /gal | gal/100 ft <sup>2</sup> |
| Cartridge   | 200-266 ft <sup>2</sup> /case       | 63-83                | 1.19-1.59               |
| 5 gal box   | 833-1,000 ft <sup>2</sup> /set**    | 83-100               | 1.0-1.2                 |
| 15 gal drum | 2,500-3,000 ft <sup>2</sup> /set**  |                      |                         |
| 50 gal drum | 8,333-10,000 ft <sup>2</sup> /set** |                      |                         |

### Full Spray

| Packaging | Typical Coverage Rates*             |                      |                         |
|-----------|-------------------------------------|----------------------|-------------------------|
|           | per package                         | ft <sup>2</sup> /gal | gal/100 ft <sup>2</sup> |
| 5 gal     | 600-1,000 ft <sup>2</sup> /set**    | 83-100               | 1.0-1.2                 |
| 15 gal    | 1,800-3,000 ft <sup>2</sup> /set**  |                      |                         |
| 50 gal    | 6,000-10,000 ft <sup>2</sup> /set** |                      |                         |

### Spatter Pattern

| Packaging | Typical Coverage Rates*              |                      |                         |
|-----------|--------------------------------------|----------------------|-------------------------|
|           | per package                          | ft <sup>2</sup> /gal | gal/100 ft <sup>2</sup> |
| 5 gal     | 1,300-1,800 ft <sup>2</sup> /set**   | 130-180              | 0.56-0.77               |
| 15 gal    | 3,900-5,400 ft <sup>2</sup> /set**   |                      |                         |
| 50 gal    | 13,000-18,000 ft <sup>2</sup> /set** |                      |                         |

\* Coverage rates are approximate and may vary based on substrate type and application. Approved substrates include structural concrete decks, JM Vapor Barrier SA or SAR, ENRGY 3, Protector HD®, RetroPlus, DuraBoard, SeparatoR CGF, Securock, DensDeck, DensDeck Prime, DEXcell®, smooth modified asphalt membranes and granulated asphalt membranes. Please contact JM Technical Services for other approved substrates.

\*\* A set is defined as an equal Part 1 and Part 2.

Technical specifications as shown in this literature are intended to be used as general guidelines only. Please refer to the Safety Data Sheet and product label prior to using this product. The Safety Data Sheet is available by calling (800) 922-5922 or on the web at [www.jm.com/roofing](http://www.jm.com/roofing). The physical and chemical properties of the product listed herein represent typical, average values obtained in accordance with accepted test methods and are subject to normal manufacturing variations. They are supplied as a technical service and are subject to change without notice. Check with the regional sales representative nearest you for current information.

All Johns Manville products are sold subject to Johns Manville's standard Terms and Conditions, which includes a Limited Warranty and Limitation of Remedy. For a copy of the Johns Manville standard Terms and Conditions or for information on other Johns Manville roofing products and systems, visit [www.jm.com/terms-conditions](http://www.jm.com/terms-conditions).